

Calculus of Constructions with Recursive Types

Last modified: April 15, 2015 at 1:18am

1. Calculus of Constructions

Our language is based on the *Calculus of Constructions*, a special case of the *Pure Type System*. We give the definition as follows:

- (i) A *Calculus of Constructions* (λC) is a triple tuple $(\mathcal{S}, \mathcal{A}, \mathcal{R})$ where
 - (a) $\mathcal{S} = \{\star, \square\}$ is a set of *sorts*;
 - (b) $\mathcal{A} = \{(\star, \square)\} \subseteq \mathcal{S} \times \mathcal{S}$ is a set of *axioms*;
 - (c) $\mathcal{R} = \{(\star, \star), (\star, \square), (\square, \star), (\square, \square)\} \subseteq \mathcal{S} \times \mathcal{S}$ is a set of *rules*.
- (ii) *Raw expressions* A and *raw environments* Γ are defined in Figure 1.

| | | | |
|----------|-------|--------------------|--------------------|
| A | $::=$ | x | (variable) |
| | | \star | (star) |
| | | \square | (square) |
| | | $A A$ | (application) |
| | | $\lambda x : A. A$ | (abstraction) |
| | | $\Pi x : A. A$ | (product) |
| Γ | $::=$ | \emptyset | (empty) |
| | | $\Gamma, x : A$ | (variable binding) |

Figure 1. Syntax of λC

We use s, t to range over *sorts*, x, y, z to range over *variables*, and A, B, C, a, b, c to range over *expressions*.

- (iii) Π and λ are used to bind variables. Let $FV(A)$ denote free variable set of A . Let $A[x := B]$ denote the substitution of x in A with B . We use $A \rightarrow B$ as a syntactic sugar for $(\Pi_1 : A. B)$.
- (iv) The β -reduction (\rightarrow_β) is the smallest binary relation on raw expressions satisfying

$$(\lambda x : A. M)N \rightarrow_\beta M[x := N]$$

which can be used to define the notation \rightarrow_β and $=_\beta$ by convention. Reduction rules are given in Figure 2. Highlighted premises and rules are only for call-by-value evaluation.

- (v) Type assignment rules for $(\mathcal{S}, \mathcal{A}, \mathcal{R})$ are given in Figure 3.

| | |
|------------------------|--|
| Values: $v ::=$ | $\lambda x : A.B \mid \Pi x : A.B$ |
| (R-Beta) | $\frac{N \in \text{Value}}{(\lambda x : A.M)N \longrightarrow M[x := N]}$ |
| (R-AppL) | $\frac{M \longrightarrow M'}{MN \longrightarrow M'N}$ |
| (R-AppR) | $\frac{v \in \text{Value} \quad M \longrightarrow M'}{vM \longrightarrow vM'}$ |

Figure 2. Reduction rules for λC

| | | |
|--------|--|-------------------------------|
| (Ax) | $\frac{}{\emptyset \vdash \star : \square}$ | |
| (Var) | $\frac{\Gamma \vdash A : s}{\Gamma, x : A \vdash x : A}$ | $x \notin \text{dom}(\Gamma)$ |
| (Weak) | $\frac{\Gamma \vdash b : B \quad \Gamma \vdash A : s}{\Gamma, x : A \vdash b : B}$ | $x \notin \text{dom}(\Gamma)$ |
| (App) | $\frac{\Gamma \vdash f : (\Pi x : A.B) \quad \Gamma \vdash a : A}{\Gamma \vdash fa : B[x := a]}$ | |
| (Lam) | $\frac{\Gamma, x : A \vdash b : B \quad \Gamma \vdash (\Pi x : A.B) : t}{\Gamma \vdash (\lambda x : A.b) : (\Pi x : A.B)}$ | $t \in \{\star, \square\}$ |
| (Pi) | $\frac{\Gamma \vdash A : s \quad \Gamma, x : A \vdash B : t}{\Gamma \vdash (\Pi x : A.B) : t}$ | $(s, t) \in \mathcal{R}$ |
| (Conv) | $\frac{\Gamma \vdash a : A \quad \Gamma \vdash B : s \quad A =_{\beta} B}{\Gamma \vdash a : B}$ | |

Figure 3. Typing rules for λC

2. Extend with recursive types

2.1 Core language

We extend Calculus of Constructions (λC) with recursive types, namely λC_{μ} . Differences with λC are highlighted. Figure 4 shows the extended syntax.

| | | |
|--------------|--------------------------|--------------------|
| $A ::=$ | x | (variable) |
| | \star | (star) |
| | \square | (square) |
| | $A A$ | (application) |
| | $\lambda x : A.A$ | (abstraction) |
| | $\Pi x : A.A$ | (product) |
| | $\mu x.A$ | (recursive type) |
| | $\text{fold}[\mu x.A] A$ | (roll) |
| | $\text{unfold } A$ | (unroll) |
| | $\text{beta } A$ | (type reduction) |
| $\Gamma ::=$ | \emptyset | (empty) |
| | $\Gamma, x : A$ | (variable binding) |

Figure 4. Syntax of λC_{μ}

Since recursive types are introduced and due to the practical concern, we use the *call-by-name* reduction strategy, i.e. iteratively reducing the *left-most outer-most* redex. Figure 5 shows the dynamic semantics with no call-by-value specific premises or rules.

| | | |
|-----------------|---|---------------|
| values: | $v ::= \lambda x : A. B$ | (abstraction) |
| | $ \Pi x : A. B$ | (product) |
| | $ \text{fold}[\mu x. A] B$ | (roll) |
| (R-AppLam) | $\frac{}{(\lambda x : A. M) N \longrightarrow M[x := N]}$ | |
| (R-AppL) | $\frac{M \longrightarrow M'}{MN \longrightarrow M' N}$ | |
| (R-Unfold) | $\frac{M \longrightarrow M'}{\text{unfold } M \longrightarrow \text{unfold } M'}$ | |
| (R-Unfold-Fold) | $\frac{}{\text{unfold } (\text{fold}[\mu x. A] M) \longrightarrow M}$ | |
| (R-Mu) | $\frac{}{\mu x. M \longrightarrow M[x := \mu x. M]}$ | |
| (R-Beta) | $\frac{}{\text{beta } M \longrightarrow M}$ | |

Figure 5. Reduction rules for λC

The extended typing rules are shown in Figure 6. Compared with λC , the original *Conv* rule is replaced by the new *Beta* rule where the latter only performs one step of reduction defined in Fig.5.

2.2 Soundness of core language

Lemma 2.2.1 (Substitutions)

Assume we have

$$\Gamma, x : A \vdash B : C \quad (1)$$

$$\Gamma \vdash D : A, \quad (2)$$

then

$$\Gamma[x := D] \vdash B[x := D] : C[x := D].$$

Proof. This is trivial by induction on the typing derivation of (1) by typing rules in Fig.6. We only discuss two cases for example. Let E^* denote $E[x := D]$. Consider following cases

- The last applied rule to obtain (1) is *Var*. There are 2 sub-cases:

1. It is derived by

$$\frac{\Gamma \vdash A : s}{\Gamma, x : A \vdash x : A},$$

then we have $(B : C) \equiv (x : A)$. And $\Gamma \vdash (x : A)^* \equiv (D : A)$ which holds by (2).

| | | |
|----------|--|-------------------------------|
| (Ax) | $\frac{}{\emptyset \vdash \star : \square}$ | |
| (Var) | $\frac{\Gamma \vdash A : s}{\Gamma, x : A \vdash x : A}$ | $x \notin \text{dom}(\Gamma)$ |
| (Weak) | $\frac{\Gamma \vdash b : B \quad \Gamma \vdash A : s}{\Gamma, x : A \vdash b : B}$ | $x \notin \text{dom}(\Gamma)$ |
| (App) | $\frac{\Gamma \vdash f : (\Pi x : A. B) \quad \Gamma \vdash a : A}{\Gamma \vdash fa : B[x := a]}$ | |
| (Lam) | $\frac{\Gamma, x : A \vdash b : B \quad \Gamma \vdash (\Pi x : A. B) : t}{\Gamma \vdash (\lambda x : A. b) : (\Pi x : A. B)}$ | $t \in \{\star, \square\}$ |
| (Pi) | $\frac{\Gamma \vdash A : s \quad \Gamma, x : A \vdash B : t}{\Gamma \vdash (\Pi x : A. B) : t}$ | $(s, t) \in \mathcal{R}$ |
| (Mu) | $\frac{\Gamma, x : s \vdash A : s}{\Gamma \vdash (\mu x. A) : s}$ | |
| (Fold) | $\frac{\Gamma \vdash a : (A[x := \mu x. A]) \quad \Gamma \vdash \mu x. A : s}{\Gamma \vdash (\text{fold}[\mu x. A] a) : \mu x. A}$ | |
| (Unfold) | $\frac{\Gamma \vdash a : \mu x. A \quad \Gamma \vdash A[x := \mu x. A] : s}{\Gamma \vdash (\text{unfold } a) : A[x := \mu x. A]}$ | |
| (Beta) | $\frac{\Gamma \vdash a : A \quad \Gamma \vdash B : s \quad A \longrightarrow B}{\Gamma \vdash (\text{beta } a) : B}$ | |

Figure 6. Typing rules for λC_μ

2. It is derived by

$$\frac{\Gamma, x : A \vdash E : s}{\Gamma, x : A, y : E \vdash y : E},$$

then we need to show $\Gamma^*, y : E^* \vdash y : E^*$. And it directly follows the induction hypothesis, i.e. $\Gamma^* \vdash E^* : s$.

- The last applied rule to obtain (1) is *App*, i.e.

$$\frac{\Gamma, x : A \vdash B_1 : (\Pi y : C_1. C_2) \quad \Gamma, x : A \vdash B_2 : C_1}{\Gamma, x : A \vdash (B_1 B_2) : C_2[y := B_2]}.$$

By the induction hypothesis, we can obtain $\Gamma^* \vdash B_1^* : (\Pi y : C_1^*. C_2^*)$ and $\Gamma^* \vdash B_2^* : C_1^*$. Thus, $\Gamma^* \vdash (B_1^* B_2^*) : (C_2^*[y := B_2^*])$, i.e. $\Gamma^* \vdash (B_1 B_2)^* : (C_2[y := B_2])^*$.

□

Theorem 2.2.2 (Subject Reduction)

If $\Gamma \vdash A : B$ and $A \longrightarrow A'$ then $\Gamma \vdash A' : B'$ for some B' such that either $B' \equiv B$ or $B' \longrightarrow B$.

Proof. Let \mathcal{D} be the derivation of $\Gamma \vdash A : B$. The proof is by induction on dynamic semantics shown in Fig.5.

case *R-AppLam*: $\frac{}{(\lambda x : A. M)N \longrightarrow M[x := N]}.$

Derivation \mathcal{D} has the following form

$$\frac{\frac{\Gamma, x : A \vdash M : A'}{\Gamma \vdash (\lambda x : A. M) : (\Pi x : A. A')} \text{Lam} \quad \Gamma \vdash N : A}{\Gamma \vdash (\lambda x : A. M)N : A'} \text{App}$$

Thus, by Lemma 2.2.1 we can obtain $\Gamma \vdash M[x := N] : A'$.

$$\text{case } \mathbf{R-AppL}: \frac{M \longrightarrow M'}{MN \longrightarrow M'N}.$$

Derivation \mathcal{D} has the following form

$$\frac{\Gamma \vdash M : (\Pi x : A.A') \quad \Gamma \vdash N : A}{\Gamma \vdash MN : A'} \text{App}$$

By the induction hypothesis we have $\Gamma \vdash M' : (\Pi x : A.A')$. Hence,

$$\frac{\Gamma \vdash M' : (\Pi x : A.A') \quad \Gamma \vdash N : A}{\Gamma \vdash M'N : A'} \text{App}$$

$$\text{case } \mathbf{R-Unfold}: \frac{M \longrightarrow M'}{\text{unfold } M \longrightarrow \text{unfold } M'}.$$

Derivation \mathcal{D} has the following form

$$\frac{\Gamma \vdash M : \mu x.A}{\Gamma \vdash (\text{unfold } M) : A[x := \mu x.A]} \text{Unfold}$$

By the induction hypothesis we have $\Gamma \vdash M' : \mu x.A$. Hence,

$$\frac{\Gamma \vdash M' : \mu x.A}{\Gamma \vdash (\text{unfold } M') : A[x := \mu x.A]} \text{Unfold}$$

$$\text{case } \mathbf{R-Unfold-Fold}: \frac{}{\text{unfold } (\text{fold}[\mu x.A] M) \longrightarrow M}.$$

Derivation \mathcal{D} has the following form

$$\frac{\frac{\Gamma \vdash M : (A[x := \mu x.A])}{\Gamma \vdash (\text{fold}[\mu x.A] M) : \mu x.A} \text{Fold}}{\Gamma \vdash \text{unfold } (\text{fold}[\mu x.A] M) : (A[x := \mu x.A])} \text{Unfold}$$

$$\text{case } \mathbf{R-Mu}: \frac{}{\mu x.M \longrightarrow M[x := \mu x.M]}.$$

Derivation \mathcal{D} has the following form

$$\frac{\Gamma, x : s \vdash M : s}{\Gamma \vdash (\mu x.M) : s} \text{Mu}$$

$$\text{Hence, by Lemma 2.2.1 we have } \frac{\Gamma, x : s \vdash M : s \quad \Gamma \vdash \mu x.M : s}{\Gamma \vdash (M[x := \mu x.M]) : s}.$$

$$\text{case } \mathbf{R-Beta}: \frac{}{\text{beta } M \longrightarrow M'}.$$

Derivation \mathcal{D} has the following form

$$\frac{\Gamma \vdash M : A \quad \Gamma \vdash B : s \quad A \longrightarrow B}{\Gamma \vdash (\text{beta } M) : B} \text{Beta}$$

By the induction hypothesis we have $\Gamma \vdash M' : A$ and $A \longrightarrow B$. Hence,

$$\frac{\Gamma \vdash M' : A \quad \Gamma \vdash B : s \quad A \longrightarrow B}{\Gamma \vdash (\text{beta } M') : B} \text{Beta}$$

□

Theorem 2.2.3 (Progress)

If $\cdot \vdash A : B$ then either A is a value v or there exists A' such that $A \longrightarrow A'$.

Proof. We can give the proof by induction on the derivation of $\cdot \vdash A : B$ by typing rules in Fig.6:

$$\text{case } \mathbf{Var}: \frac{\cdot \vdash A : s}{\cdot, x : A \vdash x : A}.$$

This case cannot be reached. Proof is by contradiction. If we have $\cdot \vdash x : A$ then x is assigned with type A from a context “.” without A , which is not possible.

case Weak: $\frac{\cdot \vdash b : B \quad \cdot \vdash A : s}{\cdot, x : A \vdash b : B}$.

The result is trivial by induction hypothesis.

case App: $\frac{\cdot \vdash M : (\Pi x : A. B) \quad \cdot \vdash N : A}{\cdot \vdash MN : B}$.

By induction hypothesis on $\cdot \vdash M : (\Pi x : A. B)$, there are two possible cases.

1. $M = v$ is a value. Hence $v = \lambda x : A. M'$ where $\cdot \vdash M' : B$. Then $MN = vN = (\lambda x : A. M')N = M'[x := N]$. By the substitution lemma, $\cdot \vdash (M'[x := N]) : B$ which is just $\cdot \vdash MN : B$.
2. $M \longrightarrow M'$. The result is obvious by the operational semantic $\frac{M \longrightarrow M'}{MN \longrightarrow M'N} R\text{-AppL}$.

case Lam: $\frac{\dots}{\cdot \vdash (\lambda x : A. M) : (\Pi x : A. B)}$.

The result is trivial if let $v = \lambda x : A. M$.

case Pi: $\frac{\cdot \vdash A : s \quad \cdot, x : A \vdash B : t}{\cdot \vdash (\Pi x : A. B) : t}$.

The result is trivial if let $v = \Pi x : A. B$.

case Mu: $\frac{\dots}{\cdot \vdash (\mu x. A) : s}$.

The result is trivial since we always have such reduction $\mu x. A \longrightarrow A[x := \mu x. A]$.

case Fold: $\frac{\dots}{\cdot \vdash (\text{fold}[\mu x. A] M) : \mu x. A}$.

The result is trivial if let $v = \text{fold}[\mu x. A] M$.

case Unfold: $\frac{\cdot \vdash a : \mu x. A \quad \cdot \vdash A[x := \mu x. A] : s}{\cdot \vdash (\text{unfold } a) : A[x := \mu x. A]}$.

By induction hypothesis on $\cdot \vdash a : \mu x. A$, there are two possible cases.

1. $a = v$ is a value. Hence $a = \text{fold}[\mu x. A] b$ where $\cdot \vdash b : (A[x := \mu x. A])$. Then by the *R-Unfold-Fold* rule, $\text{unfold } a = \text{unfold } (\text{fold}[\mu x. A] b) = b$. Thus $\cdot \vdash (\text{unfold } a) : A[x := \mu x. A]$.
2. $a \longrightarrow a'$. The result is obvious by the reduction rule $\frac{M \longrightarrow M'}{\text{unfold } M \longrightarrow \text{unfold } M'} R\text{-Unfold}$.

case Beta: $\frac{\dots}{\cdot \vdash (\text{beta } a) : B}$.

The result is trivial since we always have such reduction $\text{beta } a \longrightarrow a$.

□

2.3 Examples of typable terms

- A polymorphic fixed-point constructor $\text{fix} : (\Pi \alpha : \star. (\alpha \rightarrow \alpha) \rightarrow \alpha)$ can be defined as follows:

$$\begin{aligned} \text{fix} &= \lambda \alpha : \star. \lambda f : \alpha \rightarrow \alpha. \\ &\quad (\lambda x : (\mu \sigma. \sigma \rightarrow \alpha). f((\text{unfold } x) x)) \\ &\quad (\text{fold}[\mu \sigma. \sigma \rightarrow \alpha] (\lambda x : (\mu \sigma. \sigma \rightarrow \alpha). f((\text{unfold } x) x))) \end{aligned}$$

Note that this is the so called call-by-name fixed point combinator. It is useless in a call-by-value setting, since the expression $\text{fix } \alpha g$ diverges for any g .

- Using `fix`, we can build recursive functions. For example, given a “hungry” type $H = \mu\sigma.\alpha \rightarrow \sigma$, the “hungry” function h where

$$h = \lambda\alpha : \star.\text{fix}(\alpha \rightarrow H)(\lambda f : \alpha \rightarrow H.\lambda x : \alpha.\text{fold}[H] f)$$

can take arbitrary number of arguments.

3. Formal Elaboration of Datatypes and Case Analysis

3.1 Extended Language

We extend λC_μ with simple datatypes and case analysis, namely $\lambda C_{\mu c}$. Differences with λC_μ are highlighted in Figure 7.

| | | | |
|----------|-------|--|-----------------------------------|
| pgm | $::=$ | $\overline{decl}; A$ | (Declarations) |
| $decl$ | $::=$ | data $T = K \overline{A}$ | (Datatype) |
| u | $::=$ | $x \mid K$ | (Variables and data constructors) |
| A | $::=$ | u | (Term atoms) |
| | | \star | (Star) |
| | | \square | (Square) |
| | | $A A$ | (Application) |
| | | $\lambda x : A.A$ | (Abstraction) |
| | | $\Pi x : A.A$ | (Product) |
| | | $\mu x.A$ | (Recursive type) |
| | | $\text{fold}[\mu x.A] A$ | (Roll) |
| | | $\text{unfold } A$ | (Unroll) |
| | | $\text{beta } A$ | (Type reduction) |
| | | let $x = A$ in A | (Let binding) |
| | | case A of $p \Rightarrow \overline{A}$ | (Case analysis) |
| p | $::=$ | $K x : A$ | (Pattern) |
| Γ | $::=$ | \emptyset | (Empty) |
| | | $\Gamma, u : A$ | (Variable binding) |

Figure 7. Syntax of $\lambda C_{\mu c}$

The extended typing rules are shown in Figure 8. To save space, we only show the new typing rules.

3.2 Translation Overview

We use a type-directed translation. The typing relations have the form:

$$\Gamma \vdash e : A \rightsquigarrow \hat{e}$$

It states that λC_μ expression \hat{e} is the translation of $\lambda C_{\mu c}$ expression e . Figure 9 shows the translation rules, which are the typing rules of the previous section extended with the resulting \hat{e} expression.

References

- [1] Herman Geuvers. The church-scott representation of inductive and coinductive data. Types, 2014.

| | |
|---|---|
| $\boxed{\Gamma \vdash \text{pgm} : A}$ | |
| (Pgm) | $\frac{\overline{\Gamma_0 \vdash \text{decl} : \Gamma_d} \quad \Gamma = \Gamma_0, \overline{\Gamma_d} \quad \Gamma \vdash e : A}{\Gamma_0 \vdash \overline{\text{decl}}; e : A}$ |
| $\boxed{\Gamma \vdash \text{decl} : \Gamma'}$ | |
| (Data) | $\frac{\overline{\Gamma, T : \star \vdash \overline{A} \rightarrow T : \star}}{\Gamma \vdash (\text{data } T = \overline{K \overline{A}}) : (T : \star, K : \overline{A} \rightarrow T)}$ |
| $\boxed{\Gamma \vdash e : A}$ | |
| (Case) | $\frac{\Gamma \vdash e : T \quad \overline{\Gamma \vdash_p p \Rightarrow e : T \rightarrow B}}{\Gamma \vdash \text{case } e \text{ of } \overline{p \Rightarrow e} : B}$ |
| (Let) | $\frac{\Gamma \vdash e_1 : A \quad \Gamma, x : A \vdash e_2 : B}{\text{let } x = e_1 \text{ in } e_2 : B}$ |
| $\boxed{\Gamma \vdash_p p \Rightarrow e : T \rightarrow B}$ | |
| (Alt) | $\frac{K : \overline{A} \rightarrow T \in \Gamma \quad \Gamma, x : \overline{A} \vdash e : B}{\Gamma \vdash_p \overline{K x : \overline{A}} \Rightarrow e : T \rightarrow B}$ |

Figure 8. Typing rules for $\lambda C_{\mu}c$

- [2] Simon Peyton Jones and Erik Meijer. Henk: a typed intermediate language. *TIC*, 97, 1997.
- [3] J-W Roorda and JT Jeuring. Pure type systems for functional programming. 2007.
- [4] Morten Heine Sørensen and Pawel Urzyczyn. *Lectures on the Curry-Howard isomorphism*, volume 149. Elsevier, 2006.

A. Appendix

| | | |
|--|---|--|
| | $\boxed{\Gamma \vdash e : A \rightsquigarrow \hat{e}}$ | |
| (Ax) | $\frac{}{\emptyset \vdash \star : \square \rightsquigarrow \star}$ | |
| (Var) | $\frac{x : A \in \Gamma}{\Gamma \vdash x : A \rightsquigarrow x}$ | |
| (App) | $\frac{\Gamma \vdash f : (\Pi x : A. B) \rightsquigarrow \hat{f} \quad \Gamma \vdash a : A \rightsquigarrow \hat{a}}{\Gamma \vdash fa : B[x := a] \rightsquigarrow \hat{f}\hat{a}}$ | |
| (Lam) | $\frac{\Gamma, x : A \vdash b : B \rightsquigarrow \hat{b} \quad \Gamma \vdash (\Pi x : A. B) : t}{\Gamma \vdash (\lambda x : A. b) : (\Pi x : A. B) \rightsquigarrow \lambda x : A. \hat{b}} \quad t \in \{\star, \square\}$ | |
| (Pi) | $\frac{\Gamma \vdash A : s \quad \Gamma, x : A \vdash B : t}{\Gamma \vdash (\Pi x : A. B) : t \rightsquigarrow \Pi x : A. B} \quad (s, t) \in \mathcal{R}$ | |
| (Mu) | $\frac{\Gamma, x : s \vdash A : s}{\Gamma \vdash (\mu x. A) : s \rightsquigarrow \mu x. A}$ | |
| (Fold) | $\frac{\Gamma \vdash a : (A[x := \mu x. A]) \rightsquigarrow \hat{a} \quad \Gamma \vdash \mu x. A : s}{\Gamma \vdash (\text{fold}[\mu x. A] a) : \mu x. A \rightsquigarrow \text{fold}[\mu x. A] \hat{a}}$ | |
| (Unfold) | $\frac{\Gamma \vdash a : \mu x. A \rightsquigarrow \hat{a} \quad \Gamma \vdash A[x := \mu x. A] : s}{\Gamma \vdash (\text{unfold } a) : A[x := \mu x. A] \rightsquigarrow \text{unfold } \hat{a}}$ | |
| (Beta) | $\frac{\Gamma \vdash a : A \rightsquigarrow \hat{a} \quad \Gamma \vdash B : s \quad A \longrightarrow B}{\Gamma \vdash (\text{beta } a) : B \rightsquigarrow \text{beta } \hat{a}}$ | |
| (Let) | $\frac{\Gamma \vdash e_1 : A \rightsquigarrow \hat{e}_1 \quad \Gamma, x : A \vdash e_2 : B \rightsquigarrow \hat{e}_2}{\text{let } x = e_1 \text{ in } e_2 : B \rightsquigarrow (\lambda x : A. \hat{e}_2) \hat{e}_1}$ | |
| (Case) | $\frac{\Gamma \vdash e : T \rightsquigarrow \hat{e} \quad \overline{\Gamma \vdash_p p \Rightarrow e : T \rightarrow B \rightsquigarrow E_1}}{\Gamma \vdash \text{case } e \text{ of } \overline{p \Rightarrow e} : B \rightsquigarrow (\text{unfold } \hat{e}) B \overline{E_1}}$ | |
| | $\boxed{\Gamma \vdash_p p \Rightarrow e : T \rightarrow B \rightsquigarrow \hat{e}}$ | |
| (Alt) | $\frac{K : \overline{A} \rightarrow T \in \Gamma \quad \Gamma, x : \overline{A} \vdash e : B \rightsquigarrow \hat{e}}{\Gamma \vdash_p K \overline{x} : \overline{A} \Rightarrow e : T \rightarrow B \rightsquigarrow \lambda(x : \overline{A}). \hat{e}}$ | |
| | $\boxed{\Gamma \vdash \text{decl} : \Gamma' \rightsquigarrow \hat{e}}$ | |
| (Data) | $\frac{\overline{\Gamma, T : \star \vdash \overline{A} \rightarrow T : \star}}{\Gamma \vdash (\text{data } T = \overline{K \overline{A}}) : (T : \star, K : \overline{A} \rightarrow T) \rightsquigarrow E}$ | |
| $E ::= \text{let } T = \mu\beta. \Pi\alpha : \star. (\overline{A[T := \beta]} \rightarrow \alpha) \rightarrow \alpha \text{ in}$ $\text{let } K_i^{i \in 1..n} = \lambda(x : \overline{A_i}).$ $\text{fold}[T] (\lambda(\alpha : \star) (\overline{c : \overline{A} \rightarrow \alpha}. c_i \overline{x}) \text{ in}$ | | |
| | $\boxed{\Gamma \vdash \text{pgm} : A \rightsquigarrow \hat{e}}$ | |
| (Pgm) | $\frac{\overline{\Gamma_0 \vdash \text{decl} : \Gamma_d \rightsquigarrow E_1} \quad \Gamma = \Gamma_0, \overline{\Gamma_d}}{\Gamma \vdash e : A \rightsquigarrow \hat{e} \quad \Gamma_0 \vdash E_1 \oplus \hat{e} : A \rightsquigarrow E} \quad \Gamma_0 \vdash \overline{\text{decl}}; e : A \rightsquigarrow E$ | |

Figure 9. Type-directed translation from $\lambda C_{\mu}c$ to λC_{μ}