

PG180-A02

256b GDDR6 x16

TALL DP + DP + DP + HDMI/DP + USB

TABLE OF CONTENTS

Page Description

1	Table of Contents
2	Block Diagram
3	PCI Express
4	PCI Termination
5	MEMORY: GPU Partition A/B
6	MEMORY: FBA Partition 31..0
7	MEMORY: FBA Partition 63..32
8	MEMORY: FBB Partition 31..0
9	MEMORY: FBB Partition 63..32
10	MEMORY: GPU Partition C/D
11	MEMORY: FBC Partition 31..0
12	MEMORY: FBC Partition 63..32
13	MEMORY: FBD Partition 31..0
14	MEMORY: FBD Partition 63..32
15	GPU PWR and GND
16	GPU Decoupling
17	GPU DECOUPLING
18	IFPAB TALL-DP
19	IFPE DP
20	IFPF USBC
21	IFPC HDMI 2.0/DP
22	IFPD DP
23	NVHS INTERFACE
24	MISC: FAN,THERMAL,JTAG,GPIO,STEREO
25	MISC3: ROM, STRAPS



Page Description

26	MISC: XTAL, PLL
27	MISC: USB PPC
28	PS: USB VR
29	PS: 5V, 5V BACKUP
30	PS: PEXVDD, 1V8
31	PS: FBVDD CONTROLLER
32	PS: FBVDD CONTROLLER OVR3
33	PS: FBVDD PHASE 1, 2
34	PS: NVVDD CONTROLLER OVR8
35	PS: NVVDD Phase 1, 2
36	PS: NVVDD Phase 3, 4
37	PS: NVVDD Phase 5, 6
38	PS: NVVDD Phase 7, 8
39	PS: INPUT SWITCH RTD3
40	PS: INPUT SWITCH RTD3 USB
41	PS: INPUT SWITCH RAIL BALANCE
42	PS: 12V CURRENT STEERING
43	PS: VR THERMAL PROTECTION
44	PS: INPUTS, FILTERING AND MONITORING
45	PS: CURRENT STEERING,HOT UNPLUG DETECT
46	PS: PRE-FILTER
47	SEQUENCE: 5V, 1V8, NV3V3 ENABLE
48	SEQUENCE: NV, PEX, FB ENABLE
49	SEQUENCE: PCIE VOLTAGE MONITOR
50	SEQUENCE: DISCHARGE


Page Description


51	SEQUENCE: MISC
52	LED & FAN HEADERS
53	LED 2
54	Mechanical: Bracket/Thermal Solution


base on V372-02S change for D18 Z
 1. P.23 remove SL1 & BRIDGE_LED_VDD & SL1_BRG_PRST*
 2. P.52 remove LED change FAN connector
 3. P.53 remove LED
 4. P.38/44 add FUSE
 5. P.5~14 mem add <>
 6. P.53 LED use V336-0D
 7. P.32 remove
 8. P.35~38 dual MOS
 9. P.33 change dual MOS
 10. P.43 remove
 11. P.31 change to UP1666
 12. P.21 remove colay DP





VOLTAGE	MAX_CURRENT	MIN_WIDTH
12V	5.5A	0.406
3.3V	3.0A	0.400
0V	8.5A	0.300






















































	MICRO-STAR INT'L CO.,LTD MS-V373		
	Size	Document Description	Rev
	Custom	Page23:NVHS INTERFACE	2.0
	Date: Thursday, July 26, 2018 Sheet 23 of 54		



H=High :Tied to 1.8V
M=Middle:Tied to 0.9V
L=Low :Tied to 0V

STRAP2	STRAP1	STRAP0	RAMCFG[4:0]	
L	L	L	0000	RAMCFG TBD
L	L	H	0001	RAMCFG TBD
L	H	L	0010	RAMCFG TBD
L	H	H	0011	RAMCFG TBD
H	H	L	0110	RAMCFG TBD
H	H	H	0111	RAMCFG TBD

ROM_SO	ROM_SI	ROM_SCLK	DUMMY[2:0] FS_OVERT	1:ENABLE 0:DISABLE	
L	L	L	XXX1	FS_OVERT ENABLE	DEFAULT
L	L	M	XXX0	FS_OVERT DISABLE	

STRAP5	STRAP4	STRAP3	SMB_ALT_ADDR	DEVID_SEL	PCIE_CFG	VGA_DEVICE
M	H	H	1	1	1	1
M	H	L	1	1	1	0
M	L	H	1	1	0	1
M	L	L	1	1	0	0
L	H	M	1	0	1	1
L	M	H	1	0	1	0
L	M	L	1	0	0	1
L	L	M	1	0	0	0
H	H	H	0	1	1	1
H	H	L	0	1	1	0
H	L	H	0	1	0	1
H	L	L	0	1	0	0
L	H	H	0	0	1	1
L	H	L	0	0	1	0
L	L	H	0	0	0	1
L	L	L	0	0	0	0

1:SMB_ALT_ADDR ENABLE
0:SMB_ALT_ADDR DISABLE





1:DEVID_SEL REBRAND
0:DEVID_SEL ORIGNAL

1:PCIE_CFG LOW POWER
0:PCIE_CFG HIGH POWER

1:VGA_DEVICE ENABLE
0:VGA_DEVICE DISABLE

Default


RAMCFG[4:0]	DENSITY	WIDTH	VENDOR
00000	8Gb	256-bit	Samsung
00001	8Gb	256-bit	Micron
00010	8Gb	256-bit	Hynix
00110	16Gb	256-bit	Samsung
00111	16Gb	256-bit	Samsung



MICRO-STAR INT'L CO.,LTD
MS-V373


Size Custom	Document Description Page25:MISC3_ROM, STRAPS	Rev 2.0
Date: Thursday, July 26, 2018		Sheet 25 of 54







remove






MSI CONFIDENTIAL
00017967 jonepei (裴亮樂)
RD(C)2018102901 RMA工程課
石阿鋒 (00068760)

MICRO-STAR INT'L CO.,LTD		
MS-V373		
	Size	Document Description
	Custom	Page32:PS_FBDD CONTROLLER OVR3
	Date	Thursday, July 26, 2018
Sheet 32 of 54		Rev 2.0






These MLCCs should be placed close to the total current SUM resistors of each phase.




MICRO-STAR INT'L CO.,LTD

MS-V373



Size Custom	Document Description Page34:PS_ NVDD CONTROLLER OVR8	Rev 2.
Date: Thursday, July 26, 2018	Sheet 34 of 54	





EXT_12V Input CAP






Backup













12V CURRENT STEERING (UNDER POWER BOOT):
GUIDES CURRENT FROM PEX EDGE TO PEX 6/8 PIN INPUT AREA













12V CURRENT STEERING (UNDER POWER BOOT):
GUIDES CURRENT FROM PEX EDGE TO PEX 8 PIN INPUT AREA






MSI CONFIDENTIAL
00017967 jonepei (裴亮樂)
RD(C)2018102901 RMA工程課
石阿鋒 (00068760)


MICRO-STAR INT'L CO.,LTD		
MS-V373		
Size	Document Description	Rev
Custom	Page43.PS_VR THERMAL PROTECTION	2.0
Date: Thursday, July 26, 2018		Sheet 43 of 54












PCIE Voltage Monitor



BOM Configuration

OPTIONS	PEX3V3_SENSE	PEX12V_SENSE	OTHER_12V_SENSE
Use Pre-Filter	Pre-Filter NO STUFF U12 NO STUFF Q3,Q5 NO STUFF D15	Pre-Filter NO STUFF U13 NO STUFF Q4	Pre-Filter
Use INA3221	Voltage_Monitor	INA3221 NO STUFF U12 NO STUFF Q4	INA3221
NO INA3221 NO Pre-Filter	Voltage_Monitor	Voltage_Monitor	N/A

Power Supply


INA3221:3V3_SEQ

Pre_Filter(ADC_MUX):3V3(PEX)


Dual Pre-Filter case:


Only use the Primary Pre-Filter to sense 3V3PEX
and All Input 12Vs

Signal	Direction	Function
3V3	INPUT	Sense the 3V3 Voltage from PCIE golden finger
12V	INPUT	Sense the 12V Voltage from PCIE golden finger
PS_VMON_PG000	OPEN-DRAIN	Floating(H) once both 3V3 and 12V reach Vth
GC6_FB_EN	INPUT	Indicator for RTD3/GC6 residence,Use to Mask the VMON_PG000
PS_PF_SKIP	INPUT	From INA3221(VPU) or Pre-filter(SKIP)
PS_PF_BSOK	INPUT	From INA3221(PV) or Pre-filter(BS_OK)
PS_RTD3_12V_SW	INPUT	GC6_FB_EN && IDLE_IN_SW



MICRO-STAR INT'L CO.,LTD			
MS-V373			
Size Custom	Document Description	Rev	
	Page50:SEQUENCE_ DISCHARGE	2	
Date: Thursday, July 26, 2018		Sheet	50 of 54











LED BOOST




Size Custom	Document Description Page52:LED & FAN HEADERS	Rev 2.0
Date: Thursday, July 26, 2018		Sheet 52 of 54

Firmware Programming

Debug

27.31,32,33,48
27.31,32,33,48

5V_LED

MICRO-STAR INT'L CO.,LTD
MS-V373

Size	Document Description	Rev
Custom	Page53.LED_CONTROLLER_IT8295	2.0
Date: Thursday, July 26, 2018		Sheet 53 of 54

