HD7970(C386PI)Repair Guide

Feb/14/2012
Medison_Huang
CSC-GRMA

ASUS Model name	HD7970-DC2-3GD5-2D4S
ASUS P/N	60YV01N0-VG0A02
Graphics Engine	AMD RedeonHD7970
GPU P/N	02002-00060100
Bus Standard	PCI Express 3.0
Video Memory	GDDR5 3GB
Engine Clock	925 MHz
Memory Clock	5500 MHz (1375 MHz GDDR5)
Memory Interface	384-bit

Page1. Basic Information about the Model

Page2. Block Diagram

Page3. Power Sequence and Power Flow

Page4. Power Sequence and Power Flow

Page5. Power Sequence and Power Flow

Page6. Important Signal map (Top side)

Block Diagram



PowerFlow


UP6206A
2 phase
(PH7030*1+PH5030*2)
4.1A
+MVDD
1.6V/28A
+VDDC_PG
+VDDCI_PG
11A
6.9A
3 phase
CHiL8228G + IR3598
16 phase
(PH7030*1+PH5030*2)
+VDDC
1.05V/180A
Max:240A
12V_PEX8_L
11.6A
5phase
+1.8V
12V_PEX8_R

PowerFlow


+12V_BUS
5.3A
3.7A
UP6205A
2 phase
(PH7030*1+PH5030*2)
+VDDCI
1.1V/34A
+VDDC_PG
0.7A
APW7165A
1 phase
(EMB20N03V+EMB20N03V)
+1.8V
1.8V/4A
Vin_Rail_up
0.5A
APW7165A
1 phase
(EMB20N03V+EMB20N03V)
+0.94V
0.94V/6A
Vin_Rail_up
LM7805BJ3
+5.0V
0.2A+0.15A
APL5315
+3.3_VDDA
0.15A
For Micro-controller
0.35A
+3V3_BUS
0.1A

Power sequence




+MVDD
+VDDC
+VDDCI
VDDCI_EN
+12V_F
+5V
V1.8
27M
0.94V
+3.3V_BUS