


NV11, 2MX32 SDR, RGB, INTERNAL DVI-I, AGP.

PCI DEVICE ID 0X0=0X110 FOR NV11.

STRAPS: AGP4X, SIDEBAND DIS, FAST WRITE ENA, ADP BIOS, NORMAL PCIAD, 14.318MHZ
STRAP_RAM_TYPE [5:2]=0000-2MX32 SDR SDRAM















HISTORY REV. C00:

- 1) C00: Implemented Separate DFP_VREF and DFP_RSET for each TMDS channel.
- 2) C00: Added RC networks for FBDQS and FBCLK.
- 3) C00: Fixed 64 bit memory interface.
- 4) C00: Added more bulk decoupling caps to 3.3V rail.
- 5) C00: Added alternative footprint for D800 and C808.
- 6) C00: Changed HSYNC/VSNC caps from 220pf to 22pf.
- 7) C00: Recalculated DFP hi frequency caps to have RSF from 65mhz to 108mhz.




Micro-Star International Co., LTD.
MS-8817 based on P39C00


Size B	Document Number HISTORY	Rev 1
Date:	Tuesday, September 26, 2000	Sheet 1 of 10





TVED[11:0] <<<
VFPD[7:0] <<<
DFPD[11:0] <<<



BRACKET WITH RIB VGA (3.235)







Micro-Star International Co., LTD.

MS-8817

Size B	Document Number ROM VIP & VIDEO I/F	Rev 1
Date:	Tuesday, September 26, 2000	Sheet 9 of 10

