P216-A02 DESIGN -- NV43, 128 MB DDR3, VGA, DVI-I, SD/HDTV, VIVO PAGE SUMMARY: 20050203 Verson 10 Adding BJT into 1155 VID4 to solve always pull low issue. ATS2G GPIO contorller reset pin set to 3v3. Adding OVT &SMI# Func. with F75387 Remove FAN JU1(12V only) Solve Cap dummy issue with 3 pin Adding EMI Fucn. into south DVI Change GPIO to GPU & Memory -2005-0214 BASE LEVEL GENERIC SCHEMATIC ONLY, COMMON & NO\_STUFF ASSEMBLY NOTES AND BOM NOT FINAL NV43-U 500/500MHz 128MB DDR3 8M/32 DVI+VGA+HD/TVOUT NV43-U 500/500MHz 128MB DDR3 8M/32 DVI+VGA+HD/TVIO 602-10216-0001-200 602-10216-0002-200 602-10216-0003-200 <UNDEFINED> Micro-Star International Co., LTD.

PAGE DETAIL TABLE OF CONTENTS & REVISION HISTORY

ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS AND OTHER DOCUMENTS OF INFORMATION (TOGETHER AND SEPARATELY, MATERIALS) ARE BEING PROVIDED AS IS: THE MATERIALS MAY CONTAIN KNOWN AND UNKNOWN VIOLATIONS OR DEVIATIONS OF INDUSTRY STANDARDS AND SPECIFICATIONS. NVIDIA MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY OR OTHERWISE WITH RESPECT TO THE MATERIALS OR OTHERWISE, AND EXPRESSLY DISCLAMS ALL MAY ARRANTIES INCLUDING, WITHOUT LIMITATION, THE WARRANTIES OR OTHERWISE, AND EXPRESSLY DISCLAMS ALL MAY ARRANTIES INCLUDING, WITHOUT LIMITATION, THE WARRANTIES OR OTHERWISE, AND EXPRESSLY DISCLAMS OF A PARTICULAR PURPOSE, OR ARISING FROM A COURSE OF DEALING, TRADE USAGE, TRADE PRACTICE, OR INDUSTRY STANDARDS.









































