

PG411 A01


GP104 - 8GB GDDR5, 256b, 256Mx32
Tall DVI-D + DP + DP + HDMI + DP

TABLE OF CONTENTS

Page	Description
1	Table of Contents
2	Block Diagram
3	PCI Express
4	MEMORY: GPU Partition A/B
5	MEMORY: FBA[31:0]
6	MEMORY: FBA[63:32]
7	MEMORY: FBB[31:0]
8	MEMORY: FBB[63:32]
9	MEMORY: GPU Partition C/D
10	MEMORY: FBC[31:0]
11	MEMORY: FBC[63:32]
12	MEMORY: FBD[31:0]
13	MEMORY: FBD[63:32]
14	GPU PWR and GND
15	GPU Decoupling
16	IFPAB DVI-D-DL
17	IFPE DP
18	IFPEF DP
19	IFPC HDMI 2.0/DP
20	IFPD DP
21	MIOA/B Interface and Frame Lock
22	MISC1: Fan, Thermal, JTAG, GPIO, Stereo
23	MISC2: ROM, XTAL, Straps
24	PS: 1V8, 1V8_AON
25	PS: 5V, PEX_VDD





Page	Description
26	PS: FBVDD
27	PS: NVVDD_OVR8
28	PS: Blank Page
29	PS: NVVDD Phase 1-4
30	PS: NVVDD Phase 5 & 6
31	PS: Blank Page
32	PS: Dynamic Power Balance Phases
33	PS: Dynamic Power Balance Logic
34	PS: NV3V3, NV12V
35	PS: Inputs, Filtering, and Monitoring
36	PS: Shutdown and Sequencing
37	PS: 12V Current Steering PSI Control and LED
38	MECH: Bracket/Thermal

ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS AND OTHER DOCUMENTS OR INFORMATION (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." THE MATERIALS MAY CONTAIN KNOWN AND UNKNOWN VIOLATIONS OR DEVIATIONS OF INDUSTRY STANDARDS AND SPECIFICATIONS. NVIDIA MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY OR OTHERWISE WITH RESPECT TO THE MATERIALS OR OTHERWISE, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING, WITHOUT LIMITATION, THE WARRANTIES OF DESIGN, OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR ARISING FROM A COURSE OF DEALING, TRADE USAGE, TRADE PRACTICE, OR INDUSTRY STANDARDS.







MICRO-STAR INT'L CO.,LTD
MS-V330

Size Custom	Document Description Table of Contents	Rev 5.0
Date: <u>Saturday, April 08, 2016</u>		Sheet <u>1</u> of <u>38</u>



LED Connector









QUADRO OPTIONS SHOWN IN YELLOW
and prefix "QD:"


Remove POWER BRAKE































FBVDD







2


- [illegible]





1. DP AUX to DP connector: AUX AC coupled
2. DP AUX to DP-DVI dongle: AUX pass through





STRAP2	STRAP1	STRAP0	RAMCFG[4:0]	
L	L	L	00000	
L	H	L	00010	
L	H	H	00011	
H	H	L	00110	
H	H	H	00111	
ROM_SO	ROM_SI	ROM_SCLK	SOR_EXPOSED[3:0]	1:ENABLE 0:DISABLE
L	L	L	1111 DEFAULT	SOR0/1/2/3 ENABLE
L	L	H	1110	
L	H	L	1101	
L	H	H	1100	
H	L	L	1011	
H	L	H	1010	
H	H	L	1001	
H	H	H	1000	
L	L	M	0111	
L	M	L	0110	
L	M	H	0101	
L	H	M	0100	
H	L	M	0011	
H	M	L	0010	
H	M	H	0001	
H	H	M	0000	

STRAP5	STRAP4	STRAP3	SMB_ALT_ADDR	DEVID_SEL	PCIE_CFG	VGA_DEVICE
M	H	H	1	1	1	1
M	H	L	1	1	1	0
M	L	H	1	1	0	1
M	L	L	1	1	0	0
L	H	M	1	0	1	1
L	M	H	1	0	1	0
L	M	L	1	0	0	1
L	L	M	1	0	0	0
H	H	H	0	1	1	1
H	H	L	0	1	1	0
H	L	H	0	1	0	1
H	L	L	0	1	0	0
L	H	H	0	0	1	1
L	H	L	0	0	1	0
L	L	H	0	0	0	1 DEFAULT
L	L	L	0	0	0	0




H=High :Tied to 1.8V
M=Middle:Tied to 0.9V
L=Low :Tied to 0V

1:SMB_ALT_ADDR ENABLE
0:SMB_ALT_ADDR DISABLE



1:DEVID_SEL REBRAND
0:DEVID_SEL ORIGNAL



1:PCIE_CFG LOW POWER
0:PCIE_CFG HIGH POWER

1:VGA_DEVICE ENABLE
0:VGA_DEVICE DISABLE




CFG[3:0] Config Width	Vendor
0000	256Mx32 256-bit Samsung
0001	256Mx32 256-bit Micron
0010	256Mx32 256-bit Hynix
0011	Reserved
0100	Reserved
0101	Reserved
0110	Reserved
0111	Reserved






PEX PLL Switcher





MICRO-STAR INT'L CO.,LTD
MS-V330

Size Custom	Document Description Table of Contents	Rev 5.0
Date: Saturday, April 09, 2016		Sheet 25 of 39

NCP81274 +UP9511 nVIDIA GPU POWER CKT - 8 PHASE





	MICRO-STAR INT'L CO.,LTD		
	MS-V330		
	Size Custom	Document Description Table of Contents	Rev 5.0
Date: Saturday, April 08, 2016 Sheet: 27 of 36			





MICRO-STAR INT'L CO.,LTD		
MS-V330		
Size	Document Description	Rev
Custom	Table of Contents	5.0
Date: Saturday, April 08, 2016		Sheet 28 of 39

Power Supply: NVVDD PHASE 1~4




Power Supply: VDDC PHASE 5-8








MICRO-STAR INT'L CO.,LTD		
MS-V330		
Size Custom	Document Description Table of Contents	Rev 5.0
Date: Saturday, April 08, 2016		Sheet 31 of 38





MICRO-STAR INT'L CO.,LTD		
MS-V330		
Size Custom	Document Description Table of Contents	Rev 5.0
Date: Saturday, April 08, 2016		Sheet 32 of 38




MICRO-STAR INT'L CO.,LTD		
MS-V330		
Size Custom	Document Description Table of Contents	Rev 5.0
Date: Saturday, April 08, 2016		Sheet 33 of 36









Brackets:

Brackets:





Brackets:




Brackets:



Brackets:



Mechanical Holes Symbol



GPU Stiffner

