## 8885 (C69), 4/8Mx16 DDR, 32/64MB, LFH and RGB-TV-out, PCI

PCI DEVICE ID = 0X172 FOR GF4-MX420-XX.



## MS-8878 BASE ON P73-A04 MODIFY

- Page 1. Add CE1 and RE1 for EMI solution. Add compability with M/B. rename , C22 to C144,R4 to R111,R5 to R112,R6 to R113,U1 to U101 change NET name, U100.AH17 to BUF\_PCIRST\_ also at the R112 and C144. Page 4. U300.9,U300.10,U300.1,U300.2 and U300.7 pin connect to GND.
- Page 5. remove VGA2 function.
- Page 9. Remove SAA7114H function and ADD AV-OUT & S\_OUT conector.

remove L500, C500, C505, C506, C538, C539, C507, C508

- Page 10. C613,C604,C605,C614,L600 and L601 change to DIP type,ADD C620 , Q1 change to AOS4800
- Page 11. R704~R719, R726~R733, R745, R746 PAD size change to 0603 type and Add R747 10k ohm. Add parallel bios function.

R746,R747 stuff ( 00 )

Page 6 . Add Fan power function.

## MS-8878 VER:310 MODIFY

Page 2. Add 74XCT74 buffer for PCI\_RST function.

Page 5. Add 75ohm and bypass Cap. for TV-OUT function.

Page 9. Swap S-OUT.3 and S-OUT.4 net name.


Page 10. Change DIP type CAP. footprint.


Page 11. Change U1000.22 net name


## MS-8885 BASE ON MS-8878 VER:310


- Page 2. Remove AGP interface.
- Page 3. Add PCI interface & level shift IC (Insert page).
- Page 7. Add LFH interface.
- Page 10. Change AV\_OUT & S\_OUT connector to S-TV-out( 9 pin).
- Page 13. Add H/W monitor.
- Page 14. Add Linear Power Supplies.


































5. TV out, video capture, stereo

A DIST	Micro-Star International Co., LTD.	
	MS-8885	
	Size Document Number Custom TV out , video capture	Rev 300
•	Date: Tuesday, November 19, 2002 Sheet 10 of	15

