REAL

PCI-EXPRESS EDGE CONNECTOR



SYMBOL LEGEND

DNI	DO NOT INSTALL
#	ACTIVE LOW
	DIGITAL GROUND
	ANALOG GROUND

Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date:	Friday, April 11, 2008
Rev	17
Sheet	1 of 20
Title	RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI
Doc No.	105-B350xx-00C



Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date: Friday, April 11, 2008 Rev 17

Sheet 2 of 20

Title RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI

Doc No. 105-B350xx-00C



Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date: Friday, April 11, 2008 Rev 17

Sheet 3 of 20

Title RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dpvi

Doc No. 105-B350xx-00C



Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date:	Friday, April 11, 2008
Rev	17
Sheet	4 of 20
Title	RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI
Doc No.	105-B350xx-00C



Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date: Friday, April 11, 2008 Rev 17

Sheet 5 of 20

Title RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI Doc No. 105-B350xx-00C



DIVIDER RESISTORS	DDR2	GDDR3
MVREF TO 1.8V	100R	40.2R
MVREF TO GND	100R	100R

Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date: Friday, April 11, 2008 Rev 17

Sheet 6 of 20

Title RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVT

Doc No. 105-B350xx-00C



Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date: Friday, April 11, 2008 Rev 17

Sheet 7 of 20

Title RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI Doc No. 105-B350xx-00C

CHANNEL A: RANK 0 128MB DDR2



Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date:	Friday, April 11, 2008
Rev	17
Sheet	8 of 20
Title	RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI
Doc No.	105-B350xx-00C



+MVDD = 0.8 * (1+ (ER12 / ER13))

Memory Power Seq









Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date: Friday, April 11, 2008 Rev 17

Sheet 9 of 20

Title RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI

Doc No. 105-B350xx-00C



Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date: Monday, April 28, 2008	Rev 17
Sheet 10 of 20	
Title RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI	Doc No. 105-B350xx-00C



Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date: Friday, April 11, 2008 Rev 17

Sheet 11 of 20

Title RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI

Doc No. 105-B350xx-00C









Vout=1.25V* [1+(ER305/ER304)]





Shared Power Rails



Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date: Friday, April 11, 2008 Rev 17

Sheet 12 of 20

Title RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI Doc No. 105-B350xx-00C

PIN BASED STRAPS

+3.3V

DNI	MR50	10K	R50	10K	GPIO_0	
DNI	MR51	10K	R51	10K	GPIO_1	
MR52	10K	DNI	R52	10K	GPIO_2	
MR53	10K	DNI	R53	10K	GPIO_3	
MR54	10K	DNI	R54	10K	GPIO_4	
MR55	10K	DNI	R55	10K	GPIO_5	
MR56	10K	DNI	R56	10K	GPIO_6	
MR57	10K	NTSC	R57	10K	GPIO_7	
MR58	10K		R58	10K	GPIO_8	
MR59	10K		R59	10K	GPIO_9	
MR63	10K		R63	10K	GPIO_13	
MR62	10K		R62	10K	GPIO_12	
MR61	10K		R61	10K	GPIO_11	
MR65	10K	DNI	R65	10K	GENERICC	GENERICC {3}
DNI	MR64	10K	DNI	R64	10K	GENERICB	GENERICB {3}
MR66	10K		R66	10K	A_VSYNC_DAC1	A_VSYNC_DAC1 {3,14}
MR67	10K		R67	10K	A_HSYNC_DAC1	A_HSYNC_DAC1 {3,14}
MR68	10K	DNI	R68	10K	PSYNC	
MR69	10K	DNI	R69	10K	GPIO21_BB_EN	GPIO21_BB_EN {3}
MR70	10K	DNI	R70	10K		DPVSS-VID0 {4}
MR71	10K	DNI	R71	10K		VID_1 {4}
MR72	10K	DNI	R72	10K		VID_2 {4}
DNI	MR73	10K		R73	10K		DPAVSS-VID3 {4}
MR74	10K	DNI	R74	10K		DPAVSS-VID4 {4}
MR75	10K	DNI	R75	10K		DPAVSS-VID5 {4}
MR76	10K	DNI	R76	10K		VID_6 {3}
MR77	10K	DNI	R77	10K		VID_7 {3}
DNI	MR80	10K		R80	10K	A_VSYNC_DAC2	A_VSYNC_DAC2 {3,15}
MR79	10K	DNI	R79	10K	A_HSYNC_DAC2	A_HSYNC_DAC2 {3,15}
MR60	10K	DNI	R60	10K	DVALID	
DNI	MR87	10K	DNI	R87	10K		PWRCNTL_0 {3}
DNI	MR46	10K				GPIO_22	GPIO_22 {3}
DNI	MR88	10K		R88	10K		GPIO_18 {3}

RV610: INSTALL MR58
RV620: INSTALL R58

PSYNC {3,4}
DVALID {3}

RV610: (DEFAULT) MR70, R73, MR74, MR75 INSTALLED

RV620: MR70, MR73, MR74, MR75 MUST BE INSTALLED

{3} GPIO_[13..0]

GPIO_0
GPIO_1
GPIO_2
GPIO_3
GPIO_4
GPIO_5
GPIO_6
GPIO_7
GPIO_8
GPIO_9
GPIO_10
GPIO_11
GPIO_12
GPIO_13

GPIO(0) - TX_PWRS_ENB (Transmitter Power Savings Enable) ATI PCIE FEATURE I
0: 50% Tx output swing for mobile mode
1: full Tx output swing (Default setting for Desktop)

GPIO(1) - TX_DEEMPH_EN (Transmitter De-emphasis Enable) ATI PCIE FEATURE II
0: Tx de-emphasis disabled for mobile mode
1: Tx de-emphasis enabled (Default setting for Desktop)

GPIO(3:2) - ATI Internal Use Only - Reserved (Default: 00)

GPIO(4) - DEBUG_ACCESS
ATI Internal Use Only - Reserved (Default: 0)

GPIO(5) - ATI Internal Use Only - Reserved (Default: 0)

GPIO(6) - ATI Internal Use Only - Reserved (Default: 0)

GPIO(7) - TV OUT STANDARD (Jumper position overwrite resistor settings)
0 - PAL TVO (Jumper is closed)
1 - NTSC TVO (Jumper is open)

GPIO(8) - ATI Internal Use Only - Reserved (Default: 0)

GPIO(9,13:11) - CONFIG[3..0] IF BIOS_ROM_EN=1 [default] (GPIO_22)
tmel - AT25F512A (512 kbit)0010
AT25F1024A (1 Mbit)0011
ST Microelectronics- M25P05A (512 kbit) 0100
M25P10A (1 Mbit) 0101
M25P20 (2 Mbit) 0101
Chingis (formerly PMC) -
Pm25LV512 (512 kbit) 0100
Pm25LV010 (1 Mbit) 0101

If BIOS_ROM_EN = 0, then Config[2:0] defines the primary memory aperture size. (Config 3 = don care).
x000 128MB
x001 256MB
x010 64MB
x011 32MB
x100 512MB
x101 1GB
x110 2GB
x111 4GB

GENERICC, GENERICB - ATI Internal Use Only - Reserved (Default: 0)

VSYNC - VIP_DEVICE_STRAP_EN
0: Slave VIP host port devices present (use if Theater is populated)
1: No slave VIP host port devices reporting presence during reset (use for configurations without video-in)

HSYNC - ATI Internal Use Only - Reserved (Default 0)

PSYNC - VGA DISABLE : 1 for disable (set to 0 for normal operation)

GPIO_21 - ATI Internal Use Only - Reserved (Default: 0)

VID_0 - ATI Internal Use Only - Reserved (Default: 0)

VID_1 - MSI_DIS (Default: 0)

VID_2 - ATI Internal Use Only - Reserved (Default: 0)

VID_3 - ATI Internal Use Only - Reserved (Default: 0)

VID_4 - ATI Internal Use Only - Reserved (Default: 0)

VID_5 - 64BAR_EN_A (Default: 0)
Enable 64-bit BARS

VID_6:7 - ATI Internal Use Only - Reserved (Default: 00)

VSYNC - DDR2 VENDOR SELECT ATI Board Feature I
(see GPIO_18)

HSYNC2 - ATI Internal Use Only - Reserved (Default: 0)

BIF_CLK_PM_EN
0 - Disable CLKREQ# power management capability
1 - Enable CLKREQ# power management capability

GPIO_15 - FOR FUTURE EXPANSION

GPIO_22_ROMCSb - Enable external BIOS ROM device (Default 1)

GPIO_18 - DDR2 MEM VENDOR [V2SYNC:GPIO_18] ATI Board Feature I
QUIMONDA [0:0]
HYNIX [0:1]
SAMSUNG [1:0]

Pull-Down Resistors are for BU until built-in pull-downs are verified.

Overlap pads to save space and to prevent assembly of both resistors.

Layout

Ground — High logic voltage

Signal

Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date: Friday, April 11, 2008 Rev 17

Sheet 13 of 20

Title RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI

Doc No. 105-B350xx-00C

Place close to Connector
Pseudo differential RGB signals should be routed from the ASIC to the display connector without switching reference plane or running over split plane
Resistors are footprint options for the inductors. Footprints should be overlapped. (R1024-26)

{3} A_R_DAC1
{3} A_RB_DAC1
{3} A_G_DAC1
{3} A_GB_DAC1
{3} A_B_DAC1
{3} A_BB_DAC1

R1029 37.4R
R1028 37.4R
R1027 37.4R
R1003 75R
R1002 75R
R1001 75R
C1001 8.0pF 402
C1002 8.0pF 402
C1003 8.0pF 402
C1005 8.0pF 402
C1006 8.0pF 402
C1004 8.0pF 402

A_R_DAC1_M L1004 47nH
A_G_DAC1_M L1005 47nH
L1006 47nH

BAT54SLT1 ED62
BAT54SLT1 ED63
BAT54SLT1 ED64
+3.3V

+5V
+5V_VESA
EF1 0.2A

A_R_DAC1_F
A_G_DAC1_F
A_B_DAC1_F

DDCDATA_DAC1_R
DDCCLK_DAC1_R
A_HSYNC_DAC1_R
A_VSYNC_DAC1_R

Place close to Connector
SHOULD BE A LOW INDUCTANCE PATH TO PIN 5

C1010 100nF

MJ1001
1 R
2 G
3 B
11 MS0
12 MS1
4 MS2
15 MS3
9 NC
13 HS
14 VS
5 VSS
6 VSS#6
7 VSS#7
8 VSS#8
10 VSS#10
16 CASE
17 CASE#17
G3179C219-005

SLIM VGA

{3} CRT1DDCDATA
R1004 10K 402
R1005 1.9K 402
BSH111 Q1001
DDCDATA_DAC1_5V
R1006 33R
DDCDATA_DAC1_R

{3} CRT1DDCCLK
R1007 10K 402
R1008 1.9K 402
BSH111 Q1002
DDCCLK_DAC1_5V
R1009 33R
DDCCLK_DAC1_R

C1999 100nF
{3,13} A_HSYNC_DAC1
A_HSYNC_DAC1_B
U1999A SN74HCT125D
R1010 33R 402
A_HSYNC_DAC1_R

{3,13} A_VSYNC_DAC1
A_VSYNC_DAC1_B
U1999B SN74HCT125D
R1011 33R 402
A_VSYNC_DAC1_R

SYNC and DDC should be routed from the ASIC to the display connector without switching reference plane or running over split plane

DB15 pin	Standard VGA	DDC1 Host	DDC2B or DDC2B+ Host	DDC2AB Host	DDC1/2 Display
11	Monitor ID bit 0	Monitor ID bit 0	Monitor ID bit 0	Monitor ID bit 0	Optional
12	Monitor ID bit 1	Data from display	SDA	SDA	SDA
4	Monitor ID bit 2	Monitor ID bit 2	Monitor ID bit 2	Monitor ID bit 2	Optional
15	Monitor ID bit 3	Open	SCL	SCL	SCL
		+5V	+5V	+5V	
9	N/C Mechanical Key	50mA min 1A max	50mA min 1A max	300mA min 1A max	Optional
Hardware Support	No	Yes	Yes	No	Yes

Based on VESA Display Data Channel (DDC) Standard Ver. 3 Dec. 15, 1997

{4} TjX2M
{4} TjX2P
R107 0R
R108 0R
R102 100R

{4} TjX4M
{4} TjX4P
R109 0R
R111 0R
R104 100R

DDCCLK_DAC1_R
DDCDATA_DAC1_R
A_VSYNC_DAC1_R

{4} TjX1M
{4} TjX1P
R112 0R
R114 0R
R101 100R

{4} TjX3M
{4} TjX3P
R115 0R
R116 0R
R103 100R

+3.3V
Q1021 MMBT3904
R1022 10K
HPD_DVI1
{3} HPD1

{4} TjX0M
{4} TjX0P
R117 0R
R118 0R
R100 100R

{4} TjX5M
{4} TjX5P
R119 0R
R120 0R
R105 100R

R1023 10K
{4} TjXCP
{4} TjXCM
R121 0R
R122 0R
R106 100R

A_R_DAC1_F
A_G_DAC1_F
A_B_DAC1_F
A_HSYNC_DAC1_R

+5V_VESA
J1001
25 CASE
1 TMDS Data2-
2 TMDS Data2+
3 TMDS Data2/4 Shield
4 TMDS Data4-
5 TMDS Data4+
6 DDC Clock
7 DDC Data
8 Analog VSYNC
9 TMDS Data1-
10 TMDS Data1+
11 TMDS Data1/3 Shield
12 TMDS Data3-
13 TMDS Data3+
14 +5V Power
15 GND (for +5V)
16 Hot Plug Detect
17 TMDS Data0-
18 TMDS Data0+
19 TMDS Data0/5 Shield
20 TMDS Data5-
21 TMDS Data5+
22 TMDS Clock Shield
23 TMDS Clock+
24 TMDS Clock-
C1 Analog Red
C2 Analog Green
C3 Analog Blue
C4 Analog HYNC
C5 Analog GND
C6 Analog GND#C6
26 CASE#26
27 CASE#27
28 CASE#28
29 CASE#29
30 CASE#30
DVI_CONNECTOR

TMDS_2(Daul_Link) + DAC_1-CRT

Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date: Friday, April 11, 2008
Rev 17
Sheet 14 of 20
Title RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO DVI
Doc No. 105-B350xx-00C



TMDS_1(Single_Link) + DAC_2-CRT

Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date:	Friday, April 11, 2008
Rev	17
Sheet	15 of 20
Title	RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI
Doc No.	105-B350xx-00C



The 7-pin MiniDIN footprint allows one of the two MiniDINs:
- 7-pin Svideo/Composite MiniDIN P/N 6071001500G
- 4-pin Svideo MiniDIN P/N 6070001000G

Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date: Friday, April 11, 2008 Rev 17

Sheet 16 of 20

Title RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI Doc No. 105-B350xx-00C







Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date: Friday, April 11, 2008 | Rev 17

Sheet 17 of 20

Title: RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI

Doc No. 105-B350xx-00C







Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date: Friday, April 11, 2008 Rev 17

Sheet 18 of 20

Title RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI Doc No. 105-B350xx-00C

<variant name>

Title	Schematic No.	Date:
RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI	105-B350xx-00C	**Friday, April 11, 2008**

REVISION HISTORY

NOTE: **This schematic represents the PCB, it does not represent any specific SKU.**
For Stuffing options (component values, DNI , ? please consult the product specific BOM.
Please contact AMD representative to obtain latest BOM closest to the application desired.

Rev 17

Sch Rev	PCB Rev	Date	REAL REVISION DESCRIPTION
01	00A	2007.05.07	START NEW SCHEMATIC. DERIVED FROM B170 (RV610) SCHEMATIC.
02	00A	2007.05.17	p. 4 MR155/R155 FIX SHORT
03	00A	2007.05.17	RM R7, NR7, R5, MB60, MR45, R45, R890, R1248, R1247, R1242, R1243, C853, C863; ADD R2, B890, MR890, C846; CHANGE R1022, R1023;
04	00A	2007.05.22	REMOVE GND_TXVSSR, GND_PVSS; AG23 NOW NC - WAS SCHEM MISTAKE; ADD R858 FOR BUO; R858 CHANGE TO 1210;
05	00A	2007.05.24	CTF: ADD Q1252, R1254, R1255, R1256, R1258, Q1253, Q1254, CHANGE U1250 TO SINGLE FF; UPDATE BLOCK DIAGRAM.
06	00A	2007.05.25	LVTM: ADD R110, RM R109, MR109, R108, R107;
07	00A	2007.05.28	LVTM: ADD C118, RM C104; REMOVE MR85, MR86 FOR SIMPLIFICATION;
08	00A	2007.05.28	XTALIN/OUT: LAYOUT EASEMENT; REMOVE MR108 (R849 ALREADY THERE); LVTM: ADD C119 (LOWER COST OPTION); POWER SUPPLY: REMOVE R706, MR707, R606 & MR607;
09	00A	2007.05.29	REMOVAL OF +5V: ADD R861, MR861, R862, REG861, R869, R863, R867; REMOVE MU830, U830, C830. R833, R834, C831, R832, MR832, R831, MR831; CONNECT DDC TO 5V_VESA;
010	00A	2007.05.30	CHNG C858 TO 3.3VBUS; CONNECTION TO R845 CHNG; ADD R870, MR870, C867;
011	00A	2007.05.30	REMOVE R4033; REMOVE B201-204; ADD R30-33 [PLACE NEAR ASIC]; REMOVE R3004, R3005;
012	00A	2007.05.31	REMOVE C164-C166, C170, C172 PER SIMULATION RESULTS - THESE CAPS DO NOT IMPROVE DECOUPLING. RM TP860 (LAYOUT CONSTRAINTS. ALREADY ICT TP ON THAT NET);
013	00A	2007.05.31	RM R154-R157, MR154-157 -> FUNCTIONALITY TAKEN BY EXISTING STRAPS. LAYOUT USE PLACE OF M/R154-7; ADD R7; RM MR706, MR606, B889, R863; ADD D861;
014	00A	2007.05.32	ADD SOCKET SK1
015	00A	2007.06.1	SK? CORRECTED TO SK1.
016	00B	2007.06.25	NO NETLIST CHANGES; - MOUNTING HOLES CHANGED TO 3.175mm;
017	00C	2007.10.01	p. 1 - CONNECT B7 TO GND (SEE PA RV6XX H1) - REMOVE R2. IT IS ALWAYS POPULATED, NO NEED TO ZERO OHM. THIS BOARD DOES NOT SUPPORT JTAG DEBUG; p. 11 - REMOVE R839. THIS CIRCUIT IS VERIFIED, THERE IS NO NEED TO BE ABLE TO DISCONNECT IT; p. 12 - REMOVE R870 - THIS OPTION NOT USED, VCNTRL MUST BE HIGHER THAN +3.3V; - MR870 REMOVED - ALWAYS POPULATED, DO NOT NEED ZERO OHM RESISTOR OPTION; - REMOVE R860 - WAS BRING UP ONLY OPTION; p. 17 - REPLACED FAN CIRCUIT WITH ONE THAT HAS FEEDBACK: - ADD R4033, R4031, R4019, R4034, R4006, R4035, Q4004, R4035, Q40002. R4009, R4011, Q4003, R4012, R4013;



RV620 B350 DDR2-BGA84 LP 4-Layer

REV 01

Advanced Micro Devices Inc.
1 Commerce Valley Drive East
Markham, Ontario

Date:	Friday, April 11, 2008
Rev	17
Sheet	20 of 20
Title	RH RV620 256/128MB DDR2-BGA84 32/16Mx16 VO dDVI
Doc No.	105-B350xx-00C