V078-10 BASE ON V079-0A modify

P501-A01 DESIGN -- G73, 256 MB DDR2, VGA, DVI-I, HDTV

PAGE SUMMARY:

REV HISTORY

Base on P501_A01 modify

7/25-0A

1.PAGE:12 Removed TMDS C/D connecter

2.PAGE:10 Add DACC Fly cable DSub

9/26-0A

1.PAGE:10,16 revised DACA hotplug circuit

10/19-10

1.chage Q3,Q4,Q6 footprint for power reserve

SKU	VARIANT	NVPN	ASSEMBLY
0	0000	600-10501-0000-100	G73 400/350MHz 256MB 128bit DDR2 16MX16 DVI-I+VGA+HDTVOUT
1	0001	600-10501-0001-100	G73-V 375/350MHZ 256MB 128bit DDR2 16MX16 DVI-I+VGA+HDTVOUT
2	<UNDEFINED>	<UNDEFINED>	<UNDEFINED>
3	<UNDEFINED>	<UNDEFINED>	<UNDEFINED>
4	<UNDEFINED>	<UNDEFINED>	<UNDEFINED>
5	<UNDEFINED>	<UNDEFINED>	<UNDEFINED>
6	<UNDEFINED>	<UNDEFINED>	<UNDEFINED>
7	<UNDEFINED>	<UNDEFINED>	<UNDEFINED>
8	<UNDEFINED>	<UNDEFINED>	<UNDEFINED>
9	<UNDEFINED>	<UNDEFINED>	<UNDEFINED>
10	<UNDEFINED>	<UNDEFINED>	<UNDEFINED>
11	<UNDEFINED>	<UNDEFINED>	<UNDEFINED>
12	<UNDEFINED>	<UNDEFINED>	<UNDEFINED>
13	<UNDEFINED>	<UNDEFINED>	<UNDEFINED>
14	<UNDEFINED>	<UNDEFINED>	<UNDEFINED>
15	<UNDEFINED>	<UNDEFINED>	<UNDEFINED>

Micro-Star International Co., LTD.

MS-V079

Size: Custom | Document Number: P501 Overview | Rev: 0A

Date: Friday, October 20, 2006 | Sheet 1 of 20

16X PCIe Interface



GPU: FB-Interface A



Micro-Star International Co., LTD.		
MS-V079		
Size: Custom	Document Number: GPU: FB-Interface A	Rev: 0A
Date: Wednesday, October 25, 2006	Sheet 3 of 20	

FBA MEMORY 1st bank 0..31

PLACE ALL DISCRETE COMPONENTS AS NEAR AS POSSIBLE TO MEMORY











Micro-Star International Co., LTD.			
MS-V079			
Size: Custom	Document Number: FBA MEMORY 1st bank 0..31		Rev: 0A
Date: Thursday, October 26, 2006	Sheet 4 of 20		

FBA MEMORY 1st bank 32..63

PLACE ALL DISCRETE COMPONENTS AS NEAR AS POSSIBLE TO MEMORY



Micro-Star International Co., LTD.

MS-V079

Size: Custom | Document Number: FBA MEMORY 1st bank 32..63 | Rev: 0A

Date: Thursday, October 26, 2006 | Sheet 5 of 20

GPU: FB-Interface C



FBC MEMORY 2nd bank 0..31

PLACE ALL DISCRETE COMPONENTS AS NEAR AS POSSIBLE TO MEMORY



Micro-Star International Co., LTD.			
MS-V079			
Size: Custom	Document Number: FBC MEMORY 2nd bank 0..31		Rev: 0A
Date: Thursday, October 26, 2006	Sheet 7 of 20		

FBC MEMORY 2nd bank 32..63

PLACE ALL DISCRETE COMPONENTS AS NEAR AS POSSIBLE TO MEMORY



Primary Display (DACA), Slim DB15

DACA NET RULES

NET	NV_CRITICAL	NV_IMPEDANCE	DIFFPAIR
DACA_RED	1	50OHM	
DACA_GREEN	1	50OHM	
DACA_BLUE	1	50OHM	
DACA_RED_C	1	50OHM	
DACA_GREEN_C	1	50OHM	
DACA_BLUE_C	1	50OHM	
DACA_HSYNC	2	50OHM	
DACA_VSYNC	2	50OHM	
A VB	2	50OHM	
A HB	2	50OHM	
DACA_HSYNC_BUF	2	50OHM	
DACA_VSYNC_BUF	2	50OHM	
DACA_HSYNC_C	2	50OHM	
DACA_VSYNC_C	2	50OHM	
I2CA_SCL	2	50OHM	
I2CA_SDA	2	50OHM	
I2CA_SCL_T	2	50OHM	
I2CA_SDA_T	2	50OHM	
I2CA_SCL_C	2	50OHM	
I2CA_SDA_C	2	50OHM	

NET	VOLTAGE	MAX_CURRENT	MIN_WIDTH
DACA_VDD	3.30000	0.07	16.0
DACA_VREF			10.0
DACA_RSET			10.0

DACA RGB-FILTER





Micro-Star International Co., LTD.	
MS-V079	
Size: Custom	Document Number: Primary Display (DACA), Slim DB15
Rev: 0A	
Date: Thursday, October 26, 2006	Sheet 9 of 20

Secondary Display (DACC), DB15

DACC NET RULES

NET	NV_CRITICAL	NV_IMPEDANCE	DIFFPAIR
DACC_RED	1	50OHM	
DACC_GREEN	1	50OHM	
DACC_BLUE	1	50OHM	
DACC_RED_C	1	50OHM	
DACC_GREEN_C	1	50OHM	
DACC_BLUE_C	1	50OHM	
DACC_HSYNC	2	50OHM	
DACC_VSYNC	2	50OHM	
CVB	2	50OHM	
CHB	2	50OHM	
DACC_HSYNC_BUF	2	50OHM	
DACC_VSYNC_BUF	2	50OHM	
DACC_HSYNC_C	2	50OHM	
DACC_VSYNC_C	2	50OHM	
I2CB_SCL	2	50OHM	
I2CB_SDA	2	50OHM	
I2CB_SCL_T	2	50OHM	
I2CB_SDA_T	2	50OHM	
I2CB_SCL_C	2	50OHM	
I2CB_SDA_C	2	50OHM	

NET	VOLTAGE	MAX_CURRENT	MIN_WIDTH
DACC_VDD	3.30000	0.07 / 0.14	16.0
DACC_VREF			10.0
DACC_RSET			10.0

I2C B for HDMI.

FOR ESD DIODES

Place in output filter section!

Micro-Star International Co., LTD.			
MS-V079			
Size: Custom	Document Number: Secondary Display (DACC), DB15		Rev: 0A
Date: Thursday, October 26, 2006		Sheet 10 of 20	

INTERNAL TMDS .. LINK A & B

IFPAB NET RULES

NET	NV_CRITICAL	NV_IMPEDANCE	DIFFPAIR

NET	VOLTAGE	MAX_CURRENT	MIN_WIDTH
IFPAB_PLLVDD	3.30000	0.04	16.0
IFPAB_IOVDD	3.30000	0.24	16.0
IFPABRSET			12.0
DVI_SOUTH_HPD_C	1	50OHM	
DVI_SOUTH_HPD_R	1	50OHM	



Hotplug Detection



Micro-Star International Co., LTD.	
MS-V079	
Size: Custom	Document Number: INTERNAL TMDS .. LINK A & B
Rev: 0A	
Date: Wednesday, October 25, 2006	Sheet 11 of 20

INTERNAL TMDS .. LINK C

IFPAB NET RULES

NET	NV_CRITICAL	NV_IMPEDANCE	DIFFPAIR
IFPCD_RSET	1	50OHM	
DVI_MID_HPD_C	1	50OHM	
DVI_MID_HPD_R	1	50OHM	

NET	VOLTAGE	MAX_CURRENT	MIN_WIDTH
IFPCD_PLLVDD	3.30000	0.04	16.0
IFPC_IOVDD	3.30000	0.12	16.0
IFPD_IOVDD	3.300000	0.12	16.0



CEC pullup and clamping must be disconnected from HDMI connector when Power down

G3 VIP/MIOB/MIOA

G3 VIP/MIOB



G3 MIOA



Micro-Star International Co., LTD.		
MS-V079		
Size: Custom	Document Number: G3 VIP/MIOB/MIOA	Rev: 0A
Date: Wednesday, October 25, 2006	Sheet 13 of 20	

DACB .. MiniDIN VIDEO OUT CONNECTOR

DACB NET RULES

NET	NV_CRITICAL	NV_IMPEDANCE	DIFFPAIR
DACB_C_OUT	1	560HM	
MDIN_COUT_C	1	560HM	
DACB_CVBS_OUT	1	560HM	
MDIN_YOUT_C	1	560HM	
DACB_PB_OUT	1	560HM	
MDIN_PBOUT_C	1	560HM	
MDIN_SCL_C	2	500HM	
MDIN_SDA_C	2	500HM	

NET	VOLTAGE	MAX_CURRENT	MIN_WIDTH
DACB_VDD	3.30000	0.07	16.0
DACB_VREF			16.0
DACB_RSET			16.0





Micro-Star International Co., LTD.	
MS-V079	
Size: Custom	Document Number: DACB .. MiniDIN VIDEO OUT
Rev: 0A	
Date: Wednesday, October 25, 2006	Sheet 14 of 20

GND/XTAL/PLLVDD







	Micro-Star International Co., LTD.		
	MS-V079		
Size: Custom	Document Number: GND/XTAL/PLLVDD		Rev: 20
Date: Thursday, October 26, 2006	Sheet 15 of 20		

GPIO / JTAG / HDCP / BIOS / SPDIF



GPIO & JTAG

GPIO Assignment Table

GPIO	I/O	FUNCTION
0	IN	RESERVED
1	IN	DVI SOUTH HOTPLUG DET
2	IN	RESERVED
3	IN	RESERVED
4	IN	RESERVED
5	OUT	RESERVED
6	OUT	RESERVED
7	IN	RESERVED
8	IN	RESERVED
9	OUT	FAN Control(ON/OFF)
10	OUT	RESERVED
11	IN	RESERVED
12	IN	RESERVED

GPIO ON/OFF FAN Control



BIOS (serial)



HDCP



SPDIF



MISC NET RULES

NET	NV_CRITICAL	NV_IMPEDANCE	DIFFPAIR
I2CC_SCL	2	50OHM	
I2CC_SDA	2	50OHM	
I2CC_SCL_G	2	50OHM	
I2CC_SDA_G	2	50OHM	
I2CH_SCL	2	50OHM	
I2CH_SDA	2	50OHM	
ROM_CS*	2	50OHM	
ROM_SI	2	50OHM	
ROM_SO	2	50OHM	
ROM_SCLK	2	50OHM	
DVI_SOUTH_HPD	2	50OHM	
SPDIF	1	50OHM	
SPDIF_IN	1	50OHM	

Micro-Star International Co., LTD.	
MS-V079	
Size: Custom	Document Number: GPIO / JTAG / HDCP / BIOS / SPDIF
Rev: 0A	
Date: Wednesday, October 25, 2006	Sheet 16 of 20

STRAPS, Mechanical Parts

Straps

Assembly: BIOS



REG: NV_PEXTDEV_BOOT_0

Bit	Signal	VALUE_ID	VALUEs
00: PCI_AD_SWAP		PCI_AD_SWAP	0 REVERSED 1 NORMAL
01: SUB_VENDOR		SUB_VENDOR	0 NO_BIOS 1 read from BIOS
02: RAM_CFG_0		RAM_CFG[3:0]	0000 8Mx16 DDR2 128BIT 0001 RFU 0010 16Mx16 DDR2 128BIT 0011 RFU 0100 RFU 0101 RFU 0110 RFU 0111 32Mx16 DDR2 128BIT 1000 8M x16 DDR2 64BIT 1001 RFU 1010 16Mx16 DDR2 64BIT 1011 RFU 1100 RFU 1101 RFU 1110 RFU 1111 32Mx16 DDR2 64BIT
03: RAM_CFG_1			
04: RAM_CFG_2			
05: RAM_CFG_3			
06: CRYSTAL_0		CRYSTAL[1:0]	00 13.500 Mhz 01 14.318180 Mhz 10 27.000 Mhz 11 unknown
22: CRYSTAL_1			
07: TV_MODE_0		TV_MODE[1:0]	00 SECAM 01 NTSC 10 PAL 11 CRT
08: TV_MODE_1			
09: AGPBlxEnable		AGP_30_8x	0 AGP8x enabled 1 AGP8x disabled
10: AGP_SBA		AGP_SBA[0]	0 SBA enabled 1 SBA disabled
11: AGP_FASTWR		AGP_FASTWR[0]	0 enabled 1 disabled
12: PCI_DEVID_0		PCI_DEVID[3:0]	0000 0x140 ... 1111 0x014F 0000 (default 0x140)
13: PCI_DEVID_1			0101 (0x145)
20: PCI_DEVID_2			
21: PCI_DEVID_3			
14: BUS_TYPE		BUS_TYPE[3]	0 PCI 1 AGP
15: FP_IFACE		FP_IFACE[0]	0 24Bit 1 12Bit (DEFAULT)
23: FB_0		FB[1:0]	00 64M 01 128M 10 256M (DEFAULT) 11 512M
24: FB_1			
25: BR		BR[0]	0 BRIDGE disabled 1 BRIDGE enabled
26: BR_128M		BR bits are ignored if BRIDGE is disabled	
27: BR_AGP			
28: BR_ID			
29: ROM_TYPE_0		ROM_TYPE[1:0]	00 Parallel 01 Serial_AT25F 10 Serial_SST45VF 11 RFU
30: ROM_TYPE_1			
16: USER_0		STRAP_USER[3:0]	0000 (default)
17: USER_1			
18: USER_2			
19: USER_3			
31: SLOT_CLOCK_CFG			0 COMMON PCIE REF CLK enabled 1 COMMON PCIE REF CLK disabled

REG: NV_STRAP_1

Bit	Signal	VALUE_ID	VALUEs
11: PEX_PLL_EN_TERM100			0 (default – internal term on)
12: 3GIO_PADCFG_LUT_ADR[0]			
13: 3GIO_PADCFG_LUT_ADR[1]			
14: 3GIO_PADCFG_LUT_ADR[2]			

Mechanical parts



MSI	Micro-Star International Co., LTD.		
	MS-V079		
Size: Custom	Document Number: STRAPS, Mechanical Parts		Rev: 0A
Date: Thursday, October 26, 2006	Sheet 17 of 20		

Power Supply:TMDS_IOVDD/A3V3/5V

NETNAME	MAX_CURRENT	MIN_LINE_WIDTH	VOLTAGE
DDC_5V	0.1	12.0	5.00000
A2V5	0.96	25.0	2.50000
TMDS_IOVDD	0.24	20.0	3.30000
A3V3	0.4	20.0	3.30000
GND		35.0	0.000000

DDC 5V



TMDS IO SUPPLY WITH BACKDRIVE PROTECTION



A3V3 Power Supply



FM1 FM4

FM2 FM5

FM3 FM6

EMC suggestion reserve



MSI	Micro-Star International Co., LTD.	
	MS-V079	
Size: Custom	Document Number: TMDS_IOVDD/A3V3/5V	Rev: 0A
Date: Wednesday, October 25, 2006	Sheet 18 of 20	

PowerSupplyI: NVVDD, A2V5

Net Name	LINE_WIDTH	Current	Voltage
12V_F	30MIL	3	12V
NVVDD PEX1V2	30MIL 24MIL	15 1.5	1.2V 1.20000
NVVDD_SENSE	16MIL	0.5	1.2V
NVVDD_SENSE_M	16MIL	0.5	1.2V





A2V5

Vout = VRef * (1+Rtop/Rbot)

2.48V = 0.8V * (1+(3.32k/1.07k)) (ISL6549)

2.5V = 0.5V * (1+(4.53k/1.13k)) (SC2621A)

NVVDD

Vout = VRef * (1+Rtop/Rbot)

1.2V = 0.8V * (1+(1.54k/3.09k)) (ISL6549)

1.2V = 0.5V * (1+(14.7k/10.5k)) (SC2621A)

1.153V = 0.8V * (1+(1.18k/2.67k)) (ISL6549)

MSI	Micro-Star International Co., LTD.		
	MS-V079		
Size: Custom	Document Number: NVVDD, A2V5		Rev: 0A
Date: Thursday, October 26, 2006		Sheet 19 of 20	

PowerSupplyIII: FBVDDQ,PEX1V2