



(1) PCI-EXPRESS EDGE CONNECTOR




GIGABYTE			
Title: PCI Express			
Size	Custom	Document Number	Rev
		GV-N580GAMING-4GD	1.0
Date:	Monday, February 27, 2017		Sheet 1 of 29


(2) ELLESMERE PCIE INTERFACE




(3) ELLESMERE MEM INTERFACE CH A/B




(4) ELLESMERE MEM INTERFACE CH C/D



(5) GDDR5 MEMORY CH A/B





(6) GDDR5 MEMORY CH C/D




(7) ELLESMERE GPIO STRAP CF XTAL

SCUDBG BUS		
IO ADDRESS	FUNCTION	DEVICE
DDCVGA BUS		
IO ADDRESS	FUNCTION	DEVICE
0x00	EXT TEMP SENSOR	LM8903






PIN BASED STRAPS		
2	1	7
3	2	8
4	3	9
5	4	10
6	5	11
7	6	12
8	7	13
9	8	14
10	9	15
11	10	16
12	11	17
13	12	18
14	13	19
15	14	20
16	15	21
17	16	22
18	17	23
19	18	24
20	19	25
21	20	26
22	21	27
23	22	28
24	23	29
25	24	30
26	25	31
27	26	32
28	27	33
29	28	34
30	29	35
31	30	36
32	31	37
33	32	38
34	33	39
35	34	40
36	35	41
37	36	42
38	37	43
39	38	44
40	39	45
41	40	46
42	41	47
43	42	48
44	43	49
45	44	50
46	45	51
47	46	52
48	47	53
49	48	54
50	49	55
51	50	56
52	51	57
53	52	58
54	53	59
55	54	60
56	55	61
57	56	62
58	57	63
59	58	64
60	59	65
61	60	66
62	61	67
63	62	68
64	63	69
65	64	70
66	65	71
67	66	72
68	67	73
69	68	74
70	69	75
71	70	76
72	71	77
73	72	78
74	73	79
75	74	80
76	75	81
77	76	82
78	77	83
79	78	84
80	79	85
81	80	86
82	81	87
83	82	88
84	83	89
85	84	90
86	85	91
87	86	92
88	87	93
89	88	94
90	89	95
91	90	96
92	91	97
93	92	98
94	93	99
95	94	100


(8) ELLESMERE DAC1 LOCK




GIGABYTE			
Title ELLESMERE DAC1 LOCK			
Size	Document Number	Rev	
Custom	GV-RX580GAMING-4GD	1.0	
Date:	Monday, February 27, 2017	Sheet	8 of 28










OPTIONAL ESD PROTECTION DIODES




GIGABYTE			
ELLESMERE LVTMDP E/F			
Size	Document Number	Rev	
Customer	GV-RX580GAMING-4GD	1.0	
Date	Monday, February 27, 2017	Sheet	11 of 29


(12) ELLESMERE POWER











-2%


IOUT = 1.3A RMS MAX

The circuit diagram shows a current source with a feedback loop. The output current IOUT is 1.3A RMS MAX. The feedback loop is formed by a resistor network (R302, R301, R303) and a capacitor (C304). The feedback signal is compared to a reference voltage (VREF) at the inverting input of the op-amp. The output of the op-amp drives the current source. The feedback loop is highlighted with a green dashed circle. The feedback signal is also compared to a reference voltage (VREF) at the inverting input of the op-amp. The output of the op-amp drives the current source. The feedback loop is highlighted with a green dashed circle.

Modify size to 0603 save cost by dtho 20160315


2016.4.16 Modify Size By Bingq.cui

VOUT = Vref x (1 + RS/R4)







GIGABYTE			
Title SMALL RAIL REGULATORS			
Size Custom	Document Number GV-RX580GAMING-4GD		Rev 1.1
Date: Monday, February 27, 2017	Sheet	20 of 28	











(19) POWER MANAGEMENT



6PIN&8PIN CONNECT COLAY by diho 20160514



POWER UP SEQUENCE			
Sub-Rails (3.3V/12V UP) → +1.8V → 0.900V	RF_VDDC VDDC → VDDC VDD		





The diagram illustrates a PCB layout for a 100W LED driver. Key components and their placements include:


- Capacitors:** Several electrolytic capacitors are shown, including a 1000µF 25V capacitor at the input, a 100µF 25V capacitor at the output, and various smaller capacitors (e.g., 10µF, 1µF, 0.1µF) for filtering and decoupling.
- Resistors:** Various resistors are placed throughout the circuit, including a 10kΩ resistor for a feedback loop and several 1W resistors for power dissipation.
- LED Strip:** A 100W LED strip is connected to the output of the driver, with a current of 1.5A and a voltage of 12V indicated.
- IC Footprint:** A large integrated circuit footprint is shown, labeled "100W LED DRIVER". It includes pins for VCC, GND, and LED, and is connected to a 100W LED strip.
- Power and Grounding:** The layout shows a power input of 100W and a ground connection. The output is connected to a 100W LED strip.








(21) DEBUG CIRCUITS



DIGITAL POTS




DIGITAL POTS




GIGABYTE			
Title DEBUG CIRCUITS			
Size	Document Number		Rev
Custom	GV-RX580GAMING-4GD		1.0
Date:	Monday, February 27, 2017	Sheet	24 of 29

0	00A	0000000	
1	00B	0000000	1. Add SPI0 to SPI000 10000 2. Update SPI000 data register
2	00C	0000000	PC000: - add serial resistor R1000 - R1007 - add pull-down resistor L1000 - L1007 Remove C400, C403, V0400, C410, C414, R400
3	00D	0000000	Modify G000 Design

GIGABYTE			
Title			
BLOCK DIAGRAM			
Size	Document Number		Rev
Custom	GV-RX580GAMING-4GD		1.0
Date:	Monday, February 27, 2017	Sheet	28 of 28





Vout = 8 ~ 7.5V


ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." THE MATERIALS MAY CONTAIN KNOWN AND UNKNOWN VIOLATIONS OR DEVIATIONS OF INDUSTRY STANDARDS AND SPECIFICATIONS. NVIDIA MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY OR OTHERWISE WITH RESPECT TO THE MATERIALS AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING, WITHOUT LIMITATION, THE WARRANTIES OF DESIGN, NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR ARISING FROM A COURSE OF DEALING, TRADE USAGE, TRADE PRACTICE, OR INDUSTRY STANDARDS.

ASSEMBLY
PAGE DETAIL


ASSEMBLY DESCRIPTION
MECH Bracket Thermal

File			
Rev	Document Number	Rev	1.0
Customer	GM-4000GAMING-400		
Date	Monday, February 27, 2017	Sheet	28 of 29


Add MOS VRHOT CIRCUIT



Near VDDC each high side MOS



{14,21}



(28)

ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS AND OTHER DOCUMENTS OR INFORMATION (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS". THE MATERIALS MAY CONTAIN KNOWN AND UNKNOWN VIOLATIONS OR DEVIATIONS OF INDUSTRY STANDARDS AND SPECIFICATIONS. NVIDIA MAKES NO WARRANTIES, EXPRESS, IMPLIED, STATUTORY OR OTHERWISE WITH RESPECT TO THE MATERIALS OR OTHERWISE, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING, WITHOUT LIMITATION, THE WARRANTIES OF DESIGN, OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR ARISING FROM A COURSE OF DEALING, TRADE USAGE, TRADE PRACTICE OR INDUSTRY STANDARDS.

PAGE DETAIL

MECH: Bracket/Thermal

Title			
Size	Document Number	Rev	
CUSTOMER	GV-RX580GAMING-4GD	1.0	
Date:	Monday, February 27, 2017	Sheet	29 of 29