

P141-A03, NV31/NV34/NV18B

4(8,16)Mx16, 64(128,256)MB, VIDEO IN/OUT, DVI-I, VGA

Page Overview

- 1 31P141 OVERVIEW
- 2 NV31 AGP Section and AGP connector
- 3 NV31 FRAMEBUFFER Interface
- 4 MEMORY Partition A Bits 0..31
- 5 MEMORY Partition A Bits 31..63
- 6 MEMORY Partition C Bits 0..31
- 7 MEMORY Partition C Bits 31..63
- 8 NV31 DACA, DACB output, SYNC amplifier
- PLL Section
- 9 PRIMARY DISPLAY (DACA) Filter and DB15 Connector
- 10 SECONDARY DISPLAY (DACB)
- DACB Multiplexer Filter long DB15 Connector
- 11 NV31 INTERNAL TMDS Transmitter
- TMDS Backdrive circuit
- Hotplug detection and DV/H Connector
- 12 VIDEO CAPTURE Philips 7114 I/O
- 13 VIDEO IN/OUT, Filter and Connector
- VIDEO INTERNAL Input
- 14 VIP, DVO, GPIO Section
- 15 BIOS, STRAPPS
- 16 POWER SUPPLY: NVVDD, FBVDDQ, A3V3, TMDS
- 17 POWER SUPPLY: FBVDD, DDC5V

HISTORY:

A00

- X00: INITIAL VERSION
- X01: First Review
  - Replaced series resistors in sync lines with 33ohms
  - Moved clamping diodes next to GPU
  - Added parallel caps to EMI filter DACB
  - Removed not needed strap on SAA7114
  - Connected RESET and WP of SST ROM to ROMVCC
  - Added parallel ROM and Strapps
  - Added FBVDD regulator
  - Added STEREO glasses circuit
  - Removed Decoupling CAPs on VIP VDD, covered by Caps on page 2
  - Added ROM\_VCC for cleaner planes
  - Changed used TMDS lines of IFPA and IFPB to TP from NTP
  - Changed Resistor for AGP Vref circuit to 158k
- X02: Final Review
  - Added clock termination resistors
  - Added net name for FBCALxxx
  - Added cap on filter input for FB\_DLLVDD, DACA\_VDD & DACB\_VDD
  - Changed netnames for SAA7114 NTPs to NTP\_xxx
  - Added 1uF cap parallel to fan connector
  - Changed all xxCALxx resistors to 50 Ohms
  - Changed all FBxDQS\*-<x> to NTP\_FBxDQS\*-<x> with NO\_TEST property

A01

- X00: Fixed pin swap on parallel ROM A12 & A13
  - Added charge pump for SC2612
  - Added resistors to swap GPIO for DACB loadtest
  - Added resistors for I2C on internal Video IN connector
- X01: Updated variant information for new Sbom structure

A02

- X00: Added sw adjust for NVVDD
  - Exchanged TMDSIOVDD regulator to lower the voltage drop
  - Changed TMDSPLLVDD regulator bypass to A3V3
  - Addrd 1k series resistor in DACB load detection circuit

A03


- X00: Removed GPIO5 from NVVDD adjust
  - Fixed values for DAC Rset resitors
  - Removed Sync Buffer bypass
  - Removed 2nd voltage selection fet
  - Changed to new internal video connector
  - Added snubber to NVVDD and FBVDD regulator

8912 version 210 base on P141-A03 Modify.

1.Page 13 add 1\*4 pin vedio-in connector.

602-10141-0000-000 Base Schematic


## AGP CONNECTOR AND NV31 AGP SECTION




## AGP rules

[illegible]






## NV31 Framebuffer Interface








Place CKE pull down at T-point!










PLACE ALL DISCRETE COMPONENTS AS NEAR AS POSSIBLE TO MEMORY!













		NET	NET_PHYSICAL_TYPE	VOLTAGE
		60	CHICKLED	100K_TRACK
		61	CHICKLED	100K_TRACK
		62	CHICKLED	100K_TRACK
		63	CHICKLED	100K_TRACK
		64	CHICKLED	100K_TRACK
		65	CHICKLED	100K_TRACK
		66	CHICKLED	100K_TRACK
		67	CHICKLED	100K_TRACK
		68	CHICKLED	100K_TRACK
		69	CHICKLED	100K_TRACK
		70	CHICKLED	100K_TRACK
		71	CHICKLED	100K_TRACK
		72	CHICKLED	100K_TRACK
		73	CHICKLED	100K_TRACK
		74	CHICKLED	100K_TRACK
		75	CHICKLED	100K_TRACK
		76	CHICKLED	100K_TRACK
		77	CHICKLED	100K_TRACK
		78	CHICKLED	100K_TRACK
		79	CHICKLED	100K_TRACK
		80	CHICKLED	100K_TRACK
		81	CHICKLED	100K_TRACK
		82	CHICKLED	100K_TRACK
		83	CHICKLED	100K_TRACK
		84	CHICKLED	100K_TRACK
		85	CHICKLED	100K_TRACK
		86	CHICKLED	100K_TRACK
		87	CHICKLED	100K_TRACK
		88	CHICKLED	100K_TRACK
		89	CHICKLED	100K_TRACK
		90	CHICKLED	100K_TRACK
		91	CHICKLED	100K_TRACK
		92	CHICKLED	100K_TRACK
		93	CHICKLED	100K_TRACK
		94	CHICKLED	100K_TRACK
		95	CHICKLED	100K_TRACK
		96	CHICKLED	100K_TRACK
		97	CHICKLED	100K_TRACK
		98	CHICKLED	100K_TRACK
		99	CHICKLED	100K_TRACK
		100	CHICKLED	100K_TRACK
		101	CHICKLED	100K_TRACK
		102	CHICKLED	100K_TRACK
		103	CHICKLED	100K_TRACK
		104	CHICKLED	100K_TRACK
		105	CHICKLED	100K_TRACK
		106	CHICKLED	100K_TRACK
		107	CHICKLED	100K_TRACK
		108	CHICKLED	100K_TRACK
		109	CHICKLED	100K_TRACK
		110	CHICKLED	100K_TRACK
		111	CHICKLED	100K_TRACK
		112	CHICKLED	100K_TRACK
		113	CHICKLED	100K_TRACK
		114	CHICKLED	100K_TRACK
		115	CHICKLED	100K_TRACK
		116	CHICKLED	100K_TRACK
		117	CHICKLED	100K_TRACK
		118	CHICKLED	100K_TRACK
		119	CHICKLED	100K_TRACK
		120	CHICKLED	100K_TRACK
		121	CHICKLED	100K_TRACK
		122	CHICKLED	100K_TRACK
		123	CHICKLED	100K_TRACK
		124	CHICKLED	100K_TRACK
		125	CHICKLED	100K_TRACK
		126	CHICKLED	100K_TRACK
		127	CHICKLED	100K_TRACK
		128	CHICKLED	100K_TRACK
		129	CHICKLED	100K_TRACK
		130	CHICKLED	100K_TRACK
		131	CHICKLED	100K_TRACK
		132	CHICKLED	100K_TRACK
		133	CHICKLED	100K_TRACK
		134	CHICKLED	100K_TRACK
		135	CHICKLED	100K_TRACK
		136	CHICKLED	100K_TRACK
		137	CHICKLED	100K_TRACK
		138	CHICKLED	100K_TRACK
		139	CHICKLED	100K_TRACK
		140	CHICKLED	100K_TRACK
		141	CHICKLED	100K_TRACK
		142	CHICKLED	100K_TRACK
		143	CHICKLED	100K_TRACK
		144	CHICKLED	100K_TRACK
		145	CHICKLED	100K_TRACK
		146	CHICKLED	100K





Primary Display (DACA), DB15 only!

NET	NET_SPACING_RULE
REF	20MM_20MM_20MM
REF	20MM_20MM_20MM
REF	20MM_20MM_20MM
DACA_RED	20MM_20MM_20MM
DACA_GREEN	20MM_20MM_20MM
DACA_BLUE	20MM_20MM_20MM



Place all filter components on the side nearest to the reference GND plane!


Route all signals only on layers referenced to GND!

Don't split the reference GND plane beneath a RGB signal!




## INTERNAL DUAL LINK TMDS POWER AND DECOUPLING



Unused Transmitter




## TMDS backdrive prevention

[illegible]


## DualLink Transmitter




## Hotplug Detection





## VIDEO CAPTURE









## VIDEO IN/OUT CONNECTOR /STEREO GLASSES



## INTERNAL VIDEO IN CONNECTOR







## NV31 VIP







TMDS PLL Supply






$$V_o = \frac{0.9V \cdot (R_{top} + R_{bot})}{R_{bot}}$$

ISL6225  $F_{VDD} = [0.9V \cdot (1K + 375)] /$   
 NV31  $R_{VDD} = 3.3V$   
 NV18B  $F_{VDD} = [0.9V \cdot (1K + 4.3K)] / 4.3K$   
 $\approx 1.656V$  need







## H/W Monitor Funtion



## TEMPERATURE SENSING CIRCUIT



GPOS	GPOS	Q1	Q2	Q3	Vout
0	0	off	off	off	9V
1	0	on	off	off	10V
0	1	off	on	off	11V
1	1	on	on	on	12V