P1065-B00

GF116 MXM V3.0 Type B, LVDS, Quad DP, DVI, VGA, SLI GB1-192, 3072MB/1536MB GDDR5 x16

TABLE OF CONTENTS

Page Description

- Table of Contents
- PCI Express Interface
- Frame Buffer Interface A
- Frame Buffer Interface B and C
- Frame Buffer Partition A Lower Half
- Frame Buffer Partition A Upper Half
- Frame Buffer Partition B Lower Half
- Frame Buffer Partition B Upper Half
- Frame Buffer Partition C Lower Half
- Frame Buffer Partition C Upper Half
- 11 NVVDD and FBVDDQ Decoupling
- 12 DAC_A, DAC_B, LVDS
- DP Links C, D, E, F 13
- 14 MIOA, SLI B2B
- GPIO, JTAG, INFO_ROM, Thermal Sensor
- Straps, VGA Disable, PADCFG, VBLOS
- 17 PLL, Crystal, Spread, MXM Test Points, Mounting Holes
- 18 MXM Connector
- FBVDDQ, PEX_PLLVDD, PEX_VDD, 3V3_RUN
- NVVDD Power Supply

NVIDIA CORPORATION 2701 SAN TOMAS EXPRESSWAY

SANTA CLARA, CA 95050, USA

NV_PN 600-11065-0013-100





































