







	D1200	. 1	ESDSVSU1U-CILEN	DNI	BTIQP	_
	D1201	. 1	ESDEVAUTU-COLFRI	DNI	BTX2N	
I	D1 <b>2</b> 02	1	ESDSVSUTU-COLFRI	DNI	BTXIP	
I	D1903	1	ESDSV3U1U-02LRH	DNI	BTXIN	
	D1904	1	ESDSV3U1U-02LRH	DNI	BTXXP	
	D1905	1	ESDSVSUTU-CELFO	DNI	BTXON	Ξ
	D1205	1	ESDSVSUTU-CELFO	DNI	BTXCP	_
I	D1 <b>2</b> 07	1	ESDSVSUTU-CELFO	DNI	BTXCN	Ξ
	$\neg \nu$					_
	D1208	1	ESDSV3U1U-03LRH	DNI	DDC4CLK_HDM	_
<u> </u>	D1209	. 1	ESDEVSUTU-COLFRI	DNI	DDC4DAT_HDM	
	D1210	1	ESDEVSUTU-COLFRI	DNI	HPD HDMI	

AMD - PLATFORM HARDWARE ENG #48, No.1387, ZHANGDONG ROAD SHANGHAI, CHINA 201203	口		COMPANIES NO., MARTHONISTO PT COLUMNISTO MICHORYCON INC.  (In the Administration of companies to the base of the companies of	
NHEET: TOBAGO TMDPAB HDM	REV:	1.0	unbessel con design, including, on the interests, scriptors sensing of unbesselsmilling bears and applicate property and decisions expected by their consequences making limit use of the limitation considerable and consequences making limit use of the limitation considerable and consequences making limit use of the limitation considerable and consequences making limit use of the limitation considerable and consequences making limitation and consequences are also as a consequence are also as a consequence and consequences are also as a consequence and consequences are also as a consequence are also as a consequence and consequences are also as a consequence are also as a consequence are a consequence and consequences are a consequences are a consequence and consequences are consequences are a consequence and consequences are a consequenc	
SMEET NUMBER:         7         OF         20           DOCUMENT NUMBER:         105_C936x_00A			TTUE: TOBAGO G5 4X32bit	
NOTES: NOTE				













































TOP Single end RGB 50 ohm +/- 10% 0.102mm 4.02 mils



L3 Single end Memory 48 ohm +/- 5 ohm 0.11mm 4.33 mils



Bottom Single end Memory 48 ohm +/- 5 ohm 0.11mm 4.33 mils



TOP
Different
TMMS
80 ohm +/- 10 %
0.11 mm / 0.16 mm
4.33 mils / 6.3 mils



L3 Different Memory clock 80 ohm +/- 10 % 0.11 mm / 0.16 mm 4.33 mils / 6.3 mils



Bottom Different PCIE 85 ohm +/- 10 % 0.112 mm / 0.188 mm 4.41 mils / 7.04 mils



Consideration, and referent for the content to the

