

CLASSIFICATION

SHANGHAI BIZUPWINGS I&E FOREIGN TRADE CO.LTD.

Lithium manganese dioxide Coincell

P/N	Diameter (mm)	Height (mm)	Nominal Voltage (V)	Nominal Capacity (mAh)	STD Current (mA)	Max. Current (mA)	Continuous Current (μA)	Weight (g)
CR632	6.8	3.20	3.0	15	0.03	3	1	0.20
CR927	9.5	2.70	3.0	30	0.05	5	1	0.60
CR1025	10	2.50	3.0	30	0.05	5	1	0.60
CR1130	11.6	3.00	3.0	48	0.05	5	1	0.90
CR1212	12.5	1.20	3.0	15	0.05	5	1	0.50
CR1216	12.5	1.60	3.0	25	0.05	5	1	0.70
CR1220	12.5	2.00	3.0	40	0.05	5	1	0.85
CR1225	12.5	2.50	3.0	48	0.10	5	1	1.00
CR1616	16	1.60	3.0	50	0.10	8	1	1.15
CR1620	16	2.00	3.0	70	0.10	8	2	1.30
CR1625	16	2.50	3.0	90	0.10	8	2	1.40
CR1632	16	3.20	3.0	130	0.20	10	2	1.80
CR2016	20	1.60	3.0	80	0.20	15	2	1.75
CR2020	20	2.00	3.0	115	0.20	15	2	2.10
CR2025	20	2.50	3.0	160	0.20	15	3	2.45
CR2032	20	3.20	3.0	220	0.20	15	5	2.90
CR2320	23	2.00	3.0	150	0.20	18	8	2.90
CR2325	23	2.50	3.0	210	0.20	18	8	3.50
CR2330	23	3.00	3.0	250	0.20	18	8	4.00
CR2354	23	5.40	3.0	480	0.20	18	8	6.00
CR2430	24.5	3.00	3.0	290	0.20	18	10	4.50
CR2450	24.5	5.00	3.0	580	0.40	18	13	6.20
CR2477	24.5	7.70	3.0	950	0.50	20	13	8.70
CR3032	30	3.20	3.0	580	0.50	20	13	8.00

P/N	Diameter (mm)	Height (mm)	Nominal Voltage (V)	Nominal Capacity (mAh)	STD Current (mA)	Max. Current (mA)	Continuous Current (μA)	Weight (g)
CR1616H	16	1.60	3.0	55	0.10	8	1	1.15
CR1620H	16	2.00	3.0	75	0.10	8	2	1.30
CR1625H	16	2.50	3.0	95	0.10	8	2	1.40
CR1632H	16	3.20	3.0	135	0.20	10	2	1.80
CR2016H	20	1.60	3.0	90	0.20	15	2	1.75
CR2025H	20	2.50	3.0	165	0.20	15	3	2.50
CR2032H	20	3.20	3.0	240	0.20	15	5	3.0
CR2320H	23	2.00	3.0	155	0.20	18	8	2.95
CR2325H	23	2.50	3.0	220	0.20	18	8	3.5
CR2330H	23	3.00	3.0	260	0.20	18	8	4.0
CR2354H	23	5.40	3.0	520	0.20	18	8	6.00
CR2430H	24.5	3.00	3.0	320	0.20	18	10	4.50
CR2450H	24.5	5.00	3.0	610	0.40	18	13	6.25
CR2477H	24.5	7.70	3.0	1000	0.50	20	13	8.70
CR3032H	30	3.20	3.0	600	0.50	20	13	8.00
