

Title (EN): Domain-Specific NER Adaptation

In the past years, the Named Entity Recognition (NER) technology has been under an active development and enjoy a significant increase in popularity and usage in the academic and industrial sphere. Nevertheless, vast majority of the developed NER systems have been developed as general-purpose systems. While they can perform well on multiple domains (macro level), on specific domains (micro level) their performance quality might be low. The ultimate goal of the thesis is to develop domain-specific NER models. Guidelines:

- Get familiar with the NER technology and available NER frameworks.
- Investigate possible datasets for domain-specific training of NER.
- Develop NER training datasets for several selected domains (e.g. sports, politics, music, etc.).
- Train a domain-specific NER model using existing frameworks, such as DBpedia Spotlight or StanfordNER.
- Validate and evaluate the developed domain-specific NER models.



**FACULTY
OF INFORMATION
TECHNOLOGY
CTU IN PRAGUE**

Master's thesis

Domain-specific Name Entity Recognition

Bc. Bogoljub Jakovcheski

Department of software engineering

Supervisor: Ing. Milan Dojchinovski, Ph.D.

May 15, 2018

Acknowledgements

I would like to thank my family and friends for support during writing this thesis.

Declaration

I hereby declare that the presented thesis is my own work and that I have cited all sources of information in accordance with the Guideline for adhering to ethical principles when elaborating an academic final thesis.

I acknowledge that my thesis is subject to the rights and obligations stipulated by the Act No. 121/2000 Coll., the Copyright Act, as amended. In accordance with Article 46(6) of the Act, I hereby grant a nonexclusive authorization (license) to utilize this thesis, including any and all computer programs incorporated therein or attached thereto and all corresponding documentation (hereinafter collectively referred to as the “Work”), to any and all persons that wish to utilize the Work. Such persons are entitled to use the Work in any way (including for-profit purposes) that does not detract from its value. This authorization is not limited in terms of time, location and quantity. However, all persons that makes use of the above license shall be obliged to grant a license at least in the same scope as defined above with respect to each and every work that is created (wholly or in part) based on the Work, by modifying the Work, by combining the Work with another work, by including the Work in a collection of works or by adapting the Work (including translation), and at the same time make available the source code of such work at least in a way and scope that are comparable to the way and scope in which the source code of the Work is made available.

In Prague on May 15, 2018

.....

Czech Technical University in Prague

Faculty of Information Technology

© 2018 Bogoljub Jakovcheski. All rights reserved.

This thesis is school work as defined by Copyright Act of the Czech Republic. It has been submitted at Czech Technical University in Prague, Faculty of Information Technology. The thesis is protected by the Copyright Act and its usage without author's permission is prohibited (with exceptions defined by the Copyright Act).

Citation of this thesis

Jakovcheski, Bogoljub. *Domain-specific Name Entity Recognition*. Master's thesis. Czech Technical University in Prague, Faculty of Information Technology, 2018.

Abstrakt

Klíčová slova

Abstract

Keywords

Contents

Introduction	1
Motivation	1
Goals of the thesis	1
Thesis outline	1
1 Background and related work	3
1.1 Information extraction	3
1.2 NER	3
1.3 RDF/NIF	3
1.4 DBpedia ontology	3
1.5 Evaluation/training datasets	3
1.6 Domain specific NER	3
1.7 Stanford NER	3
2 Domain specific NER	5
2.1 Data pre-processing	5
2.2 Types retrieval	5
2.3 Domain specification	5
2.4 Data transformation/output for Stanford	6
3 Experiments	7
3.1 Goals of the experiments	7
3.2 List of experiments	7
3.3 Summary of results	19
Conclusion	21
A Contents of CD	23

List of Figures

3.1	All 3 Domains Coarse BBC Coarse	7
3.2	All 3 Domains Coarse Top 10 Links	8
3.3	All 3 Domains Coarse Top 10 Links Politics	8
3.4	All 3 Domains Coarse Top 10 Links Sport	9
3.5	All 3 Domains Coarse Top 10 Links Transportation	9
3.6	All 3 Domains Fine Top 10 Links	9
3.7	All 3 Domains Fine Top 10 Links Politics	10
3.8	All 3 Domains Fine Top 10 Links Sport	10
3.9	All 3 Domains Fine Top 10 Links Transportation	10
3.10	Politics Coarse Top 10 Links Politics	11
3.11	Politics Fine Top 10 Links Politics	11
3.12	Sport Coarse Top 10 Links Sport	11
3.13	Sport Fine Top 10 Links Sport	12
3.14	Transportation Coarse Top 10 Links Transportation	12
3.15	Transportation Fine Top 10 Links Transportation	12
3.16	All 3 Domains Coarse Top 20 Links	13
3.17	All 3 Domains Coarse Top 20 Links Politics	13
3.18	All 3 Domains Coarse Top 20 Links Sport	13
3.19	All 3 Domains Coarse Top 20 Links Transportation	13
3.20	All 3 Domains Fine Top 20 Links	14
3.21	All 3 Domains Fine Top 20 Links Politics	14
3.22	All 3 Domains Fine Top 20 Links Sport	14
3.23	All 3 Domains Fine Top 20 Links Transportation	14
3.24	Politics Coarse Top 20 Links Politics	15
3.25	Politics Fine Top 20 Links Politics	15
3.26	Politics Coarse Top 20 Links Politics	15
3.27	Sport Fine Top 20 Links Sport	15
3.28	Politics Coarse Top 20 Links Politics	15
3.29	Sport Fine Top 20 Links Sport	16
3.30	All 3 Domains Coarse Top 40 Links	16

3.31	All 3 Domains Coarse Top 40 Links Politics	16
3.32	All 3 Domains Coarse Top 40 Links Sport	16
3.33	All 3 Domains Coarse Top 40 Links Transportation	17
3.34	All 3 Domains Fine Top 40 Links	17
3.35	All 3 Domains Fine Top 40 Links Politics	17
3.36	All 3 Domains Fine Top 40 Links Sport	18
3.37	All 3 Domains Fine Top 40 Links Transportation	18
3.38	Politics Coarse Top 40 Links Politics	18
3.39	Politics Fine Top 40 Links Politics	18
3.40	Politics Coarse Top 40 Links Politics	19
3.41	Sport Fine Top 40 Links Sport	19

Introduction

Motivation

Goals of the thesis

The main goal of the thesis is to show (test) does extracting information from a global domain gives us better results that extracting information from a specific domain, for example politics domain or any other domain.

Thesis outline

Background and related work

1.1 Information extraction

information extraction, that is, automatically building a relational database from information contained in unstructured text. Unlike linear-chain models, general CRFs can capture long distance dependencies between labels.

1.2 NER

NER is the problem of identifying and classifying proper names in text, including locations, such as China; people, such as George Bush; and organizations, such as the United Nations. The named-entity recognition task is, given a sentence, first to segment which words are part of entities, and then to classify each entity by type (person, organization, location, and so on). The challenge of this problem is that many named entities are too rare to appear even in a large training set, and therefore the system must identify them based only on context

1.3 RDF/NIF

1.4 DBpedia ontology

1.5 Evaluation/training datasets

1.6 Domain specific NER

1.7 Stanford NER

Domain specific NER

There are parameters of the computer used for tests shown in Table ??.

2.1 Data pre-processing

• Coarse grained • Fine grained

2.2 Types retrieval

At the main file where we write text we retrieve all types that are available for that text. After that, that text is processed with coarse and fine grained types. In coarse grained we have politics, sport and transportation specific domains. In fine grained in politics domain we retrieve in total 26 types (write them all), which we sort in 11 more specific types like for example Ambassador, Mayor, Deputy etc. are fused in one specific domain Politician. We do the same for sport domain where we retrieve in total 171 types, so those types, same as politics domain, are specified in 8 types, like SportClub, SportsLeague, SportsTeam, Athlete, Coach, OrganizationMember, SportsManager, SportsEvent. We also do the same for transportation domain, where we retrieve in total 78 types and minimized in 14 more specific types like Aircraft, Automobile, Locomotive, MilitaryVehicle, Motorcycle, On-SiteTransportation, Rocket, Ship, SpaceShuttle, SpaceStation, Spacecraft, Train, PublicTransitSystem and Infrastructure.

2.3 Domain specification

• How we choose those domains (Politics, Sport, Transportation)?

2.4 Data transformation/output for Stanford

â€” How we process data to be ready to use on Stanford NER system?

Experiments

We have provide various types of experiments. In next sections we will discuss more about every provided experiment.

3.1 Goals of the experiments

We set a few goals of the experiments. First of all we waned to test does we will get better results if we run the model of all domains in coarse grained, against the model of all domains in fine grained. In this test we run the models also with all domains texts. Then we get those models and we run it with specific domain texts, in both fine and coarse grained. Also we make experiments with specific domain model runned with domain specific texts, for example, politics domain model in coarse grained is runned with politics domain text also annotated in coarse grained, politics domain model in fine grained is runned with politics domain text also annotated in fine grained, and the same for sport and transportation domains.

3.2 List of experiments

Make it like experiment - discussion

```
CRFClassifier tagged 4307 words in 1 documents at 5867,85 words per second.
Entity P      R      F1      TP      FP      FN
POLITICS 1,0000 0,0299 0,0580 2        0        65
SPORT 0,5000 0,0127 0,0247 1         1        78
TRANSPORTATION 1,0000 0,2857 0,4444 4         0        10
Totals 0,8750 0,0438 0,0833 7         1       153

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top500Links\ner-All3DomainsTop500LinksCoarseGrained.ser.gz -testFile texts\All3DomainsBBCCoar
seGrainedSpecified.tsv
```

Figure 3.1: All 3 Domains Coarse BBC Coarse

3. EXPERIMENTS

3.2.1 Top 10 Links

In this experiment we get the model that is trained with all 3 domains together with coarse grained and we make an experiment with the text that is trained, that means text from all 3 domains annotated with coarse grained. Here we have for every domain 10 abstracts, so in total 30 annotated abstracts. This is our smallest model. How we can see from the picture in politics domain F1 value is lower than in sport and transportation. This results with lower F1 value in total, but still that is very satisfying value, because we have only 1 false positive and 2 false negative words.

```
CRFClassifier tagged 10336 words in 1 documents at 6764,40 words per second.
Entity P      R      F1      TP      FP      FN
POLITICS 0,9655 0,9333 0,9492 28      1      2
SPORT 1,0000 1,0000 1,0000 15      0      0
TRANSPORTATION 1,0000 1,0000 1,0000 9       0      0
Totals 0,9811 0,9630 0,9720 52      1      2

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top10Links\ner-All3DomainsTop10LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\T
op10Links\All3DomainsTop10LinksTextWithSameProcessedLinksOnAbstractCoarseGrainedSpecified.tsv
```

Figure 3.2: All 3 Domains Coarse Top 10 Links

In this experiment we get the previous trained model and test with politics coarse grained text. Result is not satisfying, because we have a very low recall, so that results with bad F1 value and very big false negative words. We can clearly say that this is not the model that we want to use in annotating. With those results we can say that all 3 domains together with all text perform better results than all 3 domain model tested with specified domain.

```
CRFClassifier tagged 4504 words in 1 documents at 5118,18 words per second.
Entity P      R      F1      TP      FP      FN
POLITICS 0,9655 0,3636 0,5283 28      1      49
Totals 0,9655 0,3636 0,5283 28      1      49

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top10Links\ner-All3DomainsTop10LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\T
op10Links\PoliticsCoarseGrainedTop10Links.tsv
```

Figure 3.3: All 3 Domains Coarse Top 10 Links Politics

Then we get the same model, and like previous, we tested with sport coarse grained text. So how we can see from the picture, we have perfect result, there is no false positive or false negative words, there are only true positive which results with F1 value of 1.000 (no lost words).

3.2. List of experiments

```
CRFClassifier tagged 2854 words in 1 documents at 4298,19 words per second.
Entity P      R      F1      TP      FP      FN
SPORT 1,0000  1,0000  1,0000  15      0      0
Totals 1,0000  1,0000  1,0000  15      0      0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top10Links\ner-All3DomainsTop10LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\T
op10Links\SportCoarseGrainedTop10Links.tsv
```

Figure 3.4: All 3 Domains Coarse Top 10 Links Sport

Finally we tested this model with our last domain, transportation domain with coarse grained text. Because of very small annotated words we have again perfect results without any false positive or false negative words, same as previous test, there are only true positive matches, which is what we want.

```
CRFClassifier tagged 2978 words in 1 documents at 4532,72 words per second.
Entity P      R      F1      TP      FP      FN
TRANSPORTATION 1,0000  1,0000  1,0000  9      0      0
Totals 1,0000  1,0000  1,0000  9      0      0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top10Links\ner-All3DomainsTop10LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\T
op10Links\TransportationCoarseGrainedTop10Links.tsv
```

Figure 3.5: All 3 Domains Coarse Top 10 Links Transportation

After we finish testing of all 3 domains trained with coarse grained texts, we move on with new type of experiment, model that contains all our domains and is trained with fine grained texts. We run the same experiment like in coarse grained, but now text is annotated with fine grained. So, in such small trained model is not surprising that we get the same results as in experiment with coarse grained annotated text.

```
CRFClassifier tagged 10336 words in 1 documents at 3395,53 words per second.
Entity P      R      F1      TP      FP      FN
Aircraft 1,0000  1,0000  1,0000  1      0      0
Athlete 1,0000  1,0000  1,0000  1      0      0
Coach 1,0000  1,0000  1,0000  1      0      0
PoliticalParty 0,9600  0,9231  0,9412  24     1      2
Politician 1,0000  1,0000  1,0000  4      0      0
PublicTransitSystem 1,0000  1,0000  1,0000  1,0000  7      0
Ship 1,0000  1,0000  1,0000  1      0      0
SportsClub 1,0000  1,0000  1,0000  7      0      0
SportsEvent 1,0000  1,0000  1,0000  1      0      0
SportsLeague 1,0000  1,0000  1,0000  4      0      0
SportsTeam 1,0000  1,0000  1,0000  1      0      0
Totals 0,9811  0,9630  0,9720  52     1      2

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top10Links\ner-All3DomainsTop10LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top10
Links\All3DomainsTop10LinksTextWithSameProcessedLinksOnAbstractFineGrainedSpecified.tsv
```

Figure 3.6: All 3 Domains Fine Top 10 Links

We have repeated the same experiments from previous, but now with fine grained annotation. So we tested our model with politics domain annotated in fine grained and we get exactly the same results like in coarse grained. In

3. EXPERIMENTS

this case there is no difference if we use coarse or fine grained trained model, because the results are same.

```
CRFClassifier tagged 4504 words in 1 documents at 2861,50 words per second.
Entity P      R      F1      TP      FP      FN
Election 0,0000 0,0000 0,0000 0      0      15
PoliticalParty 0,9600 0,9231 0,9412 24      1      2
Politician 1,0000 0,1111 0,2000 4      0      32
Totals 0,9655 0,3636 0,5283 28      1      49

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top10Links\ner-All3DomainsTop10LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top10
Links\PoliticsFineGrainedTop10Links.tsv
```

Figure 3.7: All 3 Domains Fine Top 10 Links Politics

The sport domain text annotated in fine grained provide also same result as coarse grained annotated domain.

```
CRFClassifier tagged 2854 words in 1 documents at 2548,21 words per second.
Entity P      R      F1      TP      FP      FN
Athlete 1,0000 1,0000 1,0000 1      0      0
Coach 1,0000 1,0000 1,0000 1      0      0
SportsClub 1,0000 1,0000 1,0000 7      0      0
SportsEvent 1,0000 1,0000 1,0000 1      0      0
SportsLeague 1,0000 1,0000 1,0000 4      0      0
SportsTeam 1,0000 1,0000 1,0000 1      0      0
Totals 1,0000 1,0000 1,0000 15      0      0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top10Links\ner-All3DomainsTop10LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top10
Links\SportFineGrainedTop10Links.tsv
```

Figure 3.8: All 3 Domains Fine Top 10 Links Sport

Same as sport domain, the transportation domain Figure 3.9 text annotated with fine grained, provide also same results.

```
CRFClassifier tagged 2978 words in 1 documents at 2538,79 words per second.
Entity P      R      F1      TP      FP      FN
Aircraft 1,0000 1,0000 1,0000 1      0      0
PublicTransitSystem 1,0000 1,0000 1,0000 7      0      0
Ship 1,0000 1,0000 1,0000 1      0      0
Totals 1,0000 1,0000 1,0000 9      0      0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top10Links\ner-All3DomainsTop10LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top10
Links\TransportationFineGrainedTop10Links.tsv
```

Figure 3.9: All 3 Domains Fine Top 10 Links Transportation

After experimenting with models that are trained with all domains together, we move on with experiments where we create specific models, both coarse and fine grained. First we tested the model that is created with politics text annotated in coarse grained. How we can see from Figure 3.10 we have a better results than that experiment that we provide in all 3 domains. The F1 value is very big which is the results of low false positive and false negative annotated words.

3.2. List of experiments

```
CRFClassifier tagged 4504 words in 1 documents at 5941,95 words per second.
Entity P      R      F1      TP      FP      FN
POLITICS 0,9737  0,9610  0,9673  74      2      3
Totals 0,9737  0,9610  0,9673  74      2      3

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top10Links\ner-PoliticsTop10LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\Top1
0Links\PoliticsCoarseGrainedTop10Links.tsv
```

Figure 3.10: Politics Coarse Top 10 Links Politics

We also provide the same experiment like previous, but now the model is annotated in fine grained. From Figure 3.11 is clearly that we have improve our model, here the F1 value is bigger that in coarse grained (see Figure 3.10) and also false positive annotated words are decreased by 1. That means even we have a complete review of our entities and can see the precision of each entity, this domain, in total, is more precise that coarse grained model and all 3 domains in coarse and fine grained.

```
CRFClassifier tagged 4504 words in 1 documents at 3568,94 words per second.
Entity P      R      F1      TP      FP      FN
Election 1,0000  0,9333  0,9655  14      0      1
PoliticalParty 0,9600  0,9231  0,9412  24      1      2
Politician 1,0000  1,0000  1,0000  36      0      0
Totals 0,9867  0,9610  0,9737  74      1      3

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top10Links\ner-PoliticsTop10LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top10Li
nks\PoliticsFineGrainedTop10Links.tsv
```

Figure 3.11: Politics Fine Top 10 Links Politics

From here, with this small amount of data we can say that it's better to use a politics specific domain, in fine grained, than a global domain, because in global domain we have 28 words annotated as true positive, but in a politics specific coarse grained domain we have 74 words annotated as true positive, which is very big difference, if we want to be precise.

We repeated the experiment for sport specific domain, but in this case the results are exactly the same in coarse and fine grained (see Figure 3.12 and Figure 3.13 as well as in all 3 domains also in coarse and fine grained

```
CRFClassifier tagged 2854 words in 1 documents at 4920,69 words per second.
Entity P      R      F1      TP      FP      FN
SPORT 1,0000  1,0000  1,0000  15      0      0
Totals 1,0000  1,0000  1,0000  15      0      0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top10Links\ner-SportTop10LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\Top10Li
nks\SportCoarseGrainedTop10Links.tsv
```

Figure 3.12: Sport Coarse Top 10 Links Sport

3. EXPERIMENTS

```
CRFClassifier tagged 2854 words in 1 documents at 2525,66 words per second.
Entity P      R      F1      TP      FP      FN
Athlete 1,0000 1,0000 1,0000 1        0        0
Coach 1,0000 1,0000 1,0000 1        0        0
SportsClub 1,0000 1,0000 1,0000 7        0        0
SportsEvent 1,0000 1,0000 1,0000 1        0        0
SportsLeague 1,0000 1,0000 1,0000 4        0        0
SportsTeam 1,0000 1,0000 1,0000 1        0        0
Totals 1,0000 1,0000 1,0000 15       0        0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top10Links\ner-SportTop10LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top10Links\
SportFineGrainedTop10Links.tsv
```

Figure 3.13: Sport Fine Top 10 Links Sport

This model is really small, only 15 annotated words, that's because we cannot make a conclusion which model is better to use. But if we speak about performance, of course the better solution is specified domain.

The transportation model, like a sport domain, is also a very small, only 9 annotated words. We provide the experiments for coarse grained (see Figure 3.14) and we get same results as in all 3 domains (see Figure 3.9). Same is happening for the fine grained domain (see Figure 3.15). In such a small trained domain, we cannot clearly say which model is better to use.

```
CRFClassifier tagged 2978 words in 1 documents at 2951,44 words per second.
Entity P      R      F1      TP      FP      FN
TRANSPORTATION 1,0000 1,0000 1,0000 9        0        0
Totals 1,0000 1,0000 1,0000 9        0        0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top10Links\ner-TransportationTop10LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\Top10Links\TransportationCoarseGrainedTop10Links.tsv
```

Figure 3.14: Transportation Coarse Top 10 Links Transportation

```
CRFClassifier tagged 2978 words in 1 documents at 3063,79 words per second.
Entity P      R      F1      TP      FP      FN
Aircraft 1,0000 1,0000 1,0000 1        0        0
PublicTransitSystem 1,0000 1,0000 1,0000 7        0        0
Ship 1,0000 1,0000 1,0000 1        0        0
Totals 1,0000 1,0000 1,0000 9        0        0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top10Links\ner-TransportationTop10LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top10Links\TransportationFineGrainedTop10Links.tsv
```

Figure 3.15: Transportation Fine Top 10 Links Transportation

In conclusion of this subsection, we can say that our strategy for creating a specific domain pays off, because in those domains we have a better results than in global domains. But let see in subsection 3.2.2 how domains will behave with a bigger data(text).

3.2.2 Top 20 Links

In subsection 3.2.1 we provide various experiments with different models. Now in this subsection we will repeat those experiments, but now we doubled the number of text to every domain, so we have 20 abstracts for every domain, in total 60 abstract. Those models, like previous, are trained in both coarse and fine grained. The first experiment in Figure 3.16

```
CRFClassifier tagged 18733 words in 1 documents at 6802,11 words per second.
Entity P      R      F1      TP      FP      FN
POLITICS 1,0000  0,9615  0,9804  50      0      2
SPORT 1,0000  1,0000  1,0000  27      0      0
TRANSPORTATION 1,0000  1,0000  1,0000  12      0      0
Totals 1,0000  0,9780  0,9889  89      0      2

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top20Links\ner-All3DomainsTop20LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\T
op20Links\All3DomainsTop20LinksTextWithSameProcessedLinksOnAbstractCoarseGrainedSpecified.tsv
```

Figure 3.16: All 3 Domains Coarse Top 20 Links

```
CRFClassifier tagged 7218 words in 1 documents at 5710,44 words per second.
Entity P      R      F1      TP      FP      FN
POLITICS 1,0000  0,3906  0,5618  50      0      78
Totals 1,0000  0,3906  0,5618  50      0      78

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top20Links\ner-All3DomainsTop20LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\T
op20Links\PoliticsCoarseGrainedTop20Links.tsv
```

Figure 3.17: All 3 Domains Coarse Top 20 Links Politics

```
CRFClassifier tagged 6810 words in 1 documents at 5198,47 words per second.
Entity P      R      F1      TP      FP      FN
SPORT 1,0000  1,0000  1,0000  26      0      0
Totals 1,0000  1,0000  1,0000  26      0      0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top20Links\ner-All3DomainsTop20LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\T
op20Links\SportCoarseGrainedTop20Links.tsv
```

Figure 3.18: All 3 Domains Coarse Top 20 Links Sport

```
CRFClassifier tagged 4705 words in 1 documents at 5535,29 words per second.
Entity P      R      F1      TP      FP      FN
SPORT 0,0000  1,0000  0,0000  0      1      0
TRANSPORTATION 1,0000  1,0000  1,0000  12      0      0
Totals 0,9231  1,0000  0,9600  12      1      0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top20Links\ner-All3DomainsTop20LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\T
op20Links\TransportationCoarseGrainedTop20Links.tsv
```

Figure 3.19: All 3 Domains Coarse Top 20 Links Transportation

3. EXPERIMENTS

```
CRFClassifier tagged 18733 words in 1 documents at 2912,47 words per second.
Entity P      R      F1      TP      FP      FN
Aircraft 1,0000 0,5000 0,6667 1       0       1
Athlete 1,0000 1,0000 1,0000 1       0       0
Coach 1,0000 1,0000 1,0000 1       0       0
Infrastructure 1,0000 0,5000 0,6667 1       0       1
PoliticalParty 1,0000 0,9512 0,9750 39      0       2
Politician 1,0000 1,0000 1,0000 11      0       0
Ship 1,0000 1,0000 1,0000 1       0       0
SpaceShuttle 1,0000 1,0000 1,0000 6       0       0
SpaceStation 1,0000 1,0000 1,0000 1       0       0
SportsClub 1,0000 1,0000 1,0000 10      0       0
SportsEvent 1,0000 1,0000 1,0000 1       0       0
SportsLeague 1,0000 1,0000 1,0000 12      0       0
SportsTeam 1,0000 1,0000 1,0000 2       0       0
Totals 1,0000 0,9560 0,9775 87      0       4

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top20Links\ner-All3DomainsTop20LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top20
Links\All3DomainsTop20LinksTextWithSameProcessedLinksOnAbstractFineGrainedSpecified.tsv
```

Figure 3.20: All 3 Domains Fine Top 20 Links

```
CRFClassifier tagged 7218 words in 1 documents at 2440,99 words per second.
Entity P      R      F1      TP      FP      FN
Election 0,0000 0,0000 0,0000 0       0       32
PoliticalParty 1,0000 0,9512 0,9750 39      0       2
Politician 1,0000 0,2000 0,3333 11      0       44
Totals 1,0000 0,3906 0,5618 50      0       78

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top20Links\ner-All3DomainsTop20LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top20
Links\PoliticsFineGrainedTop20Links.tsv
```

Figure 3.21: All 3 Domains Fine Top 20 Links Politics

```
CRFClassifier tagged 6810 words in 1 documents at 2508,29 words per second.
Entity P      R      F1      TP      FP      FN
Athlete 1,0000 1,0000 1,0000 1       0       0
Coach 1,0000 1,0000 1,0000 1       0       0
SportsClub 1,0000 1,0000 1,0000 10      0       0
SportsEvent 1,0000 1,0000 1,0000 1       0       0
SportsLeague 1,0000 1,0000 1,0000 12      0       0
SportsTeam 1,0000 1,0000 1,0000 1       0       0
Totals 1,0000 1,0000 1,0000 26      0       0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top20Links\ner-All3DomainsTop20LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top20
Links\SportFineGrainedTop20Links.tsv
```

Figure 3.22: All 3 Domains Fine Top 20 Links Sport

```
CRFClassifier tagged 4705 words in 1 documents at 2180,26 words per second.
Entity P      R      F1      TP      FP      FN
Aircraft 1,0000 0,5000 0,6667 1       0       1
Infrastructure 1,0000 0,5000 0,6667 1       0       1
Ship 1,0000 1,0000 1,0000 1       0       0
SpaceShuttle 1,0000 1,0000 1,0000 6       0       0
SpaceStation 1,0000 1,0000 1,0000 1       0       0
SportsTeam 0,0000 1,0000 0,0000 0       1       0
Totals 0,9091 0,8333 0,8696 10      1       2

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top20Links\ner-All3DomainsTop20LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top20
Links\TransportationFineGrainedTop20Links.tsv
```

Figure 3.23: All 3 Domains Fine Top 20 Links Transportation

3.2. List of experiments

```
CRFClassifier tagged 7218 words in 1 documents at 4903,53 words per second.
Entity P      R      F1      TP      FP      FN
POLITICS 0,9921  0,9766  0,9843  125     1       3
Totals 0,9921  0,9766  0,9843  125     1       3

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top20Links\ner-PoliticsTop20LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\Top2
0Links\PoliticsCoarseGrainedTop20Links.tsv
```

Figure 3.24: Politics Coarse Top 20 Links Politics

```
CRFClassifier tagged 7218 words in 1 documents at 6153,45 words per second.
Entity P      R      F1      TP      FP      FN
Election 1,0000  0,9688  0,9841  31      0       1
PoliticalParty 1,0000  0,9512  0,9750  39      0       2
Politician 1,0000  1,0000  1,0000  55      0       0
Totals 1,0000  0,9766  0,9881  125     0       3

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top20Links\ner-PoliticsTop20LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top20Li
nks\PoliticsFineGrainedTop20Links.tsv
```

Figure 3.25: Politics Fine Top 20 Links Politics

```
CRFClassifier tagged 6810 words in 1 documents at 6418,47 words per second.
Entity P      R      F1      TP      FP      FN
SPORT 1,0000  1,0000  1,0000  26      0       0
Totals 1,0000  1,0000  1,0000  26      0       0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top20Links\ner-SportTop20LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\Top20Li
nks\SportCoarseGrainedTop20Links.tsv
```

Figure 3.26: Politics Coarse Top 20 Links Politics

```
CRFClassifier tagged 6810 words in 1 documents at 4518,91 words per second.
Entity P      R      F1      TP      FP      FN
Athlete 1,0000  1,0000  1,0000  1       0       0
Coach 1,0000  1,0000  1,0000  1       0       0
SportsClub 1,0000  1,0000  1,0000  10      0       0
SportsEvent 1,0000  1,0000  1,0000  1       0       0
SportsLeague 1,0000  1,0000  1,0000  12      0       0
SportsTeam 1,0000  1,0000  1,0000  1       0       0
Totals 1,0000  1,0000  1,0000  26      0       0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top20Links\ner-SportTop20LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top20Li
nks\SportFineGrainedTop20Links.tsv
```

Figure 3.27: Sport Fine Top 20 Links Sport

```
CRFClassifier tagged 4705 words in 1 documents at 5439,31 words per second.
Entity P      R      F1      TP      FP      FN
TRANSPORTATION 1,0000  0,8333  0,9091  10      0       2
Totals 1,0000  0,8333  0,9091  10      0       2

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top20Links\ner-TransportationTop20LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotatio
n\Top20Links\TransportationCoarseGrainedTop20Links.tsv
```

Figure 3.28: Politics Coarse Top 20 Links Politics

3. EXPERIMENTS

```
CRFClassifier tagged 4705 words in 1 documents at 5032,09 words per second.
Entity P      R      F1      TP      FP      FN
Aircraft 1,0000 0,5000 0,6667 1       0       1
Infrastructure 1,0000 0,5000 0,6667 1       0       1
Ship 1,0000 1,0000 1,0000 1       0       0
SpaceShuttle 1,0000 1,0000 1,0000 6       0       0
SpaceStation 0,0000 0,0000 0,0000 0       0       1
Totals 1,0000 0,7500 0,8571 9       0       3

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top20Links\ner-TransportationTop20linksFineGrained.ser.gz -testFile domainsWithOneAnnotation\To
p20Links\TransportationFineGrainedTop20Links.tsv
```

Figure 3.29: Sport Fine Top 20 Links Sport

3.2.3 Top 40 Links

```
CRFClassifier tagged 42657 words in 1 documents at 7408,30 words per second.
Entity P      R      F1      TP      FP      FN
POLITICS 0,9890 0,9375 0,9626 90      1       6
SPORT 1,0000 1,0000 1,0000 93      0       0
TRANSPORTATION 1,0000 0,9846 0,9922 64      0       1
Totals 0,9960 0,9724 0,9841 247     1       7

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top40Links\ner-All3DomainsTop40LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\T
op40Links\All3DomainsTop40linksTextWithSameProcessedLinksOnAbstractCoarseGrainedSpecified.tsv
```

Figure 3.30: All 3 Domains Coarse Top 40 Links

TEXT

```
CRFClassifier tagged 17912 words in 1 documents at 6553,97 words per second.
Entity P      R      F1      TP      FP      FN
POLITICS 0,9890 0,3529 0,5202 90      1      165
Totals 0,9890 0,3529 0,5202 90      1      165

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top40Links\ner-All3DomainsTop40LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\T
op40Links\PoliticsCoarseGrainedTop40Links.tsv
```

Figure 3.31: All 3 Domains Coarse Top 40 Links Politics

TEXT

```
CRFClassifier tagged 13802 words in 1 documents at 6470,70 words per second.
Entity P      R      F1      TP      FP      FN
SPORT 1,0000 1,0000 1,0000 91      0       0
Totals 1,0000 1,0000 1,0000 91      0       0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top40Links\ner-All3DomainsTop40LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\T
op40Links\SportCoarseGrainedTop40Links.tsv
```

Figure 3.32: All 3 Domains Coarse Top 40 Links Sport

TEXT

3.2. List of experiments

```
CRFClassifier tagged 10943 words in 1 documents at 6560,55 words per second.
Entity P      R      F1      TP      FP      FN
SPORT 0,0000  1,0000  0,0000  0       2       0
TRANSPORTATION 1,0000  0,9846  0,9922  64      0       1
Totals 0,9697  0,9846  0,9771  64      2       1

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top40Links\ner-All3DomainsTop40LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\T
op40Links\TransportationCoarseGrainedTop40Links.tsv
```

Figure 3.33: All 3 Domains Coarse Top 40 Links Transportation

TEXT

```
CRFClassifier tagged 42657 words in 1 documents at 4228,07 words per second.
Entity P      R      F1      TP      FP      FN
Aircraft 1,0000  1,0000  1,0000  16      0       0
Athlete 1,0000  1,0000  1,0000  8       0       0
Coach 1,0000  1,0000  1,0000  1       0       0
Infrastructure 1,0000  1,0000  1,0000  14      0       0
PoliticalParty 0,9863  0,9730  0,9796  72      1       2
Politician 1,0000  0,8182  0,9000  18      0       4
PublicTransitSystem 1,0000  1,0000  1,0000  27      0       0
Ship 1,0000  1,0000  1,0000  1       0       0
SpaceShuttle 1,0000  1,0000  1,0000  6       0       0
SpaceStation 1,0000  1,0000  1,0000  1       0       0
SportsClub 1,0000  1,0000  1,0000  20      0       0
SportsEvent 1,0000  1,0000  1,0000  29      0       0
SportsLeague 1,0000  1,0000  1,0000  23      0       0
SportsTeam 1,0000  1,0000  1,0000  12      0       0
Totals 0,9960  0,9764  0,9861  248     1       6

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top40Links\ner-All3DomainsTop40LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top40
Links\All3DomainsTop40LinksTextWithSameProcessedLinksOnAbstractFineGrainedSpecified.tsv
```

Figure 3.34: All 3 Domains Fine Top 40 Links

TEXT

```
CRFClassifier tagged 17912 words in 1 documents at 3556,79 words per second.
Entity P      R      F1      TP      FP      FN
Election 0,0000  0,0000  0,0000  0       0       66
PoliticalParty 0,9863  0,9730  0,9796  72      1       2
Politician 1,0000  0,1565  0,2707  18      0       97
Totals 0,9890  0,3529  0,5202  90      1       165

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top40Links\ner-All3DomainsTop40LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top40
Links\PoliticsFineGrainedTop40Links.tsv
```

Figure 3.35: All 3 Domains Fine Top 40 Links Politics

TEXT

3. EXPERIMENTS

```
CRFClassifier tagged 13802 words in 1 documents at 3215,75 words per second.
Entity P      R      F1      TP      FP      FN
Athlete 1,0000 1,0000 1,0000 8        0        0
Coach 1,0000 1,0000 1,0000 1        0        0
SportsClub 1,0000 1,0000 1,0000 19       0        0
SportsEvent 1,0000 1,0000 1,0000 29       0        0
SportsLeague 1,0000 1,0000 1,0000 23       0        0
SportsTeam 1,0000 1,0000 1,0000 11       0        0
Totals 1,0000 1,0000 1,0000 91        0        0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top40Links\ner-All3DomainsTop40LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top40
Links\SportFineGrainedTop40Links.tsv
```

Figure 3.36: All 3 Domains Fine Top 40 Links Sport

TEXT

```
CRFClassifier tagged 10943 words in 1 documents at 3228,02 words per second.
Entity P      R      F1      TP      FP      FN
Aircraft 1,0000 1,0000 1,0000 16       0        0
Infrastructure 1,0000 1,0000 1,0000 14       0        0
PublicTransitSystem 1,0000 1,0000 1,0000 27       0        0
Ship 1,0000 1,0000 1,0000 1        0        0
SpaceShuttle 1,0000 1,0000 1,0000 6        0        0
SpaceStation 1,0000 1,0000 1,0000 1        0        0
SportsClub 0,0000 1,0000 0,0000 0        1        0
SportsTeam 0,0000 1,0000 0,0000 0        1        0
Totals 0,9701 1,0000 0,9848 65        2        0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top40Links\ner-All3DomainsTop40LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top40
Links\TransportationFineGrainedTop40Links.tsv
```

Figure 3.37: All 3 Domains Fine Top 40 Links Transportation

TEXT

```
CRFClassifier tagged 17912 words in 1 documents at 6014,78 words per second.
Entity P      R      F1      TP      FP      FN
POLITICS 0,9921 0,9804 0,9862 250      2        5
Totals 0,9921 0,9804 0,9862 250      2        5

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top40Links\ner-PoliticsTop40LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\Top40
Links\PoliticsCoarseGrainedTop40Links.tsv
```

Figure 3.38: Politics Coarse Top 40 Links Politics

TEXT

```
CRFClassifier tagged 17912 words in 1 documents at 6014,78 words per second.
Entity P      R      F1      TP      FP      FN
Election 1,0000 0,9848 0,9924 65       0        1
PoliticalParty 0,9863 0,9730 0,9796 72       1        2
Politician 1,0000 1,0000 1,0000 115      0        0
Totals 0,9960 0,9882 0,9921 252      1        3

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top40Links\ner-PoliticsTop40LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top40Lin
ks\PoliticsFineGrainedTop40Links.tsv
```

Figure 3.39: Politics Fine Top 40 Links Politics

TEXT

3.3. Summary of results

```
CRFClassifier tagged 13802 words in 1 documents at 5808,92 words per second.
Entity P      R      F1      TP      FP      FN
SPORT 1,0000  1,0000  1,0000  91      0      0
Totals 1,0000  1,0000  1,0000  91      0      0

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top40Links\ner-SportTop40LinksCoarseGrained.ser.gz -testFile domainsWithOneAnnotation\Top40Li
nks\SportCoarseGrainedTop40Links.tsv
```

Figure 3.40: Politics Coarse Top 40 Links Politics

TEXT

```
CRFClassifier tagged 13802 words in 1 documents at 4370,49 words per second.
Entity P      R      F1      TP      FP      FN
Athlete 1,0000  1,0000  1,0000  8       0      0
Coach 1,0000  1,0000  1,0000  1       0      0
SportsClub 1,0000  0,9474  0,9730  18      0      1
SportsEvent 1,0000  1,0000  1,0000  29      0      0
SportsLeague 1,0000  1,0000  1,0000  23      0      0
SportsTeam 1,0000  1,0000  1,0000  11      0      0
Totals 1,0000  0,9890  0,9945  90      0      1

C:\Dev\stanford-ner-2017-06-09>java -Xmx11g -cp stanford-ner.jar edu.stanford.nlp.ie.crf.CRFClassifier -loadClassifier
modelsWithOneAnnotation\Top40Links\ner-SportTop40LinksFineGrained.ser.gz -testFile domainsWithOneAnnotation\Top40Links\
SportFineGrainedTop40Links.tsv
```

Figure 3.41: Sport Fine Top 40 Links Sport

3.2.4 Top 100 Links

3.2.5 Top 300 Links

3.2.6 Top 400 Links

3.2.7 Top 500 Links

3.2.8 MIXED

3.2.9 With lower links on model

3.2.10 With higher links on model

3.3 Summary of results

3.3.1 Graphs

Conclusion

Contents of CD