

Embedded Software

Inter-thread communication

Agenda

- Communication design challenge
- The Message Queue - Conceptual
- Consequences

Message Queue

Communication design challenges

Communication design challenges

- Individual threads wait for a condition to become true

Communication design challenges

- Individual threads wait for a condition to become true
- Enter and leave critical sections using mutexes or semaphores
 - ▶ May happen multiple times in the space of one thread loop iteration

Communication design challenges

- Individual threads wait for a condition to become true
- Enter and leave critical sections using mutexes or semaphores
 - ▶ May happen multiple times in the space of one thread loop iteration
- May even hold multiple resources which have to be synchronized between threads
 - ▶ The sequence in which resources are taken must be thought through.


Communication design challenges

- Individual threads wait for a condition to become true
- Enter and leave critical sections using mutexes or semaphores
 - ▶ May happen multiple times in the space of one thread loop iteration
- May even hold multiple resources which have to be synchronized between threads
 - ▶ The sequence in which resources are taken must be thought through.
- **Consequence**
 - ▶ A design challenge ensuring that no deadlocks or timing issues exist
 - ▶ Readability easily becomes an issue too

The Message Queue - Conceptual


- We want an approach where
 - ▶ *all* processing within a thread must not require locking
 - ▶ however *other* threads must be able to pass control and/or data to a specific thread via some mechanism.
 - ▶ *multiple* threads may concurrently decide to pass such control and/or data

Resembles the “Producer & Consumer problem”




- The producer-consumer problem
 - ▶ A producer thread produces buffer items
 - ▶ A consumer thread consumes them
- Applied to our problem we get

Resembles the “Producer & Consumer problem”



- The producer-consumer problem
 - ▶ A producer thread produces buffer items
 - ▶ A consumer thread consumes them
- Applied to our problem we get



Further requirements for the Message Queue

Further requirements for the Message Queue

- If the receiving queue is full, then the thread or threads wishing to pass control and/or data must block waiting for more space.
 - ▶ Implies that there *is* a maximum number of elements in a queue

Further requirements for the Message Queue

- If the receiving queue is full, then the thread or threads wishing to pass control and/or data must block waiting for more space.
 - ▶ Implies that there *is* a maximum number of elements in a queue
- The consuming thread *must block* upon receiving from an empty queue

Further requirements for the Message Queue

- If the receiving queue is full, then the thread or threads wishing to pass control and/or data must block waiting for more space.
 - ▶ Implies that there *is* a maximum number of elements in a queue
- The consuming thread *must block* upon receiving from an empty queue
- Blocks are NOT to be done with polling (+ sleeps), *why?*

Further requirements for the Message Queue

- If the receiving queue is full, then the thread or threads wishing to pass control and/or data must block waiting for more space.
 - ▶ Implies that there *is* a maximum number of elements in a queue
- The consuming thread *must block* upon receiving from an empty queue
- Blocks are NOT to be done with polling (+ sleeps), *why?*
- What should we do then? - ***Conditionals***

What is the structure of the information to pass around?

What is the structure of the information to pass around?

- void* or simple array of bytes
 - ▶ Can contain anything
 - ▶ No type information - No type-safety


What is the structure of the information to pass around?

- void* or simple array of bytes
 - ▶ Can contain anything
 - ▶ No type information - No type-safety
- template based
 - ▶ Depends on the implementation, can be good solution
 - ▶ Type-safety


What is the structure of the information to pass around?

- void* or simple array of bytes
 - ▶ Can contain anything
 - ▶ No type information - No type-safety
- template based
 - ▶ Depends on the implementation, can be good solution
 - ▶ Type-safety
- Inheritance
 - ▶ Simple and extended via sub-classing
 - ▶ Type-safety
 - ▶ Might incur overhead

Using Message as a base class



Using Message as a base class




```
class Message
{
public:
    virtual ~Message(){}
};
```

```
void handler(Message* msg)
{
    // Which message???
    if(dynamic_cast<GarageDoorOpenReq*>(Msg) != NULL)
    {
        // This is the one, handle it
    }
    else if(... != NULL)
    {
        // Some other message, handle it
    }
    else if(... != NULL)
    {
        // Some other message, handle it
    }
    ...
}
```

```
struct GarageDoorOpenReq : public Message
{
    MsgQueue* mq_;
};
```

Using Message as a base class




```
class Message
{
public:
    virtual ~Message(){}
};
```

```
void handler(Message* msg)
{
    // Which message???
    if(dynamic_cast<GarageDoorOpenReq*>(msg) != NULL)
    {
        // This is the one, handle it
    }
    else if(... != NULL)
    {
        // Some other message, handle it
    }
    else if(... != NULL)
    {
        // Some other message, handle it
    }
    ...
}
```


```
struct GarageDoorOpenReq : public Message
{
    MsgQueue* mq_;
};
```

An identifier to designate which child it is



An identifier to designate which child it is

```
enum // Global enum
{
    ID_GARAGE_DOOR_OPEN_REQ=0,
    ID_GARAGE_DOOR_OPEN_CFM=1,
    ID_XXX=2,
    ID_YYY=3
};
```




```
void handler(Message* msg, size_t id)
{
    switch(id)
    {
        case ID_GARAGE_DOOR_OPEN_REQ:
            GarageDoorOpenReq* gdor = dynamic_cast<GarageDoorOpenReq*>(Msg);
            // Do stuff - call handler
            break;

        case ID_XXX:
            // ...
            break;

        default:
            std::cout << "Argh, unknown identifier, what to do???" << std::endl;
    }
}
```

Choice of item in MsgQueue

- id_ is the identifier which is to be send
- msg_ is the message to be passed



Example of what to pass around

- Combine an identifier with a class/structure
 - ▶ The compound signifies the control/data information to be send/received
 - ▶ The identifier is denoted by the receiving party NOT part of a globally defined enum; ***why not? Placed in a central place everyone knows; seems very good...?!***

The desired MsgQueue interface

MsgQueue
- queue_ : std::xxx - maxSize_ : unsigned int
+ MsgQueue(maxSize : unsigned int) + send(id : unsigned int, msg* Message = NULL) : void + receive(id : unsigned int&) : void + ~MsgQueue()

Item
+ id_ : unsigned int + msg_ : Message*

The desired MsgQueue interface

Sender threads use ***send()*** function to send messages to thread

MsgQueue
- queue_ : std::xxx
- maxSize_ : unsigned int
+ MsgQueue(maxSize : unsigned int)
+ send(id : unsigned int, msg* Message = NULL) : void
+ receive(id : unsigned int&) : void
+ ~MsgQueue()

Item
+ id_ : unsigned int
+ msg_ : Message*

The desired MsgQueue interface

Sender threads use ***send()*** function to send messages to thread

MsgQueue
- queue_ : std::xxx
- maxSize_ : unsigned int
+ MsgQueue(maxSize : unsigned int)
+ send(id : unsigned int, msg* Message = NULL) : void
+ receive(id : unsigned int&) : void
+ ~MsgQueue()

Receiver thread use ***receive()*** function to acquire a message which has been sent to it

Item
+ id_ : unsigned int
+ msg_ : Message*

The desired MsgQueue interface

Sender threads use ***send()*** function to send messages to thread

MsgQueue
- queue_ : std::xxx
- maxSize_ : unsigned int
+ MsgQueue(maxSize : unsigned int)
+ send(id : unsigned int, msg* Message = NULL) : void
+ receive(id : unsigned int&) : void
+ ~MsgQueue()


Receiver thread use ***receive()*** function to acquire a message which has been sent to it

Item
+ id_ : unsigned int
+ msg_ : Message*

List incoming messages are placed in a queue in ***struct Item***


Case - Park-a-lot 2000

- Example: Park-a-lot 2000: An automated car parking system
 - ▶ One thread steers the car
 - ▶ Another thread steers the garage door opener




Case - Park-a-lot 2000

- Example: Park-a-lot 2000: An automated car parking system
 - ▶ One thread steers the car
 - ▶ Another thread steers the garage door opener




Case - Park-a-lot 2000

- Example: Park-a-lot 2000: An automated car parking system
 - ▶ One thread steers the car
 - ▶ Another thread steers the garage door opener




Case - Park-a-lot 2000

- Example: Park-a-lot 2000: An automated car parking system
 - ▶ One thread steers the car
 - ▶ Another thread steers the garage door opener




Case - Park-a-lot 2000

- Example: Park-a-lot 2000: An automated car parking system
 - ▶ One thread steers the car
 - ▶ Another thread steers the garage door opener



Sequence Diagram



More complete example

More complete example

```
int main(int argc, char* argv[])
{
    MsgQueue garageDoorControllerMq;
    MsgQueue carMq;
    pthread_t garageDoorControllerThd;
    pthread_t carThd;

    pthread_create(& garageDoorControllerThd, NULL,
                  garageDoorOpenControllerFunc, & garageDoorControllerMq);
    pthread_create(& carThd, NULL, carFunc, & carMq);

    for(;;) sleep(100);
}
```

16

More complete example

```
int main(int argc, char* argv[])
{
    MsgQueue garageDoorControllerMq;
    MsgQueue carMq;
    pthread_t garageDoorControllerThd;
    pthread_t carThd;

    pthread_create(& garageDoorControllerThd, NULL,
                  garageDoorOpenControllerFunc, & garageDoorControllerMq);
    pthread_create(& carThd, NULL, carFunc, & carMq);

    for(;;) sleep(100);
}
```

```
void* garageDoorOpenControllerFunc(void *data)
{
    MsgQueue* mq = static_cast<MsgQueue*> (data);

    for(;;)
    {
        unsigned int id;
        Message* msg=mq->receive(id);
        garageDoorOpenControllerHandler(msg, id);
        delete msg;
    }
}
```


More complete example

```
void garageDoorOpenControllerHandler(Message* msg, size_t id)
{
    switch(id)
    {
        case ID_GARAGE_DOOR_OPEN_REQ:
            GarageDoorOpenReq* gdor = dynamic_cast<GarageDoorOpenReq*>(Msg);
            // Do stuff - call handler
            break;

        case ID_XXX:
            // ...
            break;
    }
}
```

```
void* garageDoorOpenControllerFunc(void *data)
{
    MsgQueue* mq = static_cast<MsgQueue*>(data);

    for(;;)
    {
        unsigned int id;
        Message* msg=mq->receive(id);
        garageDoorOpenControllerHandler(msg, id);
        delete msg;
    }
}
```

```
int main(int argc, char* argv[])
{
    MsgQueue garageDoorControllerMq;
    MsgQueue carMq;
    pthread_t garageDoorControllerThd;
    pthread_t carThd;
```

```
    pthread_create(& garageDoorControllerThd, NULL,
                  garageDoorOpenControllerFunc, & garageDoorControllerMq);
    pthread_create(& carThd, NULL, carFunc, & carMq);
```

```
    for(;;) sleep(100);
```

```
}
```

Park-a-lot 2000 Communication

```
class Message
{
public:
    virtual ~Message(){}
};
```

```
struct GarageDoorOpenReq : public Message
{
    MsgQueue* mq_;
};
```

```
struct GarageDoorOpenCfm : public Message
{
    bool result_;
};
```

Park-a-lot 2000 Communication

```
class Message
{
public:
    virtual ~Message(){}
};
```

```
struct GarageDoorOpenReq : public Message
{
    MsgQueue* mq_;
};
```

```
struct GarageDoorOpenCfm : public Message
{
    bool result_;
};
```

Car Thread

```
void carSendingOpenReq()
{
    // Create request
    GarageDoorOpenReq* req = new GarageDoorOpenReq;
    req->mq_ = &carMq; // Who the requester is

    // Send it
    garageDoorControllerMq.send(ID_GARAGE_DOOR_OPEN_REQ, req);
}
```

Park-a-lot 2000 Communication

```
class Message
{
public:
    virtual ~Message(){}
};
```

```
struct GarageDoorOpenReq : public Message
{
    MsgQueue* mq_;
};
```

```
struct GarageDoorOpenCfm : public Message
{
    bool result_;
};
```

Car Thread

```
void carSendingOpenReq()
{
    // Create request
    GarageDoorOpenReq* req = new GarageDoorOpenReq;
    req->mq_ = &carMq; // Who the requester is

    // Send it
    garageDoorControllerMq.send(ID_GARAGE_DOOR_OPEN_REQ, req);
}
```

GDC Thread

```
void handleGarageOpenDoorReq(GarageDoorOpenReq* req)
{
    // Create responds
    GarageDoorOpenCfm* cfm = new GarageDoorOpenCfm;
    cfm->result_ = openGarageDoor(); // The door is open

    // Send responds to requester...
    req->mq_->send(ID_GARAGE_DOOR_OPEN_CFM, cfm);
}
```

Park-a-lot 2000 Communication

```
class Message
{
public:
    virtual ~Message(){}
};
```

```
struct GarageDoorOpenReq : public Message
{
    MsgQueue* mq_;
};
```

```
struct GarageDoorOpenCfm : public Message
{
    bool result_;
};
```

Car Thread

```
void carSendingOpenReq()
{
    // Create request
    GarageDoorOpenReq* req = new GarageDoorOpenReq;
    req->mq_ = &carMq; // Who the requester is

    // Send it
    garageDoorControllerMq.send(ID_GARAGE_DOOR_OPEN_REQ, req);
}
```

GDC Thread

```
void handleGarageOpenDoorReq(GarageDoorOpenReq* req)
{
    // Create responds
    GarageDoorOpenCfm* cfm = new GarageDoorOpenCfm;
    cfm->result_ = openGarageDoor(); // The door is open

    // Send responds to requester...
    req->mq_->send(ID_GARAGE_DOOR_OPEN_CFM, cfm);
}
```

Car Thread

```
void handleGarageOpenDoorCfm(GarageDoorOpenCfm* cfm)
{
    // Check responds
    if(cfm->result_)
    {
        driveIntoParkingLot();
    }
}
```

Consequences

Consequences

- Negative
 - ▶ No silver bullet by far.
 - ▶ In a performance perspective not necessarily the best solution.
 - ▶ Mostly to do with a-synchronicity, meaning that you are not guaranteed an answer but have to have some form of timeout.

Consequences

- Negative
 - ▶ No silver bullet by far.
 - ▶ In a performance perspective not necessarily the best solution.
 - ▶ Mostly to do with a-synchronicity, meaning that you are not guaranteed an answer but have to have some form of timeout.
- Positive
 - ▶ Does not inhibit misuse, but signifies a route that makes it “more” clear, as to what is to happen when.
 - ▶ Reduces the need for critical sections e.g. mutexes and semaphores.
 - ▶ Not blocked on a conditional/mutex while waiting