

Spatialisation

```

(
  NF(\iop, {|freq=78, mul=1.0, add=0.0|
    var noise = LFNoise1.ar(0.001).range(freq, freq + (freq * 0.1));
    var osc = SinOsc.ar([noise, noise * 1.04, noise * 1.02, noise * 1.08],0,0.2);
    var out = DFMI.ar(osc,freq*4,SinOsc.kr(0.01).range(0.92,1.05),1,0,0.005,0.7);
    HPF.ar(out, 40)
  }).play;
)

(
  NF(\dsc, {|freq = 1080|
    HPF.ar(
      BBandStop.ar(Saw.ar(LFNoise1.ar([19,12]).range(freq,freq*2), 0.2).excess(
        SinOsc.ar( [freq + 6, freq + 4, freq + 2, freq + 8])),
        LFNoise1.ar([12,14,10]).range(100,900),
        SinOsc.ar(20).range(9,11)
      ), 80)
    ).play;
)

var <>pindex, <>cindex;

initialize {
  if(pindex.isNil, { pindex = 1000 });
  if(cindex.isNil, { cindex = 2000 });
}

clearProcessSlots {
  pindex = 1000;
  (this.pindex - 1000).do{|i| this[this.pindex+i] = nil; }
}

clearOrInit {|clear=true|
  if(clear == true, { this.clearProcessSlots() }, { this.initialize() });
}

transform {|process, index|
  if(index.isNil && pindex.isNil, {
    this.initialize();
  });

  pindex = pindex + 1;
  this[pindex] = \filter -> process;
}

control {|process, index|
  var i = index;

  if(i.isNil, {
    this.initialize();
    cindex = cindex + 1;
    i = cindex;
  });

  this[i] = \pset -> process;
}

(
  NF(\depfm, {|freqMin=5, freqMax=20, mul=20, add=80, rate=0.5, modFreq=2100, index=0.3, amp=0.2|
    var trig, seq, freq;
    trig = Dust.kr(rate);
    seq = Diwhite(freqMin, freqMax, inf).midicps;
    freq = Demand.kr(trig, 0, seq);
    HPF.ar(PMOsc.ar(LFCub.kr([freq, freq/2, freq/3, freq/4], 0, mul, add),
      LFNoise1.ar(0.3).range(modFreq,modFreq*2), index) * amp, 50)
  }).play;
)

```

Exercises

Exercises

Spatialisation - Exercises

1. Implement a synthesis model that uses modulations such as LFO's to control a synthesis parameter but also a spatialisation one.
2. Implement a spatialisation routine with two layers where the front is controlled via granulation while the back is through bandpass filters.
3. Implement chords of synthetic sound that is then arranged spatially via any of the covered methods.
4. Implement a psuedo-ugen that does a mix of any of the covered methods.

