



hp LaserJet 5000

hp LaserJet 5000/n/gn/dn

HP LaserJet 5000 is a superior 16 ppm A3 printer that offers more printing solutions, great looking output, versatility, compatibility, reliability and effortless management at a reasonable price.

Designed specifically for users in the computer-aided design (CAD) and desktop publishing environment (DTP), the HP LaserJet 5000 helps them alleviate their printing bottlenecks.

fast performance

- 16 ppm engine
- First page out in 13 seconds
- 1200 dpi prints without performance sacrifice
- HP Transmit Once simplifies workflow and reduces network traffic

high quality output

- Prores 1200 true 1200 dpi quality
- Fastres 1200 enables the user to print 1200 dpi quality at full engine speed using minimal memory. The thinnest line that can be printed is 0.02 mm
- Ultraprecise print cartridge delivers more accurate dot placement and enhanced grey scale, lowers the cost per page and toner maintenance

versatility

- Supports media sizes up to A3+
- Maximum of four input trays, with a total capacity of 1,100 sheets
- Straight-through paper path lets you use a wider variety of paper sizes and weights, and eliminates curling of heavier media
- Duplexing (standard for LaserJet 5000dn) allows you to print on both sides of the page, reduces paper usage thereby saving money
- Paper handling architecture connector enables third party paper handling accessories
- Enhanced driver support including AutoCAD drivers
- HP PCL 6, 5e and Postscript Level 2 emulation with automatic language switch
- HP Jetdirect internal print servers allow easy connection to local network environment
- >3 Gbyte hard disk and Flash memory DIMMs provide expanded storage of forms, fonts and signatures. Hard disk also lets you MOPy using a single transmission



hp LaserJet 5000



hp LaserJet 5000n/gn



hp LaserJet 5000dn







technical specifications

recinical specifican	0113		
speed & throughput	16-page-per-minute rated engine speed for A4 documents. 100-MHz RISC processor. First page out in 13 seconds with Instant-On fuser technology (warm or cold start).* HP Transmit Once for reduced network traffic.		
print quality	300 dpi and 600 dpi. Fastres 1200 (1200 dpi quality) at engine speed (PCL 6). Prores 1200 (True 1200 dpi) at half engine speed (PCL 6 & Postscript). Resolution Enhancement technology (REI). Device-best half-toning with up to 220 levels of grey. Prints up to 4.2 mm from edge of the page. Standard 10,000 page HP Ultraprecise print cartridge (18,000 pages ECMA/132 ISO 10561).		
standard software	HP Web Jetadmin printer management software for simple installation, configuration and management from a common web browser. Enhanced driver support of standard driver features for Microsoft Windows NT 4.0, 3.51, Windows 2000, 95/98, 3.x, Macintosh, IBM OS/2 Warp, AIX and Unix (HP-UX and Solaris), MS-DOS, AutoCAD Rev 12/13/14, Linux. Download available at http://www.hp.com		
paper handling	Up to 4 input trays with a total capacity of 1100 sheets. HP LaserJet 5000: 350 sheets standard input capacity (1 x 100 multipurpose, 1 x 250 sheet tray). HP LaserJet 5000/ng/ndn: 850 sheets standard input capacity (1 x 100 multipurpose, 1 x 250 sheet tray). Tray #1 is a 100-sheet/10 envelope multipurpose tray for automatic and manual feeding of envelopes, labels, transparencies and other special media sizes 76 mm x 127 mm to 312 mm x 470 mm. Tray #2 is a standard 250-sheet input tray supporting letter, legal, 11"x17", executive, A3, A4, A5, B4 and B5. Tray #3 is a standard 500-sheet tray supporting letter, legal, 11"x17", executive, A3, A4, A5, B4, B5 and custom paper sizes (210 mm x 148 mm to 297 mm x 432 mm). Optional 250-sheet tray supports all sizes A5 to A3. Optional 500-sheet tray supports all sizes A5 to A3 and custom sizes. Optional Auto-duplex unit (standard for LaserJet 5000dn) for double-sided printing.		
media types & weights	Paper: Copier, bond, special application, recycled paper. Overhead transparencies and labels designed for laser printers using tray #1. Standard paper tray #1: 60 to 199 g/m² through face up output bin only. 60 to 128 g/m² face up or face down output bin. Iray #2 / #4: 60 to 105 g/m². Optional 250-sheet tray #3 / #4: 60 to 105 g/m². Optional 500-sheet tray #3 / #4: 60 to 105 g/m². Envelopes: 60 to 105 g/m². Duplexer: 60 to 105 g/m². A3: 297 x 420 mm (291 x ± 15 mm printable). A4: 210 x 297 mm (204 x 297 mm (205 to 105 g/m². L48 x 210 mm; (142 x 205 mm; printable). B4(JIS): 257 x 344 mm (251 x 359 mm printable). B5(JIS): 182 x 257 mm (176 x 252 mm printable). Letter: 216 x 279 mm (210 x 274 mm printable). Legal: 216 x 356 mm (2710 x 351 mm printable). Maximum size: 312 x 470 mm (303 x 460 mm printable). Envelopes = #10 regular: 241 x 105 mm (235 x 100 mm printable). Monarch: 98 x 190 mm (93 x 185 mm printable). D1: 220 x 110 mm (214 x 105 mm printable). E5: 250 x 176 mm (244 x 171 mm printable).		
network connectivity	Bidirectional IEEE 1284 compliant parallel interface. RS-232-serial (9-pin) interface. HP LaserJet 5000: two open EIO expansion slots for optional HP Jetdirect print servers and other accessories. HP LaserJet 5000n/dn: HP Jetdirect 610n internal print server for Ethernet 10/100Base-TX networks. One open EIO expansion slot for optional HP Jetdirect print servers and other accessories. HP LaserJet 5000gn: HP Jetdirect 610n internal print server for Ethernet 10/100Base-TX networks.		
memory	HP LaserJet 5000 – 4 MB; HP LaserJet 5000n/gn – 12 MB; HP LaserJet 5000dn – 36 MB; 2 open 100 pin DIMN slots (3 for LaserJet 5000) for memory expansion to 164 MB. Optional EIO based hard disk (standard for LaserJet 5000gn) for mopying, forms, fonts and signatures.		
printer languages	HP PCL 5e, PCL 6, and Postscript Level 2 emulation. Each printer provides automatic language switching.		
control panel	Two-line back-lit LCD display and 3 LED's. Messages can be displayed in 16 languages.		
typefaces	80 scaleable TrueType® fonts built in; 30 via HP Fontsmart. Postscript Level 2 emulation. HP Fontsmart software provides easy-to-use font management capabilities. Intellifont and TrueType® rasterizer built in.		
operating & environmental ranges	Temperature for printer and toner: Operating 10° to 32.5°C. Storage: 0° to 35°C. Humidity: Operating 20% to 80% RH. Storage 10% to 95% RH. Acoustics — Operating position: Lp<58 dB (A) printing, Lp<33 dB (A) standby (per ISO 9296, DIN 45635, T.19). Bystander 1m: Lp<52 dB (A) printing, Lp<28 dB (A) standby (per ISO 7779, DIN 45635, T.19). Sound Power: Lwad = 4.4 bels (A) in Powersave. Printing at 16 ppm Lwad = 6.6 bels (A). Printing at 8 ppm Lwad = 6.3 bels (A).		
power requirements	Source: 100 to 127 volts (+/-10%) or 220 to 240 volts (+/-10%). Printer's voltage ranges depends upon the country in which the printer is purchased. Frequency: 50 or 60 Hz (+/- 2 Hz). Power Consumption – Printing: 365 watts. Standby: 40 watts. Powersave: 27 watts (EPA ENERGY STAR).		
size/weights	W x D x H: HP LaserJet 5000: 475 x 585 x 375 mm, Weight: 23 kg. HP LaserJet 5000n and 5000gn: 475 x 625 x 515 mm, Weight: 34 kg. HP LaserJet 5000dn: 475 x 649 x 615 mm, Weight: 45 kg.		
certifications	cUL and UL 1950 listed to UL 1950/CSA 950; complies with IEC 950/EN 60950, FCC Part 15 Class B certified, CISPR-22, Product CDRH certified Class 1 Laser Product (safe for office/EDP use).		
duty cycle	Up to 65,000 pages per month.		
warranty	Standard one year return to HP.		
	•		

The HP LaserJet 5000 is available as part of HP Printadvantage, a complete package that lets you procure and manage your printing requirements in one easy transaction. For more information contact: http://www.hp.com/printadvantage HP has designed the HP LaserJet 5000/n/gn/dn printers and their supplies for optimum print quality. For more information contact the Hewlett-Packard internet website at: http://www.hp.com For information on Third Party printing solutions please refer to http://www.jetcaps.com or to the global solutions catalogue http://www.hpgsc.com

For more information, please call your local HP sales office or representative: **Austria**: 0810/006080 (local rate call), **Azerbaijan**: (+994) 12 97 35 61, **Belgium**: (02) 778 34 00, **Luxembourg**: (+352) 263 16034, **Bulgaria**: (+359) 2960 1940, **CIS**: (007) 095 797 3500, **Croatia and Slovenia**: (+385 1) 60 60 200, **Czech Republic**: (00 420 2) 613 07 111 (Prague), **Denmark**: 45991125, **Dubai** (**Gulf Region**): (971) 488 15 456, **East Central Europe (Vienna HQ plus Albania)**: (+43) 1-250 00, **Finland**: (09) 88721, **France**: (1) 69 82 6060, **Germany**: 0180 532 6222 (0.48 DM per minute), **Greece**: (01) 619 64 11, **Hungary**: (+36) 1 382-1111, **Iceland**: (354) 570 1000, **Ireland**: (00) 353 1 61 58 200, **Israe**!: (972) 9 952 4848, **Italy**: (02) 92121, **Kasachstan**: (+7) 3272 98 08 24, **Morocco** (**African Region**): (212) 222 21340, **Netherlands**: (020) 5476666, **Norway**: 22 735600, **Poland**: infolinia 0-801 607 607 (0,29 PLZ + VAT/min), **Portugal**: (808) 206 001, **Romania**: (+401) 250 6197, **RSA**: (27)11 806 1000 **Slovakia**: (+421 7) 68 20 90 11, **Spain**: (91) 6311600, **Sweden**: (08) 444 2000, **Switzerland**: 0848 88 44 66, **Turkey**: (0212) 2216969, **UK**: (0990) 474747, **Ukraine**: (+380) 44 490 6120, **Uzbekistan**: (+998) 71 169 1488, **Yugoslavia**: (+381) 11 627 134, **Multi Country Operations (MCO) (Geneva**): (22) 7804111, **European Headquarters (Geneva**): (22) 7808111.

ordering information

C4110A	hp LaserJet 5000 A3, general office printer
C4111A	hp LaserJet 5000n A3, network ready office printer
C4112A	hp LaserJet 5000gn A3, etwork ready graphics printer
C8068A	hp LaserJet 5000dn A3, network ready office printer with duplex included
	supplies & accessories
C4110-67901	110V maintenance kit (150,000 pages)
C4110-67902	220V maintenance kit (150,000 pages)
C2985B	hp EIO disk drive >3GB
C4113A	automatic duplex unit
C4114A	optional 250-sheet paper feeder and tray
C4115A	optional 500-sheet paper feeder and tray
C4116A	replacement 250-sheet paper input tray
C4117A	replacement 500-sheet paper input tray
C4129X	p ultraprecise print cartridge (10,000 pages)
C4130X	oallet quantity print cartridge
H5479A	hp supportpack for hardware services
	hp jetdirect 600n/610r

	illierilai priili server
J3110A	for Ethernet/10Base-T networks
J3111A	for Ethernet/10Base-T & 10Base2 and LocalTalk networks
J3112A	for Token Ring networks (to be replaced by J4167A as of Spring 01)
J4169A	for 10/100Base-TX networks

	memory DIMMs
C4286A	2 MB Flash DIMM
C4287A	4 MB Flash DIMM
C4135A	4 MB EDO DIMM
C4136A	8 MB EDO DIMM
C4137A	16 MB EDO DIMM
C7842A	8 MB Sync DRAM
C7843A	16 MB Sync DRAM
C7845A	32 MB Sync DRAM
C7846A	64 MB Sync DRAM

interface and cable
parallel (25-pin to 36-pin male) (3m), hp vectra, IBM PC/AT and compatibles
serial (9-pin female to 9-pin male) (3m), hp vectra
serial (9-pin female to 9-pin male) (3m), IBM PC/AT and compatibles
25-pin (female) to 9-pin (male) serial cable adapter
Macintosh serial
Macintosh network

Microsoft, Windows and MS Windows are U.S. registered trademarks of Microsoft Corporation. All other brands and product names are trademarks or registered trademarks of their respective companies. The information in this document is subject to change without notice.

© Copyright Hewlett-Packard 2001 Printed in the Netherlands 04/01 5980-4417EEE