HP Color LaserJet Enterprise M750 Printer series



M750n • M750dn • M750xh



(HP Color LaserJet Enterprise M750n shown)

HP Color LaserJet Enterprise M750 Printer series



HP Color LaserJet Enterprise M750dn

Print large-volumes of professional-quality colour documents on a wide range of paper sizes. Maintain productivity with intuitive, easy-to-use management tools. Conveniently print directly from laptop PCs, smartphones or tablets.¹

Top features

Enable colour printing from postcards to posters

- Print on a wide variety of paper sizes—from 3 x 5-inch postcards to 12.6 x 17.72-inch SRA3 media.
- Produce high-volume print jobs without frequent paper changes, with a paper capacity up to 2,350 sheets.⁶
- Improve efficiency with a printer that automatically recognizes paper size and type for best printing results.
- Increase efficiency and versatility with automatic two-sided printing.³

Get great colour prints plus uncompromised speed

- Print documents rapidly—up to 30 ppm letter/A4.7
- Get a first page out in as fast as 10 seconds with Instant-on Technology.
- Get consistent print quality automatically on text, images and graphics with HP Easy Color and HP ImageREt.
- Achieve sharp contrast and vivid colour with the high-gloss toner in Original HP LaserJet print cartridges.

Count on a printer that is easy to use and manage

- Enable easy printing from smartphones, tablets and laptops at work, home, or on-the-go.¹
- Easily integrate enterprise-ready gigabit networking and robust security options into your printing fleet.
- Supervise printing fleets remotely using intuitive management tools. Control colour printing usage and costs.
- Quickly print using the easy access USB port. Safeguard data with the High-Performance Secure Hard Disk.⁵

Minimize your environmental impact.

- Reduce packaging waste with pre-installed toner cartridges—no boxes, wrappers or manuals.
- Reduce environmental impact and use up to 50 percent less paper with two-sided printing.³
- Get free and easy recycling—cartridges returned through HP Planet Partners are recycled responsibly.²
- Reduce the environmental impact of excess shipping materials with HP ClearView packaging.⁴

- ¹ Local printing requires mobile device and printer to be on the same network. Remote printing requires an Internet connection to an HP Web-connected printer. App or software and HP ePrint account registration may also be required. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area. See https://px.com/go/mobileprinting for more details.
- ² Program availability varies. HP print cartridge return and recycling is currently available in more than 50 countries and territories around the world through the HP Planet Partners program. For more information, or to request return envelopes and bulk collection boxes, visit hp.com/recycle
- ³ Automatic two-sided printing is available on the dn and xh model only.
- HP ClearView Packaging is available on the xh model only.
 HP High-Performance Secure Hard Disk is available only for the xh model.
- Optional 500-sheet paper tray and 3 x 500-sheet paper tray are available and sold separately for the n and dn models.
- Measured using ISO/IEC 24734, excludes first set of test documents. For more information see <u>hp.com/go/printerclaims</u>. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

Product walkaround

- 1 300-sheet output
- 2 Built-in auto duplex (M750dn/M750xh)
- 3 One door access to easy-to-replace print cartridges
- 4 250-sheet input tray additional 500-sheet tray
- 5 4-line, Colour Display
- 6 Easy access USB
- 7 100-sheet MP Tray, with long paper extension
- 8 Built-in 10/100/Gigabit Networking - USB 2.0 Hi Speed Port
- 9 1 GB Memory on Board



Series at a glance







| | M750n | M750dn | M750xh |
|--------------------------------------|--------------|--------------|--------------|
| Part number | D3L08A | D3L09A | D3L10A |
| 100-sheet multipurpose tray | \checkmark | \checkmark | \checkmark |
| 250-sheet input tray 2 | \checkmark | \checkmark | \checkmark |
| 500-sheet input tray 3 | \checkmark | \checkmark | \checkmark |
| Automatic two-sided printing | √ | \checkmark | \checkmark |
| 300-sheet output bin | \checkmark | \checkmark | \checkmark |
| 500-sheet input tray (add up to 2) | Optional | Optional | \checkmark |
| 3 x 500-sheet paper feeder and stand | Optional | Optional | √ |
| HP High Performance Secure Hard Disk | NA | NA | \checkmark |
| Walk-up USB port | √ | √ | √ |
| ENERGY STAR® qualified | √ | $\sqrt{}$ | $\sqrt{}$ |

HP Services

Downtime can have serious consequences, so HP provides support beyond the standard warranty. You benefit from reduced risk, maximized uptime, predictable service delivery and no unbudgeted repair costs.

Optimized Care (optimum performance and stability): 4 hour Onsite Support, Maintenance Kit Replacement Service, Installation with Network Configuration Service

Standard Care (high level of uptime): Next Business Day Onsite Support, Maintenance Kit Replacement Service, Installation with Network Configuration Service

Basic Care (minimum recommended support): Next Business Day Onsite Support

4 hr Onsite Support: Onsite support within four hours after a service call received within the coverage window

Next Business Day Onsite Support: Onsite service the next business day after the service call is received

Maintenance Kit Replacement Service: Onsite replacement of your printer's maintenance kit including parts, materials, and labour

Installation with Network Configuration Service: Assembly, network configuration, and basic administrator familiarization

For more information about HP Care Pack,

HP Contractual, or HP Managed Print Services, visit hp.com/go/printservices

Product at a glance

Printers

| HP Color LaserJet Enterprise M750n | D3L08A |
|--|--------|
| HP Color LaserJet Enterprise M750dn | D3L09A |
| HP Color LaserJet Enterprise M750xh | D3L10A |
| Toner cartridges¹ | |
| HP 650A Black LaserJet Toner Cartridge (~13,500 pages) | CE270A |

| HP 650A Black LaserJet Toner Cartridge (~13,500 pages) | CE270A |
|--|--------|
| HP 650A Cyan LaserJet Toner Cartridge (~15,000 pages) | CE271A |
| HP 650A Yellow LaserJet Toner Cartridge (~15,000 pages) | CE272A |
| HP 650A Magenta LaserJet Toner Cartridge (~15,000 pages) | CE273A |
| | |

Orderable supplies

| HP Color LaserJet 110-Volt Fuser Kit (~150,000 pages) | CE977A |
|---|--------|
| HP Color LaserJet 220-Volt Fuser Kit (~150,000 pages) | CE978A |
| HP Color LaserJet Transfer Kit (~150,000 pages) | CE516A |
| HP Color LaserJet Toner Collection Unit | CE980A |
| | |

Accessories

| CE860A |
|--------|
| CE725A |
| J8026A |
| J3263G |
| |

| HP Care Packs | |
|--|---------|
| HP 3-year DMR w/Next Coverage Day Call to Repair Hardware Support | HZ057E |
| HP 4-year DMR w/Next Coverage Day Call to Repair Hardware Support | HZ058E |
| HP 5-year DMR w/Next Coverage Day Call to Repair Hardware Support | HZ059E |
| HP 1-year Post Warranty 4 hour 13x5 Color LaserJet Hardware Support | UV271PE |
| HP 1-year Post Warranty 4 hour 9x5 Color LaserJet Hardware Support | UV272PE |
| HP 3-year 4 hour 13x5 Color LaserJet Hardware Support | UV276E |
| HP 4-year 4 hour 13x5 Color LaserJet Hardware Support | UV277E |
| HP 5-year 4 hour 13x5 Color LaserJet Hardware Support | UV278E |
| HP 3-year Next Business day Color LaserJet Hardware Support | UX964E |
| HP 4-year Next Business day Color LaserJet Hardware Support | UV280E |
| HP 5-year Next Business day Color LaserJet Hardware Support | UV279E |
| HP 3-year 4 hour 9x5 Color LaserJet Hardware Support | UX965E |
| HP 4-year 4 hour 9x5 Color LaserJet Hardware Support | UV281E |
| HP 5-year 4 hour 9x5 Color LaserJet Hardware Support | UV282E |
| HP 3-year Next business day + Disk Memory Retention Color LaserJet Support | UX963E |
| HP 4-year Next business day + Disk Memory Retention Color LaserJet Support | UX899E |

UX880E

HP 5-year Next business day + Disk Memory Retention Color LaserJet Support

Paper

hp.com/apac/paper

Software

HP Web Jetadmin: hp.com/go/wja HP Universal Print Driver: hp.com/go/upd

EcoHighlights



- Reduce energy use with Instant-on Technology¹
- · Avoid reprints with the consistency of Original HP toners plus HP Professional Colour Technologies
- Reduce paper use by up to 50% using automatic two-sided printing²
- Convenient cartridge recycling in 53 countries



¹ Compared with traditional fusing. ² Automatic two-sided printing is available on the dn and xh models only

¹ Average colour composite (C/M/Y) and black declared yields based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see hp.com/go/learnaboutsupplies

Technical specifications

| | HP Color LaserJet Enterprise M750n (D3L08A) | HP Color LaserJet Enterprise M750dn (D3L09A) | HP Color LaserJet Enterprise M750xh (D3L10A) |
|---|---|---|---|
| Function | Print only | Print only | Print only |
| Print | | | |
| Duplex print options | Manual (driver support provided) | Automatic (standard) | Automatic (standard) |
| Print speed ¹ | Black (A4): Up to 30 ppm Colour (A4): Up to 30 ppm | Black (A4): Up to 30 ppm Colour (A4): Up to 30 ppm | Black (A4): Up to 30 ppm Colour (A4): Up to 30 ppm |
| First page out ² | Black (A4): As fast as 10 sec Colour (A4): As fast as 10 sec | Black (A4): As fast as 10 sec Colour (A4): As fast as 10 sec | Black (A4): As fast as 10 sec Colour (A4): As fast as 10 sec |
| Print technology | Laser | Laser | Laser |
| Print resolution | Black (best): Up to 600 x 600 dpi Colour (best): Up to 600 x 600 dpi | Black (best): Up to 600×600 dpi Colour (best): Up to 600×600 dpi | Black (best): Up to 600 x 600 dpi Colour (best): Up to 600 x 600 dpi |
| Print resolution technologies | HP ImageREt 3600 | HP ImageREt 3600 | HP ImageREt 3600 |
| Print cartridges number | 4 (1 each black, cyan, magenta, yellow) | 4 (1 each black, cyan, magenta, yellow) | 4 (1 each black, cyan, magenta, yellow) |
| Printer smart software features | HP ePrint, Open Extensibility Platform, FutureSmart Firmware, HP Easy Color, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs | HP ePrint, Open Extensibility Platform, FutureSmart Firmware, HP Easy Color, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs | HP ePrint, Open Extensibility Platform, FutureSmart Firmware, HP Easy Color, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs |
| Mobile printing capability ³ | HP ePrint, Apple AirPrint™ | HP ePrint, Apple AirPrint™ | HP ePrint, Apple AirPrint™ |
| Standard print languages | HP PCL 6, HP PCL 5c (HP PCL 5c driver available from the Web only), HP Postscript Level 3 emulation, native PDF printing (v 1.4), Apple AirPrint™ | HP PCL 6, HP PCL 5c (HP PCL 5c driver available from the Web only), HP Postscript Level 3 emulation, native PDF printing (v 1.4), Apple AirPrint™ | HP PCL 6, HP PCL 5c (HP PCL 5c driver available from the Web only), HP Postscript Level 3 emulation, native PDF printing (v 1.4), Apple AirPrint™ |
| Printer management | HP Web Jetadmin; HP Utility (Mac) | HP Web Jetadmin; HP Utility (Mac) | HP Web Jetadmin; HP Utility (Mac) |
| onnectivity | | | |
| Standard connectivity | 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 2 Internal USB Host | 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 2 Internal USB Host | 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 2 Internal USB Host |
| Network capabilities | Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 100Base-T; 802.3az (EEE) support on Fast Ethernet and Gig Links; IPsec (standard); 802.11b/g/n wireless networking (optional) | Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gig Links; IPsec (standard); 802.11b/g/n wireless networking (optional) | Via HP Jetdirect Ethernet embedded print server (standard) supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gig Links; IPsec (standard); 802.11b/g/n wireless networking (optional) |
| Network ready | Standard (built-in Gigabit Ethernet) | Standard (built-in Gigabit Ethernet) | Standard (built-in Gigabit Ethernet) |
| Wireless capability | Optional, enabled with purchase of a HW accessory, HP Jetdirect 2700w USB Wireless Print Server J8026A | Optional, enabled with purchase of a HW accessory, HP Jetdirect 2700w USB Wireless Print Server J8026A | Optional, enabled with purchase of a HW accessory, HP Jetdirect 2700w USB Wireless Print Server J8026A |
| lemory | 1 GB | 1 GB | 1 GB |
| rocessor speed | 800 MHz | 800 MHz | 800 MHz |
| uty cycle nonthly, A4)4 | Up to 120,000 pages | Up to 120,000 pages | Up to 120,000 pages |
| ecommended monthly age volume ⁵ | 2,500 to 13,000 pages | 2,500 to 13,000 pages | 2,500 to 13,000 pages |
| Paper handling | | | |
| Input | 100-sheet multipurpose tray, 250-sheet input tray 2, 500-sheet input tray 3; Optional: 500-sheet input tray (add up to 2) or 3 x 500-sheet paper feeder and stand | 100-sheet multipurpose tray, 250-sheet input tray 2, 500-sheet input tray 3; Optional: 500-sheet input tray (add up to 2) or 3 x 500-sheet paper feeder and stand | 100-sheet multipurpose tray, 250-sheet input tray 2, 500-sheet input tray 3 |
| Output | 300-sheet output bin | 300-sheet output bin | 300-sheet output bin |
| Media type | Paper (extra heavy, glossy, heavy, heavy glossy, high gloss images, intermediate, light, plain, recycle, tough), envelopes, labels, cardstock, transparencies | Paper (extra heavy, glossy, heavy, heavy glossy, high gloss images, intermediate, light, plain, recycle, tough), envelopes, labels, cardstock, transparencies | Paper (extra heavy, glossy, heavy, heavy glossy, high gloss images, intermediate, light, plain, recycle, tough), envelopes, labels, cardstock, transparencies |
| Media weight | Tray 1: 60 to 220 g/m²; Trays 2, 3: 60 to 120 g/m² plain papers, up to 160 g/m² coated papers; Optional tray 4, 5, 6: 60 to 120 g/m² plain papers, up to 160 g/m² coated papers | Tray 1: 60 to 220 g/m²; Trays 2, 3: 60 to 120 g/m² plain papers, up to 160 g/m² coated papers; Optional tray 4, 5, 6: 60 to 120 g/m² plain papers, up to 160 g/m² coated papers | Tray 1: 60 to 220 g/m²; Trays 2, 3, 4, 5, 6: 60 to 120 g/m² plain papers, up to 160 g/m² coated papers |
| Supported media sizes | Tray 1: A3, A4, A4-R, A5, A6, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS), B6 (JIS); 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Postcard (JIS), Dpostcard (JIS), Envelopes: B5, C5, C6, DL; Tray 2, 3, 4, 5, 6: A3, A4, A4-R, A5, RA4, SRA4, B4 (JIS), B5 (JIS); BK (270 x 390), 8K (260 x 368), | Tray 1: A3, A4, A4-R, A5, A6, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS), B6 (JIS); 8K (270 × 390), 8K (260 × 368), 8K (273 × 394), 16K (195 × 270), 16K (184 × 260), 16K (197 × 273); Postcard (JIS), Dpostcard (JIS), Envelopes: B5, C5, C6, DL; Tray 2, 3, 4, 5, 6: A3, A4, A4-R, A5, RA4, SRA4, B4 (JIS), B5 (JIS); 8K (270 × 390), 8K (260 × 368), | Tray 1: A3, A4, A4-R, A5, A6, RA3, SRA3, RA4, SRA4, B4 (JIS), B5 (JIS), B6 (JIS); 8K (270 x 390), 8K (260 x 368), 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Postcard (JIS), Dpostcard (JIS), Envelopes: B5, C5, C6, DL; Tray 2, 3, 4, 5, 6: A3, A4, A4-R, A5, RA4, SRA4, B4 (JIS), B5 (JIS); 8K (270 x 390), 8K (260 x 368), |
| | 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Dpostcard (JIS) | 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Dpostcard (JIS) | 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), 16K (197 x 273); Dpostcard (JIS) |
| Dimensions (W x D x H) | 8K (273 x 394), 16K (195 x 270), 16K (184 x 260), | | |

Technical specifications

What's in the box

HP Color LaserJet Enterprise M750n printer; Print cartridges (1 each Black, Cyan, Yellow, Magenta); HP Color LaserJet 500-sheet input Tray; CDs containing device software and eleCall to Repaironic User's Guide; Documentation (including Getting Started Guides); Power cord

HP Color LaserJet Enterprise M750dn printer; Print cartridges (1 each Black Cvan Yellow Magenta); HP Color LaserJet 500-sheet input Tray; CDs containing device software and eleCall to Repaironic User's Guide; Documentation (including Getting Started Guides); Power cord

HP Color LaserJet Enterprise M750xh printer; Print cartridges (1 each Black Cyan, Yellow Magenta); HP Color LaserJet 500-sheet input Tray; HP Color LaserJet 500-sheet feeder tray 4, 5, 6; CDs containing device software and User's Guide; Documentation (including Getting Started Guides): power cord

Warranty features Compatible operating

One-year, onsite warranty

Windows 8 (32-bit/64-bit), Windows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows XP (SP2 or higher) (32-bit/64-bit), Windows Server 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac OS X version 10.6.8, 10.7.5 Lion, 10.8 Mountain Lion. For the latest operating system support see: AirPrint™ (support.apple.com/kb/ht4356); Android (android.com); Citrix and Windows Terminal Services (<u>hp.com/go/upd</u>); HP ePrint Software Driver (hp.com/go/eprintsoftware); Linux (hplip.net); Novell (novell.com/iprint); SAP device types (hp.com/go/sap/drivers); SAP Print (hp.com/go/sap/print); UNIX (hp.com/go/unix); UNIX JetDirect (hp.com/go/jetdirectunix_software)

Compatible Network Operating Systems: Windows 8.1 (32-bit/64-bit); Windows 8 Basic (32-bit/64-bit); Windows 8 Pro (32-bit/64-bit); Windows 8 Enterprise (32-bit/64-bit): Windows 8 Enterprise N (32-bit/64-bit); Windows 8 Enterprise RT (32-bit only); Windows 7 (32-bit/64-bit) (Including Starter Edition); Windows Vista (32-bit) (Including Starter Edition); Windows Vista (64-bit); Windows XP (SP2 or higher) (32-bit/64-bit); Windows Server 2012 R2; Windows Server 2012 (No Software Installer support); Windows Server Win7/2008 R2 (SP1); Windows Server 2008 (Standard Edition); Windows Server 2008 (Enterprise Edition); Windows Server 2008 (32-bit/64-bit) (SP1); Windows Server 2008 (32-bit/64-bit) (SP2); Windows Server 2008 R2 (32-bit/64-bit) (Standard Edition, Enterprise Edition); Windows Server 2008 Server Terminal Services; Windows Server 2008 Server Terminal Services with Citrix XenApp; Windows Server 2003 (Standard Edition); Windows Server 2003 (Enterprise Edition); Windows Server 2003 (32-bit/64-bit) (SP1); Windows Server 2003 (32-bit/64-bit) (SP2); Windows Server 2003 R2 (32-bit/64-bit) (Standard Edition, Enterprise Edition); Windows Server 2003 Server Terminal Services: Windows Server 2003 Server Terminal Services w/Citrix Metaframe XP with Feature Release 3; Windows Server 2003 Server Terminal Services w/Citrix Presentation Server 4.0: Windows Server 2003 Server Terminal Services with Citrix Presentation Server 4.5; Novell NetWare 6; Novell NetWare 6.5 [SP8 minimum for full Windows Vista, Windows 7 and Windows XP (SP7 if only Windows XP)]; Novell Novell iPrint Client v5.4 for Windows XP, Windows Vista and Windows 7, (x86 and x64); Novell Novell iPrint Support Only; Novell Novell Open Enterprise Server 2 (Linux); Novell Novell Open Enterprise Server 6.5; Other Citrix (Print): Citirx XenApps 6.0, Xen Server 5.6, Xen Desktop 5.5; Other Cluster Support; Mac 10.5; Mac 10.6.8; Mac 10.7.5; Mac 10.8.x; Mac 10.9.x; For Linux OS versions, refer to the HP Linux web site: hplipopensource.com/hplip-web/index.html; Unix HPUX 11i; IBM AIX 3.2.5 or higher; MPE-iX; Citrix MetaFrame Server; Red Hat Linux 7.x or higher; Solaris 2.5 or higher (SPARC systems only); SuSe Linux 8.x or higher. (For Microsoft IPv6 compatibility use Windows 2003, Windows XP Home, Windows XP Professional and Windows Vista)

One-year, onsite warranty

Windows 8 (32-bit/64-bit), Windows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows XP (SP2 or higher) (32-bit/64-bit), Windows Server 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac OS X version 10.6.8 10.7.5 Lion, 10.8 Mountain Lion. For the latest operating system support see: AirPrint™ (support.apple.com/kb/ht4356); Android (android.com); Citrix and Windows Terminal Services (hp.com/go/upd); HP ePrint Software Driver (hp.com/go/eprintsoftware); Linux (hplip.net); Novell (novell.com/iprint); SAP device types (hp.com/go/sap/drivers); SAP Print (hp.com/go/sap/print); UNIX (hp.com/go/unix); UNIX JetDirect (hp.com/go/jetdirectunix_software)

Compatible Network Operating Systems:

Windows 8.1 (32-bit/64-bit); Windows 8 Basic (32-bit/64-bit); Windows 8 Pro (32-bit/64bit): Windows 8 Enterprise (32-bit/64-bit): Windows 8 Enterprise N (32-bit/64-bit); Windows 8 Enterprise RT (32-bit only); Windows 7 (32-bit/64-bit) (Including Starter Edition); Windows Vista (32-bit) (Including Starter Edition); Windows Vista (64-bit); Windows XP (SP2 or higher) (32-bit/64-bit); Windows Server 2012 R2; Windows Server 2012 (No Software Installer support); Windows Server Win7/2008 R2 (SP1); Windows Server 2008 (Standard Edition); Windows Server 2008 (Enterprise Edition); Windows Server 2008 (32-bit/64-bit) (SP1); Windows Server 2008 (32-bit/64-bit) (SP2); Windows Server 2008 R2 (32-bit/64-bit) (Standard Edition, Enterprise Edition); Windows Server 2008 Server Terminal Services; Windows Server 2008 Server Terminal Services with Citrix XenApp; Windows Server 2003 (Standard Edition); Windows Server 2003 (Enterprise Edition); Windows Server 2003 (32-bit/64-bit) (SP1); Windows Server 2003 (32-bit/64-bit) (SP2); Windows Server 2003 R2 (32-bit/64-bit) (Standard Edition, Enterprise Edition); Windows Server 2003 Server Terminal Services: Windows Server 2003 Server Terminal Services w/Citrix Metaframe XP with Feature Release 3; Windows Server 2003 Server Terminal Services w/Citrix Presentation Server 4.0: Windows Server 2003 Server Terminal Services with Citrix Presentation Server 4.5; Novell NetWare 6; Novell NetWare 6.5 [SP8 minimum for full Windows Vista, Windows 7 and Windows XP (SP7 if only Windows XP)]; Novell Novell iPrint Client v5.4 for Windows XP, Windows Vista and Windows 7, (x86 and x64); Novell Novell iPrint Support Only; Novell Novell Open Enterprise Server 2 (Linux); Novell Novell Open Enterprise Server 6.5; Other Citrix (Print): Citirx XenApps 6.0, Xen Server 5.6, Xen Desktop 5.5; Other Cluster Support; Mac 10.5; Mac 10.6.8; Mac 10.7.5; Mac 10.8.x; Mac 10.9.x; For Linux OS versions, refer to the HP Linux web site: hplipopensource.com/hplip-web/index.html; Unix HPUX 11i; IBM AIX 3.2.5 or higher; MPE-iX; Citrix MetaFrame Server; Red Hat Linux 7.x or higher; Solaris 2.5 or higher (SPARC systems only); SuSe Linux 8.x or higher. (For Microsoft IPv6 compatibility use Windows 2003, Windows XP Home, Windows XP Professional and Windows Vista)

One-year, onsite warranty

Windows 8 (32-bit/64-bit), Windows 7 (32-bit/64-bit), Windows Vista (32-bit/64-bit), Windows XP (SP2 or higher) (32-bit/64-bit), Windows Server 2012 (64-bit), Windows Server 2008 (32-bit/64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2003 (SP1 or higher) (32-bit/64-bit), Mac OS X version 10.6.8, 10.7.5 Lion, 10.8 Mountain Lion. For the latest operating system support see: AirPrint™ (support.apple.com/kb/ht4356); Android (android.com); Citrix and Windows Terminal Services (<u>hp.com/go/upd</u>); HP ePrint Software Driver (hp.com/go/eprintsoftware); Linux (hplip.net); Novell (novell.com/iprint); SAP device types (hp.com/go/sap/drivers); SAP Print (hp.com/go/sap/print); UNIX (hp.com/go/unix); UNIX JetDirect (hp.com/go/jetdirectunix_software)

Compatible Network Operating Systems:

Windows 8.1 (32-bit/64-bit); Windows 8 Basic (32-bit/64-bit); Windows 8 Pro (32-bit/64bit): Windows 8 Enterprise (32-bit/64-bit): Windows 8 Enterprise N (32-bit/64-bit); Windows 8 Enterprise RT (32-bit only); Windows 7 (32-bit/64-bit) (Including Starter Edition); Windows Vista (32-bit) (Including Starter Edition); Windows Vista (64-bit); Windows XP (SP2 or higher) (32-bit/64-bit); Windows Server 2012 R2; Windows Server 2012 (No Software Installer support); Windows Server Win7/2008 R2 (SP1); Windows Server 2008 (Standard Edition); Windows Server 2008 (Enterprise Edition); Windows Server 2008 (32-bit/64-bit) (SP1); Windows Server 2008 (32-bit/64-bit) (SP2); Windows Server 2008 R2 (32-bit/64-bit) (Standard Edition, Enterprise Edition); Windows Server 2008 Server Terminal Services; Windows Server 2008 Server Terminal Services with Citrix XenApp; Windows Server 2003 (Standard Edition); Windows Server 2003 (Enterprise Edition); Windows Server 2003 (32-bit/64-bit) (SP1); Windows Server 2003 (32-bit/64-bit) (SP2); Windows Server 2003 R2 (32-bit/64-bit) (Standard Edition, Enterprise Edition); Windows Server 2003 Server Terminal Services: Windows Server 2003 Server Terminal Services w/Citrix Metaframe XP with Feature Release 3; Windows Server 2003 Server Terminal Services w/Citrix Presentation Server 4.0: Windows Server 2003 Server Terminal Services with Citrix Presentation Server 4.5; Novell NetWare 6; Novell NetWare 6.5 [SP8 minimum for full Windows Vista, Windows 7 and Windows XP (SP7 if only Windows XP); Novell Novell iPrint Client v5.4 for Windows XP, Windows Vista and Windows 7, (x86 and x64); Novell Novell iPrint Support Only; Novell Novell Open Enterprise Server 2 (Linux); Novell Novell Open Enterprise Server 6.5; Other Citrix (Print): Citirx XenApps 6.0, Xen Server 5.6, Xen Desktop 5.5; Other Cluster Support; Mac 10.5; Mac 10.6.8; Mac 10.7.5; Mac 10.8.x; Mac 10.9.x; For Linux OS versions, refer to the HP Linux web site: hplipopensource.com/hplip-web/index.html; Unix HPUX 11i; IBM AIX 3.2.5 or higher; MPE-iX; Citrix MetaFrame Server; Red Hat Linux 7.x or higher; Solaris 2.5 or higher (SPARC systems only); SuSe Linux 8.x or higher. (For Microsoft IPv6 compatibility use Windows 2003, Windows XP Home, Windows XP Professional and Windows Vista)

Technical specifications

| Minimum system requirements | PC: Windows 8, Windows 7 (SP1 or higher), Windows Vista, Windows XP (SP2 or higher), Windows Server 2012 (64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2008, Windows Server 2003 (SP1 or higher); 200 MB available hard disk space; CD-ROM or DVD drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0), or network connection. Operating system compatible HW system requirements see microsoft.com Mac: Mac OS X v 10.6, OS X 10.7 Lion, OS X 10.8 Mountain Lion; 1 GB of available hard-disk space; CD-ROM or DVD drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0), or network connection. Operating system compatible HW system requirements see apple.com | PC: Windows 8, Windows 7 (SP1 or higher), Windows Vista, Windows XP (SP2 or higher), Windows Server 2012 (64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2008, Windows Server 2003 (SP1 or higher); 200 MB available hard disk space; CD-ROM or DVD drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0), or network connection. Operating system compatible HW system requirements see microsoft.com Mac: Mac OS X v 10.6, OS X 10.7 Lion, OS X 10.8 Mountain Lion; 1 GB of available hard-disk space; CD-ROM or DVD drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0), or network connection. Operating system compatible HW system requirements see apple.com | PC: Windows 8, Windows 7 (SP1 or higher), Windows Vista, Windows XP (SP2 or higher), Windows Server 2012 (64-bit), Windows Server 2008 R2 (64-bit), Windows Server 2008, Windows Server 2003 (SP1 or higher); 200 MB available hard disk space; CD-ROM or DVD drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0), or network connection. Operating system compatible HW system requirements see microsoft.com Mac: Mac OS X v 10.6, OS X 10.7 Lion, OS X 10.8 Mountain Lion; 1 GB of available hard-disk space; CD-ROM or DVD drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0), or network connection. Operating system compatible HW system requirements see apple.com |
|--------------------------------------|--|---|---|
| Fonts and Typefaces | 105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at hp.com/go/laserjetfonts | 105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at hp.com/go/laserjetfonts | 105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at hp.com/go/laserjetfonts |
| Control panel | 5.2 cm (2.03"), 4-line colour, graphical and text, LCD control panel display; 7 job control buttons (Menu, Select, Stop, Back/Exit, Help, Up arrow, Down arrow); 3 LED status lights (Attention, Data, Ready); Enhanced help with animated graphics; Walk-up USB port with cover | 5.2 cm (2.03"), 4-line colour, graphical and text, LCD control panel display; 7 job control buttons (Menu, Select, Stop, Back/Exit, Help, Up arrow, Down arrow); 3 LED status lights (Attention, Data, Ready); Enhanced help with animated graphics; Walk-up USB port with cover | 5.2 cm (2.03"), 4-line colour, graphical and text, LCD control panel display; 7 job control buttons (Menu, Select, Stop, Back/Exit, Help, Up arrow, Down arrow); 3 LED status lights (Attention, Data, Ready); Enhanced help with animated graphics; Walk-up USB port with cover |
| Display | 5.2 cm (2.03 inch), 4-line Colour Graphic Display (CGD) | 5.2 cm (2.03 inch), 4-line Colour Graphic Display (CGD) | 5.2 cm (2.03 inch), 4-line Colour Graphic Display (CGD) |
| Power ⁶ | Power supply type: Built-in power supply Power supply required: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz) (Not dual voltage, power supply varies by part number with # Option code identifier) Power consumption: 677.41 watts (Printing B&W), 654.92 watts (Printing Colour), 59.46 watts (Ready), 9.09 watts (Sleep), 0.35 watts (Off) | Power supply type: Built-in power supply Power supply required: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz) (Not dual voltage, power supply varies by part number with # Option code identifier) Power consumption: 677.41 watts (Printing B&W), 654.92 watts (Printing Colour), 59.46 watts (Ready), 9.09 watts (Sleep), 0.35 watts (Off) | Power supply type: Built-in power supply Power supply required: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz) (Not dual voltage, power supply varies by part number with # Option code identifier) Power consumption: 677.41 watts (Printing B&W), 654.92 watts (Printing Colour), 59.46 watts (Ready), 9.09 watts (Sleep), 0.35 watts (Off) |
| Software included | HP PCL 6 Discrete Printer Driver; Mac SW Link to Web (Mac Installer); Windows Installer | HP PCL 6 Discrete Printer Driver; Mac SW Link to Web (Mac Installer); Windows Installer | HP PCL 6 Discrete Printer Driver; Mac SW Link to Web (Mac Installer); Windows Installer |
| Acoustic [®] | Acoustic power emissions: 6.7 B(A) Acoustic power emissions (ready): 5.0 B(A) Acoustic pressure emissions bystander (active, printing): 64.9 dB(A) Acoustic pressure emissions bystander (ready): 47.15 dB(A) | Acoustic power emissions: 6.7 B(A) Acoustic power emissions (ready): 5.0 B(A) Acoustic pressure emissions bystander (active, printing): 64.9 dB(A) Acoustic pressure emissions bystander (ready): 47.15 dB(A) | Acoustic power emissions: 6.7 B(A) Acoustic power emissions (ready): 5.0 B(A) Acoustic pressure emissions bystander (active, printing): 64.9 dB(A) Acoustic pressure emissions bystander (ready): 47.15 dB(A) |
| Operating environment | Operating humidity range: 10 to 70% RH Non-operating humidity range: 10 to 90% RH Recommended operating humidity range: 30 to 70% RH Operating temperature range: 59 to 81°F (15 to 27°C) Recommended operating temperature range: 63 to 77°F (17 to 25°C) Storage temperature range: 32 to 95°F (0 to 35°C) | Operating humidity range: 10 to 70% RH Non-operating humidity range: 10 to 90% RH Recommended operating humidity range: 30 to 70% RH Operating temperature range: 59 to 81° F (15 to 27° C) Recommended operating temperature range: 63 to 77° F (17 to 25° C) Storage temperature range: 32 to 95° F (0 to 35° C) | Operating humidity range: 10 to 70% RH Non-operating humidity range: 10 to 90% RH Recommended operating humidity range: 30 to 70% RH Operating temperature range: 59 to 81° F (15 to 27° C) Recommended operating temperature range: 63 to 77° F (17 to 25° C) Storage temperature range: 32 to 95° F (0 to 35° C) |
| Security management | Management security: SNMPv3, SSL/TLS, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WJA-10 IPsec Configuration using IPsec Plug-in | Management security: SNMPv3, SSL/TLS, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WJA-10 IPsec Configuration using IPsec Plug-in | Management security: SNMPv3, SSL/TLS, 802.1X authentication (EAP- PEAP, EAP-TLS), IPP over TLS, IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WJA-10 IPsec Configuration using IPsec Plug-in |
| Electromagnetic emission standard | CISPR 22:2008/EN 55022:2010 (Class A), EN 61000-3-2:2006 +A1:2009 +A2:2009; EN 61000-3-3:2008; EN 55024:2010; FCC Title 47 CFR, Part 15 Class A(USA); (CES-003, Issue 4 (Canada); EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries | CISPR 22:2008/EN 55022:2010 (Class A), EN 61000-3-2:2006 +A1:2009 +A2:2009; EN 61000-3-3:2008; EN 55024:2010; FCC Title 47 CFR, Part 15 Class A(USA); ICES-003, Issue 4 (Canada); EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries | CISPR 22:2008/EN 55022:2010 (Class A), EN 61000-3-2:2006 +A1:2009 +A2:2009; EN 61000-3-3:2008; EN 55024:2010; FCC Title 47 CFR, Part 15 Class A(USA); ICES-003, Issue 4 (Canada); EMC Directive 2004/108/EC with CE Marking (Europe); other EMC approvals as required by individual countries |
| Safety approvals and requirements | IEC 60950-1:2005 +A1; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011; IEC 60825-1:2007 (Class 1 Laser/Led Product); EN 60825-1:2007 (Class 1 Laser/LED Product); UL/cUL Listed (USA/Canada); GS Certificate (Germany, Europe); IEC 62479:2010; EN 62479:2010; Low Voltage Directive 2006/95/EC with CE Marking (Europe); other safety approvals as required by individual countries | IEC 60950-1:2005 +A1; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011; IEC 60825-1:2007 (Class 1 Laser/Led Product); EN 60825-1:2007 (Class 1 Laser/LED Product); UL/cUL Listed (USA/Canada); GS Certificate (Germany, Europe); IEC 62479:2010; EN 62479:2010; Low Voltage Directive 2006/95/EC with CE Marking (Europe); other safety approvals as required by individual countries | IEC 60950-1:2005 +A1; EN 60950-1:2006 +A11:2009 +A1:2010 +A12:2011; IEC 60825-1:2007 (Class 1 Laser/Led Product); EN 60825-1:2007 (Class 1 Laser/LED Product); UL/cUL Listed (USA/Canada); GS Certificate (Germany, Europe); IEC 62479:2010; EN 62479:2010; Low Voltage Directive 2006/95/EC with CE Marking (Europe); other safety approvals as required by individual countries |











Ordering Information

| Number | Description |
|--------|-------------------------------------|
| D3L08A | HP Color LaserJet Enterprise M750n |
| D3L09A | HP Color LaserJet Enterprise M750dn |
| D3L10A | HP Color LaserJet Enterprise M750xh |
| | |

Supported paper

Asia Pacific: hp.com/apac/printingsupplies

Solutions

For more solutions information, please visit hp.com/go/gsc

Hewlett-Packard offices

| Australia China | (613) 8833 5000 (010) 6564 3888 | hp.com.au hp.com.cn |
|--------------------|------------------------------------|------------------------|
| | | |
| Hong Kong | (852) 3559 7777 | <u>hp.com.hk</u> |
| India | (80) 2612 9000 | <u>hp.com/in</u> |
| Indonesia | (62-21) 5799 1088 | hp.com/id |
| Japan | (03) 5628 1101 | <u>hp.com/jp</u> |
| Korea | (02) 2199 0114 | <u>hp.co.kr</u> |
| Malaysia | (603) 2332 3333 | hp.com.my |
| New Zealand | (09) 918 9555 | hp.co.nz |
| Philippines | (632) 888 5900 | hp.com/ph |
| Singapore | (65) 6275 3888 | hp.com.sg |
| Taiwan | (02) 8722 9000 | hp.com.tw |
| Thailand | (662) 353 9500 | hp.com/th |
| Vietnam | (848) 3823 4151 | hp.com/vn |

For the following countries, please fax your queries to: (65) 6275 6707 Bangladesh • Bhutan • Brunei • Cambodia • Maldives • Nepal • Pakistan • Srilanka For more information, please visit us at <a href="https://px.ncbi.nlm.ncbi.

For more information visit our website at hp.com

© Copyright 2013 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

ENERGY STAR and the ENERGY STAR logo are registered U.S. marks. Windows is a registered trademark of Microsoft Corporation. AirPrint, iPad, iPhone, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. Linux is a U.S. registered trademark of Linus Torvalds.



¹ Measured using ISO/IEC 24734, excludes first set of test documents. For more information see <u>hp.com/go/printerclaims</u>. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

 $^{^{2}\,\,\}text{Exact speed varies depending on the system configuration, software application, driver and document complexity.}$

³ Requires an Internet connection to the printer. Feature works with any connected Internet- and e-mail-capable device. Requires HP Web Services Account Registration. Print times may vary. For a list of supported documents, and image types, see hp.com/go/eprintcenter. And for additional solutions, see hp.com/go/mobile-printing-solutions. Supports the following devices running iOS 4.2 or later: iPad®, iPad® 2, iPhone® (3GS or later), iPod touch® (3rd generation or later). Works with HP's AirPrint™ enabled printers and requires the printer be connected to the same network as your iOS device. Wireless performance is dependent upon physical environment and distance from the access point. AirPrint, the AirPrint Logo, iPad, iPhone, and iPod touch are trademarks of Apple® Inc., registered in the U.S. and other countries.

⁴ Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Colour LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

⁵ HP recommends that the number of pages per month of imaged output be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.

⁶ Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies.
Actual yields vary considerably based on images printed and other factors. For details see hp.com/go/learnaboutsupplies

Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty.

⁸ Acoustic values are subject to change. For current information see hp.com/support. Configuration tested: base model, simplex printing, A4 paper at an average of 30 ppm.