CSE 31 Computer Organization

Lecture 9 – C Memory Management (cont.)

Announcement

Labs

- Lab 3 due this week (with 7 days grace period after due date)
 - Demo is REQUIRED to receive full credit
- Lab 4 out this week
 - Due at 11:59pm on the same day of your next lab
 - You must demo your submission to your TA within 14 days

Reading assignment

- Reading 03 (zyBooks 3.1 3.7, 3.9) due 11-OCT
 - Complete Participation Activities in each section to receive grade towards Participation
 - IMPORTANT: Make sure to submit score to CatCourses by using the link provided on CatCourses

Announcement


- Homework assignment
 - Homework 02 (zyBooks 2.1 2.9) due 04-OCT
 - Complete Challenge Activities in each section to receive grade towards Homework
 - IMPORTANT: Make sure to submit score to CatCourses by using the link provided on CatCourses

Normal C Memory Management (review)

~ FFFF FFFF_{hex}

- A program's address space contains 4 regions:
 - stack: local variables, grows downward
 - heap: space requested for pointers via malloc(); resizes dynamically, grows upward
 - static data: Initialized/uninitialized static and global variables
 - code/text: loaded when program starts, does not change

For now, OS somehow prevents accesses between stack and heap (gray hash lines). Wait for virtual memory



~ 0_{hex}

K&R Malloc/Free Implementation (review)

- Each block of memory is preceded by a header that has two fields:
 - size of the block
 - a pointer to the next block
- All free blocks are kept in a circular linked list, the pointer field is unused in an allocated block
- malloc() searches the free list for a block that is big enough. If none is found, more memory is requested from the operating system. If what it gets can't satisfy the request, it fails.
- free() checks if the blocks adjacent to the freed block are also free
 - If so, adjacent free blocks are merged (coalesced) into a single, larger free block
 - Otherwise, the freed block is just added to the free list

Choosing a block in malloc()

- If there are multiple free blocks of memory that are big enough for some request, how do we choose which one to use?
 - best-fit: choose the smallest block that is big enough for the request
 - first-fit: choose the first block we see that is big enough
 - next-fit: like first-fit but remember where we finished searching and resume searching from there

Tradeoffs of allocation policies

- Best-fit: Tries to limit fragmentation but at the cost of time (must examine all free blocks for each malloc).
 - Leaves lots of small blocks (why?)
- First-fit: Quicker than best-fit (why?) but potentially more fragmentation.
 - Tends to concentrate small blocks at the beginning of the free list (why?)
- Next-fit: Does not concentrate small blocks at front like first-fit, should be faster as a result.

Quiz – Pros and Cons of fits

- 1) first-fit results in many small blocks at the beginning of the free list
- 2) next-fit is slower than first-fit, since it takes longer in steady state to find a match
- 3) best-fit leaves lots of tiny blocks

123

- a) FFT
- b) FTT
- c) TFF
- d) TFT
- e) TTT

Quiz – Pros and Cons of fits

- 1) first-fit results in many small blocks at the beginning of the free list
- 2) next-fit is slower than first-fit, since it takes longer in steady state to find a match
- 3) best-fit leaves lots of tiny blocks

123

- a) FFT
- b) FTT
- c) TFF
- d) TFT
- e) TTT

Summary

- C has 3 pools of memory
 - <u>Static storage</u>: global and static variable storage, basically permanent, entire program run
 - The Stack: local variable storage, parameters, return address
 - The Heap (dynamic storage): malloc() grabs space from here, free() returns it.
- malloc() handles free space with freelist. Three different ways to find free space when given a request:
 - First fit (find first one that's free)
 - Next fit (same as first, but remembers where left off)
 - Best fit (finds most "snug" free space)

Slab Allocator

- ▶ A different approach to memory management (used in GNU libc)
- Divide blocks in to "large" and "small" by picking an arbitrary threshold size (say 128kB). Blocks larger than this threshold are managed with a freelist (as before).
- For small blocks, allocate blocks in sizes that are powers of 2
 - e.g., if program wants to allocate 20 bytes, actually give it 32 bytes

Slab Allocator

- Bookkeeping for small blocks is relatively easy
 - Use a bitmap for each range of blocks of the same size
- Allocating is easy and fast
 - Compute the size of the block to allocate and find a free bit in the corresponding bitmap.
- Freeing is also easy and fast
 - Figure out which slab the address belongs to and clear the corresponding bit.

Slab Allocator

16 byte blocks:				
32 byte blocks:				
64 byte blocks:				

16 byte block bitmap: 11011000

32 byte block bitmap: 0111

64 byte block bitmap: 00

Slab Allocator Tradeoffs

- Extremely fast for small blocks.
- Slower for large blocks
 - But presumably the program will take more time to do something with a large block, so the overhead is not as critical.
- Minimal space overhead
- No external fragmentation (as we defined it before)
 - For small blocks, but still have wasted space!

Internal vs. External Fragmentation

- With the slab allocator, difference between requested size and next power of 2 is wasted
 - e.g., if program wants to allocate 20 bytes and we give it a
 32 byte block, 12 bytes are unused.
- We also refer to this as fragmentation, but call it internal fragmentation since the wasted space is actually within an allocated block.
- External fragmentation: wasted space between allocated blocks.

Buddy System

- Yet another memory management technique (used in Linux kernel)
- Like GNU's "slab allocator", but only allocate blocks in sizes that are powers of 2 (internal fragmentation is possible)
- Keep separate free lists for each size
 - e.g., separate free lists for 16 byte, 32 byte,
 64 byte blocks, etc.

Buddy System

- If no free block of size n is available, find a block of size 2n and split it in to two blocks of size n
- ▶ When a block of size n is freed, if its neighbor of size n is also free, combine the blocks into a single block of size 2n
 - Buddy is a block in other half larger block



Same speed advantages as slab allocator

Allocation Schemes

- So which memory management scheme (K&R, slab, buddy) is best?
 - There is no single best approach for every application.
 - Different applications have different allocation / deallocation patterns.
 - A scheme that works well for one application may work poorly for another application.

Automatic Memory Management

- Dynamically allocated memory is difficult to track
 - Why not track it automatically?
- If we can keep track of what memory is in use, we can reclaim everything else.
 - Unreachable memory is called garbage, the process of reclaiming it is called garbage collection.
- So how do we track what is in use?

Tracking Memory Usage

- Techniques depend heavily on the programming language and rely on help from the compiler.
- Start with all pointers in global variables and local variables (<u>root set</u>).
- Recursively examine dynamically allocated objects we see a pointer to.
 - We can do this in constant space by reversing the pointers on the way down
- How do we recursively find pointers in dynamically allocated memory?

Tracking Memory Usage

- Again, it depends heavily on the programming language and compiler.
- Could have only a single type of dynamically allocated object in memory
 - E.g., simple Lisp/Scheme system with only cons cells
- Could use a strongly typed language (e.g., Java)
 - Don't allow conversion (casting) between arbitrary types.
 - C/C++ are not strongly typed.
- We will cover 3 schemes to collect garbage

Scheme 1: Reference Counting

- For every chunk of dynamically allocated memory, keep a count of number of pointers that point to it.
- When the count reaches 0, reclaim the memory.
- Simple assignment statements can result in a lot of work, since may update reference counts of many items

Reference Counting Example

- For every chunk of dynamically allocated memory, keep a count of number of pointers that point to it.
 - When the count reaches 0, reclaim.

```
int *p1, *p2;
p1 = (int *)malloc(sizeof(int));
p2 = (int *)malloc(sizeof(int));
*p1 = 10; *p2 = 20;

Reference
count = 1

Reference
count = 1

10
```

Reference Counting Example

- For every chunk of dynamically allocated memory, keep a count of number of pointers that point to it.
 - When the count reaches 0, reclaim.

```
int *p1, *p2;
p1 = (int *)malloc(sizeof(int));
p2 = (int *)malloc(sizeof(int));
*p1 = 10; *p2 = 20;
p1 = p2;

Reference
count = 2
Reference
count = 0
10
```

Reference Counting (p1, p2 are pointers)

```
p1 = p2;
```

- ▶ Increment reference count for p2
- If p1 held a valid value, decrement its reference count
- If the reference count for p1 is now 0, reclaim the storage it points to.
 - \circ If the storage pointed to by p1 was pointing to other pointers, decrement all their reference counts, and so on...
- Must also decrement reference count when local variables cease to exist.