

1. Description

1.1. Project

Project Name	Robot_Arm
Board Name	NUCLEO-L476RG
Generated with:	STM32CubeMX 6.14.0
Date	03/12/2025


1.2. MCU

MCU Series	STM32L4
MCU Line	STM32L4x6
MCU name	STM32L476RGTx
MCU Package	LQFP64
MCU Pin number	64

1.3. Core(s) information

Core(s)	Arm Cortex-M4

2. Pinout Configuration




3. Pins Configuration

Pin Number LQFP64	Pin Name (function after	Pin Type	Alternate Function(s)	Label
	reset)			
1	VBAT	Power		
2	PC13	I/O	GPIO_EXTI13	B1 [Blue PushButton]
3	PC14-OSC32_IN (PC14)	I/O	RCC_OSC32_IN	
4	PC15-OSC32_OUT (PC15)	I/O	RCC_OSC32_OUT	
5	PH0-OSC_IN (PH0) *	I/O	RCC_OSC_IN	
6	PH1-OSC_OUT (PH1) *	I/O	RCC_OSC_OUT	
7	NRST	Reset		
12	VSSA/VREF-	Power		
13	VDDA/VREF+	Power		
14	PA0	I/O	TIM2_CH1	
16	PA2	I/O	USART2_TX	USART_TX
17	PA3	I/O	USART2_RX	USART_RX
18	VSS	Power		
19	VDD	Power		
21	PA5 **	I/O	GPIO_Output	LD2 [green Led]
22	PA6	I/O	TIM3_CH1	
31	VSS	Power		
32	VDD	Power		
37	PC6	I/O	TIM8_CH1	
41	PA8	I/O	TIM1_CH1	
46	PA13 (JTMS-SWDIO)	I/O	SYS_JTMS-SWDIO	TMS
47	VSS	Power		
48	VDDUSB	Power		
49	PA14 (JTCK-SWCLK)	I/O	SYS_JTCK-SWCLK	TCK
55	PB3 (JTDO-TRACESWO) *	I/O	SYS_JTDO-SWO	SWO
58	PB6	I/O	TIM4_CH1	
60	BOOT0	Boot		
63	VSS	Power		
64	VDD	Power		

^{**} The pin is affected with an I/O function

^{*} The pin is affected with a peripheral function but no peripheral mode is activated

4. Clock Tree Configuration



Page 4

1. Power Consumption Calculator report

1.1. Microcontroller Selection

Series	STM32L4
Line	STM32L4x6
MCU	STM32L476RGTx
Datasheet	DS10198_Rev4

1.2. Parameter Selection

Temperature	25
Vdd	3.0

1.3. Battery Selection

Battery	Li-SOCL2(A3400)
Capacity	3400.0 mAh
Self Discharge	0.08 %/month
Nominal Voltage	3.6 V
Max Cont Current	100.0 mA
Max Pulse Current	200.0 mA
Cells in series	1
Cells in parallel	1


1.4. Sequence

_	_	
Step	Step1	Step2
Mode	RUN	STOP2
Vdd	3.0	3.0
Voltage Source	Battery	Battery
Range	Range1-High	NoRange
Fetch Type	SRAM2	n/a
CPU Frequency	80 MHz	0 Hz
Clock Configuration	HSE PLL	ALL CLOCKS OFF
Clock Source Frequency	4 MHz	0 Hz
Peripherals		
Additional Cons.	0 mA	0 mA
Average Current	10.7 mA	1.18 μΑ
Duration	0.1 ms	0.9 ms
DMIPS	100.0	0.0
Ta Max	103.56	105
Category	In DS Table	In DS Table

1.5. Results

Sequence Time	1 ms	Average Current	1.07 mA
Battery Life	4 months, 10	Average DMIPS	100.0 DMIPS
	days, 3 hours		

1.6. Chart



2. Software Project

2.1. Project Settings

Name	Value
Project Name	Robot_Arm
Project Folder	C:\Users\bradm\OneDrive\Desktop\ECEN361\FINAL_PROJECT_STUFF\Robot_
Toolchain / IDE	STM32CubeIDE
Firmware Package Name and Version	STM32Cube FW_L4 V1.18.1
Application Structure	Advanced
Generate Under Root	Yes
Do not generate the main()	No
Minimum Heap Size	0x200
Minimum Stack Size	0x400

2.2. Code Generation Settings

Name	Value
STM32Cube MCU packages and embedded software	Copy only the necessary library files
Generate peripheral initialization as a pair of '.c/.h' files	No
Backup previously generated files when re-generating	No
Keep User Code when re-generating	Yes
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power consumption)	No
Enable Full Assert	No

2.3. Advanced Settings - Generated Function Calls

Rank	Function Name	Peripheral Instance Name
1	SystemClock_Config	RCC
2	MX_GPIO_Init	GPIO
3	MX_USART2_UART_Init	USART2
4	MX_TIM2_Init	TIM2
5	MX_TIM3_Init	TIM3
6	MX_TIM1_Init	TIM1
7	MX_TIM4_Init	TIM4
8	MX_TIM8_Init	TIM8

3. Peripherals and Middlewares Configuration

3.1. RCC

Low Speed Clock (LSE): Crystal/Ceramic Resonator

3.1.1. Parameter Settings:

System Parameters:

VDD voltage (V)

Instruction Cache

Prefetch Buffer

Data Cache

3.3

Enabled

Enabled *

Enabled

Flash Latency(WS) 4 WS (5 CPU cycle)

RCC Parameters:

HSI Calibration Value 16

MSI Calibration Value 0

MSI Auto Calibration Disabled

HSE Startup Timout Value (ms) 100

LSE Startup Timout Value (ms) 5000

Power Parameters:

Power Regulator Voltage Scale Power Regulator Voltage Scale 1

3.2. SYS

Debug: Serial Wire

Timebase Source: SysTick

3.3. TIM1

Channel1: PWM Generation CH1

3.3.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value) 79 *
Counter Mode Up

Counter Period (AutoReload Register - 16 bits value) 1999 *
Internal Clock Division (CKD) No Division

Repetition Counter (RCR - 16 bits value) 0
auto-reload preload Disable

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit) Disable (Trigger input effect not delayed)

Trigger Event Selection TRGO Reset (UG bit from TIMx_EGR)

Trigger Event Selection TRGO2 Reset (UG bit from TIMx_EGR)

Break And Dead Time management - BRK Configuration:

BRK State Disable
BRK Polarity High
BRK Filter (4 bits value) 0

BRK Sources Configuration

Digital Input
 COMP1
 COMP2
 Disable
 DFSDM
 Disable

Break And Dead Time management - BRK2 Configuration:

BRK2 State Disable
BRK2 Polarity High
BRK2 Filter (4 bits value) 0

BRK2 Sources Configuration

Digital Input
 COMP1
 COMP2
 Disable
 DFSDM
 Disable

Break And Dead Time management - Output Configuration:

Automatic Output State Disable

Off State Selection for Run Mode (OSSR) Disable

Off State Selection for Idle Mode (OSSI) Disable

Lock Configuration Off

Clear Input:

Clear Input Source Disable

PWM Generation Channel 1:

Mode PWM mode 1

Pulse (16 bits value) 0

Output compare preload Enable
Fast Mode Disable
CH Polarity High
CH Idle State Reset

3.4. TIM2

Channel1: PWM Generation CH1

3.4.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value) 79 *

Counter Mode Up

Counter Period (AutoReload Register - 32 bits value) 1999 *

Internal Clock Division (CKD) No Division auto-reload preload Disable

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit) Disable (Trigger input effect not delayed)

Trigger Event Selection TRGO Reset (UG bit from TIMx_EGR)

Clear Input:

Clear Input Source Disable

PWM Generation Channel 1:

Mode PWM mode 1

Pulse (32 bits value) 0
Output compare preload Enable
Fast Mode Disable
CH Polarity High

3.5. TIM3

Channel1: PWM Generation CH1

3.5.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value) 79 *
Counter Mode Up

Counter Period (AutoReload Register - 16 bits value) 1999 *
Internal Clock Division (CKD) No Division

auto-reload preload Disable

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit) Disable (Trigger input effect not delayed)

Trigger Event Selection TRGO Reset (UG bit from TIMx_EGR)

Clear Input:

Clear Input Source Disable

PWM Generation Channel 1:

Mode PWM mode 1

Pulse (16 bits value) 0
Output compare preload Enable
Fast Mode Disable
CH Polarity High

3.6. TIM4

Channel1: PWM Generation CH1

3.6.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value) 79 *

Counter Mode Up

Counter Period (AutoReload Register - 16 bits value) 1999 *

Internal Clock Division (CKD) No Division

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit) Disable (Trigger input effect not delayed)

Disable

Trigger Event Selection TRGO Reset (UG bit from TIMx_EGR)

Clear Input:

auto-reload preload

Clear Input Source Disable

PWM Generation Channel 1:

Mode PWM mode 1

Pulse (16 bits value) 0

Output compare preload Enable

Fast Mode Disable

CH Polarity High

3.7. TIM8

Channel1: PWM Generation CH1

3.7.1. Parameter Settings:

Counter Settings:

Prescaler (PSC - 16 bits value) 79 *
Counter Mode Up

Counter Period (AutoReload Register - 16 bits value) 1999 *
Internal Clock Division (CKD) No Division

Repetition Counter (RCR - 16 bits value) 0
auto-reload preload Disable

Trigger Output (TRGO) Parameters:

Master/Slave Mode (MSM bit)

Disable (Trigger input effect not delayed)

Trigger Event Selection TRGO Reset (UG bit from TIMx_EGR)

Trigger Event Selection TRGO2 Reset (UG bit from TIMx_EGR)

Break And Dead Time management - BRK Configuration:

BRK State Disable
BRK Polarity High
BRK Filter (4 bits value) 0

BRK Sources Configuration

Digital Input
 COMP1
 COMP2
 Disable
 DFSDM
 Disable

Break And Dead Time management - BRK2 Configuration:

BRK2 State Disable
BRK2 Polarity High
BRK2 Filter (4 bits value) 0

BRK2 Sources Configuration

- Digital Input
- COMP1
- COMP2
- Disable
- DFSDM
- Disable
- Disable

Break And Dead Time management - Output Configuration:

Automatic Output State Disable
Off State Selection for Run Mode (OSSR) Disable
Off State Selection for Idle Mode (OSSI) Disable
Lock Configuration Off

Clear Input:

Clear Input Source Disable

PWM Generation Channel 1:

Mode PWM mode 1

Pulse (16 bits value) 0
Output compare preload Enable
Fast Mode Disable
CH Polarity High
CH Idle State Reset

3.8. **USART2**

Mode: Asynchronous

3.8.1. Parameter Settings:

Basic Parameters:

Baud Rate 115200

Word Length 8 Bits (including Parity)

Parity None Stop Bits 1

Advanced Parameters:

Data Direction Receive and Transmit

Over Sampling 16 Samples
Single Sample Disable

Advanced Features:

Auto Baudrate Disable TX Pin Active Level Inversion Disable RX Pin Active Level Inversion Disable Disable Data Inversion TX and RX Pins Swapping Disable Enable Overrun DMA on RX Error Enable MSB First Disable

* User modified value

4. System Configuration

4.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
RCC	PC14- OSC32_IN (PC14)	RCC_OSC32_IN	n/a	n/a	n/a	
	PC15- OSC32_OU T (PC15)	RCC_OSC32_O UT	n/a	n/a	n/a	
SYS	PA13 (JTMS- SWDIO)	SYS_JTMS- SWDIO	n/a	n/a	n/a	TMS
	PA14 (JTCK- SWCLK)	SYS_JTCK- SWCLK	n/a	n/a	n/a	TCK
TIM1	PA8	TIM1_CH1	Alternate Function Push Pull	No pull-up and no pull-down	Low	
TIM2	PA0	TIM2_CH1	Alternate Function Push Pull	No pull-up and no pull-down	Low	
TIM3	PA6	TIM3_CH1	Alternate Function Push Pull	No pull-up and no pull-down	Low	
TIM4	PB6	TIM4_CH1	Alternate Function Push Pull	No pull-up and no pull-down	Low	
TIM8	PC6	TIM8_CH1	Alternate Function Push Pull	No pull-up and no pull-down	Low	
USART2	PA2	USART2_TX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	USART_TX
	PA3	USART2_RX	Alternate Function Push Pull	No pull-up and no pull-down	Very High	USART_RX
Single Mapped Signals	PH0- OSC_IN (PH0)	RCC_OSC_IN	n/a	n/a	n/a	
	PH1- OSC_OUT (PH1)	RCC_OSC_OUT	n/a	n/a	n/a	
	PB3 (JTDO- TRACESWO)	SYS_JTDO- SWO	n/a	n/a	n/a	SWO
GPIO	PC13	GPIO_EXTI13	External Interrupt Mode with Falling edge trigger detection	No pull-up and no pull-down	n/a	B1 [Blue PushButton]
	PA5	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LD2 [green Led]

4.2. DMA configuration

nothing configured in DMA service

Robot_Arm Project
Configuration Report

4.3. NVIC configuration

4.3.1. NVIC

Interrupt Table	Enable	Preenmption Priority	SubPriority	
Non maskable interrupt	true	0	0	
Hard fault interrupt	true	0	0	
Memory management fault	true	0	0	
Prefetch fault, memory access fault	true	0	0	
Undefined instruction or illegal state	true	0	0	
System service call via SWI instruction	true	0	0	
Debug monitor	true	0	0	
Pendable request for system service	true	0	0	
System tick timer	true	0	0	
PVD/PVM1/PVM2/PVM3/PVM4 interrupts through EXTI lines 16/35/36/37/38	unused			
Flash global interrupt	unused			
RCC global interrupt	unused			
TIM1 break interrupt and TIM15 global interrupt	unused			
TIM1 update interrupt and TIM16 global interrupt	unused			
TIM1 trigger and commutation interrupts and TIM17 global interrupt	unused			
TIM1 capture compare interrupt	unused			
TIM2 global interrupt	unused			
TIM3 global interrupt	unused			
TIM4 global interrupt	unused			
USART2 global interrupt	unused			
EXTI line[15:10] interrupts	unused			
TIM8 break interrupt	unused			
TIM8 update interrupt	unused			
TIM8 trigger and commutation interrupts	unused			
TIM8 capture compare interrupt	unused			
FPU global interrupt	unused			

4.3.2. NVIC Code generation

Enabled interrupt Table	Select for init	Generate IRQ	Call HAL handler
	sequence ordering	handler	
Non maskable interrupt	false	true	false
Hard fault interrupt	false	true	false
Memory management fault	false	true	false
Prefetch fault, memory access fault	false	true	false
Undefined instruction or illegal state	false	true	false


Enabled interrupt Table	Select for init	Generate IRQ	Call HAL handler
	sequence ordering	handler	
System service call via SWI instruction	false	true	false
Debug monitor	false	true	false
Pendable request for system service	false	true	false
System tick timer	false	true	true

^{*} User modified value

5. System Views

5.1. Category view

5.1.1. Current



6. Docs & Resources

Type Link

BSDL files https://www.st.com/resource/en/bsdl_model/stm32l4_bsdl.zip

IBIS models https://www.st.com/resource/en/ibis_model/stm32l4_ibis.zip

System View https://www.st.com/resource/en/svd/stm32l4_svd.zip

Description

Presentations https://www.st.com/resource/en/product_presentation/stm32-

stm8_embedded_software_solutions.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32_eval-

tools_portfolio.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32_stm8_functi

onal-safety-packages.pdf

Presentations https://www.st.com/resource/en/product_presentation/stm32-

stm8_software_development_tools.pdf

Presentations https://www.st.com/resource/en/product_presentation/microcontrollers-

stm32-family-overview.pdf

Presentations https://www.st.com/resource/en/product_presentation/microcontrollers-

stm32l4-series-product-overview.pdf

Brochures https://www.st.com/resource/en/brochure/brstm32ulp.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32l4.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32nucleo.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32trust.pdf

Flyers https://www.st.com/resource/en/flyer/flstm32gui.pdf

Magazine Articles https://www.st.com/resource/en/magazine/design-

elektronik_august2017.pdf

Magazine Articles https://www.st.com/resource/en/magazine/design-

elektronik_october2016.pdf

Product https://www.st.com/resource/en/certification_document/sesip-2000002-

Certifications 01-cert.pdf

Product https://www.st.com/resource/en/certification_document/sesip-2000002-

Certifications 01-st2.pdf

Product https://www.st.com/resource/en/certification_document/psa-

Certifications certificate_stm32l4.pdf

Application Notes https://www.st.com/resource/en/application_note/an1709-emc-design-

guide-for-stm8-stm32-and-legacy-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an2606-stm32-

microcontroller-system-memory-boot-mode-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3126-audio-and-

waveform-generation-using-the-dac-in-stm32-products-

stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3154-can-protocol-

 $used\hbox{-}in\hbox{-}the\hbox{-}stm 32\hbox{-}bootloader\hbox{-}stm icroelectronics.pdf$

Application Notes https://www.st.com/resource/en/application_note/an3155-usart-protocol-

used-in-the-stm32-bootloader-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an3156-usb-dfu-

protocol-used-in-the-stm32-bootloader-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4221-i2c-protocol-

used-in-the-stm32-bootloader-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4286-spi-protocol-

used-in-the-stm32-bootloader-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4555-getting-started-

with-stm32l4-series-and-stm32l4-series-hardware-development-

stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4566-extending-the-

dac-performance-of-stm32-microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application note/an4612-migrating-from-

stm32l1-series-to-stm32l4-series-and-stm32l4-series-microcontrollers-

stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4616-migrating-from-

stm32f401-and-stm32f411-lines-to-stm32l4-series-and-stm32l4-series-

microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4621-stm32l4-and-

stm32l4-ultralowpower-features-overview-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4629-adc-hardware-

- oversampling-for-microcontrollers-of-the-stm32-l0-and-l4-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4649-migrating-from-stm32f1-series-to-stm32l4-series--stm32l4-series-microntrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4655-virtually-increasing-the-number-of-serial-communication-peripherals-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4726-stm32cube-firmware-examples-for-stm32l4-series-and-stm32l4-series-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4729-stm32l0l4-firewall-overview-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4730-using-the-firewall-embedded-in-stm32l0l4l4-series-mcus-for-secure-access-to-sensitive-parts-of-code-and-data-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4746-optimizing-power-and-performance-with-stm32l4-and-stm32l4-series-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4750-handling-of-soft-errors-in-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4754-migrating-between-stm32l486xx476xx-and-stm32l443xx433xx-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4776-generalpurpose-timer-cookbook-for-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4803-highspeed-si-simulations-using-ibis-and-boardlevel-simulations-using-hyperlynx-si-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4809-migrating-between-stm32l0-series-and-stm32l4-series--stm32l4-series-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4821-migrating-from-stm32f405415-line-and-stm32f407417-line-to-stm32l4-series-and-

- stm32l4-series-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4822-migrating-between-stm32l476xx486xx-and-stm32l496xx4a6xx-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4831-migrating-from-stm32f2x5-line-to-stm32l4-series-and-stm32l4-series-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4832-migrating-from-stm32f303-line-to-stm32l4-series-and-stm32l4-series-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4989-stm32-microcontroller-debug-toolbox-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4990-getting-started-with-sigmadelta-digital-interface-on-applicable-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4995-using-anelectromyogram-technique-to-detect-muscle-activitystmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5012-analogtodigital-audio-conversion-example-using-stm32l4-series-microcontroller-peripherals-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5017-migrating-between-stm32l476xx486xx-and-stm32l4-series-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5027-interfacing-pdm-digital-microphones-using-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5105-getting-started-with-touch-sensing-control-on-stm32-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5138-migrating-from-stm32l4-and-stm32l4-to-stm32l5-series-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5408-migrating-from-stm32l0-stm32l1-and-stm32l4-series-associated-with-sx12xx-

- transceivers-to-stm32wl-series-microcontrollers-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4760-quadspiinterface-on-stm32-microcontrollers-and-microprocessors-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4899-stm32microcontroller-gpio-hardware-settings-and-lowpower-consumptionstmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5612-esd-protection-of-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4991-how-to-wake-up-an-stm32-microcontroller-from-lowpower-mode-with-the-usart-or-the-lpuart-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4838-introduction-to-memory-protection-unit-management-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4879-introduction-to-usb-hardware-and-pcb-guidelines-using-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5372-migrating-from-stm32l4-and-stm32l4--to-stm32u5-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5225-introduction-to-usb-typec-power-delivery-for-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4777-how-to-optimize-power-consumption-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4894-how-to-use-eprom-emulation-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5537-how-to-use-adcoversampling-techniques-to-improve-signaltonoise-ratio-on-stm32-mcusstmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5036-guidelines-for-thermal-management-on-stm32-applications-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5690-how-to-use-

- vrefbuf-peripheral-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4230-introduction-to-random-number-generation-validation-using-the-nist-statistical-test-suite-for-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2548-introduction-to-dma-controller-for-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2867-guidelines-for-oscillator-design-on-stm8afals-and-stm32-mcusmpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3236-how-to-increase-the-number-of-touchkeys-for-touch-sensing-applications-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an3960-guidelines-for-esd-for-touch-sensing-applications-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4013-introduction-to-timers-for-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4277-how-to-use-pwm-shutdown-for-motor-control-and-digital-power-conversion-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4299-how-to-improve-conducted-noise-robustness-for-touch-sensing-applications-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4310-how-to-choose-the-sampling-capacitor-for-touch-sensing-applications-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4312-how-to-design-surface-sensors-for-touch-sensing-applications-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4316-how-to-tune-touch-sensing-applications-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4635-how-tooptimize-lpuart-power-consumption-on-stm32-mcusstmicroelectronics.pdf

- Application Notes https://www.st.com/resource/en/application_note/an4759-introduction-to-using-the-hardware-realtime-clock-rtc-and-the-tamper-management-unit-tamp-with-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4908-getting-started-with-usart-automatic-baud-rater-detection-for-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4943-how-to-use-chromart-accelerator-to-refresh-an-lcdtft-display-on-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5156-introduction-to-security-for-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5543-guidelines-for-enhanced-spi-communication-on-stm32-mcus-and-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/cd00211314-how-to-optimize-the-adc-accuracy-in-the-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an2639-solderingrecommendations-and-package-information-for-leadfree-ecopack2-mcusand-mpus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an5020-introduction-to-digital-camera-interface-dcmi-for-stm32-mcus-stmicroelectronics.pdf
- Application Notes https://www.st.com/resource/en/application_note/an4044-floating-point-for related Tools unit-demonstration-on-stm32-microcontrollers-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application_note/an4323-getting-started-for related Tools with-stemwin-library-stmicroelectronics.pdf
& Software

Application Notes https://www.st.com/resource/en/application_note/an4435-guidelines-for-for related Tools obtaining-ulcsaiec-607301603351-class-b-certification-in-any-stm32- & Software application-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4631-how-to-for related Tools calibrate-an-stm32l0xx-internal-rc-oscillator-stmicroelectronics.pdf & Software

Application Notes https://www.st.com/resource/en/application_note/an4657-stm32-

for related Tools inapplication-programming-iap-using-the-usart-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4666-parallel-

for related Tools synchronous-transmission-using-gpio-and-dma-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4701-proprietary-for related Tools code-readout-protection-on-microcontrollers-of-the-stm32f4-series-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4726-stm32cube-

for related Tools firmware-examples-for-stm32l4-series-and-stm32l4-series-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4736-how-to-

for related Tools calibrate-stm32l4-series-microcontrollers-internal-rc-oscillator-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4758-proprietary-for related Tools code-readout-protection-on-stm32l4-stm32l4-stm32g4-and-stm32wb-

& Software series-mcus-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4767-onthefly-

for related Tools firmware-update-for-dual-bank-stm32-microcontrollers-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4834-implementation-for related Tools of-transmitters-and-receivers-for-infrared-remote-control-protocols-with-

& Software stm32cube-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4841-digital-signal-for related Tools processing-for-stm32-microcontrollers-using-cmsis-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4968-proprietary-for related Tools code-read-out-protection-pcrop-on-stm32f72xxx-and-stm32f73xxx-

& Software microcontrollers-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application note/an5056-integration-

for related Tools guide-for-the-xcubesbsfu-stm32cube-expansion-package-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5282-using-

for related Tools xcuberccalib-software-to-calibrate-stm32wb-series-internal-rc-oscillators-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5360-getting-started-

for related Tools with-projects-based-on-the-stm32mp1-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5361-getting-started-

for related Tools with-projects-based-on-dualcore-stm32h7-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5394-getting-started-

for related Tools with-projects-based-on-the-stm32l5-series-in-stm32cubeide-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5418-how-to-build-a-for related Tools simple-usbpd-sink-application-with-stm32cubemx-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5426-migrating-

for related Tools graphics-middleware-projects-from-stm32cubemx-540-to-stm32cubemx-

& Software 550-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5564-getting-started-

for related Tools with-projects-based-on-dualcore-stm32wl-microcontrollers-in-

& Software stm32cubeide-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4865-lowpower-timer-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application note/an5676-how-to-

for related Tools calibrate-internal-rc-oscillators-on-stm32u5-series-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5698-adapting-the-for related Tools xcubestl-functional-safety-package-for-stm32-iec-61508-compliant-to-

& Software other-safety-standards-stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5731-stm32cubemx-

for related Tools and-stm32cubeide-threadsafe-solution-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5857-using-

for related Tools xcuberccalib-software-to-calibrate-stm32c0-series-internal-rc-oscillator-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an4502-stm32-

for related Tools smbuspmbus-expansion-package-for-stm32cube-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5126-how-to-for related Tools calibrate-internal-oscillators-on-stm32g0-mcus-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4777-how-to-for related Tools optimize-power-consumption-on-stm32-mcus-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an5952-how-to-use-

for related Tools cmake-in-stm32cubeide-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4894-how-to-use-

for related Tools eeprom-emulation-on-stm32-mcus-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an4635-how-to-

for related Tools optimize-lpuart-power-consumption-on-stm32-mcus-

& Software stmicroelectronics.pdf

Application Notes https://www.st.com/resource/en/application_note/an5054-how-to-perform-for related Tools secure-programming-using-stm32cubeprogrammer-stmicroelectronics.pdf

& Software

Application Notes https://www.st.com/resource/en/application_note/an6179-how-to-for related Tools integrate-the-stl-firmware-into-a-time-critical-user-application-

& Software stmicroelectronics.pdf

Design Notes & https://www.st.com/resource/en/design_tip/dt0088-fir-filter-design-by-

Tips sampling-windowing-and-modulating-the-sinc-function-

stmicroelectronics.pdf

Design Notes & https://www.st.com/resource/en/design_tip/dt0089-the-goertzel-algorithm-

Tips to-compute-individual-terms-of-the-discrete-fourier-transform-dft-

stmicroelectronics.pdf

Design Notes & https://www.st.com/resource/en/design_tip/dt0091-lattice-wave-digital-

Tips filter-design-and-automatic-c-code-generation-stmicroelectronics.pdf

Design Notes & https://www.st.com/resource/en/design_tip/dt0092-lattice-wave-digital-

Tips filter-test-and-performance-verification-stmicroelectronics.pdf

Design Notes & https://www.st.com/resource/en/design_tip/dt0117-microphone-array-

Tips beamforming-in-the-pcm-and-pdm-domain-stmicroelectronics.pdf

Errata Sheets https://www.st.com/resource/en/errata_sheet/es0250-

stm32l471xx475xx476xx486xx-device-errata-stmicroelectronics.pdf

Datasheet https://www.st.com/resource/en/datasheet/dm00108832.pdf

Programming https://www.st.com/resource/en/programming_manual/pm0214-stm32-

Manuals cortexm4-mcus-and-mpus-programming-manual-stmicroelectronics.pdf

Reference https://www.st.com/resource/en/reference_manual/rm0351-stm32l47xxx-

Manuals stm32l48xxx-stm32l49xxx-and-stm32l4axxx-advanced-armbased-32bit-

mcus-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1163-description-of-

& Articles wlcsp-for-microcontrollers-and-recommendations-for-its-use-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1204-tape-and-reel-

& Articles shipping-media-for-stm32-microcontrollers-in-bga-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1205-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-fpn-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1206-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-qfp-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1207-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-so-packages-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1208-tape-and-reel-

& Articles shipping-media-for-stm8-and-stm32-microcontrollers-in-tssop-and-ssop-

packages-stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1433-reference-device-

& Articles marking-schematics-for-stm32-microcontrollers-and-microprocessors-

stmicroelectronics.pdf

Technical Notes https://www.st.com/resource/en/technical_note/tn1489-security-bulletin-

& Articles tn1489stpsirt-physical-attacks-on-stm32-and-stm32cube-firmware-

stmicroelectronics.pdf

User Manuals https://www.st.com/resource/en/user_manual/um2305-stm32l4-and-

stm32l4-series-safety-manual-stmicroelectronics.pdf

User Manuals https://www.st.com/resource/en/user_manual/um3166-stm32l4-and-

stm32l4-series-ulcsaiec-607301603351-selftest-library-user-guide-

stmicroelectronics.pdf