

# ENTERPRISE APPLICATION DEVELOPMENT – LAB 1

C15478448





### **ENTERPRISE APPLICATION DEVELOPMENT**

COURSE: DT228/4 Lab 1

# Table of Contents

PART 1 – HTTP API ENDPOINTS	2
PART 2 – PRODUCTS EXTENSION + SQL INJECTION	6
PART 3 – ELIMINATE SECURITY HOLES	8
PART 4 – SEQUELIZE ORM	10
PART 5 – TEST DATA (SEEDERS)	11
PART 6 – RESTFUL API	15

# Folder Structure

Massive-Express – Contains Parts 1-3

Sequelize-ORM – Contains Parts 4-6

Document - This Document in .docx and .pdf

Screenshots – Screenshots for all Outputs

### Note:


- To run this project you must enter in the following command in the
   Massive-Express and Sequelize-ORM folder: npm install
- Sequelize-ORM contains a **README.txt** which contains all of the commands on how to set up the models, migrations and seeders

# **Problem Sets**

# Part 1 - HTTP API Endpoints

### **GET /users**

Details: List all users email and sex in order of most recently created. Do not include password hash in your output.




### GET /users/:id

Show above details of the specified user.



### **GET /products**

List all products in ascending order of price.




# **GET /products/:id**

Show details of the specified products.



### **GET /purchases**

List purchase items to include the receiver's name and, address, the purchaser's email address and the price, quantity and delivery status of the purchased item. Order by price in descending order.



All endpoints serve the expected data as checked with the database against it, explanation is in the code.

# Part 2 – Products Extension + SQL Injection

# **GET products[?name=string]**




# **SQL** Injection


Database before the query.

id	title	price	created_at	deleted_at	tags	updated_at
1	Dictionary	9.99		†	+   {Book}	+ I
2 i	Python Book	29.99	2011-01-01 20:00:00+00	i	{Book, Programming, Python}	i
	Ruby Book	27.99	2011-01-01 20:00:00+00	i	{Book, Programming, Ruby}	i
4	Baby Book	7.99	2011-01-01 20:00:00+00	i	{Book,Children,Baby}	i
5 1	Coloring Book	5.99	2011-01-01 20:00:00+00	i	{Book,Children}	i
6 i	Desktop Computer	499.99	2011-01-01 20:00:00+00	i	{Technology}	i
7 i	Laptop Computer	899.99	2011-01-01 20:00:00+00	i	{Technology}	i
8	MP3 Player	108.00	2011-01-01 20:00:00+00	i	{Technology,Music}	i
9 j	42" LCD TV	499.00	2011-01-01 20:00:00+00	i i	{Technology,TV}	i
10 j	42" Plasma TV	529.00	2011-01-01 20:00:00+00	i i	{Technology,TV}	i
11 j	Classical CD	9.99	2011-01-01 20:00:00+00	i i	{Music}	i
12 j	Holiday CD	9.99	2011-01-01 20:00:00+00	i i	{Music}	i
13 j	Country CD	9.99	2011-01-01 20:00:00+00	i i	{Music}	i
14 i	Pop CD	9.99	2011-01-01 20:00:00+00	i i	{Music}	i
15 j	Electronic CD	9.99	2011-01-01 20:00:00+00	i i	{Music}	i
16 j	Comedy Movie	14.99	2011-01-01 20:00:00+00	i i	{Movie,Comedy}	i
17 j	Documentary	14.99	2011-01-01 20:00:00+00	i i	{Movie}	i
18 j	Romantic	14.99	2011-01-01 20:00:00+00	i i	{Movie}	i
19 j	Drama	14.99	2011-01-01 20:00:00+00	i i	{Movie}	i
20 j	Action	14.99	2011-01-01 20:00:00+00	i i	{Movie}	i
21 j	Playstation4	399.99	2019-02-16 12:39:45.034+00	i	{Console,Games}	i
22 j	Playstation5	399.99	2019-02-16 12:51:46.396+00	i	{Console,Games}	i
23 j	Playstation6	399.99	2019-02-16 16:02:50.917+00		{Console,Games}	<u> </u>

### Entering in the query.




### Database after the query.



# Part 3 – Two Solutions to Eliminate Security Holes

# **Parameterised Query**




After entering in the query, it does not delete from the database as it is prone to SQL Injection.


22 (22 )	Playstation5 rows)	399.99	2019-02-16 12:51:46.396+00	i	{Console,Games}	i				
33	[pgguide=# select * from products;									
id	title	price	created_at	deleted_at	tags	updated_at				
1	Dictionary	9.99	2011-01-01 20:00:00+00		   {Book}					
2	Python Book	29.99	2011-01-01 20:00:00+00	i	{Book, Programming, Python}	i				
3	Ruby Book	27.99	2011-01-01 20:00:00+00	i	{Book, Programming, Ruby}	i				
4	Baby Book	7.99	2011-01-01 20:00:00+00	i	{Book,Children,Baby}	i				
5	Coloring Book	5.99	2011-01-01 20:00:00+00	i	{Book,Children}	i				
6	Desktop Computer	499.99	2011-01-01 20:00:00+00	i	{Technology}	j				
7	Laptop Computer	899.99	2011-01-01 20:00:00+00	i	{Technology}	İ				
8	MP3 Player	108.00	2011-01-01 20:00:00+00		{Technology,Music}	İ				
9	42" LCD TV	499.00	2011-01-01 20:00:00+00		{Technology,TV}	İ				
10	42" Plasma TV	529.00	2011-01-01 20:00:00+00		{Technology,TV}	İ				
11	Classical CD	9.99	2011-01-01 20:00:00+00	į i	{Music}	İ				
12	Holiday CD	9.99	2011-01-01 20:00:00+00		{Music}	İ				
13	Country CD	9.99	2011-01-01 20:00:00+00		{Music}	İ				
14	Pop CD	9.99	2011-01-01 20:00:00+00		{Music}	İ				
15	Electronic CD	9.99	2011-01-01 20:00:00+00	İ	{Music}	ì				
16	Comedy Movie	14.99	2011-01-01 20:00:00+00		{Movie,Comedy}	İ				
17	Documentary	14.99	2011-01-01 20:00:00+00		{Movie}	İ				
18	Romantic	14.99	2011-01-01 20:00:00+00	į i	{Movie}	İ				
19	Drama	14.99	2011-01-01 20:00:00+00		{Movie}	İ				
20	Action	14.99	2011-01-01 20:00:00+00		{Movie}	İ				
21	Playstation4	399.99	2019-02-16 12:39:45.034+00		{Console,Games}	ı				
22	Playstation5	399.99	2019-02-16 12:51:46.396+00		{Console,Games}	1				
(22 rows)										
pggui	pgguide=# []									

The database is unaffected after entering in the SQL Injection query.

### **Stored Procedure**



After entering in the query, it does not delete from the database as it is prone to SQL Injection.



The database is unaffected after entering in the SQL Injection query.

### Note:

- /products/?name=... Ability to perform SQL Injection
- /productssol1/?name=... Parameterised Query (SQL Injection Prevention)
- /productssol2/?name=... Stored Procedure (SQL Injection Prevention)

All is explained in the code on how this is done.

# Part 4 - Sequelize ORM


# Setup

- 1. npm install --save sequelize-cli
- 2. node\_modules/.bin/sequelize init

The following folders are created:

- config
- models
- migrations
- seeders

### **Folder Structure**



Inside the folder **Sequelize-ORM** the <u>README.txt</u> contains the setup commands in creating models and migrations.

### Note

- It's important to add the "**updated\_at**" column to ensure that the appropriate associations are all set up and working with the models.

# Part 5 – Test Data (Seeders)


### **Product – Sample Data**

```
return queryInterface.bulkInsert('products', {

id: 25,
    title: 'Playstation8',
    price: 399.99,
    created_at: new Date(),
    tags: '{"Console", "Games"}',
    updated_at: new Date()
}, {};

down: (queryInterface, Sequelize) => {

return queryInterface, ulkDelete('products', { where: { title: 'Playstation8' } }, {});
};
```



# **User – Sample Data**

### Purchase - Sample Data

```
return queryInterface, Sequelize) => {

return queryInterface, Sequelize) => {

return queryInterface.bulkInsert('purchases', [{
 created_at: new Date(),
 name: 'Gabriel',
 address: 'Some Address',
 state: 'WA',
 zipcode: 99215,
 user_id: 2000

}], {});

down: (queryInterface, Sequelize) => {

return queryInterface.bulkDelete('purchases', { where: { name: 'Gabriel' } }, {});
};

return queryInterface.bulkDelete('purchases', { where: { name: 'Gabriel' } }, {});
};
```

```
| pgguide=# select * from purchases WHERE name='Gabriel';
| id | created_at | name | address | state | zipcode | user_id |
| 1001 | 2019-02-17 15:55:33.474+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1002 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1003 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1004 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1005 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1006 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1007 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1008 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1009 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1009 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1009 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1009 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1009 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1009 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1009 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1009 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1009 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1009 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1009 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1009 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 |
| 1009 | 2019-02-17 20:04:30.201+00 | Gabriel | Some Address | WA | 90215 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000
```

### Purchase Item – Sample Data

```
README.txt 20190216121605-demo-purchase-item.js

'use strict';

module.exports = {

up: (queryInterface, Sequelize) => {

return queryInterface.bulkInsert('purchase_items', [{

id: 3000,
purchase_id: 1,
product_id: 3,
price: 300.00,
quantity: 9192,
state: 'Delivered'

}], {});

down: (queryInterface, Sequelize) => {


return queryInterface, Sequelize) => {

return queryInterface.bulkDelete('purchase_items', { where: { quantity: 9191 } }, {});
}

return queryInterface.bulkDelete('purchase_items', { where: { quantity: 9191 } }, {});
}
```

### Part 6 - RESTful API

### **GET /products[?name=string]**



### GET /products/:id



# **POST /products**



### **New Instance Confirmation**

### PUT /products/:id



You supply the ID and the updated\_at field gets updated, that's why this column is needed.

# **DELETE /products/:id**



### **Deletion Confirmation**