

Database Schema

1. CustomUser Table

This table stores user information.

Column Name	Data Type	Constraints
id	Integer (AutoField)	Primary Key, Auto Increment
email	Varchar(254)	Unique, Not Null
name	Varchar(255)	Not Null
Phone	Varchar(15)	Not Null, Validated using regex (<code>^\+?1?\d{9,15}\$</code>)
address	Text	Not Null
created_at	DateTime	Auto Now Add
is_active	Boolean	Default: True
is_admin	Boolean	Default: False
is_staff	Boolean	Default: False

2. Topping Table

Column Name	Data Type	Constraints
id	Integer (AutoField)	Primary Key, Auto Increment
name	Varchar(100)	Not Null
price	Decimal(6, 2)	Not Null, Validated using MinValueValidator (must be ≥ 0)

3. Pizza Table

This table stores pizza information.

Column Name	Data Type	Constraints
id	Integer (AutoField)	Primary Key, Auto Increment
name	Varchar(100)	Not Null
base_price	Decimal(6, 2)	Not Null, Validated using MinValueValidator (must be ≥ 0)

5. Pizza Toppings Table (Many-to-Many Relationship)

This table represents the many-to-many relationship between Pizza and Topping.

Column Name	Data Type	Constraints
id	Integer (AutoField)	Primary Key, Auto Increment
pizza_id	Integer	Foreign Key to Pizza.id, On Delete: CASCADE
topping_id	Integer	Foreign Key to Topping.id, On Delete: CASCADE

5. Order Table

This table stores order information.

Column Name	Data Type	Constraints
id	Integer (AutoField)	Primary Key, Auto Increment
customer_id	Integer	Foreign Key to CustomUser.id, On Delete: CASCADE
total_price	Decimal(8, 2)	Not Null, Validated using MinValueValidator (must be >= 0)
created_at	DateTime	Auto Now Add
status	Varchar(10)	Choices: Pending, Completed, Cancelled

4. Order_Pizzas Table (Many-to-Many Relationship)

This table represents the many-to-many relationship between Order and Pizza.

Column Name	Data Type	Constraints
id	Integer (AutoField)	Primary Key, Auto Increment
order_id	Integer	Foreign Key to Order.id, On Delete: CASCADE
pizza_id	Integer	Foreign Key to Pizza.id, On Delete: CASCADE