

Question – 1

Database ecommerce created

```
1 • create database ecommerce;
2 • use ecommerce;
3 • create table gold_member_users (userid int, signup_date date);
4 • create table sales (userid int, created_date date, product_id int);
5 • create table users(userid int, signup_date date);
6 • create table product(product_id int, product_name varchar(50), price int);
7
8 • alter table gold_member_users add column user_name varchar(50);
9 • alter table users add column user_name varchar(50);
10 • alter table sales add column user_name varchar(50);
```

Data insert

```
insert into users values (1,'2017-09-22','John'), (2,'2015-01-15','Michel'),
(3,'2014-11-04','Mary');
```

```
insert into gold_member_users values(1,'2017-09-22','John'),(3,'2014-11-04','Mary');
```

```
insert into product values (1,'Mobile', 980),
(2,'Ipad',870),(3,'Laptop',330);
```

- insert into sales values
(1, '2017-04-19', 2, 'John'),
(3, '2019-12-18', 1, 'Mary'),
(2, '2020-07-20', 3, 'Michel'),
(1, '2019-10-23', 2, 'John'),
(1, '2018-03-19', 3, 'John'),
(3, '2016-12-20', 2, 'Mary'),
(1, '2016-11-09', 1, 'John'),
- select * from users;
- select * from gold_member_users;
- select * from sales;
- select * from product;

5. Count all the records of all four tables using single query

```

43 • select 'users', count(*) as count_of_table from users union all
44 select 'gold_member_users', count(*) from gold_memeber_user union all
45 select 'sales', count(*) from sales union all
46 select 'product', count(*) from product;

```

Result Grid		Filter Rows:	Export:	Wrap Cell Content:
	users	count_of_table		
▶	users	3		
	gold_member_users	2		
	sales	13		
	product	4		

6. What is the total amount each customer spent on an ecommerce company

```

-- What is the total amount each customer spent on ecommerce company
• select s.user_name,sum(p.price) as total_amount from sales s
  inner join product p on s.product_id = p.product_id group by s.user_name;

```

7. Find the distinct dates of each customer visited the website: output should have 2 columns date and customer name

```

-- Find the distinct dates of each customer visited the website:
-- output should have 2 columns date and customer name
• select distinct s.created_date as visit_date, s.user_name
  from sales s
  order by s.user_name, s.created_date;

```

8. Find the first product purchased by each customer using 3 tables (users, sales, product)

```

• with first_purchased as (
  select
    s.user_name,u.userid,u.signup_date,
    s.created_date,s.product_id,p.product_name,
    dense_rank() over (partition by s.user_name order by s.created_date) as first_pursed
  FROM sales s
  JOIN product p ON s.product_id = p.product_id
  JOIN users u ON s.user_name = u.user_name
)
  select
    user_name,created_date AS first_purchase_date,product_name
  FROM first_purchased
  WHERE first_pursed = 1;

```

9. What is the most purchased item of each customer and how many times the customer has purchased it: output should have 2 columns count of the items as item_count and customer name

-- 9. What is the most purchased item of each customer and how many times the customer has purchased it:
 -- output should have 2 columns count of the items as item_count and customer name

```

with highest_count as(
select s.user_name, s.product_id, count(*) as item_count, p.product_name,
       row_number() over(partition by user_name order by count(*) desc) as highest
  from sales s join product p on s.product_id = p.product_id
 group by s.user_name, s.product_id ,p.product_name )
select user_name, product_id,product_name, item_count from highest_count where highest = 1;

```

10. Find out the customer who is not the gold_member_user

```

-- 10 Find out the customer who is not the gold_member_user
select * from gold_member_users;
select u.user_name from users u left join gold_member_users g on u.userid = g.userid where g.user_name is null;

```

11. What is the amount spent by each customer when he was the gold_memberorder by user

```

-- 11.What is the amount spent by each customer when he was the gold_memberorder by user
select s.user_name,sum(p.price) as total_amount from sales s
inner join product p on s.product_id = p.product_id
inner join gold_member_users g on g.userid = s.userid
group by s.user_name;

```

12.Find the Customers names whose name starts with M

```

-- 12.Find the Customers names whose name starts with M
select user_name from users where user_name like 'M%';

```

13.Find the Distinct customer Id of each customer

```

-- 13 Find the Distinct customer Id of each customer
select distinct userid , user_name from users;

```

14.Change the Column name from product table as price_value from price

```

-- 14.Change the Column name from product table as price from price_value
alter table product change price price_value int;

```

15.Change the Column value product_name – **lpad to Iphone** from product table

- -- 15.Change the Column value product_name - Ipad to Iphone from product table
- SET SQL_SAFE_UPDATES = 0;
- update product set product_name = "Iphone" where product_name = "Ipad";
- select * from product;

16.Change the table name of **gold_member_users** to **gold_membership_users**

```
-- 16.Change the table name of gold_member_users to gold_membership_users
-- EXEC sp_rename 'old_table_name', 'new_table_name';
rename table gold_member_users to gold_memeber_user;
```

17.Create a new column as **Status** in the table crate above **gold_membership_users** the Status values should be 2 Yes and No if the user is gold member, then status should be Yes else No.

- -- 17.Create a new column as Status in the table gold_membership_user
- -- the Status values should be 2 Yes and No if the user is gold member, then status should be Yes
- alter table gold_memeber_user add column status varchar(5);
- alter table users add column user_status varchar(5);

```
126 • update users u
127     set user_status =
128     case
129     when exists (
130         select 1
131         from gold_memeber_user g
132         where g.userid = u.userid
133     ) then 'Yes'
134     else 'No'
135     end;
136 • select * from users;
137
```

Result Grid

Filter Rows:

Export:

Wrap Cell Content:

	userid	signup_date	user_name	user_status
▶	1	2017-09-22	John	Yes
	2	2015-01-15	Michel	No
	3	2014-11-04	Mary	Yes

18.Delete the users_ids 1,2 from users table and roll the back changes once both the rows are deleted one by one mention the result when performed roll back

```
-- 18.Delete the users_ids 1,2 from users table and roll the back changes once  
-- both the rows are deleted one by one mention the result when performed roll back
```

- `start transaction;`
- `delete from users where userid = 1;`
- `DELETE FROM users WHERE userid = 2;`
- `select * from users;`
- `ROLLBACK;`

19.Insert one more record as same (3,'Laptop',330) as product table

```
-- 19.Insert one more record as same (3,'Laptop',330) as product table  
insert into product values (3,'Laptop',330);  
select * from product;
```

20.Write a query to find the duplicates in product table

```
151 -- 20 Write a query to find the duplicates in product table  
152 • with duplicated as(  
153   select product_id, product_name, row_number() over(partition by product_id) as present_count from product)  
154   select product_id,product_name from duplicated where present_count <> 1;  
155
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content: IA

	product_id	product_name
▶	3	Laptop

Question - 2

Write a query to find for each date the number of different products sold and their names.

-- Column names: (sell_date, product)

```

5
6 • insert into sales_details values ('2020-05-30', 'Headphones'),
7   ('2020-06-01','Pencil'), ('2020-06-02','Mask'),
8   ('2020-05-30','Basketball'), ('2020-06-01','Book'),
9   ('2020-06-02', ' Mask '),('2020-05-30','T-Shirt');
10
11 • select * from sales_details;

```

Result Grid	Filter Rows:	Export:	Wrap Cell Content:
sell_date	product		
2020-05-30	Headphones		
2020-06-01	Pencil		
2020-06-02	Mask		
2020-05-30	Basketball		
2020-06-01	Book		
2020-06-02	Mask		
2020-05-30	T-Shirt		

Output

```

12
13 • select sell_date,
14   count(distinct trim(product)) as num_sold ,
15   group_concat(distinct trim(product)) as product_list
16   from sales_details group by sell_date;

```

Result Grid	Filter Rows:	Export:	Wrap Cell Content:
sell_date	num_sold	product_list	
2020-05-30	3	Basketball,Headphones,T-Shirt	
2020-06-01	2	Book,Pencil	
2020-06-02	1	Mask	

Question – 3

Find the total salary of each department


```

4 • insert into dept_tbl values
5   ('1111-MATH', 'RAHUL', 10000),
6   ('1111-MATH', 'RAKESH', 20000),
7   ('2222-SCIENCE', 'AKASH', 10000),
8   ('222-SCIENCE', 'ANDREW', 10000),
9   ('22-CHEM', 'ANKIT', 25000),
10  ('3333-CHEM', 'SONIKA', 12000),
11  ('4444-BIO', 'HITESH', 2300),
12  ('44-BIO', 'AKSHAY', 10000);
13
14 • select * from dept_tbl;

```

Result Grid			
		Filter Rows:	Export:
	id_deptname	emp_name	salary
▶	1111-MATH	RAHUL	10000
	1111-MATH	RAKESH	20000
	2222-SCIENCE	AKASH	10000
	222-SCIENCE	ANDREW	10000
	22-CHEM	ANKIT	25000
	3333-CHEM	SONIKA	12000
	4444-BIO	HITESH	2300
	44-BIO	AKSHAY	10000

```

18 • select
19     substring_index(id_deptname, '-', -1) as department,
20     sum(salary) as total_salary
21 from dept_tbl
22 group by department
23 order by department;
24

```

Result Grid		
		Filter Rows:
		Export: Wrap Cell Content:
	department	total_salary
▶	BIO	12300
	CHEM	37000
	MATH	30000
	SCIENCE	20000

Question – 4

```

7 • insert into email_signup values
8   (1, 'Rajesh@Gmail.com', '2022-02-01'),
9   (2, 'Rakesh_gmail@rediffmail.com', '2023-01-22'),
10  (3, 'Hitest@Gmail.com', '2020-09-08'),
11  (4, 'Salil@Gmmail.com', '2019-07-05'),
12  (5, 'Himanshu@Yahoo.com', '2023-05-09'),
13  (6, 'Hitesh@Twitter.com', '2015-01-01'),
14  (7, 'Rakesh@facebook.com', null);
15 • select * from email_signup;

```

Result Grid	Filter Rows:	Export:	Wrap Cell
id	email_id	signup_date	
1	Rajesh@Gmail.com	2022-02-01	
2	Rakesh_gmail@rediffmail.com	2023-01-22	
3	Hitest@Gmail.com	2020-09-08	
4	Salil@Gmmail.com	2019-07-05	
5	Himanshu@Yahoo.com	2023-05-09	
6	Hitesh@Twitter.com	2015-01-01	
7	Rakesh@facebook.com	NULL	

write the query to replace null value with '1970-01-01'

```

18 • update email_signup set signup_date = "1970-01-01" where signup_date is null;

```

Result Grid	Filter Rows:	Export:	Wrap Cell Content:
id	email_id	signup_date	
1	Rajesh@Gmail.com	2022-02-01	
2	Rakesh_gmail@rediffmail.com	2023-01-22	
3	Hitest@Gmail.com	2020-09-08	
4	Salil@Gmmail.com	2019-07-05	
5	Himanshu@Yahoo.com	2023-05-09	
6	Hitesh@Twitter.com	2015-01-01	
7	Rakesh@facebook.com	1970-01-01	

Date difference

```

20 • select
21     max(signup_date) as latest_signup,
22     min(signup_date) as first_signup,
23     datediff(max(signup_date), min(signup_date)) as date_difference
24 from email_signup
25 where lower(email_id) like '%@gmail.com';
26

```

Result Grid	Filter Rows:	Export:	Wrap Cell Content:
latest_signup	first_signup	date_difference	
2022-02-01	2020-09-08	511	

Question – 5


```

7 -- Create a table named sales_data with columns: product_id, sale_date, and
5 • create table sales_data (product_id int, sale_date date, quantity_sold int);
6 • insert into sales_data value
7 (1, '2022-01-01', 20),
8 (2, '2022-01-01', 15),
9 (1, '2022-01-02', 10),
10 (2, '2022-01-02', 25),
11 (1, '2022-01-03', 30),
12 (2, '2022-01-03', 18),
13 (1, '2022-01-04', 12),
14 (2, '2022-01-04', 22) ;

```

Result Grid	Filter Rows:	Export:	Wrap Cell Content:
product_id	sale_date	quantity_sold	
2	2022-01-01	15	
1	2022-01-02	10	
2	2022-01-02	25	
1	2022-01-03	30	
2	2022-01-03	18	
1	2022-01-04	12	
2	2022-01-04	22	

sales_data1

1) Assign rank by partition based on product_id and find the latest product_id sold

```

17 -- 1 Assign rank by partition based on product_id and find the latest product_id sold
18 • select *, rank() over(partition by product_id order by sale_date) as latest_product_sold from sales_data;
19

```



Result Grid	Filter Rows:	Export:	Wrap Cell Content:
product_id	sale_date	quantity_sold	latest_product_sold
1	2022-01-01	20	1
1	2022-01-02	10	2
1	2022-01-03	30	3
1	2022-01-04	12	4
2	2022-01-01	15	1
2	2022-01-02	25	2
2	2022-01-03	18	3
2	2022-01-04	22	4

2) Retrieve the quantity_sold value from a previous row and compare the quantity_sold.

```

20 -- Retrieve the quantity_sold value from a previous row and compare the quantity_sold.
21 • select
22     product_id,
23     sale_date,
24     quantity_sold,
25     lag(quantity_sold) over (partition by product_id order by sale_date) as previous_quantity,
26     quantity_sold - lag(quantity_sold) over (partition by product_id order by sale_date) as difference
27 from sales_data;
28
29 -- Partition based on product_id and return the first and last values in ordered set.

```



Result Grid					
Filter Rows: <input type="text"/>					
Export:  Wrap Cell Content: 					
	product_id	sale_date	quantity_sold	previous_quantity	difference
▶	1	2022-01-01	20	NULL	NULL
	1	2022-01-02	10	20	-10
	1	2022-01-03	30	10	20
	1	2022-01-04	12	30	-18
	2	2022-01-01	15	NULL	NULL
	2	2022-01-02	25	15	10
	2	2022-01-03	18	25	-7
	2	2022-01-04	22	18	4

3) Partition based on product_id and return the first and last values in ordered set.

```

29 -- Partition based on product_id and return the first and last values in ordered set.
30
31 • select
32     product_id,
33     sale_date,
34     quantity_sold,
35     first_value(quantity_sold) over (partition by product_id order by sale_date) as first_sold,
36     last_value(quantity_sold) over (
37         partition by product_id
38         order by sale_date
39         ROWS BETWEEN UNBOUNDED PRECEDING AND UNBOUNDED FOLLOWING
40     ) as last_sold
41 from sales_data;
42

```

Result Grid					
Filter Rows: <input type="text"/>					
Export:  Wrap Cell Content: 					
	product_id	sale_date	quantity_sold	first_sold	last_sold
▶	1	2022-01-01	20	20	12
	1	2022-01-02	10	20	12
	1	2022-01-03	30	20	12
	1	2022-01-04	12	20	12
	2	2022-01-01	15	15	22
	2	2022-01-02	25	15	22
	2	2022-01-03	18	15	22
	2	2022-01-04	22	15	22