NAME

cs_show_cluster_patterns - search log files for cluster patterns

SYNOPSIS

cs_show_cluster_patterns OPTION

DESCRIPTION

cs_show_cluster_patterns searches log files for cluster patterns. Please note that most cluster components do logging to their local node only.

OPTIONS

--help

show help.

--version

show version.

--writecfg

show some internal variables.

--show

show all patterns.

--fencing

show fencing patterns.

--migration

show migration patterns.

--count

count total for each pattern.

--zip

count from compressed logs, too. This could take some time.

EXAMPLES

```
* show migrations
```

cs_show_cluster_patterns -m

cs_show_cluster_patterns -c | grep -v "=.0\$"

count occurance of patterns, show non-null only

cs_show_cluster_patterns -s | grep "^Jan"

show whole lines, but only for January. Useful if logs contain December as well.

EXIT STATUS

 ${\bf 0} \ {\bf Successful} \ program \ execution.$

>0 Usage, syntax or execution errors.

FILES

/usr/sbin/cs_show_cluster_patterns

the program itself.

/etc/ClusterTools2/cs_show_cluster_patterns the configuration.

/etc/corosync/corosync.conf

the corosync configuration, maybe defining log file.

/var/log/messages

the default log file.

BUGS

This script depends on LC_MESSAGES respective RC_LANG set to en_US or C. Furthermore the scripts sort output by month. This results in wrong order of lines, if a logfile f.e. contains December and January. Feedback is welcome, please use the project page at

https://build.opensuse.org/package/show?package=ClusterTools2&project=home%3Afmherschel

SEE ALSO

COPYRIGHT

(c) 2011-2016 L.Pinne, Germany.

cs_show_cluster_patterns comes with ABSOLUTELY NO WARRANTY.

For details see the GNU General Public License at http://www.gnu.org/licenses/gpl.html