

NAME

cs_show_error_patterns – search log files for known error patterns

SYNOPSIS

cs_show_error_patterns [*OPTION*]

DESCRIPTION

cs_show_error_patterns searches log files for known error patterns. The total number of matches for each pattern is printed.

OPTIONS**--help**

show help.

--version

show version.

--writecfg

show some internal variables.

--zip

search compressed logs, too. This could take some time.

EXIT STATUS

0 Successful program execution.

>0 Usage, syntax or execution errors.

EXAMPLES

```
# cs_show_error_patterns | grep -v "= 0$"
```

search in the current log files, show only patterns that match at least one time.

FILES

/usr/sbin/cs_show_error_patterns

the program itself.

/etc/ClusterTools2/cs_show_error_patterns

the configuration.

/var/log/

the directory with log files.

BUGS

This script depends on LC_MESSAGES respective RC_LANG set to en_US or C. On SLES12, only a fraction of entries might be found. Feedback is welcome, please use the project page at <https://build.opensuse.org/package/show?package=ClusterTools2&project=home%3Afmherschel>

SEE ALSO

grep(1), **dmesg(1)**, **syslog(8)**, **logrotate(8)**, **mcelog(8)**, **journalctl(8)**, **ClusterTools2(7)**

COPYRIGHT

(c) 2011-2016 L.Pinne, Germany.

cs_show_error_patterns comes with ABSOLUTELY NO WARRANTY.

For details see the GNU General Public License at <http://www.gnu.org/licenses/gpl.html>