

NAME

cs_delcib – remove cluster information base from cluster node

SYNOPSIS

cs_delcib *OPTION*

DESCRIPTION

cs_delcib cleans up a pacemaker HA cluster node. It removes the cluster information base, the policy engine logs, the ring status and core files that a cluster node has generated during its operation. Only the basic cluster configuration in /etc will be left. To entirely remove a configuration from a cluster, cs_delcib has to be called on each node.

Calling this command will shut down the cluster service and all resources on the node. It also will remove the complete cluster resource configuration and cluster history on that node.

OPTIONS

- offline** remove CIB and PE logs.
- force** stop cluster service and resources, remove CIB and PE logs.
- help** show help.
- version** show version.

EXIT STATUS

- 0** Successful program execution.
- >0** Usage, syntax or execution errors.

FILES

- /usr/sbin/cs_delcib
the program itself.
- /etc/ClusterTools2/cs_delcib
the configuration.
- /var/lib/corosync/, /var/lib/heartbeat/cores/, /var/lib/heartbeat/crm/, /var/lib/pacemaker/cib/,
/var/lib/pengine/
the directories to be cleaned up, SP2 and SP3 differ.
- /var/adm/backup/
the directory to backup the cib.xml.

BUGS

Feedback is welcome, please use the project page at
<https://build.opensuse.org/package/show?package=ClusterTools2&project=home%3Afmherschel>

SEE ALSO

hb_report(8), **make_hb_backup(8)**

COPYRIGHT

(c) 2011-2014 L.Pinne, Germany.
 cs_delcib comes with ABSOLUTELY NO WARRANTY.
 For details see the GNU General Public License at <http://www.gnu.org/licenses/gpl.html>