

NAME

cs_list_clone_files – list files that should not be cloned

SYNOPSIS

cs_list_clone_files [*OPTION*]

DESCRIPTION

cs_list_clone_files shows files that usually should not be identical, after an VM image has been cloned.

OPTIONS

--help show help.

--version show version.

--writecfg show some internal variables.

--content show content of files.

--md5sum show md5sum of files.

EXAMPLES

- * List names of files that usually should not be identical on cloned systems.
grep "^/" /etc/ClusterTools2/cs_list_clone_files
- * Calculate checksums for config files that might not appear on a freshly cloned system.
cs_list_clone_files -m
- * Count existing config files that might not appear on a freshly cloned system.
cs_sum_base_config -m 2>/dev/null | grep -v "=.NA\$" | wc -l

EXIT STATUS

- 0** Successful program execution.
- >0** Usage, syntax or execution errors.

FILES

/usr/sbin/cs_list_clone_files
the program itself.

/etc/ClusterTools2/cs_list_clone_files
the configuration.

BUGS

Lines starting with a hash (#) are silently dropped when displaying the content of files.
Feedback is welcome, please use the project page at
<https://build.opensuse.org/package/show?package=ClusterTools2&project=home%3Afmherschel>

SEE ALSO

md5sum(1), **virt-clone(1)**, **machine-id(5)**, **systemd-machine-id-setup(1)**, **dbus-uuidgen(1)**, **clone-master-clean-up(1)**, **cs_sum_base_config(8)**, **ClusterTools2(7)**,
https://wiki.microfocus.com/index.php/SUSE_Manager/Register_Clones ,
<https://www.novell.com/support/kb/doc.php?id=7012170> ,
<https://www.novell.com/support/kb/doc.php?id=7017994> ,
https://kb.vmware.com/selfservice/microsites/search.do?language=en_US&cmd=displayKC&externalId=1541

COPYRIGHT

(c) 2016-2017 L.Pinne, Germany.
cs_list_clone_files comes with ABSOLUTELY NO WARRANTY.
For details see the GNU General Public License at <http://www.gnu.org/licenses/gpl.html>