

New Instance Deployment Checklist

When deploying a new instance of pivot-web2 on the VM, follow these steps to ensure proper configuration across all deployment scripts and services.

1. Environment Variables (.env)

- ☐ Create unique `.env` file for the new instance
 - ☐ Set `SERVICE_NAME=newrunner-NAME` (unique identifier, e.g., `newrunner-algo1`)
 - ☐ Set `SERVER_ADDRESS=:PORT` (assign unique port, e.g., `:8082`, `:8083`)
 - ☐ Set `SAXO_ENVIRONMENT` (sim or live)
 - ☐ Set `LOG_LEVEL` (debug, info, warn, error)
 - ☐ Set `SIGNUP_SECRET` (keep consistent or unique per instance)
 - ☐ Set all Saxo credentials (`SIM_CLIENT_ID`, `SIM_CLIENT_SECRET`, etc.)
 - ☐ **Store separately** in instance-specific directory

2. DNS & Subdomain

- ☐ Create unique subdomain at registrar (e.g., `instance-name.pipsnticks.se`)
 - ☐ Add A record pointing to VM IP: `34.79.13.81`
 - ☐ Wait for DNS propagation (test with `dig instance-name.pipsnticks.se`)

3. Systemd Service Configuration

File to modify: `scripts/setup-newrunner-service.sh`

- ☐ Update `SERVICE_NAME` variable (must match `.env` `SERVICE_NAME`)

```
SERVICE_NAME="newrunner-algo1"
```

- ☐ Update `DEPLOY_DIR` variable (unique directory per instance)

```
DEPLOY_DIR="/opt/newrunner-algo1"
```

- ☐ Update `BINARY_NAME` variable (optional, can be same across instances or unique)

```
BINARY_NAME="newrunner-algo1"
```

- ☐ Update `PORT` variable (must match `.env` `SERVER_ADDRESS` port)

```
PORT=8082
```

- ☐ Update subdomain reference in echo output (cosmetic, for clarity)

```
echo "    - Subdomain: instance-name.pipsnticks.se"
```

- ☐ Update systemd SyslogIdentifier (for log filtering)

```
SyslogIdentifier=$SERVICE_NAME
```

- ☐ Run script: `./scripts/setup-newrunner-service.sh`
 - Creates `/etc/systemd/system/SERVICE_NAME.service` file
 - Creates deployment directory with proper ownership
 - Enables service (but doesn't start it yet)

4. Nginx Configuration

File to modify: `scripts/setup-newrunner-nginx.sh`

- ☐ Update `SERVICE_NAME` variable (if using for reference)

```
SERVICE_NAME="newrunner-algo1"
```

- ☐ Update `SUBDOMAIN` variable (must match DNS subdomain from step 2)

```
SUBDOMAIN="instance-name.pipsnticks.se"
```

- ☐ Update `PORT` variable (must match `.env` `SERVER_ADDRESS` port)

```
PORT=8082
```

- ☐ Update nginx config filenames (references to "newrunner")

```
# In gcloud command:
sudo tee /etc/nginx/sites-available/newrunner-algo1 << 'EOF'
# ...
proxy_pass http://127.0.0.1:8082; # Match PORT above
# ...
server_name instance-name.pipsnticks.se; # Match SUBDOMAIN
```

- ☐ Update log file paths (for clarity, use instance name)

```
access_log /var/log/nginx/newrunner-algo1.access.log;
error_log /var/log/nginx/newrunner-algo1.error.log;
```

- ☐ Run script: `./scripts/setup-newrunner-nginx.sh`
 - Creates nginx config at `/etc/nginx/sites-available/newrunner-algo1`
 - Enables symlink at `/etc/nginx/sites-enabled/newrunner-algo1`
 - Tests and reloads nginx
- ☐ **Manual step:** Obtain SSL certificate

```
gcloud compute ssh pivot-trading-vm --zone=europe-west1-b \
  --command='sudo certbot --nginx -d instance-name.pipsnticks.se'
```

- Certbot will auto-update nginx config with SSL
- Test HTTPS: `curl -I https://instance-name.pipsnticks.se`

5. Application Deployment

File to reference: `scripts/deploy-service.sh`

This script is configured for deploying to the default instance. For new instances:

- ☐ Create instance-specific deployment script OR
- ☐ Run `deploy-service.sh` with manual adjustments:

```
# Before running, edit the script to set:
DEPLOY_DIR="/opt/newrunner-algo1"
SERVICE_NAME="newrunner-algo1"
BINARY_NAME="newrunner-algo1"
```

- ☐ Or create new script: `deploy-service-algo1.sh`
 - Copy `deploy-service.sh`
 - Update all hardcoded values above
 - Keep deployment logic identical
- ☐ Run deployment: `./scripts/deploy-service.sh` (or custom variant)
 - Deploys application code
 - Builds binary on VM
 - Preserves `.env` and `data/` directory

6. Verify Deployment

- ☐ Check service status:

```
gcloud compute ssh pivot-trading-vm --zone=europe-west1-b \  
  --command='sudo systemctl status newrunner-algo1'
```

- ☐ View service logs:

```
gcloud compute ssh pivot-trading-vm --zone=europe-west1-b \  
  --command='sudo journalctl -u newrunner-algo1 -f'
```

- ☐ Test HTTP endpoint (before SSL):

```
curl -I http://instance-name.pipsnticks.se
```

- ☐ Test HTTPS endpoint (after certbot):

```
curl -I https://instance-name.pipsnticks.se
```

- ☐ Check logs endpoint (with proper SERVICE_NAME):

```
curl -I https://instance-name.pipsnticks.se/diagnos/logs?  
code=SIGNUP_SECRET  
# Logs should show SERVICE_NAME in filtering
```

7. Configuration Updates for Multi-Instance Scripts

These scripts may need awareness of multiple instances:

- ☐ `scripts/deploy-env-only.sh`
 - Currently hardcoded for `SERVICE_NAME="newrunner"`
 - For multiple instances, either:
 - Create instance-specific variant: `deploy-env-only-algo1.sh`
 - Or add command-line argument support: `./deploy-env-only.sh newrunner-algo1`
- ☐ `scripts/check-services-health.sh`
 - Currently checks both `runner` (legacy) and `newrunner` (default instance)
 - Update to include all new instances
 - Add loop to check all services: `newrunner`, `newrunner-algo1`, `newrunner-algo2`, etc.

- ☐ `scripts/deploy-trading-config.sh` (if exists)
 - Verify which instances need updated trading config
 - May need instance selection parameter

8. Log Isolation Verification

- ☐ Verify logs are properly isolated by `SERVICE_NAME`:

```
# Should only show logs from specific instance
sudo journalctl -u newrunner-algo1 -n 100
sudo journalctl -u newrunner-algo2 -n 100
```

- ☐ Test `/diagnos/logs` endpoint for each instance:
 - Should only display that instance's logs
 - `SERVICE_NAME` from `.env` controls filtering

Summary of Files to Modify Per Instance

File	Variables to Update	Purpose
<code>.env</code>	<code>SERVICE_NAME</code> , <code>SERVER_ADDRESS</code> , credentials	Instance configuration
<code>setup-newrunner-service.sh</code>	<code>SERVICE_NAME</code> , <code>DEPLOY_DIR</code> , <code>BINARY_NAME</code> , <code>PORT</code>	Systemd service creation
<code>setup-newrunner-nginx.sh</code>	<code>SUBDOMAIN</code> , <code>PORT</code> , config file names, log paths	Nginx proxy configuration
<code>deploy-service.sh</code>	<code>DEPLOY_DIR</code> , <code>SERVICE_NAME</code> , <code>BINARY_NAME</code>	Application deployment
<code>deploy-env-only.sh</code>	<code>SERVICE_NAME</code> , <code>REMOTE_DIR</code> , <code>SERVER_ADDRESS</code> check	Environment-only deployment
<code>check-services-health.sh</code>	Add new instance to service list	Health monitoring

Troubleshooting

Issue: Logs are showing mixed output from multiple instances

- **Check:** Verify `SERVICE_NAME` in `.env` is unique
- **Fix:** Ensure each instance has unique `SERVICE_NAME` and runs own systemd service

Issue: nginx proxying to wrong port

- **Check:** `PORT` in `setup-newrunner-nginx.sh` matches `SERVER_ADDRESS` in `.env`
- **Fix:** Update both to same port number

Issue: Service fails to start

- **Check:** DEPLOY_DIR exists with proper ownership
- **Fix:** Run `setup-newrunner-service.sh` to recreate directories
- **Also check:** .env file is in DEPLOY_DIR with proper permissions (644 or 600)

Issue: SSL certificate fails

- **Check:** DNS propagation completed (dig SUBDOMAIN)
- **Fix:** Wait for DNS propagation, retry certbot
- **Also check:** nginx is running and accessible on port 80

Issue: `/diagnos/logs` returns wrong logs

- **Check:** SERVICE_NAME environment variable in running process
- **Command:** `ps aux | grep BINARY_NAME` to see environment
- **Fix:** Verify EnvironmentFile in systemd service points to correct `.env`