


# MACHINE LEARNING FOR DEVELOPERS – A SHORT INTRODUCTION

Gregor Roth / 1&1 Mail & Media Development & Technology GmbH



## Software Engineer vs. Data Engineer vs. Data Scientist

- **Software Engineer**  
"builds applications and systems"
- **Data Engineer**  
„builds systems that consolidate, store, and retrieve data from the various applications and systems [...]"
- **Data Scientist**  
“builds analysis on top of data.  
This may come in the form of [...] a machine learning algorithm that is then implemented into the code base by software engineers and data engineers”



definitions taken from <http://101.datascience.community/2016/11/28/data-scientists-data-engineers-software-engineers-the-difference-according-to-linkedin/>

# AlphaGo




“The original **AlphaGo** first *learned from studying 30 million moves of expert human play*”

„By contrast, **AlphaGo Zero** *never saw humans play*.  
Instead, it began by knowing only the rules of the game. “

source: <https://theconversation.com/googles-new-go-playing-ai-learns-fast-and-even-thrashed-its-former-self-85979>


## Supervised machine learning



*expected price*


**411,000** €

## Supervised machine learning




## Supervised machine learning

- **Regression:** predict continuous *numeric* valued output




## Supervised machine learning

- **Regression:** predict continuous *numeric* valued output



## Supervised machine learning


- **Regression:** predict continuous *numeric* valued output






## Supervised machine learning

- **Regression:** predict continuous *numeric* valued output



- **Classification:** predict a discrete number of *category* values




## Features – the input data

- Input of a prediction is a **feature vector**
- A “**feature** is an individual measurable property or characteristic of a phenomenon being observe” (taken from wikipedia)
- Challenge is to identify and extract the *relevant* features.



key features

num	size (m <sup>2</sup> )	rooms	age	...
1	90	2	23	
2	<b>101</b>	<b>3</b>	<b>3</b>	
..	...			
19754	1330	11	12	





key features

num	size (KiB)	#attachm.	dkim?	..?TEXT?..
1	<b>21</b>	<b>0</b>	<b>1</b>	<b>?</b>
2	421	3	0	<b>?</b>
..	...			

## Vectorizing text


- In most cases text will be pre-processed.  
E.g. tokenizing, stop-words, lower-casing, normalizing URLs/ email addresses, stemming, ...
- Usually, a vocabulary list of the most “important” words is used to build the feature vector.
- The vocabulary list may be generated based on the training data. E.g. by using the TF-IDF approach




key features

num	size (KiB)	#attachm.	dkim?	„able“?	„about“?	...
1	21	0	1	1	0	...
2	421	3	0	0	0	...
..	...					

## Prediction



## Prediction function



## Prediction function

- Essentially, a **prediction function** is a function which takes the feature vector ( $x$ ) and returns the prediction value ( $y$ ).
- Also called *target* or *hypothesis* function.

$$y = h_{\theta}(x)$$

- Usage example:

```
// target function h (which is output of the learn process)
Function<Double[], Double> h = ...;

// set the feature vector with house size=101 and number-of-rooms=3
Double[] x = new Double[] { 101.0, 3.0 };

// and predict the house price (label)
double y = h.apply(x);
```

## Prediction function

- Essentially, a **prediction function** is a function which takes the feature vector ( $x$ ) and returns the prediction value ( $y$ ).
- Also called *target* or *hypothesis* function.

$$y = h_{\theta}(x)$$

- Usage example:

```
// target function h (which is output of the learn process)
Function<Double[], Double> h = ...;

// set the feature vector with house size=101 and number-of-rooms=3
Double[] x = new Double[] { 101.0, 3.0 };

// and predict the house price (label)
double y = h.apply(x);
```

## Which machine learning algorithm to use?

- Which algorithm?

$$h_{\theta}(x) = ..algorithm ..$$



## Which machine learning algorithm to use?

- Which algorithm?

$$h_{\theta}(x) = ..algorithm ..$$

- Some supervising algorithms

Algorithm	Problem Type	Easy to explain ?	Average predictive accuracy	Training speed	Prediction speed	parameter tuning needed?	Works with small num. of observations	Handles lots of irrelevant features well
<b>KNN</b>	Either	Yes	Lower	Fast	Depends on n	Minimal	No	No
<b>Linear regression</b>	Regression	Yes	Lower	Fast	Fast	None	Yes	No
<b>Logistic regression</b>	Classification	Somewhat	Lower	Fast	Fast	None	Yes	No
<b>Naive Bayes</b>	Classification	Somewhat	Lower	Fast	Fast	Some	Yes	Yes
<b>Decision trees</b>	Either	Somewhat	Lower	Fast	Fast	Some	No	No
<b>AdaBoost</b>	Either	No	Higher	Slow	Fast	Some	No	Yes
<b>Neural networks</b>	Either	No	Higher	Slow	Fast	Lots	No	Yes
...	...	...						

taken from <http://www.dataschool.io/comparing-supervised-learning-algorithms/>

## Which machine learning algorithm to use?

- Which algorithm?

$$h_{\theta}(x) = ..algorithm ..$$

- Some supervising algorithms

Algorithm	Problem Type	Easy to explain ?	Average predictive accuracy	Training speed	Prediction speed	parameter tuning needed?	Works with small num. of observations	Handles lots of irrelevant features well
KNN	Either	Yes	Lower	Fast	Depends on n	Minimal	No	No
Linear regression	Regression	Yes	Lower	Fast	Fast	None	Yes	No
Logistic regression	Classification	Somewhat	Lower	Fast	Fast	None	Yes	No
Naive Bayes	Classification	Somewhat	Lower	Fast	Fast	Some	Yes	Yes
Decision trees	Either	Somewhat	Lower	Fast	Fast	Some	No	No
AdaBoost	Either	No	Higher	Slow	Fast	Some	No	Yes
Neural networks	Either	No	Higher	Slow	Fast	Lots	No	Yes
...	...	...						

taken from <http://www.dataschool.io/comparing-supervised-learning-algorithms/>

## Linear Regression

- **Linear regression** models the relationship between the input feature vector ( $x$ ) and a the response label ( $y$ ).

$$h_{\theta}(x) = \theta_0 * 1 + \theta_1 * x_1 + .. + \theta_n * x_n = \theta^T * x$$

- Thetas  $\theta$  are used within a learning process to adapt the regression function based on the training data.

## Linear Regression

- **Linear regression** models the relationship between the input feature vector ( $x$ ) and a the response label ( $y$ ).

$$h_{\theta}(x) = \theta_0 * 1 + \theta_1 * x_1 + .. + \theta_n * x_n = \theta^T * x$$

- Thetas  $\theta$  are used within a learning process to adapt the regression function based on the training data.
- Simple example

```
class LinearRegressionFunction implements Function<Double[], Double> {  
    private final Double[] thetaVector;  
  
    public LinearRegressionFunction(Double[] thetaVector) {  
        this.thetaVector = Arrays.copyOf(thetaVector, thetaVector.length);  
    }  
  
    public Double apply(Double[] featureVector) {  
        return IntStream.range(0, thetaVector.length)  
            .mapToDouble(i -> thetaVector[i] * featureVector[i])  
            .sum();  
    }  
}
```

## Linear Regression

- **Linear regression** models the relationship between the input feature vector ( $x$ ) and a the response label ( $y$ ).

$$h_{\theta}(x) = \theta_0 * 1 + \theta_1 * x_1 + .. + \theta_n * x_n = \theta^T * x$$

- Thetas  $\theta$  are used within a learning process to adapt the regression function based on the training data.
- Simple example

```
class LinearRegressionFunction implements Function<Double[], Double> {
    private final Double[] thetaVector;

    public LinearRegressionFunction(Double[] thetaVector) {
        this.thetaVector = Arrays.copyOf(thetaVector, thetaVector.length);
    }

    public Double apply(Double[] featureVector) {
        return IntStream.range(0, thetaVector.length)
            .mapToDouble(i -> thetaVector[i] * featureVector[i])
            .sum();
    }
}
```

## Process the prediction function


- Creating a **new instance** of the regression function with the theta vector. The theta vector is result of a previous train process

```
Double[] thetas = new Double[] { 1.004579, 5.286822 };  
LinearRegressionFunction func = new LinearRegressionFunction(thetas);
```

$$h_{\theta}(x) = 1.004579 * 1 + 5.286822 * x_1$$


- .. **and predict** the house price based on house size of 155 m<sup>2</sup>. The first element of the feature vector ( $x_0$ ) has to be 1 for computational reasons

```
Double[] features = new Double[] { 1.0, 155.0 };  
double predictedPrice = func.apply(features);
```



## Prediction graph incl. real price-size pairs

$$h_{\theta}(x) = 1.004579 * 1 + 5.286822 * x_1 \quad (\text{with } x_1 = \text{size})$$



How do you know that the used theta values  $\{ 1.004579, 5.286822 \}$  are the best fit?



## Evaluate the prediction function

- Evaluate the prediction functions to identify the theta vector  $\theta$  which produces the best fitting prediction.
- E.g.:

$$h_{\theta}(x) = 1.001391 * 1 + 2.058826 * \text{size}$$

$$h_{\theta}(x) = 1.003745 * 1 + 3.912451 * \text{size}$$

$$h_{\theta}(x) = 1.004579 * 1 + 5.286822 * \text{size}$$









## Evaluate the prediction function

- Evaluate the prediction functions to identify the theta vector  $\theta$  which produces the best fitting prediction.
- E.g.:

$$h_{\theta}(x) = 1.001391 * 1 + 2.058826 * \text{size}$$

$$h_{\theta}(x) = 1.003745 * 1 + 3.912451 * \text{size}$$

$$h_{\theta}(x) = 1.004579 * 1 + 5.286822 * \text{size}$$



## Evaluate the prediction function



- Evaluate the prediction functions to identify the theta vector  $\theta$  which produces the best fitting prediction.
- E.g.:

$$h_{\theta}(x) = 1.001391 * 1 + 2.058826 * \text{size}$$

$$h_{\theta}(x) = 1.003745 * 1 + 3.912451 * \text{size}$$

$$h_{\theta}(x) = 1.004579 * 1 + 5.286822 * \text{size}$$

$J(\theta)$




- Requires **test data** including labels (which represents the right “answer”)

$\begin{pmatrix} 120 \\ 3 \\ \dots \end{pmatrix}$	411,000	€
$\begin{pmatrix} 155 \\ 6 \\ \dots \end{pmatrix}$	542,000	€
$\dots$		

## Linear Regression - Cost function


- To identify the best-fitting theta parameter vector, you need a **cost function**, which will evaluate how well the prediction function performs.



$$J(\theta) = \frac{1}{2 * m} * \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)})^2$$

## Linear Regression - Cost function

- To identify the best-fitting theta parameter vector, you need a **cost function**, which will evaluate how well the prediction function performs.




$$J(\theta) = \frac{1}{2 * m} * \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)})^2$$

- Simple example:

```
double cost(Function<Double[], Double> func, List<Double[]> dataset, List<Double> labels) {
    int m = dataset.size();
    return (1.0/(2*m)) * IntStream.range(0, m)
        .mapToDouble(i -> Math.pow(func.apply(dataset.get(i)) - labels.get(i), 2))
        .sum();
}
```

## Linear Regression - Cost function

- To identify the best-fitting theta parameter vector, you need a **cost function**, which will evaluate how well the prediction function performs.



$$J(\theta) = \frac{1}{2 * m} * \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)})^2$$

Diagram illustrating the components of the cost function formula:

- $\frac{1}{2 * m}$ : for each test example
- $\sum_{i=1}^m$ : for each test example
- $h_{\theta}(x^{(i)})$ : predicted result
- $y^{(i)}$ : real result


- Simple example:

```
double cost(Function<Double[], Double> func, List<Double[]> dataset, List<Double> labels) {
    int m = dataset.size();
    return (1.0/(2*m)) * IntStream.range(0, m)
        .mapToDouble(i -> Math.pow(func.apply(dataset.get(i)) - labels.get(i), 2))
        .sum();
}
```

Diagram illustrating the components of the code example:


- `1.0/(2*m)`: for each test example
- `IntStream.range(0, m)`: for each test example
- `func.apply(dataset.get(i))`: predicted result
- `labels.get(i)`: real result

## Evaluate the prediction function - examples




$$h_{\theta}(x) = 1.001391 * 1 + 2.058826 * \text{size}$$

$J(\theta)$



1,551,418




$$h_{\theta}(x) = 1.003745 * 1 + 3.912451 * \text{size}$$

$J(\theta)$




341,769




$$h_{\theta}(x) = 1.004579 * 1 + 5.286822 * \text{size}$$

$J(\theta)$




69,829

## Evaluate the prediction function - examples




$$h_{\theta}(x) = 1.001391 * 1 + 2.058826 * \text{size}$$

$J(\theta)$




1,551,418




$$h_{\theta}(x) = 1.003745 * 1 + 3.912451 * \text{size}$$

$J(\theta)$




341,769



$$h_{\theta}(x) = 1.004579 * 1 + 5.286822 * \text{size}$$


$J(\theta)$



69,829


- How to get the best fitting Theta vector: minimize  $J(\theta)$

## How to get the best fitting prediction function (theta parameters)?






## How to get the best fitting prediction function (theta parameters)?



## How to get the best fitting prediction function (theta parameters)?



## Minimizing the cost function – Gradient descent

- **Gradient descent** minimizes the cost function, meaning that it's used to find the theta combinations that produces the *lowest cost*  $J(\theta)$  based on the training data.

*repeat* {

$$\theta_0 := \theta_0 - \alpha * \frac{1}{m} * \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)}) * x_0^{(i)}$$

$$\theta_1 := \theta_1 - \alpha * \frac{1}{m} * \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)}) * x_1^{(i)}$$

...

$$\theta_n := \theta_n - \alpha * \frac{1}{m} * \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)}) * x_n^{(i)}$$

}

- Within each iteration a new value will be computed for each theta parameter:  $\theta_0$ ,  $\theta_1$ , ... and  $\theta_n$  in parallel.
- Requires high calculating power, potentially

## Minimizing the cost function – Gradient descent

- **Gradient descent** minimizes the cost function, meaning that it's used to find the theta combinations that produces the *lowest cost*  $J(\theta)$  based on the training data.

repeat {

$$\theta_0 := \theta_0 - \alpha * \frac{1}{m} * \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)}) * x_0^{(i)}$$

$$\theta_1 := \theta_1 - \alpha * \frac{1}{m} * \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)}) * x_1^{(i)}$$

...

$$\theta_n := \theta_n - \alpha * \frac{1}{m} * \sum_{i=1}^m (h_{\theta}(x^{(i)}) - y^{(i)}) * x_n^{(i)}$$

} new n<sup>th</sup> element of theta vector

n<sup>th</sup> element of theta vector

learning rate

predicted result

real result

n<sup>th</sup> element of feature vector (of a train data record)

- Within each iteration a new value will be computed for each theta parameter:  $\theta_0$ ,  $\theta_1$ , ... and  $\theta_n$  in parallel.
- Requires high calculating power, potentially

## Gradient decent – a simple Java-based implementation

```
static LinearRegressionFunction train(LinearRegressionFunction targetFunction,
                                     List<Double[]> dataset,
                                     List<Double> labels,
                                     double alpha) {

    int m = dataset.size();
    Double[] thetaVector = targetFunction.getThetas();
    Double[] newThetaVector = new Double[thetaVector.length];

    for (int j = 0; j < thetaVector.length; j++) { // new theta of each element
        double sumErrors = 0;
        for (int i = 0; i < m; i++) {
            Double[] featureVector = dataset.get(i);
            double error = targetFunction.apply(featureVector) - labels.get(i);
            sumErrors += error * featureVector[j];
        }

        // compute the new theta value
        double gradient = (1.0 / m) * sumErrors;
        newThetaVector[j] = thetaVector[j] - alpha * gradient;
    }


    return new LinearRegressionFunction(newThetaVector);
}
```

# Train

- Train the regression function

```
LinearRegressionFunction func = new LinearRegressionFunction(new Double[] { 1.0, 1.0 });
for (int i = 0; i < 1000; i++) {
    func = Learner.train(func, dataset, labels, 0.1);
    graph.print(i, Cost.cost(func, dataset, labels));
}
```

- Graphs



## Underfitting

- **Underfitting** occurs when the machine learning algorithm **can not capture the underlying trend of the data**.
- Underfitting is often due to an excessively simple model such as

$$h_{\theta}(x) = \theta_0 * 1 + \theta_1 * \textit{size}$$

- A common way to correct underfitting is to  
**add more features**

$$h_{\theta}(x) = \theta_0 * 1 + \theta_1 * \textit{size} + \theta_2 * \textit{rooms} + ..$$


**add polynomial features**

$$h_{\theta}(x) = \theta_0 * 1 + \theta_1 * \textit{size} + \theta_2 * \textit{size}^2 + ..$$

- Adding more features often requires additional **feature scaling** which standardize the range of independent variables

## Playing with the number of parameters

- Example:




- If you add too many features, you could end up with a prediction function that is **overfitting**.
- Overfitting occurs when the function fits the training data *too well*, by **capturing noise or random fluctuations** in the *training data*.



## Detecting Overfitting

- Holdout method: Use e.g. 60% of the labelled data to train models. Use the remaining untouched labelled data for ***cross-validation*** and final ***tests***

***Labelled Data***




## Detecting Overfitting


- Holdout method: Use e.g. 60% of the labelled data to train models. Use the remaining untouched labelled data for ***cross-validation*** and final ***tests***
- Examples

### well-fitting

cost with train examples




cost with untouched examples




### overfitting


cost with train examples



cost with untouched examples



### Labelled Data




## Detecting Overfitting


- Holdout method: Use e.g. 60% of the labelled data to train models. Use the remaining untouched labelled data for ***cross-validation*** and final ***tests***
- Examples

### well-fitting

cost with train examples




cost with untouched examples




### overfitting


cost with train examples



cost with untouched examples




### Labelled Data



- Possible options to avoid overfitting
  - Use a larger set of training data.
  - Use an improved machine learning algorithm by considering regularization.
  - Use fewer features


## Putting all together

$$h_{\theta}(x) = \theta^T * x \quad \text{algorithm}$$




## Putting all together

$$h_{\theta}(x) = \theta^T * x \quad \text{algorithm}$$




## Putting all together

$$h_{\theta}(x) = \theta^T * x \quad \text{algorithm}$$



## Putting all together

$$h_{\theta}(x) = \theta^T * x \quad \text{algorithm}$$



## Machine learning libraries and tools

- In practice, you will likely rely on machine learning frameworks, libraries, and tools.
- Some examples


Software	Creator	Written in	Interface
<b>Torch</b>	Ronan Collobert, Koray Kavukcuoglu, Clement Farabet	C, Lua	Lua, LuaJIT, C, utility library for C++/OpenCL
<b>Caffe2</b>	Facebook	C++, Python	Python, MATLAB
<b>Scikit-learn</b>	David Cournapeau	C++, Python	Python
<b>Microsoft Cognitive Toolkit</b>	Microsoft Research	C++	Python, C++, Command line, BrainScript
<b>TensorFlow</b>	Google Brain team	C++, Python	Python, Java, C/C++, Go, R
<b>Spark ML</b>	Apache Software Foundation	Scala	Python, Java, Scala
<b>Deeplearning4j</b>	Skyrim engineering team; Deeplearning4j community;	C++, Java	Python, Java, Scala, Clojure
<b>Weka</b>	University of Waikato	Java	Java
...			

Parts taken from [https://en.wikipedia.org/wiki/Comparison\\_of\\_deep\\_learning\\_software](https://en.wikipedia.org/wiki/Comparison_of_deep_learning_software)



## Literature

- Andrew Ng's [Machine Learning course](#) (~11 weeks, for free)



- Udacity's [Intro to Machine Learning](#) (~10 weeks, for free)

