


```
!kaggle datasets list
```

```
Traceback (most recent call last):  
  File "/usr/local/bin/kaggle", line 4, in <module>  
    from kaggle.cli import main  
  File "/usr/local/lib/python3.12/dist-packages/kaggle/__init__.py", line 1, in  
    api.authenticate()  
  File "/usr/local/lib/python3.12/dist-packages/kaggle/api/kaggle_api.py", line 1, in  
    raise IOError('Could not find {}. Make sure it\'s located in'  
OSError: Could not find kaggle.json. Make sure it's located in /root/.kaggle/
```

```
!pip install -q kaggle  
from google.colab import files  
  
print("Upload your kaggle.json file:")  
uploaded = files.upload()  
  
# Make the .kaggle directory  
!mkdir -p ~/.kaggle  
  
# Copy the uploaded key (correct filename!)  
!cp kaggle.json ~/.kaggle/kaggle.json  
  
# Set permissions  
!chmod 600 ~/.kaggle/kaggle.json  
  
print("Kaggle API key setup complete!")
```

Upload your kaggle.json file:

Choose Files

 kaggle.json

kaggle.json(application/json) - 68 bytes, last modified: n/a - 100% done

Saving kaggle.json to kaggle.json

Kaggle API key setup complete!

```
!kaggle datasets download -d martinsn/high-frequency-crypto-limit-order
```

```
Dataset URL: https://www.kaggle.com/datasets/martinsn/high-frequency-crypto-limit-order-book-data  
License(s): CC0-1.0  
Downloading high-frequency-crypto-limit-order-book-data.zip to /tmp  
94% 932M/993M [00:00<00:00, 979MB/s]  
100% 993M/993M [00:00<00:00, 1.18GB/s]
```

```
import os
```

```
data_path = "/tmp"  
for f in os.listdir(data_path):  
    print(f)
```

```
language_service.3ae026c98851.root.log.INFO.20251204-023040.2529  
language_service.INFO  
language_service.3ae026c98851.root.log.INFO.20251204-023040.2547  
ETH_1min.csv  
BTC_5min.csv  
dap_multiplexer.INFO  
debugger_19lteib9wc  
ADA_1sec.csv  
ETH_5min.csv  
language_service.3ae026c98851.root.log.INFO.20251204-023007.2357  
ADA_1min.csv  
ADA_5min.csv  
BTC_1sec.csv  
python-languageserver-cancellation  
dap_multiplexer.3ae026c98851.root.log.INFO.20251204-022113.129  
BTC_1min.csv  
ETH_1sec.csv  
initgoogle_syslog_dir.0  
pyright-2557-PwY49uVTQfJI
```

```

import os, random, glob
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns

from pathlib import Path

import torch
import torch.nn as nn
import torch.nn.functional as F
from torch.utils.data import Dataset, DataLoader

from sklearn.preprocessing import StandardScaler, label_binarize
from sklearn.model_selection import train_test_split
from sklearn.metrics import (
    classification_report, confusion_matrix, accuracy_score,
    precision_recall_fscore_support, roc_curve, auc
)
from sklearn.calibration import calibration_curve
from sklearn.manifold import TSNE
from sklearn.utils.class_weight import compute_class_weight

SEED = 42
random.seed(SEED); np.random.seed(SEED)
torch.manual_seed(SEED)
if torch.cuda.is_available():
    torch.cuda.manual_seed_all(SEED)

device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
print("Device:", device)

```

Device: cuda

```

data_path = "/tmp" # your files are here
csv_files = glob.glob(os.path.join(data_path, "*.csv"))

if not csv_files:
    raise FileNotFoundError("No .csv files in /tmp. Upload or download

preferred = [f for f in csv_files if "BTC_1sec" in os.path.basename(f)]
lob_file = preferred[0] if preferred else csv_files[0]

print("Using file:", lob_file)

df = pd.read_csv(lob_file, nrows=500_000)

```

```

print(df.head(), "\nShape:", df.shape)

num_cols = df.select_dtypes(include=[np.number]).columns.tolist()
print("Numeric columns:", len(num_cols))

# Detect bid/ask prices
bids = [c for c in num_cols if "bid" in c.lower() and "price" in c.lower()]
asks = [c for c in num_cols if "ask" in c.lower() and "price" in c.lower()]

if bids and asks:
    best_bid = bids[0]
    best_ask = asks[0]
    df["mid_price"] = (df[best_bid] + df[best_ask]) / 2
    df["spread"] = df[best_ask] - df[best_bid]
else:
    price_col = num_cols[0]
    df["mid_price"] = df[price_col]
    df["spread"] = 0.0

# Order Flow Imbalance
bid_sizes = [c for c in num_cols if "bid" in c.lower() and "size" in c.lower()]
ask_sizes = [c for c in num_cols if "ask" in c.lower() and "size" in c.lower()]

if bid_sizes and ask_sizes:
    df["ofi_best"] = (df[bid_sizes[0]] - df[ask_sizes[0]]) / (
        df[bid_sizes[0]] + df[ask_sizes[0]] + 1e-9
    )
else:
    df["ofi_best"] = 0.0

# Volatility
df["mid_ret_inst"] = df["mid_price"].pct_change().fillna(0.0)
df["mid_vol"] = df["mid_ret_inst"].rolling(50).std().fillna(0.0)

# Labels
HORIZON = 10s
s
df["price_future"] = df["mid_price"].shift(-HORIZON)
df["ret"] = (df["price_future"] - df["mid_price"]) / df["mid_price"]

THRESH = 0.0001
def lab(r):
    if r > THRESH: return 1
    elif r < -THRESH: return -1
    else: return 0

df["label_raw"] = df["ret"].apply(lab)
df = df.dropna(subset=["price_future"]).reset_index(drop=True)

```

```
df = df.dropna(subset=["price_rate"],reset_index(drop=True),

labels_raw = df["label_raw"].values
unique_labels = np.unique(labels_raw)
label_to_idx = {lab:i for i,lab in enumerate(unique_labels)}
idx_to_label = {i:lab for lab,i in label_to_idx.items()}
labels_idx = np.vectorize(label_to_idx.get)(labels_raw)

print("Label counts:", df["label_raw"].value_counts())
```

Using file: /tmp/BTC_1sec.csv

	Unnamed: 0	system_time	midpoint	spread	buy
0	0	2021-04-07 11:32:42.122161+00:00	56035.995	0.01	0
1	1	2021-04-07 11:32:43.122161+00:00	56035.995	0.01	0
2	2	2021-04-07 11:32:44.122161+00:00	56035.995	0.01	0
3	3	2021-04-07 11:32:45.122161+00:00	56035.995	0.01	0
4	4	2021-04-07 11:32:46.122161+00:00	56035.995	0.01	0

	sells	bids_distance_0	bids_distance_1	bids_distance_2	bids_distance_3
0	0.0	-8.922836e-08	-2.676851e-07	-0.00005	-0.00005
1	0.0	-8.922836e-08	-2.676851e-07	-0.00005	-0.00005
2	0.0	-8.922836e-08	-2.676851e-07	-0.00005	-0.00005
3	0.0	-8.922836e-08	-2.676851e-07	-0.00005	-0.00005
4	0.0	-8.922836e-08	-2.676851e-07	-0.00005	-0.00005

	...	asks_market_notional_5	asks_market_notional_6	\
0	...	0.0	0.0	
1	...	0.0	0.0	
2	...	0.0	0.0	
3	...	0.0	0.0	
4	...	0.0	0.0	

	asks_market_notional_7	asks_market_notional_8	asks_market_notional_9
0	0.0	0.0	0.0
1	0.0	0.0	0.0
2	0.0	0.0	0.0
3	0.0	0.0	0.0
4	0.0	0.0	0.0

	asks_market_notional_10	asks_market_notional_11	asks_market_notional_12
0	0.0	0.0	0.0
1	0.0	0.0	0.0
2	0.0	0.0	0.0
3	0.0	0.0	0.0
4	0.0	0.0	0.0

	asks_market_notional_13	asks_market_notional_14
0	0.0	0.0
1	0.0	0.0
2	0.0	0.0
3	0.0	0.0
4	0.0	0.0

```
[5 rows x 156 columns]
Shape: (500000, 156)
Numeric columns: 155
Label counts: label_raw
0      399990
1      100000
Name: count, dtype: int64
```

SELECT FEATURES + SCALE + DATASET + LOADERS

```
ignore = {"price_future", "ret", "label_raw"}
feature_cols = [c for c in num_cols if c not in ignore]
for extra in ["spread", "ofi_best", "mid_vol"]:
    if extra not in feature_cols:
        feature_cols.append(extra)

print("Final feature count:", len(feature_cols))

scaler = StandardScaler()
features = scaler.fit_transform(df[feature_cols].values.astype(np.float32))

# Class weights
class_weights = compute_class_weight(
    class_weight="balanced",
    classes=unique_labels,
    y=labels_raw
)
weights_tensor = torch.tensor(class_weights, dtype=torch.float32)

class LOBSequenceDataset(Dataset):
    def __init__(self, X, Y, seq_len=100):
        self.X = X
        self.Y = Y
        self.L = seq_len

    def __len__(self):
        return len(self.X) - self.L

    def __getitem__(self, idx):
        x = torch.tensor(self.X[idx:idx+self.L], dtype=torch.float32)
        y = torch.tensor(self.Y[idx+self.L-1], dtype=torch.long)
        return x, y

SEQ_LEN = 100
dataset = LOBSequenceDataset(features, labels_idx, seq_len=SEQ_LEN)
```

```

N = len(dataset)
train_end = int(0.70 * N)
val_end   = int(0.85 * N)

train_idx = list(range(0, train_end))
val_idx   = list(range(train_end, val_end))
test_idx  = list(range(val_end, N))

class Subset(Dataset):
    def __init__(self, base, idxs):
        self.base = base; self.idxs = idxs
    def __len__(self): return len(self.idxs)
    def __getitem__(self, i): return self.base[self.idxs[i]]

train_ds = Subset(dataset, train_idx)
val_ds   = Subset(dataset, val_idx)
test_ds  = Subset(dataset, test_idx)

BATCH_SIZE = 256
train_loader = DataLoader(train_ds, batch_size=BATCH_SIZE, shuffle=True)
val_loader   = DataLoader(val_ds, batch_size=BATCH_SIZE, shuffle=False)
test_loader  = DataLoader(test_ds, batch_size=BATCH_SIZE, shuffle=False)

```

Final feature count: 157

LOSS, TRAINING & EVALUATION UTILITIES

```

n_features = len(feature_cols)
n_classes  = len(unique_labels)

criterion = nn.CrossEntropyLoss(weight=weights_tensor.to(device))

def train_epoch(model, loader, opt, crit):
    model.train()
    tot, correct, total = 0,0,0
    for x,y in loader:
        x,y = x.to(device), y.to(device)
        opt.zero_grad()
        out = model(x)
        loss = crit(out,y)
        loss.backward()
        opt.step()
        tot += loss.item()*x.size(0)
        pred = out.argmax(1)
        correct += (pred==y).sum().item()
        total += x.size(0)

```

```

        return tot/total, correct/total

@torch.no_grad()
def eval_epoch(model, loader, crit):
    model.eval()
    tot, correct, total = 0,0,0
    for x,y in loader:
        x,y = x.to(device), y.to(device)
        out = model(x)
        loss = crit(out,y)
        tot += loss.item()*x.size(0)
        pred = out.argmax(1)
        correct += (pred==y).sum().item()
        total += x.size(0)
    return tot/total, correct/total

def train_model_with_history(model, train_loader, val_loader, optimizer, criterion):
    hist = {"epoch":[], "train_loss":[], "train_acc":[], "val_loss":[], "val_acc":[]}
    for e in range(1, epochs+1):
        tl, ta = train_epoch(model, train_loader, optimizer, criterion)
        vl, va = eval_epoch(model, val_loader, criterion)
        hist["epoch"].append(e)
        hist["train_loss"].append(tl)
        hist["train_acc"].append(ta)
        hist["val_loss"].append(vl)
        hist["val_acc"].append(va)
        print(f"[{name}] Epoch {e}: TL={tl:.4f}, TA={ta:.3f}, VL={vl:.4f}, VA={va:.3f}")
    return hist

@torch.no_grad()
def get_predictions(model, loader):
    model.eval()
    preds = []; truths = []
    for x,y in loader:
        x,y = x.to(device), y.to(device)
        out = model(x)
        p = out.argmax(1)
        preds.append(p.cpu().numpy())
        truths.append(y.cpu().numpy())
    preds = np.concatenate(preds)
    truths = np.concatenate(truths)
    return np.vectorize(idx_to_label.get)(truths), np.vectorize(idx_to_label.get)(preds)

@torch.no_grad()
def get_probabilities(model, loader):
    model.eval()
    PROBS = []
    for x,_ in loader:

```



```
        x = x.to(device)
        out = model(x)
        PROBS.append(torch.softmax(out, dim=1).cpu().numpy())
    return np.vstack(PROBS)
```

```
criterion = nn.CrossEntropyLoss(weight=weights_tensor.to(device))
EPOCHS = 10 # as you requested
```

```
def train_epoch(model, loader, optimizer, criterion):
```

```
    model.train()
    total_loss = 0.0
    correct = 0
    total = 0
```

```
    for x, y in loader:
        x = x.to(device)
        y = y.to(device)
```

```
        optimizer.zero_grad()
        logits = model(x)
        loss = criterion(logits, y)
        loss.backward()
        optimizer.step()
```

```
        total_loss += loss.item() * x.size(0)
        preds = logits.argmax(1)
        correct += (preds == y).sum().item()
        total += x.size(0)
```

```
    avg_loss = total_loss / total
    acc = correct / total
    return avg_loss, acc
```

```
@torch.no_grad()
```

```
def eval_epoch(model, loader, criterion):
```

```
    model.eval()
    total_loss = 0.0
    correct = 0
    total = 0
```

```
    for x, y in loader:
        x = x.to(device)
        y = y.to(device)
```

```
        logits = model(x)
```

```

        loss = criterion(logits, y)

        total_loss += loss.item() * x.size(0)
        preds = logits.argmax(1)
        correct += (preds == y).sum().item()
        total += x.size(0)

    avg_loss = total_loss / total
    acc = correct / total
    return avg_loss, acc

def train_model_with_history(model, train_loader, val_loader, optimizer, criterion):
    history = {
        "epoch": [],
        "train_loss": [],
        "train_acc": [],
        "val_loss": [],
        "val_acc": []
    }

    for epoch in range(1, epochs + 1):
        tr_loss, tr_acc = train_epoch(model, train_loader, optimizer, criterion)
        val_loss, val_acc = eval_epoch(model, val_loader, criterion)

        history["epoch"].append(epoch)
        history["train_loss"].append(tr_loss)
        history["train_acc"].append(tr_acc)
        history["val_loss"].append(val_loss)
        history["val_acc"].append(val_acc)

        print(f"[{name}] Epoch {epoch}: "
              f"train_loss={tr_loss:.4f}, train_acc={tr_acc:.3f}, "
              f"val_loss={val_loss:.4f}, val_acc={val_acc:.3f}")

    return history

@torch.no_grad()
def get_predictions(model, loader):
    model.eval()
    all_preds_idx, all_labels_idx = [], []

    for x, y in loader:
        x = x.to(device)
        y = y.to(device)
        logits = model(x)
        preds = logits.argmax(1)
        all_preds_idx.append(preds.cpu().numpy())

```

```

        all_labels_idx.append(y.cpu().numpy())

all_preds_idx = np.concatenate(all_preds_idx)
all_labels_idx = np.concatenate(all_labels_idx)

# map indices -> original labels {-1, 0, 1 or subset}
vec_map = np.vectorize(idx_to_label.get)
all_preds = vec_map(all_preds_idx)
all_labels = vec_map(all_labels_idx)
return all_labels, all_preds

@torch.no_grad()
def get_probabilities(model, loader):
    model.eval()
    probs = []
    for x, _ in loader:
        x = x.to(device)
        logits = model(x)
        p = torch.softmax(logits, dim=1)
        probs.append(p.cpu().numpy())
    return np.vstack(probs)

```

ANALYSIS / VISUALIZATION FUNCTIONS

```

def plot_curves(history, name):
    epochs = history["epoch"]

    plt.figure(figsize=(10,4))

    # Loss
    plt.subplot(1,2,1)
    plt.plot(epochs, history["train_loss"], label="Train")
    plt.plot(epochs, history["val_loss"], label="Val")
    plt.xlabel("Epoch")
    plt.ylabel("Loss")
    plt.title(f"{name} - Loss")
    plt.legend()

    # Accuracy
    plt.subplot(1,2,2)
    plt.plot(epochs, history["train_acc"], label="Train")
    plt.plot(epochs, history["val_acc"], label="Val")
    plt.xlabel("Epoch")
    plt.ylabel("Accuracy")

```

```

plt.title(f"{name} - Accuracy")
plt.legend()

plt.tight_layout()
plt.show()

def plot_confusion(model, name, loader=None):
    if loader is None:
        loader = test_loader
    y_true, y_pred = get_predictions(model, loader)
    cm = confusion_matrix(y_true, y_pred, labels=unique_labels)

    plt.figure(figsize=(4,3))
    sns.heatmap(
        cm,
        annot=True,
        fmt="d",
        xticklabels=unique_labels,
        yticklabels=unique_labels
    )
    plt.xlabel("Predicted")
    plt.ylabel("True")
    plt.title(f"Confusion Matrix - {name}")
    plt.tight_layout()
    plt.show()

    print(f"\nClassification report for {name}:")
    print(classification_report(y_true, y_pred, labels=unique_labels))

def plot_pred_distribution(model, name, loader=None):
    if loader is None:
        loader = test_loader
    y_true, y_pred = get_predictions(model, loader)
    pred_counts = pd.Series(y_pred).value_counts().sort_index()

    plt.figure(figsize=(4,3))
    sns.barplot(x=pred_counts.index.astype(str), y=pred_counts.values)
    plt.xlabel("Predicted Class")
    plt.ylabel("Count")
    plt.title(f"{name} - Prediction Distribution")
    plt.tight_layout()
    plt.show()

    print(f"\nPrediction counts for {name}:\n", pred_counts)

```

```

def plot_confidence_hist(model, name, loader=None, bins=20):
    if loader is None:
        loader = test_loader
    probs = get_probabilities(model, loader)
    max_conf = probs.max(axis=1)

    plt.figure(figsize=(5,3))
    plt.hist(max_conf, bins=bins, alpha=0.8)
    plt.xlabel("Max Softmax Probability")
    plt.ylabel("Frequency")
    plt.title(f"{name} - Confidence Histogram")
    plt.tight_layout()
    plt.show()

def plot_reliability(model, name, loader=None, n_bins=10):
    if loader is None:
        loader = test_loader
    probs = get_probabilities(model, loader)
    y_true, y_pred = get_predictions(model, loader)

    correct = (y_true == y_pred).astype(int)
    max_conf = probs.max(axis=1)

    prob_true, prob_pred = calibration_curve(correct, max_conf, n_bins)

    plt.figure(figsize=(4,3))
    plt.plot(prob_pred, prob_true, marker="o")
    plt.plot([0,1],[0,1],"k--")
    plt.xlabel("Predicted probability")
    plt.ylabel("Observed accuracy")
    plt.title(f"{name} - Calibration Curve")
    plt.tight_layout()
    plt.show()

def plot_pred_vs_true_heatmap(model, name, loader=None):
    if loader is None:
        loader = test_loader
    y_true, y_pred = get_predictions(model, loader)
    dfp = pd.DataFrame({"True": y_true, "Pred": y_pred})
    ct = dfp.value_counts().unstack(fill_value=0)

    plt.figure(figsize=(4,4))
    sns.heatmap(ct, annot=True, fmt="d")
    plt.xlabel("Predicted")
    plt.ylabel("True")
    plt.title(f"{name} - True vs Pred Counts")

```

```

plt.tight_layout()
plt.show()

print(f"\nJoint distribution (True, Pred) for {name}:\n", ct)

def plot_roc(model, name, loader=None):
    if loader is None:
        loader = test_loader

    probs = get_probabilities(model, loader)
    y_true, _ = get_predictions(model, loader)

    Y_bin = label_binarize(y_true, classes=unique_labels)

    plt.figure(figsize=(6,4))
    for i, lab in enumerate(unique_labels):
        fpr, tpr, _ = roc_curve(Y_bin[:, i], probs[:, i])
        auc_val = auc(fpr, tpr)
        plt.plot(fpr, tpr, label=f"Class {lab} (AUC={auc_val:.3f})")

    plt.plot([0,1],[0,1],"k--")
    plt.xlabel("False Positive Rate")
    plt.ylabel("True Positive Rate")
    plt.title(f"{name} - Multi-class ROC")
    plt.legend()
    plt.tight_layout()
    plt.show()

def get_global_metrics(model, loader, name):
    y_true, y_pred = get_predictions(model, loader)
    acc = accuracy_score(y_true, y_pred)
    precision, recall, f1, _ = precision_recall_fscore_support(
        y_true, y_pred, average="macro", labels=unique_labels, zero_d:
    )
    return {
        "Model": name,
        "Accuracy": acc,
        "Precision_macro": precision,
        "Recall_macro": recall,
        "F1_macro": f1
    }

def get_misclassifications(model, loader=None, head=20):
    if loader is None:
        loader = test_loader

```

```

y_true, y_pred = get_predictions(model, loader)
df_err = pd.DataFrame({"True": y_true, "Pred": y_pred})
mis = df_err[df_err["True"] != df_err["Pred"]]
print(f"Total misclassified: {len(mis)} / {len(df_err)}")
return mis.head(head)

```

```

@torch.no_grad()
def extract_logits(model, loader=None, max_batches=None):
    if loader is None:
        loader = test_loader
    model.eval()
    feats = []
    labs = []
    for b_idx, (x, y) in enumerate(loader):
        x = x.to(device)
        y = y.to(device)
        out = model(x)
        feats.append(out.cpu().numpy())
        labs.append(y.cpu().numpy())
        if max_batches is not None and (b_idx + 1) >= max_batches:
            break
    feats = np.vstack(feats)
    labs = np.concatenate(labs)
    labs = np.vectorize(idx_to_label.get)(labs)
    return feats, labs

def plot_tsne(model, name, loader=None, max_batches=20, perplexity=40):
    X, y = extract_logits(model, loader, max_batches=max_batches)
    if X.shape[0] < 10:
        print(f"Not enough samples for t-SNE for {name}.")
        return

    print(f"Running t-SNE for {name} on {X.shape[0]} samples...")
    tsne = TSNE(
        n_components=2,
        perplexity=perplexity,
        n_iter=n_iter,
        init="random",
        learning_rate="auto",
    )
    X2 = tsne.fit_transform(X)

    plt.figure(figsize=(6,4))
    sns.scatterplot(x=X2[:,0], y=X2[:,1], hue=y, s=12, palette="deep")
    plt.title(f"{name} - t-SNE of Logit Space")
    plt.tight_layout()

```

```

plt.show()

def batch_variance(model, loader=None):
    if loader is None:
        loader = test_loader
    model.eval()
    batch_accs = []
    with torch.no_grad():
        for x, y in loader:
            x, y = x.to(device), y.to(device)
            out = model(x)
            pred = out.argmax(1)
            acc = (pred == y).float().mean().item()
            batch_accs.append(acc)
    return np.var(batch_accs) if batch_accs else np.nan

def evaluate_model_pretty(model, name, loader=None):
    if loader is None:
        loader = test_loader
    y_true, y_pred = get_predictions(model, loader)
    print(f"\n===== {name} =====")
    print("Confusion matrix (rows=true, cols=pred):")
    print(confusion_matrix(y_true, y_pred, labels=unique_labels))
    print("\nClassification report:")
    print(classification_report(
        y_true, y_pred, labels=unique_labels
    ))

```

MODEL DEFINITIONS

```

# 8.1 CNN
class CNNLOB(nn.Module):
    def __init__(self, n_features, n_classes):
        super().__init__()
        self.conv1 = nn.Conv1d(n_features, 64, kernel_size=5, padding=
self.conv2 = nn.Conv1d(64, 128, kernel_size=5, padding=2)
self.conv3 = nn.Conv1d(128, 128, kernel_size=3, padding=1)
self.bn1 = nn.BatchNorm1d(64)
self.bn2 = nn.BatchNorm1d(128)
self.bn3 = nn.BatchNorm1d(128)
self.dropout = nn.Dropout(0.3)
self.fc = nn.Linear(128, n_classes)

```



```

def forward(self, x):
    x = x.permute(0, 2, 1)          # [B, F, T]
    x = self.bn1(F.relu(self.conv1(x)))
    x = self.bn2(F.relu(self.conv2(x)))
    x = self.bn3(F.relu(self.conv3(x)))
    x = F.adaptive_avg_pool1d(x, 1).squeeze(-1)  # [B, 128]
    x = self.dropout(x)
    return self.fc(x)

```

8.2 LSTM

```

class LSTMBOL(nn.Module):
    def __init__(self, n_features, n_classes, hidden_size=128, num_la
        super().__init__()
        self.lstm = nn.LSTM(
            input_size=n_features,
            hidden_size=hidden_size,
            num_layers=num_layers,
            batch_first=True,
            bidirectional=True,
            dropout=dropout
        )
        self.dropout = nn.Dropout(dropout)
        self.fc = nn.Linear(hidden_size * 2, n_classes)

    def forward(self, x):
        out, _ = self.lstm(x)          # [B, T, 2H]
        last = out[:, -1, :]          # last timestep
        last = self.dropout(last)
        return self.fc(last)

```

8.3 Transformer

```

class PositionalEncoding(nn.Module):
    def __init__(self, d_model, max_len=5000):
        super().__init__()
        pe = torch.zeros(max_len, d_model)  # [T, D]
        position = torch.arange(0, max_len, dtype=torch.float32).unsqueeze(1)
        div_term = torch.exp(
            torch.arange(0, d_model, 2, dtype=torch.float32)
            * (-np.log(10000.0) / d_model)
        )
        pe[:, 0::2] = torch.sin(position * div_term)
        pe[:, 1::2] = torch.cos(position * div_term)
        pe = pe.unsqueeze(0)  # [1, T, D]
        self.register_buffer("pe", pe)

```

```

def forward(self, x):
    T = x.size(1)
    return x + self.pe[:, :T, :]

```

```

class TransformerLOB(nn.Module):
    def __init__(self, n_features, n_classes, d_model=128, nhead=4, num_layers=6):
        super().__init__()
        self.input_proj = nn.Linear(n_features, d_model)
        encoder_layer = nn.TransformerEncoderLayer(
            d_model=d_model,
            nhead=nhead,
            dim_feedforward=dim_feedforward,
            dropout=dropout,
            batch_first=True
        )
        self.transformer = nn.TransformerEncoder(encoder_layer, num_layers)
        self.pos_encoder = PositionalEncoding(d_model)
        self.dropout = nn.Dropout(dropout)
        self.fc = nn.Linear(d_model, n_classes)

    def forward(self, x):
        x = self.input_proj(x)          # [B, T, D]
        x = self.pos_encoder(x)
        out = self.transformer(x)       # [B, T, D]
        last = out[:, -1, :]
        last = self.dropout(last)
        return self.fc(last)

```

8.4 TCN (Temporal Convolutional Network)

```

class Chomp1d(nn.Module):
    def __init__(self, chomp_size):
        super().__init__()
        self.chomp_size = chomp_size
    def forward(self, x):
        return x[:, :, :-self.chomp_size].contiguous()

```

```

class TemporalBlock(nn.Module):
    def __init__(self, in_channels, out_channels, kernel_size, dilation=2, dropout=0.1):
        super().__init__()
        self.conv1 = nn.Conv1d(in_channels, out_channels, kernel_size, dilation=dilation)
        self.chomp1 = Chomp1d(padding)
        self.bn1 = nn.BatchNorm1d(out_channels)
        self.conv2 = nn.Conv1d(out_channels, out_channels, kernel_size, dilation=dilation)
        self.chomp2 = Chomp1d(padding)
        self.bn2 = nn.BatchNorm1d(out_channels)

```

```

        self.relu = nn.ReLU()
        self.dropout = nn.Dropout(dropout)

        self.downsample = nn.Conv1d(in_channels, out_channels, 1) if :

def forward(self, x):
    out = self.conv1(x)
    out = self.chomp1(out)
    out = self.bn1(F.relu(out))
    out = self.dropout(out)

    out = self.conv2(out)
    out = self.chomp2(out)
    out = self.bn2(F.relu(out))
    out = self.dropout(out)

    res = x if self.downsample is None else self.downsample(x)
    return self.relu(out + res)

class TCN(nn.Module):
    def __init__(self, n_features, n_classes, channels=[64, 128, 128],
        super().__init__()
        layers = []
        in_ch = n_features
        for i, out_ch in enumerate(channels):
            dilation = 2 ** i
            padding = (kernel_size - 1) * dilation
            layers.append(
                TemporalBlock(in_ch, out_ch, kernel_size, dilation, padding)
            )
            in_ch = out_ch
        self.network = nn.Sequential(*layers)
        self.dropout = nn.Dropout(dropout)
        self.fc = nn.Linear(channels[-1], n_classes)

    def forward(self, x):
        x = x.permute(0, 2, 1)          # [B, F, T]
        out = self.network(x)           # [B, C, T]
        out = F.adaptive_avg_pool1d(out, 1).squeeze(-1)
        out = self.dropout(out)
        return self.fc(out)

# 8.5 CNN+LSTM Hybrid
class CNNLSTM(nn.Module):
    def __init__(self, n_features, n_classes, cnn_channels=64, lstm_h:
        super().__init__()

```

```

self.conv1 = nn.Conv1d(n_features, cnn_channels, kernel_size=kernel_size)
self.bn1 = nn.BatchNorm1d(cnn_channels)
self.conv2 = nn.Conv1d(cnn_channels, cnn_channels, kernel_size=kernel_size)
self.bn2 = nn.BatchNorm1d(cnn_channels)

self.lstm = nn.LSTM(
    input_size=cnn_channels,
    hidden_size=lstm_hidden,
    num_layers=lstm_layers,
    batch_first=True,
    bidirectional=True
)

self.dropout = nn.Dropout(dropout)
self.fc = nn.Linear(lstm_hidden * 2, n_classes)

def forward(self, x):
    x = x.permute(0, 2, 1)                # [B, F, T]
    x = F.relu(self.bn1(self.conv1(x)))
    x = F.relu(self.bn2(self.conv2(x)))    # [B, C, T]
    x = x.permute(0, 2, 1)                # [B, T, C]
    out, _ = self.lstm(x)                 # [B, T, 2H]
    last = out[:, -1, :]
    last = self.dropout(last)
    return self.fc(last)

# Instantiate models + optimizers
cnn_model = CNNLOB(n_features=n_features, n_classes=n_classes).to(device)
lstm_model = LSTMBOL(n_features=n_features, n_classes=n_classes).to(device)
transformer_model = TransformerLOB(n_features=n_features, n_classes=n_classes).to(device)
tcn_model = TCN(n_features=n_features, n_classes=n_classes).to(device)
cnnlstm_model = CNNLSTM(n_features=n_features, n_classes=n_classes).to(device)

optimizer_cnn = torch.optim.Adam(cnn_model.parameters(), lr=1e-3)
optimizer_lstm = torch.optim.Adam(lstm_model.parameters(), lr=1e-3)
optimizer_tr = torch.optim.Adam(transformer_model.parameters(), lr=1e-3)
optimizer_tcn = torch.optim.Adam(tcn_model.parameters(), lr=1e-3)
optimizer_cnnlstm = torch.optim.Adam(cnnlstm_model.parameters(), lr=1e-3)

```

HYPERPARAMETER SUMMARY TABLE

```
hyper_table = pd.DataFrame({
    "Model": ["CNN", "LSTM", "Transformer", "TCN", "CNN+LSTM"],
    "Learning Rate": [1e-3, 1e-3, 1e-4, 1e-3, 1e-3],
    "Batch Size": [BATCH_SIZE]*5,
    "Epochs": [EPOCHS]*5,
    "Sequence Length": [SEQ_LEN]*5,
    "Loss Function": ["Weighted CrossEntropy"]*5,
    "Optimizer": ["Adam"]*5,
    "Architecture": [
        "3x Conv1d + GAP",
        "2-layer BiLSTM",
        "2-layer Transformer Encoder",
        "3-block TCN (dilated)",
        "CNN(64) + 1-layer BiLSTM"
    ]
}).set_index("Model")

hyper_table
```

	Learning Rate	Batch Size	Epochs	Sequence Length	Loss Function	Optimizer	Architecture
Model							
CNN	0.0010	256	10	100	Weighted CrossEntropy	Adam	
LSTM	0.0010	256	10	100	Weighted CrossEntropy	Adam	2-layer BiLSTM
Transformer	0.0001	256	10	100	Weighted CrossEntropy	Adam	2-layer Transformer Encoder

Next steps:

[Generate code with hyper_table](#)

[New interactive sheet](#)

GRAPH SHOWING ALL MODEL RESULTS (Accuracy, Precision, Recall, F1)

```
import numpy as np
import matplotlib.pyplot as plt

# Extract values from metrics_df
models = metrics_df.index.tolist()
accuracy = metrics_df["Accuracy"].values
precision = metrics_df["Precision_macro"].values
recall = metrics_df["Recall_macro"].values
f1 = metrics_df["F1_macro"].values
```

```

# Grouped bar chart settings
x = np.arange(len(models))
width = 0.20


plt.figure(figsize=(12,6))

# Bars
plt.bar(x - 1.5*width, accuracy, width, label='Accuracy')
plt.bar(x - 0.5*width, precision, width, label='Precision')
plt.bar(x + 0.5*width, recall, width, label='Recall')
plt.bar(x + 1.5*width, f1, width, label='F1 Score')

# Labels & formatting
plt.ylabel('Score')
plt.title('Model Comparison: Accuracy, Precision, Recall, and F1')
plt.xticks(x, models)
plt.ylim(0, 1.0)
plt.legend()
plt.grid(axis='y', linestyle='--', alpha=0.5)

plt.tight_layout()
plt.show()


```




CONFUSION MATRIX


```
for name, model in models_to_compare.items():
    y_true, y_pred = get_predictions(model, test_loader)
    cm = confusion_matrix(y_true, y_pred, labels=unique_labels)

    plt.figure(figsize=(4,3))
    sns.heatmap(cm, annot=True, fmt='d',
                xticklabels=unique_labels,
                yticklabels=unique_labels,
                cmap="Blues")
    plt.xlabel("Predicted")
    plt.ylabel("True")
    plt.title(f"Confusion Matrix - {name}")
    plt.tight_layout()
    plt.show()
```






Confusion Matrix - Transformer




Confusion Matrix - TCN



Confusion Matrix - CNN+LSTM





CLASS-WISE PROBABILITY DISTRIBUTIONS (PER MODEL)


```
import seaborn as sns
import pandas as pd
import matplotlib.pyplot as plt

def plot_probability_distribution(model, name):
    probs = get_probabilities(model, test_loader)
    y_true, y_pred = get_predictions(model, test_loader)

    df_plot = pd.DataFrame(probs, columns=[f"Prob_{c}" for c in unique
    df_plot["True"] = y_true


    plt.figure(figsize=(8,4))
    sns.violinplot(data=df_plot.drop(columns="True"))
    plt.title(f"Probability Distribution per Class - {name}")
    plt.tight_layout()
    plt.show()

plot_probability_distribution(cnn_model, "CNN")
plot_probability_distribution(lstm_model, "LSTM")
plot_probability_distribution(transformer_model, "Transformer")
plot_probability_distribution(tcn_model, "TCN")
plot_probability_distribution(cnnlstm_model, "CNN+LSTM")
```







Probability Distribution per Class - LSTM




Probability Distribution per Class - Transformer



Probability Distribution per Class - TCN





SHAP EXPLAINABILITY FOR ALL MODELS

```
import torch
torch.backends.cudnn.enabled = False
```

```
!pip install -q shap
import shap
import random
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns

# ----- 1. Helper: sample sequences from test_ds -----
def build_sequence_arrays(dataset, n_samples=200):
    n = len(dataset)
    idxs = random.sample(range(n), min(n_samples, n))

    seq_list = []
    agg_list = []
    y_list = []

    for i in idxs:
        x, y = dataset[i]          # x: [T, F]
        x_np = x.numpy()
        seq_list.append(x_np)
        agg_list.append(x_np.mean(axis=0))
        y_list.append(y.item())

    X_seq = torch.tensor(np.stack(seq_list), dtype=torch.float32).to(device)
    X_agg = np.stack(agg_list)
    y_idx = np.array(y_list)

    return X_seq, X_agg, y_idx

# Shared background + test set for SHAP
background_seq, background_agg, _ = build_sequence_arrays(test_ds, n_samples=200)
test_seq, test_agg, test_y_idx = build_sequence_arrays(test_ds, n_samples=200)

# ----- 2. Models to explain -----
models_to_explain = {
    "CNN": cnn_model,
    "LSTM": lstm_model,
    "Transformer": transformer_model,
    "TCN": tcn_model,
    "CNN+LSTM": cnnlstm_model
}

for m in models_to_explain.values():
```

```

        m.eval()

# ----- 3. SHAP loop -----
shap_importances = {}

for model_name, model in models_to_explain.items():

    print("\n=====")
    print(f"Computing SHAP for {model_name}")
    print("=====")

    # Save original mode (train/eval)
    was_training = model.training

    # IMPORTANT: DeepExplainer needs backward through RNN -> use train
    model.train()

    # Create DeepExplainer
    explainer = shap.DeepExplainer(
        model,
        background_seq
    )

    # Compute SHAP values (disable additivity check)
    shap_values_list = explainer.shap_values(
        test_seq,
        check_additivity=False
    )

    # Restore original mode
    if not was_training:
        model.eval()

    # Sum absolute contributions across classes
    shap_abs_sum = np.zeros_like(shap_values_list[0])
    for sv in shap_values_list:
        shap_abs_sum += np.abs(sv)

    # Aggregate over time -> [N, F]
    shap_agg = shap_abs_sum.mean(axis=1)

    # Global importance over samples -> [F]
    global_importance = shap_agg.mean(axis=0)

    print(f"{model_name}: global_importance shape = {global_importance.shape}, "
          f"feature_cols length = {len(feature_cols)}")

    n_feat_importance = global_importance.shape[0]

```

```

n_feat_names = len(feature_cols)

if n_feat_importance != n_feat_names:
    print(f"WARNING: feature length mismatch for {model_name}. "
          f"Using min({n_feat_importance}, {n_feat_names}).")
    k = min(n_feat_importance, n_feat_names)
    feat_names = feature_cols[:k]
    global_importance = global_importance[:k]
else:
    feat_names = feature_cols

importance_df = pd.DataFrame({
    "feature": feat_names,
    "importance": global_importance
}).sort_values("importance", ascending=False)

shap_importances[model_name] = importance_df


# Plot top 20 SHAP features
plt.figure(figsize=(8,6))
sns.barplot(
    data=importance_df.head(20),
    x="importance",
    y="feature",
    orient="h"
)
plt.title(f"Top 20 Feature Importances by Mean |SHAP| - {model_name}")
plt.xlabel("Mean |SHAP value| (time-averaged)")
plt.ylabel("Feature")
plt.tight_layout()
plt.show()


```

```


=====
Computing SHAP for CNN
=====
CNN: global_importance shape = (2,), feature_cols length = 157
WARNING: feature length mismatch for CNN. Using min(2, 157).

```






```
=====  
Computing SHAP for LSTM  
=====  
/usr/local/lib/python3.12/dist-packages/shap/explainers/_deep/deep_pytc  
  warnings.warn(f"unrecognized nn.Module: {module_type}")  
LSTM: global_importance shape = (2,), feature_cols length = 157  
WARNING: feature length mismatch for LSTM. Using min(2, 157).
```



```
=====  
Computing SHAP for Transformer  
=====  
/usr/local/lib/python3.12/dist-packages/shap/explainers/_deep/deep_pytc  
  warnings.warn(f"unrecognized nn.Module: {module_type}")
```

```
/usr/local/lib/python3.12/dist-packages/shap/explainers/_deep/deep_pytorch
warnings.warn(f"unrecognized nn.Module: {module_type}")
Transformer: global_importance shape = (2,), feature_cols length = 157
WARNING: feature length mismatch for Transformer. Using min(2, 157).
```





```
=====
```

Computing SHAP for TCN


```
=====
```

```
/usr/local/lib/python3.12/dist-packages/shap/explainers/_deep/deep_pytorch
warnings.warn(f"unrecognized nn.Module: {module_type}")
TCN: global_importance shape = (2,), feature_cols length = 157
WARNING: feature length mismatch for TCN. Using min(2, 157).
```





```
=====  
Computing SHAP for CNN+LSTM  
=====  
/usr/local/lib/python3.12/dist-packages/shap/explainers/_deep/deep_pytorch  
  warnings.warn(f"unrecognized nn.Module: {module_type}")  
CNN+LSTM: global_importance shape = (2,), feature_cols length = 157  
WARNING: feature length mismatch for CNN+LSTM. Using min(2, 157).
```





RADAR PLOT COMPARING MODELS

```
from math import pi


df_radar = metrics_df.copy()
categories = df_radar.columns.tolist()
models = df_radar.index.tolist()

plt.figure(figsize=(6,6))
angles = [n / float(len(categories)) * 2 * pi for n in range(len(categories))]
angles += angles[:1]

for m in models:
    values = df_radar.loc[m].tolist()
    values += values[:1]
```

```
plt.polar(angles, values, marker='o', label=m)

plt.xticks(angles[:-1], categories)
plt.title("Radar Comparison of All Models")
plt.legend(loc='upper right', bbox_to_anchor=(1.3, 1.1))
plt.show()
```



CALIBRATION DISTRIBUTION (ECE-EXPECTED CALIBRATION ERROR)

```

def expected_calibration_error(model, loader=test_loader, bins=15):
    probs = get_probabilities(model, loader)
    conf = probs.max(axis=1)
    y_true, y_pred = get_predictions(model, loader)
    correct = (y_true == y_pred).astype(int)

    bin_bounds = np.linspace(0, 1, bins+1)
    ece = 0.0

    for i in range(bins):
        lower, upper = bin_bounds[i], bin_bounds[i+1]
        idx = (conf >= lower) & (conf < upper)
        if idx.sum() == 0:
            continue
        ece += abs(correct[idx].mean() - conf[idx].mean()) * idx.mean()

    return ece

for name, model in models_to_compare.items():
    print(name, "ECE:", expected_calibration_error(model))

```

```

CNN ECE: 0.5347795343050564
LSTM ECE: 0.20405988018591326
Transformer ECE: 0.4989185646115926
TCN ECE: 0.4423142166252415
CNN+LSTM ECE: 0.4572329701319024

```

FINAL SUMMARY DASHBOARD TABLE

```
summary = pd.DataFrame(columns=["Accuracy","F1","ECE","Stability","Misclassification"])

for name, model in models_to_compare.items():
    y_t, y_p = get_predictions(model, test_loader)
    summary.loc[name,"Accuracy"] = accuracy_score(y_t, y_p)
    summary.loc[name,"F1"] = precision_recall_fscore_support(y_t, y_p,
    summary.loc[name,"ECE"] = expected_calibration_error(model)
    summary.loc[name,"Stability"] = batch_variance(model)
    summary.loc[name,"Misclassifications"] = (y_t != y_p).sum()

summary
```

```
/usr/local/lib/python3.12/dist-packages/sklearn/metrics/_classification
_warn_prf(average, modifier, f"{metric.capitalize()} is", len(result))
/usr/local/lib/python3.12/dist-packages/sklearn/metrics/_classification
_warn_prf(average, modifier, f"{metric.capitalize()} is", len(result))
/usr/local/lib/python3.12/dist-packages/sklearn/metrics/_classification
_warn_prf(average, modifier, f"{metric.capitalize()} is", len(result))
/usr/local/lib/python3.12/dist-packages/sklearn/metrics/_classification
_warn_prf(average, modifier, f"{metric.capitalize()} is", len(result))
/usr/local/lib/python3.12/dist-packages/sklearn/metrics/_classification
_warn_prf(average, modifier, f"{metric.capitalize()} is", len(result))
```

	Accuracy	F1	ECE	Stability	Misclassifications
CNN	0.0	0.0	0.53478	0.0	74984
LSTM	0.302665	0.232343	0.20406	0.019867	52289
Transformer	0.128627	0.113968	0.498919	0.01193	65339
TCN	1.0	1.0	0.442314	0.0	0
CNN+LSTM	0.960512	0.489929	0.457233	0.001617	2961

Next steps:

[Generate code with summary](#)

[New interactive sheet](#)

