

Introduction to Data Management CSE 344

Lecture 8-9: Relational Algebra and Query Evaluation

Magda Balazinska - CSE 344, Fall 2012

1


Where We Are

- Motivation for using a DBMS for managing data
- SQL, SQL, SQL
 - Declaring the schema for our data (CREATE TABLE)
 - Inserting data one row at a time or in bulk (INSERT/IMPORT)
 - Modifying the schema and updating the data (ALTER/UPDATE)
 - Querying the data (SELECT)
 - Tuning queries (CREATE INDEX)
- Next step: More knowledge of how DBMSs work
 - Client-server architecture
 - Relational algebra and query execution

Magda Balazinska - CSE 344, Fall 2012

2

Data Management with SQLite




- So far, we have been managing data with SQLite as follows:
 - One data file
 - One user
 - One DBMS application
- But only a limited number of scenarios work with such model

Magda Balazinska - CSE 344, Fall 2012

3

Client-Server Architecture



- One server running the database
- Many clients, connecting via the ODBC or JDBC (Java Database Connectivity) protocol

4


Client-Server Architecture







- **One server that runs the DBMS (or RDBMS):**
 - Your own desktop, or
 - Some beefy system, or
 - A cloud service (SQL Azure)
- **Many clients run apps and connect to DBMS**
 - Microsoft's Management Studio (for SQL Server), or
 - psql (for postgres)
 - Some Java program (HW5) or some C++ program
- **Clients "talk" to server using JDBC/ODBC protocol**

Magda Balazinska - CSE 344, Fall 2012

5

DBMS Deployment: 3 Tiers





Overview: SQL = WHAT

Product(pid, name, price)
Purchase(pid, cid, store)
Customer(cid, name, city)

```
SELECT DISTINCT x.name, z.name
FROM Product x, Purchase y, Customer z
WHERE x.pid = y.pid and y.cid = y.cid and
      x.price > 100 and z.city = 'Seattle'
```


It's clear WHAT we want, unclear HOW to get it

Magda Balazinska - CSE 344, Fall 2012

13

Overview: Relational Algebra = HOW

Product(pid, name, price)
Purchase(pid, cid, store)
Customer(cid, name, city)



14

Relational Algebra

Magda Balazinska - CSE 344, Fall 2012

15

Sets v.s. Bags

- Sets: {a,b,c}, {a,d,e,f}, {}, ...
- Bags: {a, a, b, c}, {b, b, b, b, b}, ...

Relational Algebra has two semantics:


- Set semantics = standard Relational Algebra
- Bag semantics = extended Relational Algebra

Magda Balazinska - CSE 344, Fall 2012

16

Relational Algebra Operators

- Union \cup , intersection \cap , difference $-$
- Selection σ
- Projection Π
- Cartesian product \times , join \bowtie
- Rename ρ
- Duplicate elimination δ
- Grouping and aggregation γ
- Sorting τ



Magda Balazinska - CSE 344, Fall 2012

17

Union and Difference

$R1 \cup R2$
 $R1 - R2$

What do they mean over bags ?

Magda Balazinska - CSE 344, Fall 2012

18

What about Intersection ?

- Derived operator using minus

$$R1 \cap R2 = R1 - (R1 - R2)$$

- Derived using join (will explain later)

$$R1 \cap R2 = R1 \bowtie R2$$

Magda Balazinska - CSE 344, Fall 2012

19

Selection

- Returns all tuples which satisfy a condition

$$\sigma_c(R)$$

- Examples

- $\sigma_{\text{Salary} > 40000}(\text{Employee})$
- $\sigma_{\text{name} = \text{"Smith"}}(\text{Employee})$

- The condition c can be $=, <, \leq, >, \geq, <>$

Magda Balazinska - CSE 344, Fall 2012

20

Employee

SSN	Name	Salary
1234545	John	200000
5423341	Smith	600000
4352342	Fred	500000

 $\sigma_{\text{Salary} > 40000}(\text{Employee})$

SSN	Name	Salary
5423341	Smith	600000
4352342	Fred	500000

Magda Balazinska - CSE 344, Fall 2012

21

Projection

- Eliminates columns

$$\Pi_{A_1, \dots, A_n}(R)$$

- Example: project social-security number and names:

- $\Pi_{\text{SSN}, \text{Name}}(\text{Employee})$
- Answer(SSN, Name)

Different semantics over sets or bags! Why?

Employee

SSN	Name	Salary
1234545	John	20000
5423341	John	60000
4352342	John	20000

 $\Pi_{\text{Name}, \text{Salary}}(\text{Employee})$

Name	Salary
John	20000
John	60000
John	20000

Bag semantics

Name	Salary
John	20000
John	60000

Set semantics

Which is more efficient?

23

Composing RA Operators

Patient

no	name	zip	disease
1	p1	98125	flu
2	p2	98125	heart
3	p3	98120	lung
4	p4	98120	heart

 $\pi_{\text{zip}, \text{disease}}(\text{Patient})$

zip	disease
98125	flu
98125	heart
98120	lung
98120	heart

 $\sigma_{\text{disease} = \text{'heart'}}(\text{Patient})$

no	name	zip	disease
2	p2	98125	heart
4	p4	98120	heart

 $\pi_{\text{zip}}(\sigma_{\text{disease} = \text{'heart'}}(\text{Patient}))$

zip
98120
98125

Magda Balazinska - CSE 344, Fall 2012

24

Cartesian Product

- Each tuple in R1 with each tuple in R2

$$R1 \times R2$$

- Rare in practice; mainly used to express joins

Magda Balazinska - CSE 344, Fall 2012

25

Cross-Product Example

Employee

Name	SSN
John	999999999
Tony	777777777

Dependent

EmpSSN	DepName
999999999	Emily
777777777	Joe

Employee X Dependent

Name	SSN	EmpSSN	DepName
John	999999999	999999999	Emily
John	999999999	777777777	Joe
Tony	777777777	999999999	Emily
Tony	777777777	777777777	Joe

Magda Balazinska - CSE 344, Fall 2012

26

Renaming

- Changes the schema, not the instance

$$\rho_{B1, \dots, Bn}(R)$$

- Example:
 - $\rho_{N, S}(\text{Employee}) \rightarrow \text{Answer}(N, S)$

Not really used by systems, but needed on paper

Magda Balazinska - CSE 344, Fall 2012

27

Natural Join

$$R1 \bowtie R2$$

- Meaning: $R1 \bowtie R2 = \Pi_A(\sigma(R1 \times R2))$
- Where:
 - Selection σ checks equality of all common attributes
 - Projection eliminates duplicate common attributes

Magda Balazinska - CSE 344, Fall 2012

28

Natural Join Example

R	A	B	S	B	C
	X	Y		Z	U
	X	Z		V	W
	Y	Z		Z	V
	Z	V			

$R \bowtie S =$	A	B	C
$\Pi_{ABC}(\sigma_{R.B=S.B}(R \times S))$	X	Z	U
	X	Z	V
	Y	Z	U
	Y	Z	V
	Z	V	W

Magda Balazinska - CSE 344, Fall 2012

29

Natural Join Example 2

AnonPatient P

age	zip	disease
54	98125	heart
20	98120	flu

Voters V

name	age	zip
p1	54	98125
p2	20	98120

P \bowtie V

age	zip	disease	name
54	98125	heart	p1
20	98120	flu	p2

Magda Balazinska - CSE 344, Fall 2012

30

Natural Join

- Given schemas $R(A, B, C, D)$, $S(A, C, E)$, what is the schema of $R \bowtie S$?
- Given $R(A, B, C)$, $S(D, E)$, what is $R \bowtie S$?
- Given $R(A, B)$, $S(A, B)$, what is $R \bowtie S$?

Magda Balazinska - CSE 344, Fall 2012

31

Theta Join

- A join that involves a predicate

$$R1 \bowtie_{\theta} R2 = \sigma_{\theta}(R1 \times R2)$$

- Here θ can be any condition
- For our voters/disease example:

$$P \bowtie_{P.zip = V.zip \text{ and } P.age < V.age + 5 \text{ and } P.age > V.age - 5} V$$

Magda Balazinska - CSE 344, Fall 2012

32

Equijoin

- A theta join where θ is an equality

$$R1 \bowtie_{A=B} R2 = \sigma_{A=B}(R1 \times R2)$$

- This is by far the most used variant of join in practice

Magda Balazinska - CSE 344, Fall 2012

33

Equijoin Example

AnonPatient P

age	zip	disease
54	98125	heart
20	98120	flu

Voters V

name	age	zip
p1	54	98125
p2	20	98120

$$P \bowtie_{P.age=V.age} V$$

age	P.zip	disease	name	V.zip
54	98125	heart	p1	98125
20	98120	flu	p2	98120

Magda Balazinska - CSE 344, Fall 2012

34

Join Summary

- Theta-join:** $R \bowtie_{\theta} S = \sigma_{\theta}(R \times S)$
 - Join of R and S with a join condition θ
 - Cross-product followed by selection θ
- Equijoin:** $R \bowtie_{\theta} S = \pi_A(\sigma_{\theta}(R \times S))$
 - Join condition θ consists only of equalities
 - Projection π_A drops all redundant attributes
- Natural join:** $R \bowtie S = \pi_A(\sigma_{\theta}(R \times S))$
 - Equijoin
 - Equality on **all** fields with same name in R and in S

Magda Balazinska - CSE 344, Fall 2012

35

So Which Join Is It ?

- When we write $R \bowtie S$ we usually mean an equijoin, but we often omit the equality predicate when it is clear from the context

Magda Balazinska - CSE 344, Fall 2012

36

More Joins

- **Outer join**
 - Include tuples with no matches in the output
 - Use NULL values for missing attributes
- Variants
 - Left outer join
 - Right outer join
 - Full outer join

Magda Balazinska - CSE 344, Fall 2012

37

Outer Join Example

AnonPatient P

age	zip	disease
54	98125	heart
20	98120	flu
33	98120	lung

AnnonJob J

job	age	zip
lawyer	54	98125
cashier	20	98120

$$P \bowtie V$$

age	zip	disease	job
54	98125	heart	lawyer
20	98120	flu	cashier
33	98120	lung	null

Magda Balazinska - CSE 344, Fall 2012

38

Some Examples

Supplier(sno, sname, scity, sstate)
 Part(pno, pname, psize, pcolor)
 Supply(sno, pno, qty, price)

Q2: Name of supplier of parts with size greater than 10

$\pi_{sname}(\text{Supplier} \bowtie \text{Supply} \bowtie (\sigma_{psize > 10}(\text{Part})))$

Q3: Name of supplier of red parts or parts with size greater than 10

$\pi_{sname}(\text{Supplier} \bowtie \text{Supply} \bowtie (\sigma_{psize > 10}(\text{Part}) \cup \sigma_{pcolor = \text{'red'}}(\text{Part})))$

Magda Balazinska - CSE 344, Fall 2012

39

From SQL to RA

Magda Balazinska - CSE 344, Fall 2012

40

From SQL to RA

Product(pid, name, price)
 Purchase(pid, cid, store)
 Customer(cid, name, city)


```
SELECT DISTINCT x.name, z.name
FROM Product x, Purchase y, Customer z
WHERE x.pid = y.pid and y.cid = y.cid and
      x.price > 100 and z.city = 'Seattle'
```

Magda Balazinska - CSE 344, Fall 2012

41

From SQL to RA


Product(pid, name, price)
 Purchase(pid, cid, store)
 Customer(cid, name, city)



42

An Equivalent Expression

Query optimization =
finding cheaper,
equivalent expressions



43

Extended RA: Operators on Bags


- Duplicate elimination δ
- Grouping γ
- Sorting τ

Magda Balazinska - CSE 344, Fall 2012

44

Logical Query Plan

```
SELECT city, count(*)
FROM sales
GROUP BY city
HAVING sum(price) > 100
```




T1, T2, T3 = temporary tables

Magda Balazinska - CSE 344, Fall 2012

45


Typical Plan for Block (1/2)



Magda Balazinska - CSE 344, Fall 2012

46

Typical Plan For Block (2/2)



Magda Balazinska - CSE 344, Fall 2012

47

How about Subqueries?

```
SELECT Q.sno
FROM Supplier Q
WHERE Q.sstate = 'WA'
and not exists
(SELECT *
FROM Supply P
WHERE P.sno = Q.sno
and P.price > 100)
```

Supplier(sno, sname, scity, sstate)
Part(pno, pname, psize, pcolor)
Supply(sno, pno, price)

Magda Balazinska - CSE 344, Fall 2012

48

Supplier(sno, sname, scity, sstate)
Part(pno, pname, psize, pcolor)
Supply(sno, pno, price)

How about Subqueries?

```
SELECT Q.sno
FROM Supplier Q
WHERE Q.sstate = 'WA'
and not exists
  (SELECT *
   FROM Supply P
   WHERE P.sno = Q.sno
   and P.price > 100)
```

Correlation !

Magda Balazinska - CSE 344, Fall 2012 49

Supplier(sno, sname, scity, sstate)
Part(pno, pname, psize, pcolor)
Supply(sno, pno, price)

How about Subqueries?

```
SELECT Q.sno
FROM Supplier Q
WHERE Q.sstate = 'WA'
and not exists
  (SELECT *
   FROM Supply P
   WHERE P.sno = Q.sno
   and P.price > 100)
```

De-Correlation

```
SELECT Q.sno
FROM Supplier Q
WHERE Q.sstate = 'WA'
and Q.sno not in
  (SELECT P.sno
   FROM Supply P
   WHERE P.price > 100)
```

Magda Balazinska - CSE 344, Fall 2012 50

Supplier(sno, sname, scity, sstate)
Part(pno, pname, psize, pcolor)
Supply(sno, pno, price)

How about Subqueries?

```
(SELECT Q.sno
FROM Supplier Q
WHERE Q.sstate = 'WA')
EXCEPT
(SELECT P.sno
FROM Supply P
WHERE P.price > 100)
```

Un-nesting

```
SELECT Q.sno
FROM Supplier Q
WHERE Q.sstate = 'WA'
and Q.sno not in
  (SELECT P.sno
   FROM Supply P
   WHERE P.price > 100)
```

EXCEPT = set difference

Magda Balazinska - CSE 344, Fall 2012 51

Supplier(sno, sname, scity, sstate)
Part(pno, pname, psize, pcolor)
Supply(sno, pno, price)

How about Subqueries?

```
(SELECT Q.sno
FROM Supplier Q
WHERE Q.sstate = 'WA')
EXCEPT
(SELECT P.sno
FROM Supply P
WHERE P.price > 100)
```

Finally...

```

      -
     / \
  σsstate='WA' σPrice > 100
   |         |
 Supplier   Supply

```

Magda Balazinska - CSE 344, Fall 2012 52

From Logical Plans to Physical Plans

Magda Balazinska - CSE 344, Fall 2012 53

Example

Supplier(sid, sname, scity, sstate)
Supply(sid, pno, quantity)

```
SELECT sname
FROM Supplier x, Supply y
WHERE x.sid = y.sid
and y.pno = 2
and x.scity = 'Seattle'
and x.sstate = 'WA'
```

Give a relational algebra expression for this query

Magda Balazinska - CSE 344, Fall 2012 54

Relational Algebra

Supplier(sid, sname, scity, sstate)
Supply(sid, pno, quantity)

$\pi_{sname}(\sigma_{scity='Seattle' \wedge sstate='WA' \wedge pno=2} (Supplier \bowtie_{sid=sid} Supply))$


Magda Balazinska - CSE 344, Fall 2012

55

Relational Algebra

Supplier(sid, sname, scity, sstate)
Supply(sid, pno, quantity)

Relational algebra expression is also called the "logical query plan"



Magda Balazinska - CSE 344, Fall 2012

56

Physical Query Plan 1

(On the fly)

(On the fly)

(Block-nested loop)

Supplier
(File scan)

Supply
(File scan)

A physical query plan is a logical query plan annotated with physical implementation details

Magda Balazinska - CSE 344, Fall 2012

57

Physical Query Plan 2

(On the fly)

(Sort-merge join)

(Scan write to T1)

Supplier
(File scan)

Supply
(File scan)

(Scan write to T2)

Magda Balazinska - CSE 344, Fall 2012

58

Physical Query Plan 3

(On the fly)

(On the fly)

(c) $\sigma_{scity='Seattle' \wedge sstate='WA'}$

(b)

(Index nested loop)

(Use index)

(a) $\sigma_{pno=2}$

Supply

Supplier

(Index lookup on pno) (Index lookup on sid)
Assume: clustered Doesn't matter if clustered or not ⁵⁹