

Introduction to Data Management CSE 344

Lecture 12: XML and XPath

Magda Balazinska - CSE 344, Fall 2012

1

What We Have Learned So Far

- A LOT about the relational model
 - Hands on experience using a relational DBMS
 - From basic to pretty advanced SQL queries
 - Some theory: datalog and relational calculus
 - A bit about internals:
 - Relational algebra
 - Physical query plans
 - High-level overview of the query optimizer
 - Physical tuning

Magda Balazinska - CSE 344, Fall 2012

2

Where We are Going Next

- Semi-structured data model and XML
 - A very different way to manage data

Magda Balazinska - CSE 344, Fall 2012

3

XML Outline

- What is XML?
- Syntax
- Semistructured data
- DTDs
- XPath

Magda Balazinska - CSE 344, Fall 2012

4

What is XML?

- Stands for eXtensible Markup Language
 1. Advanced, **self-describing file format**
 2. Based on a flexible, **semi-structured data model**
- Applications:
 - Data exchange
 - Storing data without a rigid schema: advertisements
 - Configuration files: e.g. Web.Config
 - Document markup: e.g. XHTML

We will study only XML as data

5


XML vs Relational

- Relational data model
 - Rigid flat structure (tables)
 - Schema must be fixed in advance
 - Binary representation: good for performance, bad for exchange
 - Query language based on Relational Calculus
- Semistructured data model / XML
 - Flexible, nested structure (trees)
 - Does not require predefined schema ("self describing")
 - Text representation: good for exchange, bad for performance
 - Query language borrows from automata theory

Magda Balazinska - CSE 344, Fall 2012

6

From HTML to XML



HTML describes the presentation

Magda Balazinska - CSE 344, Fall 2012

7

HTML

```
<h1> Bibliography </h1>
<p> <i> Foundations of Databases </i>
    Abiteboul, Hull, Vianu
    <br> Addison Wesley, 1995
<p> <i> Data on the Web </i>
    Abiteboul, Buneman, Suciu
    <br> Morgan Kaufmann, 1999
```

HTML describes the presentation

Magda Balazinska - CSE 344, Fall 2012

8

XML Syntax

```
<bibliography>
  <book>
    <title> Foundations... </title>
    <author> Abiteboul </author>
    <author> Hull </author>
    <author> Vianu </author>
    <publisher> Addison Wesley </publisher>
    <year> 1995 </year>
  </book>
  ...
</bibliography>
```

XML describes the content

9

XML Terminology

- Tags: **book**, **title**, **author**, ...
- Start tag: **<book>**, end tag: **</book>**
- Elements: **<book>...</book>**, **<author>...</author>**
- Elements are nested
- Empty element: **<red></red>** abbrev. **<red/>**
- An XML document: single *root element*

Well formed XML document

- Has matching tags
- A short header
- And a root element

10

Well-Formed XML

```
<? xml version="1.0" encoding="utf-8" standalone="yes" ?>
<SomeTag>
  ...
</SomeTag>
```

Magda Balazinska - CSE 344, Fall 2012

11

More XML: Attributes

```
<book price = "55" currency = "USD">
  <title> Foundations of Databases </title>
  <author> Abiteboul </author>
  ...
  <year> 1995 </year>
</book>
```

Magda Balazinska - CSE 344, Fall 2012

12

Attributes v.s. Elements

```
<book price = "55" currency = "USD">
  <title> Foundations of DBs </title>
  <author> Abiteboul </author>
  ...
  <year> 1995 </year>
</book>
```

```
<book>
  <title> Foundations of DBs </title>
  <author> Abiteboul </author>
  ...
  <year> 1995 </year>
  <price> 55 </price>
  <currency> USD </currency>
</book>
```

Attributes are alternative ways to represent data

Magda Balazinska - CSE 344, Fall 2012

13

Comparison


Elements	Attributes
Ordered	Unordered
May be repeated	Must be unique
May be nested	Must be atomic

Magda Balazinska - CSE 344, Fall 2012

14

XML Semantics: a Tree !

```
<data>
  <person id="o555">
    <name> Mary </name>
    <address>
      <street>Maple</street>
      <no> 345 </no>
      <city> Seattle </city>
    </address>
  </person>
  <person>
    <name> John </name>
    <address>Thailand</address>
    <phone>23456</phone>
  </person>
</data>
```



Order matters !!!

15

XML Data

- XML is **self-describing**
- Schema elements become part of the data
 - Relational schema: `person(name,phone)`
 - In XML `<person>`, `<name>`, `<phone>` are part of the data, and are repeated many times
- Consequence: XML is much more flexible
- XML = **semistructured** data

Magda Balazinska - CSE 344, Fall 2012

16


Mapping Relational Data to XML Data

The canonical mapping:

Person

Name	Phone
John	3634
Sue	6343
Dick	6363

XML:



Magda Balazinska - CSE 344, Fall 2012

17

Mapping Relational Data to XML Data

Application specific mapping

Person

Name	Phone
John	3634
Sue	6343

Orders

PersonName	Date	Product
John	2002	Gizmo
John	2004	Gadget
Sue	2002	Gadget

XML

```
<people>
  <person>
    <name> John </name>
    <phone> 3634 </phone>
    <order>
      <date> 2002 </date>
      <product> Gizmo </product>
    </order>
    <order>
      <date> 2004 </date>
      <product> Gadget </product>
    </order>
  </person>
  <person>
    <name> Sue </name>
    <phone> 6343 </phone>
    <order>
      <date> 2004 </date>
      <product> Gadget </product>
    </order>
  </person>
</people>
```

XML=Semi-structured Data (1/3)

- Missing attributes:

```
<person> <name> John</name>
<phone>1234</phone>
</person>

<person> <name>Joe</name>
</person>
```

no phone !

- Could represent in a table with nulls

name	phone
John	1234
Joe	-

Magda Balazinska - CSE 344, Fall 2012

19

XML=Semi-structured Data (2/3)

- Repeated attributes

```
<person> <name> Mary</name>
<phone>2345</phone>
<phone>3456</phone>
</person>
```

Two phones !

- Impossible in tables:

name	phone		
Mary	2345	3456	???

Magda Balazinska - CSE 344, Fall 2012

20

XML=Semi-structured Data (3/3)

- Attributes with different types in different objects

```
<person> <name> <first> John </first>
<last> Smith </last>
</name>
<phone>1234</phone>
</person>
```

Structured name !

- Nested collections
- Heterogeneous collections:
 - <db> contains both <book>s and <publisher>s

Magda Balazinska - CSE 344, Fall 2012

21

Schema

Magda Balazinska - CSE 344, Fall 2012

22

Document Type Definitions (DTD)

- An XML document may have a DTD
- XML document:
 - Well-formed** = if tags are correctly closed
 - Valid** = if it has a DTD and conforms to it
- Validation is useful in data exchange
- Use <http://validator.w3.org/check> to validate
- Superseded by XML Schema (Book Sec. 11.4)
- Very complex: DTDs still used widely

Magda Balazinska - CSE 344, Fall 2012

23

Example DTD

```
<!DOCTYPE company [
  <!ELEMENT company ((person|product)*)>
  <!ELEMENT person (ssn, name, office, phone?)>
  <!ELEMENT ssn (#PCDATA)>
  <!ELEMENT name (#PCDATA)>
  <!ELEMENT office (#PCDATA)>
  <!ELEMENT phone (#PCDATA)>
  <!ELEMENT product (pid, name, description?)>
  <!ELEMENT pid (#PCDATA)>
  <!ELEMENT description (#PCDATA)>
]>
```

Magda Balazinska - CSE 344, Fall 2012

24

Example DTD

Example of valid XML document:

```
<company>
  <person> <ssn> 123456789 </ssn>
    <name> John </name>
    <office> B432 </office>
    <phone> 1234 </phone>
  </person>
  <person> <ssn> 987654321 </ssn>
    <name> Jim </name>
    <office> B123 </office>
  </person>
  <product> ... </product>
  ...
</company>
```

Magda Balazinska - CSE 344, Fall 2012

25

DTD: The Content Model

`<ELEMENT tag (CONTENT)>`


content model

- Content model:
 - Complex = a regular expression over other elements
 - Text-only = `#PCDATA`
 - Empty = `EMPTY`
 - Any = `ANY`
 - Mixed content = `(#PCDATA | A | B | C)*`

Magda Balazinska - CSE 344, Fall 2012

26

DTD: Complex Content



27

DTD: Attributes

From "sample-xml-with-dtd.xml"

```
<!DOCTYPE bib [
  <ELEMENT bib (book* )>
  <ELEMENT book (title, (author+ | editor+ ), publisher?, price )>
  <ATTLIST book year CDATA #REQUIRED >
  ...
]>

<bib>
  <book year="1994">
```

Magda Balazinska - CSE 344, Fall 2012

28

DTD: Text

Two options:

- `#PCDATA` ("Parsed Character Data") = the text inside elements
- `CDATA` ("Character Data") = the text inside attributes
- There is no `#CDATA` and no `PCDATA`

Magda Balazinska - CSE 344, Fall 2012

29

Querying

Magda Balazinska - CSE 344, Fall 2012

30

Querying XML Data

- **XPath** = simple navigation → today
- **XQuery** = the SQL of XML → Friday
- **XSLT** = recursive traversal
 - will not discuss in class

Magda Balazinska - CSE 344, Fall 2012

31

Sample Data for Queries

```


<bib>
  <book>
    <publisher> Addison-Wesley </publisher>
    <author> Serge Abiteboul </author>
    <author>
      <first-name> Rick </first-name>
      <last-name> Hull </last-name>
    </author>
    <author> Victor Vianu </author>
    <title> Foundations of Databases </title>
    <year> 1995 </year>
  </book>
  <book price="55">
    <publisher> Freeman </publisher>
    <author> Jeffrey D. Ullman </author>
    <title> Principles of Database and Knowledge Base Systems </title>
    <year> 1998 </year>
  </book>
</bib>

```

Data Model for XPath

XPath returns a sequence of items. An item is either:

- A value of primitive type, or
- A node (doc, element, or attribute)



33

XPath: Simple Expressions

`/bib/book/year`

Result: `<year> 1995 </year>`
`<year> 1998 </year>`

`/bib/paper/year`

Result: empty (there were no papers)

`/bib`

What's the difference ?

Magda Balazinska - CSE 344, Fall 2012

34

XPath: Restricted Kleene Closure

`//author`

Result: `<author> Serge Abiteboul </author>`
`<author> <first-name> Rick </first-name>`
`<last-name> Hull </last-name>`
`</author>`
`<author> Victor Vianu </author>`
`<author> Jeffrey D. Ullman </author>`

`/bib/first-name`

Result: `<first-name> Rick </first-name>`

Magda Balazinska - CSE 344, Fall 2012

35

XPath: Attribute Nodes

`/bib/book/@price`

Result: "55"

@price means that price has to be an attribute

Magda Balazinska - CSE 344, Fall 2012

36

XPath: Wildcard

`//author/*`

Result: `<first-name> Rick </first-name>`
`<last-name> Hull </last-name>`

- * Matches any element
- @* Matches any attribute

Magda Balazinska - CSE 344, Fall 2012

37

XPath: Text Nodes

`/bib/book/author/text()`

Result: Serge Abiteboul
 Victor Vianu
 Jeffrey D. Ullman

Rick Hull doesn't appear because he has `first-name`, `last-name`

Functions in XPath:

- `text()` = matches the text value
- `node()` = matches any node (= * or @* or `text()`)
- `name()` = returns the name of the current tag

Magda Balazinska - CSE 344, Fall 2012

38

XPath: Predicates

`/bib/book/author[first-name]`

Result: `<author> <first-name> Rick </first-name>`
`<last-name> Hull </last-name>`
`</author>`

Magda Balazinska - CSE 344, Fall 2012

39

XPath: More Predicates

`/bib/book/author[first-name][address[//zip][city]]/last-name`

Result: `<last-name> ... </last-name>`
`<last-name> ... </last-name>`

How do we read this ?

First remove all qualifiers (predicates):

`/bib/book/author/last-name`

Then add them one by one:

`/bib/book/author[first-name][address]/last-name`

Magda Balazinska - CSE 344, Fall 2012

40

XPath: More Predicates

`/bib/book[@price < 60]`

`/bib/book[author/@age < 25]`

`/bib/book[author/text()]`

Magda Balazinska - CSE 344, Fall 2012

41

XPath: Position Predicates

`/bib/book[2]`

The 2nd book

`/bib/book[last()]`

The last book

`/bib/book[@year = 1998] [2]`

The 2nd of all books in 1998

`/bib/book[2][@year = 1998]`

2nd book IF it is in 1998

Magda Balazinska - CSE 344, Fall 2012

42

XPath: More Axes

. means *current node* `/bib/book[./review]`

`/bib/book[./review]` Same as `/bib/book[review]`

`/bib/author/. /first-name` Same as `/bib/author/first-name`

Magda Balazinska - CSE 344, Fall 2012

43

XPath: More Axes

.. means *parent node*

`/bib/author/.. /author/zip` Same as `/bib/author/zip`

`/bib/book[./review/.. /comments]`

Same as

`/bib/book[./review/.. /comments][review]`

Hint: don't use ..

Magda Balazinska - CSE 344, Fall 2012

44

A Few Extra Examples

Run these examples on the sample xml posted on course website
Follow hw4 instructions

Each line is a separate example:

```
doc("sample-xml.xml")/book/price
doc("sample-xml.xml")/book[editor]/price
doc("sample-xml.xml")/book[price/text() > 100]/title
```

Magda Balazinska - CSE 344, Fall 2012

45

XPath: Summary

<code>bib</code>	matches a <code>bib</code> element
<code>*</code>	matches any element
<code>/</code>	matches the <code>root</code> element
<code>/bib</code>	matches a <code>bib</code> element under <code>root</code>
<code>bib/paper</code>	matches a <code>paper</code> in <code>bib</code>
<code>bib//paper</code>	matches a <code>paper</code> in <code>bib</code> , at any depth
<code>//paper</code>	matches a <code>paper</code> at any depth
<code>paper book</code>	matches a <code>paper</code> or a <code>book</code>
<code>@price</code>	matches a <code>price</code> attribute
<code>bib/book/@price</code>	matches <code>price</code> attribute in <code>book</code> , in <code>bib</code>
<code>bib/book[@price<"55"]/author/last-name</code>	matches...
<code>bib/book[@price<"55" or @price>"99"]/author/last-name</code>	matches...

Magda Balazinska - CSE 344, Fall 2012

46