

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158

```
C**AGBKG
C Continuum Dynamics, Inc.
C AGDISP Version 8.29 06/16/16
C
C SUBROUTINE AGBKG(XV,DV,T)
C
C AGBKG evaluates the background at every drop location
C
C XV - Array of current locations, velocities, etc.
C DV - Array of background information (determined here)
C T - Time
C
C DIMENSION XV(9,2),DV(6,2)
C
C INCLUDE 'AGCOMMON.INC'
C
C DATA UXI,UVI / 0.0 , 0.0 /
C
C DATA AEVAP,BEVAP / 0.240 , 0.240 /
C
C Loop for all drops - Actually for all nozzle positions
C
C VMAX=0.1
C DO I=1,NVAR
C IF (ISW(I).NE.0) THEN
C X=XO+XV(1,I)
C Y=XV(2,I)
C Z=XV(3,I)
C
C Determine mean velocity at the drop position
C CALL AGVEL(X,Y,Z,U,V,W)
C VMAX=AMAX1(VMAX,
C $ SQRT(ABS(XV(5,I)**2+XV(6,I)**2)),SQRT(ABS(V*V+W*W)))
C
C Determine decay constant
C VREL=SQRT(ABS((XV(4,I)-U)**2+(XV(5,I)-V)**2+(XV(6,I)-W)**2))
C
C Time decay evaluation
C D=EDOV(I)
C DENC=((D**3-DCUT**3)*DENF+DCUT**3*DENN)/D**3
C DTAU=3.12E-06*D*DENC
C ETAU=0.0 !PROTECT FOR DRY EVAPORATION AND CALPUFF
C REYNO=0.0688*D*VREL
C IF (VREL.GT.0.0) THEN
C IF (LDRY.EQ.0) THEN
C DTAU=DTAU/(1.0+0.197*REYNO**0.63+0.00026*REYNO**1.38)
C ELSE
C DTAU=DTAU/(1.0+APSPH*REYNO**BPSPH+CPSPH*REYNO/
C $ (1.0+DPSPH/REYNO))
C ENDIF
C ENDIF
C IF (LEVAP.NE.0) THEN
C IF (D.GT.DCUT) THEN
C EFAC=0.5+0.25*AMIN1(REYNO,2.0)
C DTEM=DTEMP
C IF (LCANF.GT.0.AND.Z.LE.HCAN) DTEM=DTEM
C ETAU=D*D/ETEM/ERATE/EFAC
C IF (VREL.GT.0.0) ETAU=ETAU/(1.0+0.27*SQRT(REYNO))
C DT=AMIN1(DT,0.002*ETAU)
C IF (LSPFLG.EQ.1) THEN
C CALL AGDISPcalcEvaporation(D,VREL,DCUT,DT,EDNV(I))
C ELSE
C IF (ETAU.EQ.0.0) THEN
C EDNV(I)=DCUT
C ELSE
C EDNV(I)=D*SQRT(AMAX1(1.0-DT/ETAU,(DCUT/DIAM)**2))
C ETAUN=DIAM*DIAM/DTEM/ERATE/EFAC
C IF (VREL.GT.0.0) ETAUN=ETAUN/(1.0+0.27*SQRT(REYNO))
C TEM=T/ETAUN
C TEM=AEVAP*TEM*(1.0+BEVAP*TEM)
C EDNV(I)=DIAM*SQRT(AMAX1(1.0-TEM,(DCUT/DIAM)**2))
C ENDIF
C ETAU=ETAUN !PROTECT FOR CALPUFF OUTPUT
C ENDIF
C ENDIF
C ENDIF
C ENDIF
C
C Scale length
C SL=0.65*Z
C QQ=0.0
C IF (NVOR.GT.0) THEN
C DO N=1,NVOR
C R=SQRT(ABS((Y-YBAR(N))**2+(Z-ZBAR(N))**2))
C SL=AMIN1(SL,0.6*R)
C R=SQRT(ABS((Y-YBAL(N))**2+(Z-ZBAL(N))**2))
C SL=AMIN1(SL,0.6*R)
C ENDDO
C ENDIF
C IF (SL.EQ.0.0) GOTO 10
C
C Turbulence
C IF (LMCRS.EQ.1) THEN
C QQ=QQMX
C ELSE
C QQ=AGINT(NWIND,WINDHTV,WINDQV,Z)
C ENDIF
C IF (LCANF.GT.0) THEN
C IF (Z.LE.HCAN) THEN
C QQ=QQMC*Z*Z*EXP(2.0*ALPHAC*(Z/HCAN-1.0))
C ELSE
C QQ=QQMX*(Z/(Z/HCAN-DOC+ZOC))**2
C ENDIF
C ENDIF
C IF (NPRP.NE.0) THEN
C DO N=1,NPRP
C R=SQRT(ABS((Y-YPRP(N))**2+(Z-ZPRP(N))**2))
C E=15.174*R/CPXI(N)
C UA=11.785*CPUR/CPXI(N)/(1.0+0.25*E*E)**2
C QQ=QQ+0.2034*UA*UA
C ENDDO
C ENDIF
C
C Determine analytic turbulent correlations with the droplet
C IF (QQ.NE.0.0) THEN
C WTAU=SL/(VREL+0.375*SQRT(QQ))
C C=T/WTAU
C EXPC=EXP(-AMIN1(C,25.0))
C EXPT=0.0
C IF (D.GT.0.0) EXPT=EXP(-AMIN1(T/DTAU,25.0))
C B=(DTAU/WTAU)**2
C IF (ABS(B-1.0).GT.0.01) THEN
C SUM1=0.5*(3.0-B)/(B-1.0)**2
C SUM2=0.5/(B-1.0)
C XK1=SUM1*(1.0-DTAU/WTAU)+SUM2
C XK2=SUM1*(EXPC-EXPT*DTAU/WTAU)+SUM2*EXPC*(1.0+C)
C XK3=SUM1*(EXPC-EXPT)+SUM2*EXPC*C
C ELSE
C XK1=0.375
C XK2=(3.0+3.0*C-C*C)*EXPC/8.0
C XK3=(5.0-C)*C*EXPC/8.0
C ENDIF
C XK4=0.5*(1.0+EXPC*(C-1.0))
C UXI=-DTAU*XK1+DTAU*EXPT*(XK2-XK3*DTAU/WTAU)+WTAU*XK4
C UVI=XK1-EXPT*(XK2-XK3*DTAU/WTAU)
C ENDIF
C
C Evaluate background parameters
C DV(1,I)=DTAU
C DV(2,I)=U
C DV(3,I)=V
C IF (LMVEL.EQ.0) THEN
C DV(4,I)=0.0
C ELSE
C DV(4,I)=W
C ENDIF
C DV(5,I)=UXI*QQ/3.0
C DV(6,I)=UVI*QQ/3.0
C ENDIF
C ENDDO
C RETURN
C END
```

10

ISW → 1 = Active droplet above surface
0 = Drop hits, penetrates
-1 = 4 sides below surface and finish

1st (211)

3.12x10⁻⁶?

Is not vrel always > 0?

55-79 Evaporation

Ignore for now.

How to do this in Python?

LCANF default = 0 Canopy Type
0 = none
1 = optical
1 = short

109-116
Only if not grand sprayer
why 15.174, 11.785, 0.2034, etc...?

0.375? Find in documentation and add code

why 25?

0.375?

5 = 8?