

Running the JGI Integration Workflow

Overview

The general stages of the workflow are:

- Loading and normalizing multi-omics datasets (e.g., transcriptomics and metabolomics)
- Integrating data (quantitative values) and metadata (sample info) between datasets
- Selecting features for analysis via statistical tests
- Building and visualizing a correlation network of integrated features
- Running multi-omics factor analysis

Note: This tutorial assumes you've already completed all stages of the workflow and environment setup detailed in *setup.pdf*.

Running the Notebook

1. You should see the JupyterLab interface rendered in your browser tab.
2. Double-click the workflow notebook `/integration_workflow.ipynb` in the left menu navigator to bring it into the workspace.
3. Double-click the configuration file in `/input_data/config/project_config.yml` to bring it into the workspace
4. Begin a workflow with all default parameters:
 - A. Ensure that the kernel is “JGI Integration” by checking the top right corner of the workspace. If not, click the kernel name and select “JGI Integration” from the dropdown menu.
 - B. Run all notebook cells in order, either with the “play” button in the top menu bar or with the keyboard shortcut in each cell (ctrl/cmd/shift-click).
 - C. Each cell performs a workflow step (data loading, normalization, integration, correlation analysis, etc.) and prints some information to the standard output for review.
 - D. Review the cell print statements to see where plots and tables are saved to the `/output_data` directory; some key results or previews are also displayed in the notebook.

Note: At any time, instead of looking through the `/output_data` directory, you can access and view the attributes of a dataset or analysis by creating a new cell and executing the command `<object>.<attribute>`. For example, running a cell with `tx_dataset.normalized_data` will show the transcriptomics count table after all dataset normalization steps, or `mx_dataset.linked_metadata` will show the metabolomics metadata table after it has been linked to the other datasets. To see all the possible attributes that you can view for each object, run a cell with the command

```
vars(<object>).keys(). For example, vars(analysis).keys() or  
vars(mx_dataset).keys().
```

5. Run a workflow with customized parameters:

- A. Update parameters in the `/input_data/config/project_config.yml` file (in the JupyterLab interface) using the guides provided in the `/jgi_integration/docs/*_parameters_explained.md` files.
- B. This will create a new parameter set to run the dataset processing and analysis stages on – make sure to change the `data_processing_tag` and/or `data_analysis_tag` in the config to create a new output directory to store the results and keep them distinct from previous runs.
- C. Rerun the notebook as described above from the beginning to re-load the updated configuration settings and run the full workflow.