Feature

⇒ Return Search Results.

	Rahul (10^5)	Raj (10^3)
Execution time	15 sec	10 sec
↓	windows XP	macbook pro m2 chip
	8 sec	10 sec
↓	C++	python
	8 sec	5 sec
↓	volcano	antarctica.

Execution time is not the right metric to compare algorithms.

Akhil	Mayank.
$100 \log_{10} n$	$N/10$

$n \leq 3500$, $N/10$ (Mayank) is better.
$n > 3500$, $100 \log_{10} n$ (Akhil) is better.

Ind vs Pak : 1.8 million ⇏ 18 lakh.
Generally > 1cr.

Youtube video : usually > 1 million.

⇏ Algo 1, Algo 2, Algo 3, Algo 4.

Asymptotic Analysis of Algorithms

↳ Analysing algorithms for large input.



Iteration ⇒ $f(n)$ = ——

n^2 + Big ⇒ $g(n)$ = ( )

$c\,g(n) > f(n)$



ass[ ] , (2)

(n)

```
for (int i=0 ; i<n ; i++) {
    if (ass[i] == 12)
        return true;
}
return false;
```

Calculate Big O

1) Find the number of iteration
2) Ignore lower order terms.

∴ no of iterations $= 100n + n^2$

n	value	Contribution of 100n
10	1000 + 100	90%
100	10000 + 10000	50%
10^5	$10^7 + 10^{10}$	$< 0.1\%$

Ignore Constants

Manoj	Pooja	For large input
n	$100 \log n$	Pooja
$10n$	$\frac{n^2}{100}$	Manoj
$N \log N$	$1000 \log N$	Pooja.
$10^{10} \log N$	$\frac{n}{10}$	Manoj

Issues in Big O

$n = 10$

Bhappu	Srinivas
$10^3 n$	n^2

According to Big O ⇒ Bhappu is better.

⇒ Bhappu algorithm is better for all input sizes ⇒ WRONG CLAIM.

n	$10^3 n$	n^2
10	10^4	100
100	10^5	10^4
1000	10^6	10^6

For $n \geq 1000$, Bhappu algorithm is better ⇒ CORRECT CLAIM.

Compare $10 \log N$ $10^5 \log N$.

Big O $\Rightarrow$ Both are same.

↓

Check the number of iterations.

Space Complexity

```
void func() {
    int x = 4;      ⇒ 4 bytes
    int y = 5;      ⇒ 4 bytes
    long z = 2L;    ⇒ 8 bytes.
}
```

⇒ 16 bytes. ⇒ O(1)

SC: O(1)

```
void func(int n) {
    int arr[n];     ⇒ 4n bytes.
    int y = 5;      ⇒ 4 bytes
    long z = 2L;    ⇒ 8 bytes.
}
```

⇒ 4n + 12

SC: O(n)

```
void fun ( int n) {
    int arr [n]          = 4n bytes.
    int arr-2 [n][n]     = 4n^2 bytes
    int x, y;            = 8 bytes
}
```

$\Rightarrow 4n^2 + 4n + 8$

SC : $O(n^2)$

```
void fun ( int arr[n])
    int x ;
    int y ;
}
```

$4n + 8$

$4n$ ↓ Input Space

8 ↓ Space created by algom.

Total Space $\Rightarrow$ Input Space + Space created by algo

$\Downarrow$

Space complexity

```
int max_num (int arr [], int n) {
    int max_ans = -1;
    for (int i=0; i<n; i++) {
        if (max_ans > arr[i])
            max_ans = arr(i);
    }
    return max_ans;
}
```

TLE ⇒ Time Limit Exceeded.

Execution time limit ⇒ 1 sec.

Processor Specs ⇒ 1 Ghz

⇒ 10^9 instructions per second.

Q Print all odd numbers till n.

```
void printOdd (int n) {
    for (int i=0 ; i<n ; i++) {
        if (i%2 != 0)
            print (i);
    }
}
```

iterations ⇒ n.

instruction per iteration ⇒ 5.

Total instructions ⇒ 5n.

Case 1 :

1 iteration $\simeq$ 10 instructions.

n iteration $\simeq$ 10n instructions.

Max number of iterations $\Rightarrow 10^8$

$10n \leq 10^9 \Rightarrow \boxed{n \leq 10^8}$

Case 2

1 iteration $\Rightarrow$ 100

Max number of iteration $\Rightarrow 10^7$

In general our code should have at max $[10^7, 10^8]$ iterations

Constraints

$1 \leq n \leq 10^5$

n^3
n^2
$n\sqrt{n}$
$n \log 10$
n
$\log n$
$\sqrt{n}$

Sol 1 : $O(n^2)$: $\simeq 10^{10}$

TLE

Sol 2 : $O(n)$ $\simeq 10^5$

Accepted

How to approach a problems

1) Read Question.
2) Read Constraints
3) Guess the Expected time Complexity.
4) Think in that direction.

$\Rightarrow$ Space $[10^6, 10^7]$ bytes

$n = 10^5$ `aa[n][n]` ✗

$n = 10^3$ `aa[n][n]` ✓

```
for (int i = 1, j = 1 ; j <= n ; i++) {
    print (i + j) ;
    if (i % n == 0)
        j++ ;
}
```

$n = 10$

$i = 1, 2, 3, 4 \ldots$

$\ldots 10$

j	i	Total
1	n	n
2	n	n
3	n	n
⋮	n	n
⋮	n	n
n	1	n

n^2

int arr[n]. — O(n).

⇒ logn

SC: O(n)

TC: O(logn)