

New Haven Media Stack Setup Guide

1. Unified Installation Script (install_media.sh)

Save this script on your LMDE 7 machine. This script sets up the directory structure and generates the Docker Compose configuration.

```
#!/bin/bash

# Setup Directories
mkdir -p ~/docker-media/config/{qbittorrent,sabnzbd,prowlarr,sonarr,rada
mkdir -p /data/media

# Create docker-compose.yml
cat < ~/docker-media/docker-compose.yml
services:
  gluetun:
    image: qmcgaw/gluetun:latest
    container_name: gluetun
    cap_add:
      - NET_ADMIN
    devices:
      - /dev/net/tun:/dev/net/tun
    environment:
      - VPN_SERVICE_PROVIDER=private internet access
      - OPENVPN_USER=YOUR_PIA_USERNAME
      - OPENVPN_PASSWORD=YOUR_PIA_PASSWORD
      - SERVER_REGIONS=SE Stockholm
    ports:
      - 8080:8080
      - 6881:6881
      - 6881:6881/udp
      - 8081:8080
    restart: unless-stopped
```

```
qbittorrent:
  image: lscr.io/linuxserver/qbittorrent:latest
  container_name: qbittorrent
  network_mode: "service:gluetun"
  environment:
    - PUID=1000
    - PGID=1000
    - WEBUI_PORT=8080
  volumes:
    - ./config/qbittorrent:/config
    - /data:/data
  healthcheck:
    test: ["CMD", "curl", "-f", "http://localhost:8080"]
    interval: 30s
    timeout: 10s
    retries: 5
    start_period: 40s
  depends_on:
    gluetun:
      condition: service_started
  restart: unless-stopped
```

```
sabnzbd:
  image: lscr.io/linuxserver/sabnzbd:latest
  container_name: sabnzbd
  network_mode: "service:gluetun"
  environment:
    - PUID=1000
    - PGID=1000
  volumes:
    - ./config/sabnzbd:/config
    - /data:/data
  healthcheck:
    test: ["CMD", "curl", "-f", "http://localhost:8080"]
    interval: 30s
    timeout: 10s
    retries: 5
```

```
    start_period: 40s
depends_on:
  gluetun:
    condition: service_started
restart: unless-stopped

prowlarr:
  image: lscr.io/linuxserver/prowlarr:latest
  container_name: prowlarr
  environment:
    - PUID=1000
    - PGID=1000
  volumes:
    - ./config/prowlarr:/config
  ports:
    - 9696:9696
  restart: unless-stopped

sonarr:
  image: lscr.io/linuxserver/sonarr:latest
  container_name: sonarr
  environment:
    - PUID=1000
    - PGID=1000
  volumes:
    - ./config/sonarr:/config
    - /data:/data
  ports:
    - 8989:8989
  restart: unless-stopped

radarr:
  image: lscr.io/linuxserver/radarr:latest
  container_name: radarr
  environment:
    - PUID=1000
    - PGID=1000
```

```
volumes:
  - ./config/radarr:/config
  - /data:/data
ports:
  - 7878:7878
restart: unless-stopped
```

```
readarr:
  image: binhex/arch-readarr:latest
  container_name: readarr
  environment:
    - PUID=1000
    - PGID=1000
  volumes:
    - ./config/readarr:/config
    - /data:/data
  ports:
    - 8787:8787
  restart: unless-stopped
```

```
lidarr:
  image: lscr.io/linuxserver/lidarr:latest
  container_name: lidarr
  environment:
    - PUID=1000
    - PGID=1000
  volumes:
    - ./config/lidarr:/config
    - /data:/data
  ports:
    - 8686:8686
  restart: unless-stopped
```

```
overseerr:
  image: lscr.io/linuxserver/overseerr:latest
  container_name: overseerr
  environment:
```

```
- PUID=1000
- PGID=1000
volumes:
  - ./config/overseerr:/config
ports:
  - 5055:5055
restart: unless-stopped

jellyfin:
  image: lscr.io/linuxserver/jellyfin:latest
  container_name: jellyfin
  environment:
    - PUID=1000
    - PGID=1000
  volumes:
    - ./config/jellyfin:/config
    - /data/media:/data/media
  ports:
    - 8096:8096
  restart: unless-stopped
EOF
echo "Setup complete!"
```

2. Execution Instructions

1. Create script: `nano install_media.sh` (paste code above, save/exit).
2. Make executable: `chmod +x install_media.sh`
3. Run script: `./install_media.sh`
4. Update credentials: `nano ~/docker-media/docker-compose.yml`
(Replace placeholders).
5. Launch stack: `cd ~/docker-media && sudo docker compose up -d`