

Media Server & VPN Stack

Interactive Deployment & Setup Guide

This guide outlines the use of the interactive Bash script designed to automate the deployment of a Docker Compose media server stack. It securely routes your traffic through a VPN using Gluetun, eliminating the need to manually edit configuration files.

Features

- **Interactive Setup:** Prompts users for VPN provider details and credentials during setup.
- **Secure Credential Handling:** Hides password input from the terminal and stores credentials safely in an `.env` file instead of hardcoding them into the Compose file.
- **Automated Generation:** Dynamically builds the `docker-compose.yml` file based on a pre-configured template.
- **One-Click Deployment:** Optionally starts the Docker stack immediately after configuration.

Included Services

The generated stack is pre-configured with the following services routed through the **Gluetun VPN** network:

- **Gluetun:** VPN Client (Network routing)
- **SABnzbd:** Usenet Client
- *Ready for expansion with Sonarr, Radarr, Prowlarr, Readarr, Lidarr, qBittorrent, and Jellyseerr.*

Prerequisites

Before running this script, ensure the host machine has the following installed and configured:

- **Docker:** The core containerization engine.
- **Docker Compose:** For orchestrating multi-container Docker applications.
- **VPN Subscription:** A valid subscription to a VPN provider supported by the Gluetun image.



Usage Instructions

Follow these steps to deploy your stack securely:

1. Prepare the Script

Ensure the script (`setup_media_server.sh`) is downloaded to your desired deployment directory. Then, make it executable:

```
chmod +x setup_media_server.sh
```

2. Run the Script

Execute the script to start the interactive configuration process:

```
./setup_media_server.sh
```

3. Follow the Prompts

Input Required: The script will pause and wait for your input.

- Enter your **VPN Service Provider** (e.g., `mullvad` , `nordvpn` , `surfshark`).
- Enter your **VPN Username**.
- Enter your **VPN Password** (Note: Your keystrokes will be hidden for security).
- Choose whether to deploy the stack immediately by typing `y` or `n` .



File Structure Post-Execution

After successfully running the script, your working directory will contain the following files:

- `setup_media_server.sh` - The original interactive deployment script.
- `.env` - Generated file containing your securely stored VPN credentials.
- `docker-compose.yml` - The generated Docker Compose configuration file tailored to your inputs.



Customization

If you wish to add more services to the stack (such as Sonarr or Radarr), you can modify the `cat <<'EOF' > docker-compose.yml` block inside the `setup_media_server.sh` script.

Crucial Rule: Make sure to include `network_mode: "service:gluetun"` for any new container that needs its internet traffic routed strictly behind the VPN.

 **Disclaimer:** Ensure you comply with your VPN provider's terms of service and local laws regarding media downloading and sharing.