

Sonarr Season Pruner

Automated Repository & Media Library Management Documentation

The **Sonarr Season Pruner** is an automated script designed to optimize your media library storage. It intelligently manages your disk usage by automatically pruning older seasons or permanently deleting entire series based on specific, customizable tags within your Sonarr environment.

Prerequisites

- **Docker** must be installed and properly configured on your host system.
- An active, operational **Sonarr** instance must be running and fully accessible across your network.

Setup Instructions

1. Configure Tags in Sonarr

To establish control over the script's decision engine, you must create and assign two specific tags within your Sonarr settings interface:

Tag Name	System Action & Behavior
no-prune	Ignore Safety: Any series assigned this tag will be completely bypassed and ignored by the execution engine, overriding global pruning logic.
delete-me	Hard Purge: Any series assigned this tag will be permanently deleted from the system, including all corresponding media files on your physical disk.

2. Environment Variables

The service relies securely on the following environment configurations to hook into your ecosystem:

- **SONARR_URL**: The absolute API/Web network address of your active Sonarr instance (e.g., `http://192.168.80.5:8989`).
- **SONARR_API_KEY**: Unique security token authentication credential found under Settings > General in your Sonarr dashboard.
- **DRY_RUN**: Safety toggle flag. Set to True for test evaluations (logs actions safely). Set to False to authorize live storage modifications and structural changes.

3. Docker Deployment

Integrate the orchestration block directly into your existing multi-container configuration by appending the service structure below into your main `docker-compose.yml` deployment file:

```
version: '3.8'

services:
  prune-service:
    image: prune-service
    container_name: prune-service
    network_mode: service:sonarr
    restart: unless-stopped
    environment:
      - SONARR_URL=http://192.168.80.5:8989
      - SONARR_API_KEY=your-api-key-here
      - DRY_RUN=True
    volumes:
      - /opt/arr-scripts/prune_seasons:/app
```

Deployment Note: Please make sure to adjust the container network stack configuration, base endpoint URLs, and security API string mappings to exactly mirror your local infrastructure environment variables.

Maintenance & Testing Operations

Safe Validation (Dry Run Testing)

It is strongly advised as a best practice to execute a manual evaluation run prior to permitting the deployment to handle live library mutations. With your variable parameter explicitly set to `DRY_RUN=True`, execute the containerized sequence directly:

```
sudo docker exec prune-service python3 /app/prune_seasons.py
```

Activating Live Execution Production

Once you have thoroughly verified the generated automation logs and confirmed that the targeting criteria matches your structural intentions, update the container settings to go live:

- Open your production `docker-compose.yml` block.
- Modify the environment directive parameter from `DRY_RUN=True` to `DRY_RUN=False`.
- Instruct the container engine to safely pull, recreate, and spin up your running process:

```
sudo docker compose up -d
```

License & Open Source Contributions

This project is maintained as an open-source tool. Community contributions, bug issue tracking, and feature expansion pull requests are thoroughly encouraged and welcome.