SoD Review – Oracle EBS R12 Query Stack

All statements are SELECT-only. Export each result to .xlsx with headers unchanged. Keep for each run: query text, bind values, instance, timestamp, row count.
Q1–Q2 feed the review tool (Q1 includes functions, which switches on Level 3) · Q3–Q5 validate findings.

Q1 · Oracle access extract, with functions → tool slot 1 · Level 1 + Level 3

One row per user × responsibility × function; the tool de-duplicates responsibilities itself. Includes role-inherited responsibilities. End Date = earliest of assignment / user / responsibility end (blank = active). Functions come from the full menu tree after exclusions. For Level 1 only, drop the *rfunc* join and the two function columns.

```
WITH asg AS (SELECT DISTINCT fu.user_name, fu.email_address, furg.start_date,
                NULLIF(LEAST(NVL(furg.end_date, DATE '4712-12-31'), NVL(fu.end_date, DATE '4712-12-31'),
                             NVL(fr.end_date, DATE '4712-12-31')), DATE '4712-12-31') end_date,
                fr.responsibility_id, fr.application_id, fr.menu_id, fr.responsibility_key,
                frt.responsibility_name, fa.application_short_name, fu.last_logon_date
               FROM fnd_user_resp_groups_all furg
               JOIN fnd_user fu               ON fu.user_id = furg.user_id
               JOIN fnd_responsibility fr     ON fr.responsibility_id = furg.responsibility_id
                                             AND fr.application_id = furg.responsibility_application_id
               JOIN fnd_responsibility_tl frt ON frt.responsibility_id = fr.responsibility_id
                                             AND frt.application_id = fr.application_id AND frt.language = USERENV('LANG')
               JOIN fnd_application fa        ON fa.application_id = fr.application_id),
     tree AS (SELECT CONNECT_BY_ROOT me.menu_id root_menu_id, me.function_id, me.grant_flag,
                     SYS_CONNECT_BY_PATH(me.menu_id, '/') || '/' menu_path
                FROM fnd_menu_entries me
               START WITH me.menu_id IN (SELECT menu_id FROM asg)
             CONNECT BY NOCYCLE PRIOR me.sub_menu_id = me.menu_id),
     rfunc AS (SELECT DISTINCT r.responsibility_id, r.application_id, fff.function_name, ffft.user_function_name
                 FROM (SELECT DISTINCT responsibility_id, application_id, menu_id FROM asg) r
                 JOIN tree t ON t.root_menu_id = r.menu_id AND t.grant_flag = 'Y'
                 JOIN fnd_form_functions fff     ON fff.function_id = t.function_id
                 JOIN fnd_form_functions_tl ffft ON ffft.function_id = fff.function_id AND ffft.language = USERENV('LANG')
                WHERE NOT EXISTS (SELECT 1 FROM fnd_resp_functions rf
                                   WHERE rf.responsibility_id = r.responsibility_id AND rf.application_id = r.application_id
                                     AND (   (rf.rule_type = 'F' AND rf.action_id = fff.function_id)
                                          OR (rf.rule_type = 'M' AND INSTR(t.menu_path, '/' || rf.action_id || '/') > 0))))
SELECT a.user_name "User Name", a.email_address "EMAIL_ADDRESS", a.responsibility_name "Responsibility Name",
       a.start_date "Start Date", a.end_date "End Date", a.responsibility_key "Responsibility Key",
       a.application_short_name "Application Short Name", a.last_logon_date "Last Logon",
       f.function_name "Function Code", f.user_function_name "Function Name"
  FROM asg a
  LEFT JOIN rfunc f ON f.responsibility_id = a.responsibility_id AND f.application_id = a.application_id
 ORDER BY 1, 3, 9;
```

Q2 · Person → Oracle user mapping → tool slot 2

Links people to users via FND_USER.EMPLOYEE_ID (username is placed in the email local part, which the tool matches on).

```
SELECT papf.person_id "PERSON_ID", papf.last_name "LAST_NAME",
       CASE WHEN fu.user_name IS NOT NULL THEN LOWER(fu.user_name) || '@'
            || NVL(SUBSTR(papf.email_address, INSTR(papf.email_address, '@') + 1), 'oracle.local') END "EMAIL_ADDRESS",
       papf.full_name "FULL_NAME"
  FROM per_all_people_f papf
  LEFT JOIN fnd_user fu ON fu.employee_id = papf.person_id
 WHERE TRUNC(SYSDATE) BETWEEN papf.effective_start_date AND papf.effective_end_date;
```

Q3 · Function-level drill-down for a flagged responsibility validation

Walks the full menu tree, removing function (F) and menu (M) exclusions.

```
WITH resp AS (SELECT fr.responsibility_id, fr.application_id, fr.menu_id, frt.responsibility_name
                FROM fnd_responsibility fr
                JOIN fnd_responsibility_tl frt ON frt.responsibility_id = fr.responsibility_id
                 AND frt.application_id = fr.application_id AND frt.language = USERENV('LANG')
               WHERE frt.responsibility_name = :p_responsibility_name),
     excl AS (SELECT rf.rule_type, rf.action_id FROM fnd_resp_functions rf JOIN resp r
                ON r.responsibility_id = rf.responsibility_id AND r.application_id = rf.application_id),
     menu_tree AS (SELECT me.function_id, me.grant_flag FROM fnd_menu_entries me
                     START WITH me.menu_id = (SELECT menu_id FROM resp)
                   CONNECT BY NOCYCLE PRIOR me.sub_menu_id = me.menu_id
                       AND me.menu_id NOT IN (SELECT action_id FROM excl WHERE rule_type = 'M'))
SELECT DISTINCT r.responsibility_name "Responsibility", fff.function_name "Function Code",
       ffft.user_function_name "Function Name"
  FROM menu_tree mt
  JOIN fnd_form_functions fff     ON fff.function_id = mt.function_id
  JOIN fnd_form_functions_tl ffft ON ffft.function_id = fff.function_id AND ffft.language = USERENV('LANG')
 CROSS JOIN resp r
 WHERE mt.grant_flag = 'Y'
   AND fff.function_id NOT IN (SELECT action_id FROM excl WHERE rule_type = 'F')
 ORDER BY 3;
```

Q4 · Conflict exercised: same user entered invoice and payment validation

```
SELECT fu.user_name "Oracle User", asp.vendor_name "Supplier", aia.invoice_num "Invoice",
       aia.invoice_amount "Invoice Amount",
       aca.check_number "Payment Doc", aca.check_date "Payment Date", aca.amount "Payment Amount"
  FROM ap_invoices_all aia
  JOIN ap_invoice_payments_all aipa ON aipa.invoice_id = aia.invoice_id
  JOIN ap_checks_all aca ON aca.check_id = aipa.check_id
  JOIN ap_suppliers asp  ON asp.vendor_id = aia.vendor_id
  JOIN fnd_user fu       ON fu.user_id = aia.created_by
 WHERE aca.created_by = aia.created_by AND aca.void_date IS NULL
   AND aca.check_date BETWEEN :p_from_date AND :p_to_date;
```

Q5 · Conflict exercised: user created supplier and entered its invoices validation

```
SELECT fu.user_name "Oracle User", asp.vendor_name "Supplier", asp.creation_date "Supplier Created",
       COUNT(aia.invoice_id) "Invoices By Same User", SUM(aia.invoice_amount) "Invoice Value"
  FROM ap_suppliers asp
  JOIN ap_invoices_all aia ON aia.vendor_id = asp.vendor_id AND aia.created_by = asp.created_by
  JOIN fnd_user fu ON fu.user_id = asp.created_by
 WHERE aia.creation_date BETWEEN :p_from_date AND :p_to_date
 GROUP BY fu.user_name, asp.vendor_name, asp.creation_date;
```