

Programming assignment 1.

Due date: Friday, October 4, 2019 at 11:59pm

.....

Implement [linearSearch\(a,key\)](#) and [binarySearch\(a,key\)](#) functions.

Part A. In this part we will calculate the **average-case running time** of each function.

1. Request the user to enter a positive integer, and call it **n**. ($n = 10^5$)
2. Generate **n** random integers between -1000 to 1000 and save them in array **a**.
3. Sort **a** (you can use any sorting algorithm you want.)
4. Pick a random number in **a** and save it in variable called **key**.
5. Call each function separately to search for the key in the given array.
6. To calculate the **average-running time**, you need to have a timer to save the total runtime when repeating step 4 and 5 for **100** times.

(**Note1**: Do not forget to divide the runtime by the number of the times you run step 4-5)

(**Note2**: Remember to choose a different random number each time you go back to step 4.)

Part B. In this part we will calculate the **worst-case running time** of each function.

1. Repeat steps **1 to 3** in part A.
2. Now to have the worst-case scenario, set the value of the key to **5000** to make sure it does not exist in the array.
3. Run each function **ONLY once** to calculate the **worst-case running time** when $n = 10^5$.
4. Calculate how much time your machine takes to run **one** single line using only your binary search function. (**Hint**: look at HW4)
5. Now using the **previous** step, estimate the worst-case running time for each algorithm when $n=10^9$ (**Just a simple calculation in your code!**).