Dynamic Rendering with Template Variables

Scott Hurrey

```
{% assign sluggedName = page.name | replace: '.md' %} modified: {{ page.last_modified_at | date: '%b-%d-%y' }}
```

Dynamic Rendering with Template Variables

Using template variables you can create URLs to integrate with other systems by including information about the user's context.

Template variables are represented by a series of values given the special syntax: @X@object.attribute@X@. These variables are expanded when rendered into their corresponding values. Within the UI, they can be used in portal modules and within the body of content items in courses.

Note that not all of these variables will resolve on all pages. For example, if the page is not inside a course, there will be no course-related variables available.

Using context variables

@X@course.locale@X@ | en US |

Context item | Context variable | Example output |

 $| \ \, Institution \ \, hierarchy \ \, nodes (As of 3900.32 \ \, use \ \, with \ \, caution. \ \, The \ \, output \ \, can \ \, be \ \, a \ \, long \ \, list \ \, that \ \, might \ \, affect \ \, an \ \, LTI \ \, launch.) \ \, | \ \, @X@course.ih_nodes@X@ | \ \, db75df7b-04e8-4d3c-b7f9-7f1371a3f325,fb11e84b-ff7f-44ab-bf77-89299b053232 \ \, launch.) \ \, | \ \, @X@course.ih_nodes@X@ | \ \, db75df7b-04e8-4d3c-b7f9-7f1371a3f325,fb11e84b-ff7f-44ab-bf77-89299b053232 \ \, launch.) \ \, | \ \, @X@course.ih_nodes@X@ | \ \, db75df7b-04e8-4d3c-b7f9-7f1371a3f325,fb11e84b-ff7f-44ab-bf77-89299b053232 \ \, launch.) \ \, | \ \, @X@course.ih_nodes@X@ | \ \, db75df7b-04e8-4d3c-b7f9-7f1371a3f325,fb11e84b-ff7f-44ab-bf77-89299b053232 \ \, launch.) \ \, | \ \, & \ \,$

@X@course.id@X@ | BIO101 | | Course name | @X@course.course_name@X@ | Introduction to Concepts in Biology | | Course primary key identifier | @X@course.pk_string@X@ | _12344_1 | | Course URL | @X@course.url@X@ | /courses/1/BIO101/ | | Course membership role | @X@course.role@X@ | student | | Course locale (As of 3900.32) |

| Institution primary node (As of 3900.32) | @X@course.ih_primary_node@X@ | fb11e84b-ff7f-44ab-bf77-89299b053232 |

 $| \mbox{ Is it an Ultra course? (As of 3900.32)} | \mbox{ @X@course.ultra_status@X@} | \mbox{ false } | \mbox{ Content primary key identifier } | \mbox{ @X@content.id@X@@X@content.pk_string@X@} | \mbox{ } 23_1 | \mbox{ Content URL } | \mbox{ @X@content.url@X@} | \mbox{ } /\mbox{ } /$

@X@request.locale@X@ | | Request return URL | @X@request.return@X@ | | System host name | @X@system.site_id@X@ |