

```

<!DOCTYPE html>
<html>
<head>
  <title>Bootstrap CDN Example</title>

  <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/css/bootstrap.min.css"
    rel="stylesheet">
</head>
<body>

<div class="container">
  <h1 class="text-primary">Hello Bootstrap 5</h1>
</div>

<script
src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.3/dist/js/bootstrap.bundle.min.js"></script>

</body>
</html>

```

```

bootstrap/
├── css/
│   ├── bootstrap.css
│   └── bootstrap.min.css
├── js/
│   ├── bootstrap.js
│   └── bootstrap.bundle.min.js
└── icons/

```

```

<script src="bootstrap/js/bootstrap.bundle.min.js"></script>

```

```

<div class="container">
  <div class="row">

    <div class="col-12 col-md-6 col-lg-4 bg-primary text-white">
      Column 1
    </div>

    <div class="col-12 col-md-6 col-lg-4 bg-success text-white">
      Column 2
    </div>

    <div class="col-12 col-md-12 col-lg-4 bg-danger text-white">
      Column 3
    </div>
  </div>
</div>

```

```
</div>
</div>
```

X

```
<div class="container">
  <div class="row">

    <div class="col-md-4">Left</div>
    <div class="col-md-4">Center</div>
    <div class="col-md-4">Right</div>

  </div>
</div>
```

```
<div class="container">
  <div class="row">

    <div class="col-md-3 bg-light">
      Sidebar
    </div>

    <div class="col-md-9 bg-secondary text-white">
      Content Area
    </div>

  </div>
</div>
```

X

```
<div class="container">
  <div class="row">

    <div class="col-sm-3">1</div>
    <div class="col-sm-3">2</div>
    <div class="col-sm-3">3</div>
    <div class="col-sm-3">4</div>

  </div>
</div>
```

```
<div class="container">
  <div class="row justify-content-center align-items-center vh-100">

    <div class="col-4 bg-primary text-white">
      Centered Content
```

```
</div>

</div>
</div>

X

<div class="row">

  <div class="col-md-6 order-md-2 bg-primary">
    First Column
  </div>

  <div class="col-md-6 order-md-1 bg-success">
    Second Column
  </div>

</div>
```

```
<nav class="d-flex flex-column flex-md-row bg-dark p-3">

  <a href="#" class="text-white me-3">Home</a>
  <a href="#" class="text-white me-3">About</a>
  <a href="#" class="text-white">Contact</a>

</nav>
```

```
X

<div class="card p-3 d-flex flex-row justify-content-between align-items-center">

  <h5>Product</h5>

  <button class="btn btn-primary">
    Buy
  </button>

</div>
```

```
<h1 class="display-1">Bootstrap Heading</h1>

<p class="lead">
  Lead paragraph text.
</p>

<p class="text-muted">
  Muted text.
</p>
```

```
<p class="fw-bold">
  Bold text.
</p>
```

X

```
<p class="text-uppercase">hello world</p>
```

```
<p class="text-lowercase">HELLO WORLD</p>
```

```
<p class="text-capitalize">hello world</p>
```

```
<form>
```

```
  <input type="text"
    class="form-control mb-3"
    placeholder="Name">
```

```
  <div class="input-group mb-3">
    <span class="input-group-text">@</span>
    <input type="text" class="form-control">
  </div>
```

```
  <div class="form-check">
    <input type="checkbox" class="form-check-input">
    <label class="form-check-label">
      Accept Terms
    </label>
  </div>
```

```
</form>
```

X

```
<div class="form-floating mb-3">
```

```
  <input type="email"
    class="form-control"
    id="email">
```

```
  <label for="email">
    Email Address
  </label>
```

```
</div>
```

```
<button class="btn btn-primary">Primary</button>
```

```
<button class="btn btn-secondary">Secondary</button>
<button class="btn btn-success">Success</button>
```

```
<button class="btn btn-outline-primary">
  Outline
</button>
```

X

```
<div class="btn-group">

  <button class="btn btn-primary">Left</button>
  <button class="btn btn-primary">Middle</button>
  <button class="btn btn-primary">Right</button>

</div>
```

```
<nav class="navbar navbar-expand-lg navbar-dark bg-dark">
```

```
  <div class="container">
```

```
    <a class="navbar-brand" href="#">
      Logo
    </a>
```

```
    <button class="navbar-toggler"
      data-bs-toggle="collapse"
      data-bs-target="#menu">
      <span class="navbar-toggler-icon"></span>
    </button>
```

```
    <div class="collapse navbar-collapse" id="menu">
```

```
      <ul class="navbar-nav me-auto">
```

```
        <li class="nav-item">
          <a class="nav-link" href="#">
            Home
          </a>
        </li>
```

```
      </ul>
```

```
      <form class="d-flex">
        <input class="form-control me-2">
        <button class="btn btn-success">
          Search
        </button>
      </form>
```

```
</div>
```

```
</div>
```

```
</nav>
```

X

```
<ul class="nav nav-tabs">
  <li class="nav-item">
    <a class="nav-link active">Tab 1</a>
  </li>
</ul>
```

```
<ul class="nav nav-pills mt-3">
  <li class="nav-item">
    <a class="nav-link active">Pill 1</a>
  </li>
</ul>
```

```
<div class="card" style="width:300px">
```

```
  
```

```
  <div class="card-body">
```

```
    <h5 class="card-title">
      John Doe
    </h5>
```

```
    <p class="card-text">
      Web Developer
    </p>
```

```
  </div>
```

```
</div>
```

X

```
<div class="d-flex">
```

```
  
```

```
</div>
```

```
<h5>User Name</h5>
```

```
<p>Media content here.</p>
```

```
</div>
```

```
</div>
```

```
<div class="m-3 p-2">
```

Content

```
</div>
```

```
<div class="mt-4 py-5">
```

Section

```
</div>
```

```
<div class="bg-primary text-white p-3">
```

Primary Section

```
</div>
```

```
<div class="bg-warning text-dark p-3">
```

Warning Section

```
</div>
```

X

```
<div class="bg-dark bg-gradient text-white p-5">
```

Gradient Background

```
</div>
```

```
<div class="d-none d-md-block">
```

Visible on tablets and above

```
</div>
```

```
<div class="d-none d-lg-flex">
```

Visible on desktops only

```
</div>
```

X

```
<div class="d-none d-md-block bg-light p-3">
```

Sidebar

```
</div>
```

```

```

X

```
<div class="card shadow-lg rounded-pill p-4">
```

Premium Card

```
</div>
```

```
<footer class="position-fixed bottom-0 w-100 bg-dark text-white text-center">
```

Fixed Footer

```
</footer>
```

X

```
<div class="position-relative d-inline-block">
```

```

```

```
<span class="badge bg-danger position-absolute top-0 start-100 translate-middle">
```

New

```
</span>
```

```
</div>
```

```
<link rel="stylesheet"
```

```
href="https://cdn.jsdelivr.net/npm/bootstrap-icons/font/bootstrap-icons.css">
```

```
<i class="bi bi-facebook"></i>
```

```
<i class="bi bi-twitter"></i>
```

```
<i class="bi bi-instagram"></i>
```

X

```
<button class="btn btn-primary">
```

```
<i class="bi bi-house"></i>
```

```
</button>
```



```
<button class="btn btn-primary"
  data-bs-toggle="modal"
  data-bs-target="#myModal">
```

Open Modal

```
</button>
```

```
<div class="modal fade" id="myModal">
```

```
  <div class="modal-dialog">
```

```
    <div class="modal-content">
```

```
      <div class="modal-header">
```

```
        <h5>Modal Title</h5>
```

```
      </div>
```

```
      <div class="modal-body">
```

```
        Hello Bootstrap Modal
```

```
      </div>
```

```
    </div>
```

```
  </div>
```

```
</div>
```

X

```
<div class="accordion" id="acc">
```

```
  <div class="accordion-item">
```

```
    <h2 class="accordion-header">
```

```
      <button class="accordion-button"
```

```
        data-bs-toggle="collapse"
```

```
        data-bs-target="#item1">
```

Section 1

```
      </button>
```

```
    </h2>
```

```
    <div id="item1"
```

```
      class="accordion-collapse collapse show">
```

```
      <div class="accordion-body">
```

Content Here

```
</div>
```

```
</div>
```

```
</div>
```

```
</div>
```

```
npm install bootstrap sass
```

```
X
```

```
$primary: #ff5722;
```

```
$border-radius: 1rem;
```

```
@import "../node_modules/bootstrap/scss/bootstrap";
```

```
X
```

```
sass custom.scss custom.css
```