

Use Case 1	Token Activation
Actor	User
User Story	As a corporate application user, I want to obtain and activate my token, so that I can add extra security and secure my access to corporate applications (i.e. using MFA)
Pre-conditions	User has activation code
Success Criteria	1. User downloads Access Authenticator app from the app store and open app 2. User clicks on "Add (+)" token 3. Selects Corporate Token from the options 4. System prompts for activation code 5. User supplies code from client's application onboarding screen (or from admin for corporate app, user profile for retail app) 6. System confirms if biometric is enabled on phone and runs backend validation 7. System enables biometric for app and displays success message
Alternative (or error) flows	1. User downloads Access Authenticator app from the app store and open app 2. User scans a QR code from a corporate application 3. System confirms if biometric is enabled on phone and runs backend validation 4. System enables biometric for app and displays success message
Acceptance Criteria (AC)	1. User sees new token entry bearing corporate or business name and corporate username 2. User sees a temporary token (TOTP) against the new entry 3. The time bound token can be validated or used on corporate applications (e.g. PrimusPlus or SME) 4. Next time, the user launches the app he will be prompted for biometric validation before TOTP will be revealed against this entry 5. Anytime the app is out of view and the user reopens, the app requests for biometric verification 6. Activation code can be used only once and within a certain time window e.g. 10mins

	7. Access Authenticator can only work on one device for the specific organization user
Technical & Design Assets	1. token/create (userId, fullname, orgId, orgName): {status, qr-data, secret, code, code-expiration}. Used by bank applications such as PrimusPlus, SME, iBank 2. token/code-info (code, deviceId, deviceModel, IPAddress, publicKey): { userId, fullname, orgId, orgName, qr-data, secret, code-expiration, countryCode, countryName}. Used by Access Authenticator to retrieve and activate app with code. 3. token/verify (userId, totp): {status, message} used by apps to verify token

Use Case 2	Token Verification
Actor	User
User Story	As a customer, I want to authorize (or login) bank application using token, so that I can secure my transactions.
Pre-conditions	User has activated a token on Access Authenticator
Success Criteria	1. System prompts for Token at login or transaction authorization 2. User launches Access Authenticator app 3. User performs biometric verification 4. System generates TOTP 5. User copies the digits to the requesting application 6. Requesting application performs validation and displays success message
Alternative (or error) flows	
Acceptance Criteria (AC)	1. TOTP times out after a period 2. TOTP generated is verified on customer application
Technical & Design Assets	1. token/verify (userId, totp): {status, message} used by apps to verify token

--	--

Use Case 3	Activation Code (Access More)
Actor	Customer
User Story	As a retail customer, I want to activate my soft token by myself, so that I do not have to go the branch.
Pre-conditions	User has access to AccessMore and has a working camera
Success Criteria	1. User logs into Access More 2. User selects Activate SoftToken from user profile menu 3. System displays a guide (indicating how to download Access Authenticator) 4. User captures his/her image 5. User captures his/her authorization PIN 6. System runs backend validation and display SoftToken Activation key 7. User copies the activation code to Access Authenticator 8. Access Authenticator runs backend validation
Alternative (or error) flows	
Acceptance Criteria (AC)	1. The activated token works on customer application
Technical & Design Assets	1. backend/token-actvn (username, imageBase64Str, userPIN): {status, code} retrieve activation code 2. token/create (userId, fullname, orgId, orgName): {status, qr-data, secret, code, code-expiration}. Used by bank applications such as PrimusPlus, SME, iBank 3. token/code-info (code, deviceId, deviceModel, IPAddress, publicKey): { userId, fullname, orgId, orgName, qr-data, secret, code-expiration, countryCode, countryName}. Used by Access Authenticator to retrieve and activate app with code. 4. token/verify (userId, totp): {status, message} used by apps to verify token

	5. backend/authorizeTxn (...signedChallenge, biometric, PIN, token): {...status, message} for authorizing transaction.
--	--

Use Case 4	Activation Code (Backoffice)
Actor	Staff
User Story	As a staff, I want to activate code customer soft token, so that customers who cannot perform self-service can be serviced.
Pre-conditions	Staff (and manager) have access to customer 360
Success Criteria	1. Staff logs into Customer360 2. Find customer record 3. After verifying customer identity, initiate Soft Token Activation 4. Customer enters code share by staff on Access Authenticator 5. System performs backend validations and displays success message
Alternative (or error) flows	On PrimusPlus 1. Staff logs into PrimusPlus admin portal 2. Find corporate record, 3. After verifying customer identity, initiate Soft Token Activation 4. Corporate admin enters code as shared by staff on Access Authenticator 5. System performs backend validations and displays success messages.
Acceptance Criteria (AC)	1. TOTP generated after token activation works
Technical & Design Assets	1. token/create (userId, fullname, orgId, orgName): {status, qr-data, secret, code, code-expiration}. Used by bank applications such as PrimusPlus, SME, iBank 2. token/code-info (code, deviceId, deviceModel, IPAddress, publicKey): { userId, fullname, orgId,

	orgName, qr-data, secret, code-expiration, countryCode, countryName}. Used by Access Authenticator to retrieve and activate app with code. 3. token/verify (userId, totp): {status, message} used by apps to verify token
--	---