# **Operating Systems**

## Assignment 4

~ Shaunak Pal

### A1) Code for Syscall\_handler:

```
push %eax
push %edx
push %fs

mov $216, %ecx
mov %ecx, %fs
push %ebx
push %eax

call syscall_handler_k

pop %eax
pop %ebx
pop %fs
pop %edx
pop %ebx
pop %eax
```

## A2) Code for syscall\_u:

```
mov 4(%esp), %eax
mov 8(%esp), %ebx
```

## A3) Code for register\_syscall:

```
static void register_syscall(void)
{
   unsigned long syscall_addr = (unsigned long)syscall_handler;
   struct idt_desc newIDT;
   if(imp_copy_idt(&newIDT)) {
      struct idt_desc oldIDT = newIDT;
}
```

```
newIDT.base[15]=oldIDT.base[128]
    (&newIDT)->base[15].lower16 = syscall_addr;
    (&newIDT)->base[15].higher16 = syscall_addr>>16;
    imp_load_idt(&newIDT, &oldIDT);
    originalIDT = oldIDT;
    printk("doing job\n");
}
else {
    printk("idt copy failed.\n");
}
```

#### A4) Code for unregister syscall:

```
static void unregister_syscall(void)
{
    struct idt_desc currentIDT;
    imp_copy_idt(&currentIDT);
    if (&currentIDT != &originalIDT) {
        imp_load_idt(&originalIDT, &currentIDT);
        imp_free_desc(&currentIDT);
    }
}
```

#### A5) Output of user-program:

root@ubuntu32-VirtualBox:/home/ubuntu32/Documents/syscall# cd kernel && make && cd ../user && make && cd ../kernel && ./load && cd ../user && ./syscall && cd ..

make -C /lib/modules/`uname -r`/build M=/home/ubuntu32/Documents/syscall/kernel make[1]: Entering directory '/usr/src/linux-headers-4.15.0-45-generic'

Building modules, stage 2.

MODPOST 1 modules

make[1]: Leaving directory '/usr/src/linux-headers-4.15.0-45-generic' make: Nothing to be done for 'default'.

syscall done!



- A6) The original IDT was stored as a global variable. Its value is update in register\_syscall function
- A7) The current IDT is obtained from the given function imp\_copy\_idt with an empty struct idt\_desc as parameter which copies the current idt to the empty struct and then we can use it.
- A8) Neither of them happens because the if condition in unregister\_syscall checks whether current IDT and original IDT are different. So since they will be the same the second time the program does not go inside the if condition so original IDT is not loaded twice and current IDT is not freed.