

Accepted Manuscript

Title: An New Pose Invariant Face Recognition System using PCA and ANFIS

Author: Reecha Sharma M.S. Patterh

PII: S0030-4026(15)00972-9
DOI: <http://dx.doi.org/doi:10.1016/j.ijleo.2015.08.205>
Reference: IJLEO 56129

To appear in:

Received date: 4-9-2014
Accepted date: 27-8-2015

Please cite this article as: R. Sharma, M.S. Patterh, An New Pose Invariant Face Recognition System using PCA and ANFIS, *Optik - International Journal for Light and Electron Optics* (2015), <http://dx.doi.org/10.1016/j.ijleo.2015.08.205>

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



An New Pose Invariant Face Recognition System using PCA and ANFIS

Reecha Sharma¹, M.S. Patterh¹

¹Department of Electronics and Communication Engineering, Punjabi University, Patiala,
147002, India.

Corresponding author email: sharmareecha@gmail.com

Abstract:

In this paper an efficient pose invariant face recognition system using PCA and ANFIS (PCA-ANFIS) has been proposed. The features of an image under test have been extracted using PCA then neuro fuzzy based system ANFIS is used for recognition. The proposed system recognizes the face images under a variety of pose conditions by using ANFIS. The training face image dataset is processed by PCA technique to compute the score values, which are then utilized in the recognition process. The proposed face recognition technique with neuro-fuzzy system recognizes the input face images with high recognition ratio. The proposed approach is implemented in the MATLAB platform and it is evaluated by employing a variety of database images under various pose variant conditions.

Keywords: *Principle Component Analysis (PCA), Face recognition, ANFIS, score value.*

1. Introduction

Face recognition is to identify or verify one or more persons in the given still or video images of a scene using a stored database of faces [1]. Face recognition can be classified into two categories; these are geometric feature-based and appearance-based [4]. The geometric feature-based methods, such as elastic bunch graph matching [5] and active appearance model [6] make

use of the geometrical parameters that measure the facial parts; whereas the appearance-based methods use the intensity or intensity-derived parameters [1]. Face recognition system consists of two stages; these are face detection and the face identification [2]. In the face detection stage, facial images are localized in an input image. In the face identification stage, the localized faces are identified as individuals registered in the system. Therefore, developing both face detection algorithms and face identification algorithms is quite important [11].

The variations involved in face recognition, include illumination, pose, and identity [3], facial expression, hair style, aging, make-up, scale. It is very difficult for even humans to recognize faces correctly when the illumination varies severely, since the same person appears to be very much different [10]. A common solution to handling pose variations in face recognition is the view-based method. In this method, the face images of the individuals to be recognized are acquired from different view angles [13]. The images of the same view are used to construct an eigen space representation for each view, and the view-specific Eigen space representations are then used for recognizing a person in different poses [12].

However the 2D image patterns of 3D face object can change dramatically due to lighting and viewing variations [7]. Recently there has been growing interest in face recognition from sets of images. Here, rather than supplying a single query image, the user supplies a set of images of the same unknown individual. In general the gallery also contains a set of images for each known individual, so the system must recover the individual whose gallery set is the best match for the given query set [9]. Recently face recognition using image-set or video sequence has attracted more and more attention within computer vision and pattern recognition community. More

importantly, compared with single snapshot, a set or a sequence of images provides much more information about the variation in the appearance of the target subject [8].

The overall structure of the paper is organized as follows: Section 2 in which proposed face recognition system using PCA and ANFIS (PCA-ANFIS) is discussed. Section 3 gives the experimental results and discussions. Section 4 concludes the paper.

2. The Proposed face recognition system using PCA-ANFIS

For the proposed work, the face images are taken from the ORL database. These images are first denoised using the Adaptive median filter, before further processing. The denoised images are given to the next process in order to calculate the score values using principle component analysis (PCA) technique. The score values so obtained from the PCA techniques are then used by ANFIS classifier for accomplishing the training process. Based on the predefined threshold value the image under test is indicated as recognized or not recognized

The face database images are represented as

$$f_d(r, s) = \{f_{d^1}(r, s), f_{d^2}(r, s) \cdots f_{d^N}(r, s)\}; i = 1, 2, 3, \cdots N, \quad (1)$$

Where N is the total number of images in the database D . These numbers of face images from the database D are utilized in the recognition process. The basic structure of our proposed face recognition system is given in Figure1.




Fig 1: Architecture of the proposed face recognition system

The proposed face detection technique consists of three stages namely

i) Preprocessing

❖ Adaptive median filter

ii) Principle component analysis.

❖ Score value calculation

iii) Classification using ANFIS.

2.1 Adaptive Medan Filter

The adaptive median filter is applied to the images $f_d(r,s)$ which is affected by the (salt and pepper) noise and acquire a noise free image as an output. The process of adaptive median filtering in noise removal is given below:

Step 1: Initialize the window w size w_z .

Step 2: Check if the center pixel $p_{cen}(r, s)$ within w is noisy. If the pixel $p_{cen}(r, s)$ is noisy go to step 3. Otherwise slide the window to the next pixel and repeat step 1.

Step 3: Sort all pixels within the window w in an ascending order and find the minimum ($p_{min}(r, s)$), median ($p_{med}(r, s)$), and maximum ($p_{max}(r, s)$) values.

Step 4: Compute if $p_{med}(r, s)$ is noisy,

$$(i.e.) p_{min}(r, s) < p_{med}(r, s) < p_{max}(r, s). \quad (2)$$

If the median value range is in between the minimum and maximum means the pixel is not a noisy and go to step 5, otherwise $p_{med}(r, s)$ is a noisy pixel and go to step 6.

Step 5: Replace the corresponding centre pixel in output image with $p_{med}(r, s)$ and go to step 8.

Step 6: Check if all other pixels are noisy. If yes then expend the window size by 2 and go to step 3. Otherwise, go to step 7.

Step 7: Replace the center pixel of the image with the noise free pixel which is the closest one of the median pixel $p_{med}(r, s)$.

Step 8: Reset window size w_z and center of window to next pixel.

Step 9: Repeat the steps until all pixels are processed.

Using the above mentioned adaptive median filter algorithm the salt and pepper noise is removed. This denoised image is then given to the next process to calculate the score values using PCA technique.

2.2 Score Value Calculation using Principle Component Analysis:

The denoised image f_d' acquired from the Adaptive median filter system is subjected to score values estimation utilizing principle component analysis [20]. The figure 2 shows the flow chart of PCA.




Figure 2: Flow Chart of the Principle component analysis

In the last step of flow chart the score values $p(\vec{x}_1)$, $p(\vec{x}_2)$... $p(\vec{x}_n)$ obtained from the PCA process for different pose images are then passed into ANFIS based classification process.

2.3 Classification using ANFIS classifier

The score value $p(\vec{x}_1)$, $p(\vec{x}_2)$... $p(\vec{x}_n)$ obtained from the PCA are classified using the well known classifier named ANFIS which comprises five layers of nodes. Out of five layers,

the first and the fourth layers possess adaptive nodes whereas the second, third and fifth layers possess fixed nodes. The architecture of the ANFIS is given in figure 3.




Figure 3: Architecture of ANFIS

The learning process of ANFIS is carried out on the extracted PCA features such as Eigen vectors. The Rule basis of the ANFIS is of the form:

If $p(\vec{x}_1)$ is A_i , $p(\vec{x}_2)$ is B_i , ..., $p(\vec{x}_n)$ is C_i then

$$Rules_i = a_i p(\vec{x}_1) + b_i p(\vec{x}_2) + c_i p(\vec{x}_n) + f_i \quad (8)$$

Where, $p(\vec{x}_1)$, $p(\vec{x}_2)$, ..., $p(\vec{x}_n)$ are the inputs, A_i , B_i and C_i are the fuzzy sets, $Rules_i$ is the output within the fuzzy region specified by the fuzzy rule, a_i , b_i , c_i and f_i are the design parameters that are determined by the training process.

Layer 1: Every node i in this layer is a square node with a node function.

$$O_{1,i} = \mu_{A_i}(p(\vec{x}_1)), \quad O_{1,i} = \mu_{B_i}(p(\vec{x}_2)), \quad O_{1,i} = \mu_{C_i}(p(\vec{x}_n)) \quad (9)$$

Usually $\mu_{A_i}(p(\vec{x}_1))$, $\mu_{B_i}(p(\vec{x}_2))$, $\mu_{C_i}(p(\vec{x}_n))$ are chosen to be bell-shaped with maximum equal to 1 and minimum equal to 0 and are defined as

$$\mu_{A_i}(p(\vec{x}_1)) = \mu_{B_i}(p(\vec{x}_2)) = \mu_{C_i}(p(\vec{x}_n)) = \frac{1}{1 + \left[\left(\frac{x - o_i}{p_i} \right)^2 \right]^{q_i}} \quad (10)$$

Where o_i, p_i, q_i is the parameter set. These parameters in this layer are referred to as premise parameters.

Layer-2: Every node in this layer is a circle node labeled Π which multiplies the incoming signals and sends the product out. For instance,

$$O_{2,i} = wt_i = \mu_{A_i}(p(\vec{x}_1)) \times \mu_{B_i}(p(\vec{x}_2)) \times \mu_{C_i}(p(\vec{x}_n)), \quad i = 1, 2 \quad (11)$$

Each node output represents the firing strength of a rule.

Layer-3: Every node in this layer is a circle node labeled N . The i^{th} node calculates the ratio of the i^{th} rules firing strength to the sum of all rule's firing strengths:

$$O_{3,i} = \overline{wt_i} = wt_i / (wt_1 + wt_2), \quad i = 1, 2 \quad (12)$$

Layer-4: Every node i in this layer is a square node with a node function

$$O_{4,i} = \overline{wt_i} \cdot Rules_i \quad i = 1, 2 \quad (13)$$

Where wt_i is the output of layer 3 and a_i, b_i, c_i, f_i are the parameter set. Parameters in this layer will be referred to as consequent parameters.

Layer-5: The single node in this layer is a circle node labeled Σ that computes the overall output as the summation of all incoming signals:

$$O_{5,i} = \sum_i \overline{wt_i} Rules_i = \frac{\sum_i wt_i Rules_i}{\sum_i wt_i} \quad (14)$$

$$Z = \frac{wt_1 Rules_1 + wt_2 Rules_2}{wt_1 + wt_2} \quad (15)$$

$$Z = \overline{wt} Rules_1 + \overline{wt} Rules_2 \quad (16)$$

Then the predefined threshold value ω and the result of the neural network (Z) is compared which is given in Eq. (17).

$$result = \begin{cases} recognized, Z \geq \omega, \\ not\ recognized, Z < \omega \end{cases} \quad (17)$$

The neural network output Z greater than the threshold value ω means, the given input image is recognized and Z less than the threshold value ω mean image is not recognized. Thus the ANFIS is well trained using the score value obtained from PCA. The performance of the well trained ANFIS is tested by giving more number of different pose images.

3. Experimental Results and Discussions

The proposed PCA-ANFIS for different pose images is implemented using MATLAB (version 7.12) with machine configuration as follows.

Processor: Intel core i7

OS: Windows 7

CPU speed: 3.20 GHz

RAM: 4GB

The performance of the proposed PCA-ANFIS technique for different pose images are evaluated by giving more number of images taken from the ORL database. Figure 4 shows some sample images taken from the database.



• **Figure 4:** Sample dataset from the ORL database

To remove the noise from the given input face images, the images are passed through the Adaptive median filter and denoised face images so obtained are shown in figure.5



Figure 5: Denoised images after Adaptive median filtering

Images	PSNR		
	Proposed adaptive median filter	Existing Average Filter (in dB)	Existing Gaussian Filter (in dB)
1	38.64005	28.37	26.35

2	33.977	26.28	24.41
3	35.1861	26.81	26.02
4	34.54	26.19	25.52
5	33.96	26.68	25.08

Table 1: Image Denoising performance of adaptive median filter and existing Average and Gaussian filtering methods.




Figure 6: Comparison of Adaptive median filtering technique with the existing average and Gaussian filtering methods.

As can be seen from the table 1 and figure 6, Adaptive median filter with PCA has achieved more denoising ratio than the other filtering methods. Adaptive median filter has given high PSNR value for different dataset images. For example in case of image 3 the PSNR in case of proposed method is 35.1861 dB where as in existing average filter is 26.81dB and in Gaussian filter is 26.02dB.

Accordingly the denoised images acquired from the Adaptive median filter are used to compute the score values utilizing the PCA based calculation. The score values in this way acquired from

the principle component analysis are given as the input to the ANFIS classifier. More number of face images are used to analyze the performance of the proposed face recognition system using different statistical performance measures.

The face images from ORL database are utilized to analyze the performance of proposed PCA-ANFIS technique with the ICA-ANFIS and LDA-ANFIS techniques. The comparison results of the proposed technique, ICA-ANFIS and LDA-ANFIS techniques are shown in the table 2.

Measures	Proposed PCA-ANFIS	ICA-ANFIS	LDA-ANFIS
Accuracy	0.9666	0.713	0.68
Sensitivity	0.9729	0.728	0.6483
Specificity	0.9605	0.712	0.7288

Table 2: Demonstrate the Performance comparison of the proposed PCA-ANFIS technique, ICA-ANFIS and LDA-ANFIS technique.

In table 2 the accuracy of the proposed PCA-ANFIS technique is 0.9666 but the ICA-ANFIS and LDA-ANFIS techniques have offer only 0.713, 0.68 of accuracy. Similarly the sensitivity and specificity of the proposed PCA-ANFIS technique is 0.9729 and 0.9605 but the ICA-ANFIS and LDA-ANFIS techniques give 0.728, 0.6483 of sensitivity and 0.712, 0.7288 of specificity respectively. Hence from the table it can be seen that proposed method recognizes the image more accurately.

Moreover proposed PCA-ANFIS is also compared with the existing FFBNN technique in terms of sensitivity, specificity and accuracy measures. The results are shown below in table 3.

Measures	Proposed PCA-ANFIS	Existing FFBNN
Accuracy	0.9666	0.8666
Sensitivity	0.9729	0.8481
Specificity	0.9605	0.8873
FPR	0.0394	0.1126
PPV	0.96	0.8933
NPV	0.9733	0.84
FDR	0.04	0.106
MCC	0.9334	0.7343

Table 3: Illustrates the Performance measures of the proposed PCA-ANFIS technique and the existing FFBNN techniques in terms of accuracy, sensitivity, specificity.

From the table it can be seen that the proposed PCA-ANFIS has given accuracy of 0.9666 but the existing FFBNN has given accuracy of only 0.8666. Similarly the sensitivity and the specificity of our proposed method are higher than the existing FFBNN. The comparison graph has been given below in figure7.




Figure 7: Proposed PCA-ANFIS technique comparison with the existing FFBNN in terms of accuracy, sensitivity and specificity measures.

From the graph it can also be seen that the performance of the proposed PCA-ANFIS is high when compared to the existing FFBNN. Thus from the performance metrics it can be seen that the proposed PCA-ANFIS efficiently recognize the images.

4. Conclusion

In this paper a face recognition technique using PCA-ANFIS is proposed. First the images under test are denoised by using Adaptive median filter and its performance is compared with average filter and Gaussian filter. From the comparative result it has been found that Adaptive median filter performs better as compared to Average and Gaussian filter. PCA is used for feature extraction and ANFIS is used for face recognition. The performance of the proposed setup (PCA-ANFIS) is compared with ICA-ANFIS and LDA-ANFIS. From the comparative results it has been found that PCA-ANFIS performs better than ICA-ANFIS and LDA-ANFIS. For example the proposed PCA-ANFIS gives accuracy of 0.9666 as compared to ICA-ANFIS which gives 0.713 and LDA-ANFIS which gives 0.68. Proposed PCA-ANFIS technique also performs better than FFBNN. It has been concluded that PCA-ANFIS set up can be used for face recognition with better accuracy.

References

- [1] Wu-Jun Li, Chong-Jun Wang, Dian-Xiang Xu and Shi-Fu Chen, "Illumination Invariant Face Recognition Based on Neural Network Ensemble", In Proceedings of 16th IEEE International Conference on Tools with Artificial Intelligence, pp. 486-490, November 2004

- [2] Rehab F. Abdel-Kader, Rabab M. Ramadan and Rawya Y. Rizk, "Rotation Invariant Face Recognition Based on Hybrid LPT/DCT Features", International Journal of Electrical and Computer Engineering, Vol. 3, No. 7, pp. 488-493, 2008
- [3] Shaohua Kevin Zhou and Rama Chellappa, "Image-based face recognition under illumination and pose variations", Journal of the Optical Society of America A, Vol. 22, No. 2, pp. 217-229, 2005
- [4] Brunelli and Poggio, "Face recognition: Features versus templates", IEEE Transactions on Pattern Analysis and Machine Intelligence, Vol. 15, No. 10, pp.1042-1052, 1993
- [5] Laurenz Wiskott, Jean-Marc Fellous, Norbert Kruger, and Christoph von der Malsburg, "Face Recognition by Elastic Bunch Graph Matching", IEEE Transactions on Pattern Analysis and Machine Intelligence, Vol.19, pp. 775-779, 1997
- [6] Edwards, Cootes and Taylor, "Face recognition using active appearance models", In Proceedings of the 5th European Conference on Computer Vision, Vol. 2, Freiburg, Germany, pp. 581-595, 1998
- [7] WenYi Zhao and Rama Chellappa, "Image based Face Recognition Issues and Methods", Image Recognition and Classification, pp. 375-402, 2002
- [8] Xi Li, Kazuhiro Fukui and Nanning Zheng, "Image-set based Face Recognition Using Boosted Global and Local Principal Angles", Springer Lecture Notes in Computer Science (LNCS), 2009
- [9] Hakan Cevikalp and Bill Triggs, "Face Recognition Based on Image Sets", In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, San Francisco : United States, 2010

- [10] Seok Cheol Kee, Kyoung Mu Lee And Sang Uk Lee, " Illumination Invariant Face Recognition Using Photometric Stereo", IEICE Transactions on Information and Systems, Vol. E83-D, No. 7, pp. 1466-1474, July 2000
- [11] Yasufumi Suzuki and Tadashi Shibata, "Illumination-Invariant Face Identification Using Edge-Based Feature Vectors In Pseudo-2d Hidden Markov Models", In Proceedings of the 14th European Signal Processing Conference, Florence, Italy, 2006
- [12] Hui-Fuang Ng, "Pose-Invariant Face Recognition Security System", Asian Journal of Health and Information Sciences, Vol. 1, No. 1, pp. 101-111, 2006
- [13] Shermina, "Impact of Locally Linear Regression and Fisher Linear Discriminant Analysis in Pose Invariant Face Recognition", International Journal of Computer Science and Network Security, VOL.10 No.10, pp. 106-110, October 2010
- [14] Zhonghua Liu, Jingbo Zhou and Zhong Jin, "Face recognition based on illumination adaptive LDA", In Proceedings of International Conference on Pattern Recognition, pp. 894-897, Istanbul, Turkey, August 2010
- [15] Muhammad Akmal Khan, Javed and Muhammad Anjum Akbar, "Face Recognition using Sub-Holistic PCA", British Journal of Science, Vol. 1, No. 1, pp. 111-120, 2011
- [16] Susheel Kumar, Shitala Prasad, Vijay Bhaskar Semwal and Tripathi, "Real Time Face Recognition using Adaboost Improved Fast PCA Algorithm", International Journal of Artificial Intelligence & Applications (IJAIA), Vol.2, No.3, July 2011
- [17] Srinivasan, "A Framework for Face Recognition Using Adaptive Binning and Adaboost Techniques", The International Journal of Multimedia & Its Applications, Vol.3, No.1, pp. 76-88, 2011.

- [18] Hafiz Imtiaz and Shaikh Anowarul Fattah, "A Spectral Domain Local Feature Extraction Algorithm for Face Recognition", International Journal of Security (IJS), Vol. 5, No. 2, pp. 62-73, 2011.
- [19] Shermina and Vasudevan "An Efficient Face Recognition System Based On the Fusion of MPCA and LPP", American Journal of Scientific Research, No. 11, pp. 6-19, 2010
- [20] Syed Navaz, Dhevi Sri and Pratap Mazumder, "Face Recognition Using Principal Component Analysis And Neural Networks", International Journal of Computer Networking, Vol. 3, No. 1, pp. 245-256, 2013.