

6.1 KNOW EVERYTHING ABOUT YOUR ALL-NEW PARTNER

VERSIONS	BlueHDi 75				BlueHDi 100 S6S				BlueHDi 130 S6S		BlueHDi 130 S6S	
	Van			Van	Van			Van	Van	Van	Van	
	Standard			Standard	Long			Standard	Long	Standard	Long	
	S				S							
	Grip		Professional	Grip		Professional / Asphalt		Professional / Asphalt	Professional / Asphalt	Professional / Asphalt	Professional / Asphalt	Asphalt
ENGINE												
Capacity (cc)	1560				1560				1499			
Cylinders / Valves	4 / 16				4 / 8				4 / 16			
Max power CEE (kW (hp)/rpm)	55 (75) / 3500				73 (99) / 3750				96 (131) / 3750			
Max torque CEE (Nm (lb/ft)/rpm)	230 (170) / 1750				254 (187) / 1750				300 (221) / 1750			
Bore and stroke (mm)	75 x 88.3				75 x 88.3				75 x 84.8			
Fuel system	Diesel - High pressure turbo-charged direct injection				Diesel - High pressure turbo-charged direct injection				Diesel - High pressure turbo-charged direct injection			
Euro status	Euro 6.1				Euro 6.1				Euro 6.2			
Stop & Start system	-				●				●			
TRANSMISSION												
Gearbox	Manual				Manual				Manual		Automatic	
Number of gears	5				5				6		8	
Driven wheels	Front											
PERFORMANCE (All figures driver alone)												
Max speed (mph)	94	92	94	101	103	103	101	103	115		114	
0-62mph (secs)	15.7	16.5	15.9	12.8	12.5	12.6	13.0	12.8	10.0	10.1	10.7	10.9
Standing to 1000m (secs)	37.1	37.7	37.3	34.8	34.6	34.6	35.0	34.8	31.9	32.1	32.5	32.6
ECONOMY MPG (Litres/100km)												
Urban cycle	57.6 (4.9)			60.1 (4.6)	61.4 (4.6)	61.4 (4.6)	57.6 (4.9)	61.4 (4.6)	57.6 (4.9)		62.8 (4.5)	62.8 (4.5)
Extra urban	68.9 (4.1)			70.6 (4.0)	70.6 (4.0)	68.9 (4.1)	65.7 (4.3)	68.9 (4.1)	68.9 (4.1)		68.9 (4.1)	67.3 (4.2)
Combined	64.2 (4.4)			65.7 (4.3)	67.3 (4.2)	65.7 (4.3)	61.4 (4.6)	65.7 (4.3)	64.2 (4.4)		65.7 (4.3)	65.7 (4.3)
CO ₂ EMISSIONS (g/km)	114			111	109	112	119	112	116		113	113
WEIGHTS (kg) with 3 seats / 2 seats												
Gross Vehicle Weight (GVW)	1970	2350	2000	2370	2370	2350	2370	2370	2390	2400	2380	2370
Kerb weight (1)	1303	1320	1319	1320	1320	1395	1430	1416	1389	1430	1380	1430
Mass in service	1500	1510	1515	1510	1512	1566	1596	1586	1576	1602	1566	1602
Maximum Indicative Payload (2)	667	1030	681	1050	1050	955	940	954	1001	970	1000	940
Max plated front axle (3)	1110	1200	1110	1200	1200	1200	1200	1200	1200	1200	1200	1200
Max plated rear axle (3)	1075	1400	1075	1400	1400	1400	1400	1400	1400	1400	1400	1400
Gross Train Weight (GTW)	2970	3100	3000	3220	3220	3200	3220	3220	3590	3600	3380	3370
Maximum braked towing weight (4)	1000	750	1000	1000	1000	950	950	950	1200	1200	1000	1000
Maximum unbraked towing weight	680	690	690	690	690	730	750	740	730	750	720	750
Maximum towball weight	74			74					74		74	
BRAKES Front/Rear	283mm Ventilated front discs / 268mm Solid rear discs											
TURNING CIRCLE between kerbs (m)	10.82	10.85	10.82	10.85	10.82	11.43			10.82	11.43	10.82	11.43
Tyres	195/65 R15	215/65 R16	195/65 R15	215/65 R16	205/60 R16		215/65 R16	205/60 R16	205/60 R16		205/60 R16	
FUEL TANK CAPACITY Litres (gallons)	50 (11)											
ADBLUE TANK CAPACITY Litres (gallons)	17 (3.74)											

(1) Without driver. Kerb weight is calculated for a European base specification vehicle including oil, water, lubricants, tools, spare wheel and 90% full fuel tank. Weights may change with the addition of equipment.

(2) Maximum indicative payload is calculated as the difference between GVW and kerb weight. However, due to manufacturing tolerances and differences in the specification of UK vehicles, the mass in service figure provides a closer indication of the vehicle weight and therefore enables a more realistic payload to be calculated. An individual vehicle must be established to establish the exact kerb weight and payload applicable to that vehicle. It is the responsibility of the driver to ensure the vehicle is operated within the legal limits

(3) Within limits of GVW.

(4) Maximum recommended towing weight within limits of GTW.